NAVAL POSTGRADUATE SCHOOL
Monterey, California

THESIS

A STUDY OF THE FEASIBILITY AND APPLICABILITY OF SHAPE CONTROLLED SPACE BASED INFLATABLE MEMBRANE STRUCTURES

by

Craig M. Whittinghill

September 2000

Thesis Advisor:	Brij Agrawal
Co-Advisor:	Donald v.Z. Wadsworth

Approved for public release; distribution is unlimited

DTIC QUALITY INSPECTED 4

20001026 140

REPORT DOCUMENTATION PAGE		Form Approved OMB No. 0704-0188
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instruction, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188) Washington DC 20503.		
1. AGENCY USE ONLY *(Leave blank)*	**2. REPORT DATE** September 2000	**3. REPORT TYPE AND DATES COVERED** Master's Thesis
4. TITLE A Study of the Feasibility and Applicability of Shape Controlled Space Based Inflatable Membrane Structures		**5. FUNDING NUMBERS**
6. AUTHOR(S) Whittinghill, Craig M.		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Postgraduate School Monterey, CA 93943-5000		**8. PERFORMING ORGANIZATION REPORT NUMBER**
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) N/A		**10. SPONSORING / MONITORING AGENCY REPORT NUMBER**
11. SUPPLEMENTARY NOTES The views expressed in this thesis are those of the author and do not reflect the official policy or position of the Department of Defense or the U.S. Government.		
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution is unlimited		**12b. DISTRIBUTION CODE**

13. ABSTRACT Inflatable structures used for space applications offer mass, volume, and cost savings to spacecraft programs, allowing larger space structures to be built. For certain space applications, there are advantages to using large structures. For example, antennas achieve higher gains when they are increased in size. Higher gains equate to higher data throughputs. Therefore, inflatable structures offer improvements in performance to certain types of spacecraft components.

Environmental factors induce surface errors on large inflatable structures, though. This degrades performance, especially for inflatable antennas. To reduce this degradation, active and passive control systems can be used to sense errors and control the shape of the antenna. One method of applying an active and passive control system is by using piezoelectric films that are either attached to or are part of the inflatable structure.

The research performed for this thesis explored the theoretical performance of a large inflatable space-based antenna via spreadsheet analysis and the physical performance of a piezoelectric film via laboratory experimentation. For the laboratory experiment, the film was attached to a drum and varying internal pressures and voltages were applied. Also, in order to validate the experimental results, an analytical model was created using MSC/PATRAN and MSC/NASTRAN software.

14. SUBJECT TERMS Piezoelectric Film, Inflatable Structure, Antennas			**15. NUMBER OF PAGES** 200
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)
Prescribed by ANSI Std. 239-18

THIS PAGE INTENTIONALLY LEFT BLANK

Approved for public release; distribution is unlimited

A STUDY OF THE FEASIBILITY AND APPLICABILITY OF SHAPE CONTROLLED SPACE BASED INFLATABLE MEMBRANE STRUCTURES

Craig M. Whittinghill
Lieutenant, United States Navy
B.S., United States Naval Academy, 1995

Submitted in partial fulfillment of the
requirements for the degrees of

**MASTER OF SCIENCE IN
SPACE SYSTEMS OPERATIONS
and
ASTRONAUTICAL ENGINEERING**

from the

**NAVAL POSTGRADUATE SCHOOL
September 2000**

Author: _____
Craig M. Whittinghill

Approved by: _____
Brij Agrawal, Thesis Advisor

_____
Donald v.Z. Wadsworth, Co-Advisor

_____
for Max F. Platzer, Chairman
Aeronautics and Astronautics Department

_____
Rudy Panholzer, Chairman
Space Systems Academic Group

THIS PAGE INTENTIONALLY LEFT BLANK

ABSTRACT

Inflatable structures used for space applications offer mass, volume, and cost savings to spacecraft programs, allowing larger space structures to be built. For certain space applications, there are advantages to using large structures. For example, antennas achieve higher gains when they are increased in size. Higher gains equate to higher data throughputs. Therefore, inflatable structures offer improvements in performance to certain types of spacecraft components.

Environmental factors induce surface errors on large inflatable structures. This degrades performance, especially for inflatable antennas. To reduce this degradation, active and passive control systems can be used to sense errors and control the shape of the antenna. One method of applying an active and passive control system is by using piezoelectric films that are either attached to or are part of the inflatable structure.

The research performed for this thesis explored the theoretical performance of a large inflatable space-based antenna via spreadsheet analysis and the physical performance of a piezoelectric film via laboratory experimentation. For the laboratory experiment, the film was attached to a drum and varying internal pressures and voltages were applied. Also, in order to validate the experimental results, an analytical model was created using MSC/PATRAN and MSC/NASTRAN software.

THIS PAGE INTENTIONALLY LEFT BLANK

TABLE OF CONTENTS

I. INTRODUCTION 1

II. APPLICATION OF INFLATABLE TECHNOLOGY 3

A. USE OF INFLATABLE TECHNOLOGY FOR ANTENNA DEVELOPMENT 3

B. APPLYING INFLATABLE TECHNOLOGY TO SPACE-BORNE COMMUNICATIONS SYSTEMS 9

C. OPERATIONAL USE OF SPACE INFLATABLE STRUCTURE TECHNOLOGY 15

III. EXPERIMENT 25

A. INFLATABLE STRUCTURE EXPERIMENTAL SET-UP 25

B. INFLATABLE STRUCTURE EXPERIMENTAL RESULTS 32

IV. ANALYTICAL MODEL SET-UP AND RESULTS 43

V. CONCLUSIONS 51

APPENDIX A - EQUATIONS USED FOR ANTENNA OPERATIONAL ANALYSIS 55

APPENDIX B - ANTENNA ANALYSIS SPREADSHEETS AND GRAPHS 57

APPENDIX C - LABORATORY EXPERIMENTAL RESULTS AND GRAPHS OF THESE RESULTS 81

APPENDIX D - ANALYTICAL MODEL INFORMATION 91

LIST OF REFERENCES 181

INITIAL DISTRIBUTION LIST 185

THIS PAGE INTENTIONALLY LEFT BLANK

ACKNOWLEDGEMENT

The author would like to thank Professor Guillermo Ramirez, Professor Ramesh Kolar, Professor Donald v.Z. Wadsworth, Jeff Knight, Christian Taranti, and Professor Brij Agrawal for their help and academic guidance with this endeavor and research.

THIS PAGE INTENTIONALLY LEFT BLANK

I. INTRODUCTION

Inflatable structures are becoming the structures of choice for use in large, space-based structures. Inflatables have a long history of development, but not until recently have they received much attention. They offer many advantages that traditional structural materials (metals, for example) do not. One of their major drawbacks, though, is the fact that they are not as rigid as traditional structural materials.

To help maintain an inflatable structures shape, a control system could be developed to sense and correct these shape errors. Piezoelectric films (thin, flexible materials that change shape when an electric field is applied or create an electric field when their shape changes) are potential control devices that can be used to sense and correct shape errors. If this can be accomplished then the uses of large, inflatable structures can be implemented.

One potential use for inflatable structures in space is as antennas. Large antennas could be included on communications satellites without increasing the cost or mass of the satellite if inflatables are used, and data throughput could be greatly increased. The Department of Defense, for one, should be interested in such a technology advance. Therefore, this thesis intends to demonstrate that this technology can be realistically applied and that it offers great advantages to those who use it.

A look into the use of inflatables as antennas will begin this thesis followed by an examination of the improvements this technology can provide a communications system. Then, a discussion of the history, advantages, funding, and current work being done on inflatables will be presented. After this, the experimental portion of this thesis will be

discussed. A description of a piezoelectric film experiment's set-up and results will be described and presented, and then the efforts made to establish an analytical model will be provided. Finally, conclusions will be drawn.

This thesis intends to show the advantages of using inflatable technology for Department of Defense uses and to demonstrate the potential for using piezoelectric films as part of a shape control system.

II. APPLICATION OF INFLATABLE TECHNOLOGY

A. USE OF INFLATABLE TECHNOLOGY FOR ANTENNA DEVELOPMENT

Antennas in space are a necessity for communications systems utilizing satellites. Today, there are a number of applications for large aperture space-based antennas. Some of these are Very Long Baseline Interferometry (VLBI), mobile communications, earth observation radiometry, active microwave sensing, and space-based radar (Freeland and Bilyeu, p. 1-2). However, placing large antennas in orbit is not easy or cheap. To make large space-borne antennas practical and affordable, inflatable, thin walled structures are being developed. Inflatable structures offer many advantages over traditional metallic, rigid structures. These will be covered later in this work, but now a look at what types of structures are being considered for manufacture and those that have been manufactured will introduce the reader to this new and growing field. To accomplish this, two programs, the Advanced Radio Interferometry between Space and Earth (ARISE) and the Inflatable Antenna Experiment (IAE) programs will be examined. However, these two programs use the same basic structure and antenna type. Before beginning an in-depth look at ARISE and IAE, a look at some other alternative antenna types is appropriate.

Research for this thesis has produced three different types of potential inflatable, space-based antennas. They are an inflatable phased array antenna, an inflatable parabolic reflector antenna with phased array feeds, and a similar parabolic reflector antenna. The latter two will be addressed together. The shapes needed to attain these

types of antennas are achieved using inflation pressure and manufactured gores that when attached together and inflated produce a desired shape. Inflatable phased array antennas (without a reflector) have been proposed as a viable solution for making large space-based antennas with apertures up to fifty-five meters in diameter. This inflatable antenna would offer all of the advantages of conventional phased arrays (multiple, steerable beams, for example), but it would not retain the desirable traits of a continually inflated space structure because it would have to be rigidized.

> Once in space, the antenna would be inflated and rigidized. The rigidization would take place by constructing the antenna using materials that solidify over a matter of hours when exposed to either the ultra-violet light or some other material solidification method. This would prevent distortion of the antenna in space when the gas used for inflation dissipates (Kunath and Sharp, 1991, p. 2).

The problem with using rigidization for the whole structure is that the inflatables lose the traits of ruggedness and damped dynamics, which are inherent in inflatables that are not rigidized (Palisoc et al, 1998, p. 748). This type of rigidized inflatable antenna would also become very complex with increasing size (Kunath and Sharp, 1991, p. 1). Therefore, the parabolic-shaped inflatable antennas offer a more attainable configuration in the short term, and consequently, more work has gone into their development.

Parabolic inflatable antennas that are being produced today include a lenticular structure with a torus and struts for support. The torus and struts are rigidized after inflation in orbit, and the lenticular structure is kept inflated with gas for the life of the satellite. The lenticular structure consists of a reflective parabolic surface and a symmetrical, radio frequency transparent canopy. The two parabolic surfaces are joined

together at the torus, which encircles the lenticular structure at the joining of the parabolic surfaces and attaches itself to the lenticular structure by means of adjustable ties. The struts then connect the antenna to the rest of the spacecraft (Cassapakis and Thomas, p. 5). Microstrip array feeds can be placed in the antenna structure so that multiple beams are available for use (Hoferer, 1998, p. 1452-1453), or the antenna can be configured for just one beam. The basic antenna structure is the same for either configuration. Figure 1 shows an artist's conception of such an antenna. This picture was found on the L'Garde, inc. webpage (www.lgarde.com).



Figure 1. Artist's Conception of an Inflatable Parabolic Antenna.

There are two major hurdles for this type of antenna to overcome: meteroids ripping holes in the surface of the structure and surface errors.

Assuming that the inflatable antenna can be deployed properly and attain its desired shape, which IAE showed was possible, the antenna must maintain its desired shape for the remainder of its design life. There are many reasons why inflatable

antennas would lose their desired shape, and this topic is addressed in a later chapter. However, one major possibility of shape loss would come from deflation. Meteroids could tear holes in the antenna, and the gas used to inflate the antenna could escape. Replacement gas is therefore needed to maintain the shape of the antenna and to keep it inflated. Analysis of the meteroid environment has led to the conclusion that inflated systems could remain operational for ten or more years. This is due to the low pressures needed to maintain the shape of the antenna and the low weight of the gas system (Palisoc et al, 1998, p. 748). The low pressures required stems from the fact that these antennas will be in a zero gravity environment in which a small internal pressure is sufficient to provide stiffness and shape (Criswell et al, p. 1046). In fact, it is estimated that a 10-meter inflated antenna system with a ten year design life would have a mass of only 145 lbm and a 30-meter inflated antenna system with a ten-year design life would have a mass of only 190 lbm (Thomas and Friese, p. 66). These values are lower by hundreds of pounds (mass) than deployable antennas made from metals of comparable size. So, having a realistic ability to maintain inflation over the design life, only surface errors remain to be resolved.

Surface errors in the antenna reflector surface can come from a number of sources, and there are a number of ways to correct these errors. All of this is covered in a later chapter, but the precision that a reflector surface needs to have to be an effective antenna should be addressed now. Good antenna performance requires that the rms (root mean square) surface accuracy of the antenna be between sixteen and twenty times better than the wavelength (λ) being used (Ulvestad, Linfield, and Smith, p. 5). For frequencies of 6.32 GHz ($\lambda = 47.5$ mm) and 8.4 GHz ($\lambda = 35.7$ mm) , the rms surface errors would

have to be kept to 2.4 mm and 1.8 mm, respectively. As an example, a 10-meter diameter antenna with a 0.77 mm rms error would have a gain of 79% of its theoretical maximum at 15 GHz which corresponds to a 20 mm wavelength (Thomas and Friese, p. 1). In later analysis, a 1 mm surface rms error is assumed, and the gain of antennas using different frequencies is calculated taking this error into account using the Ruze equation (Cassapakis, Love, and Palisoc, 1998, p. 456).

Also of concern for these large structures is atmospheric drag. If, however, these structures are placed above 750 km, there is no significant atmospheric drag (Cassapakis, 1999, p. 5). Having discussed this type of antenna in general terms, it is now appropriate to examine one use of this structure and one planned use of this structure.

The IAE was a NASA project launched from the space shuttle Endeavour as part of mission STS-77 on May 20, 1996. It was deployed in a Low Earth Orbit via a Spartan 207 retrievable satellite and remained operational for ninety minutes until jettisoned (NASA, p. 2). The reflector itself was fourteen meters in diameter, had twenty-nine meter struts, and weighed less than 200 lbs (Acree, p. 4). The design goal of the IAE was to achieve a surface precision of 1 mm root mean square error while on orbit (Freeland, p. 4). This was almost achieved, but a root mean square error of a few millimeters resulted (Freeland et al, p. 6). Still, even though no actuation system was used, the IAE could be used with frequencies around 5 GHz. This reaches into the C-band of the RF spectrum, and it could be used for mobile communications. Also, the stowage size of this antenna was roughly the size of an office desk (Freeland et al, p. 6). This experiment, the first of its kind, showed that inflatable reflectors in space are achievable, and its performance is helping the development of inflatable structures for future use.

The ARISE program is under development, but it is planned to be a Very Long Baseline Interferometry mission that will consist of at least one 25-meter diameter radio telescope that will have basically the same structure as IAE and other lenticular inflatable antennas. It will be placed in a Highly Elliptical Orbit (HEO), and the spacecraft will have a mass of approximately 1700 kg. The expected launch date is in 2008 (Chmielewski and Ulvestad, p. 2). ARISE will observe frequencies up to 86 GHz, meaning that the root mean square surface error needs to be approximately 0.175 mm. In 1999, L'Garde built a 7-meter inflatable antenna that had a 1.7 mm rms error, but it predicts that it can reduce that to 1 mm for a 25-meter reflector with appropriate development effort (Chmielewski, p. 5). More work and development is needed to make ARISE a reality. A later chapter will address the current work and funding for this technology, and another chapter will address a potential actuation method for surface accuracy maintenance. IAE and ARISE are both helping the development of inflatable structures and especially inflatable antennas. Because of the continuing maturation of this technology, the Department of Defense can benefit greatly from inflatable structures in space.

The next chapter will explore how inflatable antennas can improve data rates for space-based communications systems. A mobile, disadvantaged user (low power, small antenna) can receive extremely high volumes of data quickly if large inflatable antennas are used in space. There is one major drawback to using them (reduced footprint size), but the enhanced communications capabilities to the military are immense. With continuing research, an extremely viable group of materials for communications systems antenna design will be available.

B. APPLYING INFLATABLE TECHNOLOGY TO SPACE-BORNE COMMUNICATIONS SYSTEMS

Inflatable antennas offer many advantages to a satellite system. They are lightweight structures, can be stowed compactly, and are relatively cheap. Conventional antenna structures cannot compete with inflatable structures in these categories. Inflatable structures now make it feasible to put larger antennas in space. Larger antennas offer many advantages to ground users, especially mobile, disadvantaged users. The link can be closed for many more users, and the data rate throughputs that they can receive is excellent. To confirm these conclusions, a few link budget models were created and evaluated.

Using Excel, six different models were created. Two were Intelsat VII link budgets, and four were the Defense Satellite Communications System (DSCS) III Service Life Enhancement Program (SLEP) link budgets. These two satellite systems were selected because the military uses them for communications. One is commercially owned (Intelsat VII) and the other is a Department of Defense asset (DSCS III). Since most of the specifications for these two satellite systems and their operations were available in open literature, the link budgets have some real use numbers in them. Values for certain operational parameters (e.g., bandwidth and power for specific operational scenarios) are not available, so these were handled parametrically or nominal values were employed. Meaningful comparisons and conclusions can still be reached by this analysis. The environment used for this analysis is benign. No jamming or multiple user

considerations were modeled. Other constraints had to be applied to make the link budget analysis possible.

For the Intelsat VII link budgets, Intelsat 702 was selected, and for the DSCS III link budgets, the SLEP program was selected. Using Communications Satellites 1958-1995 produced by The Aerospace Corporation and a series of briefs produced by the U.S. Naval Space Command, bandwidths, frequencies, and antennas, for example, were extracted and entered into the models. These models can be seen in Appendix B, and to keep this chapter succinct, they can be referenced for exact data used in this analysis. The gray box entries are values entered into the model, and the rest of the boxes are solved for using equations that can be found in Appendix A. Of note, the edge of the ground footprint of the satellite system, not the center, was used in the analysis. This shows the robustness of the analysis. The Intelsat 702 spot beam and the DSCS III SLEP Channel 3 were used in the model. Also, the ship and ground antennas used for this analysis are not easily extracted from the models. For the Intelsat 702 models, the Navy Commercial Wideband SATCOM Shipboard antenna (2.7 meters) and the AN/FSC-78(V) (18.29 meters – ground antenna) were used. For DSCS III SLEP, the AN/WSC-6(V)5 (2.36 meters) was used for the shipboard antenna, and the AN/FSC-78(V) was used again for the ground antenna. The AN/WSC-6(V)5 is listed as a seven-foot antenna, but, according to Ray Gajan of the U.S. Naval Space Command, the diameter of the antenna is actually seven and three quarters feet in diameter (2.36 meters). For the disadvantaged user models using the DSCS III SLEP satellite system, the ground antenna used was the AN/FSC-78(V), and the disadvantaged user antenna was selected to be 0.25

meters (9.85 inches). With these assumptions presented, it is now appropriate to elaborate on the inflatable antenna aspect of the models.

For the inflatable antenna, two model parameters were varied. The diameter of the antenna was increased in 5-meter increments from that of the existing Intelsat 702 and DSCS III SLEP antennas to a maximum of forty meters. The second parameter was the rms surface deviation from ideal. Assuming that an rms surface error of one millimeter can be achieved on an inflatable antenna in space by use of some sort of actuation system, a degraded antenna gain was calculated for each antenna diameter. Of note, the space antenna for Intelsat 702 (existing on satellite now) and the inflatable antennas that replaced it in the analysis were both the transmitting and receiving antenna. For DSCS III SLEP equipment (existing on satellite now), a separate receive multi-beam antenna was used in the analysis since it has receive and transmit multi-beam antennas for channel 3. The inflatable antennas used to replace the existing DSCS III SLEP antennas in the analysis were used for both transmitting and receiving. The main advantages of using a larger antenna are that a weaker signal can be sensed at the satellite and more signal power can be received at the ground antenna. This is due to the increased gain of the antenna, due to its size. The result is more data throughput, since most disadvantaged users (ship or mobile) are not throughput-limited by the amount of bandwidth they are using but by the amount of received power. A major drawback to using larger space-borne antennas to improve link performance is that the ground footprint is diminished, so that only users in a smaller geographical area on the earth can access the space-borne antenna. With this in mind, an evaluation of the performance of the inflated antennas is in order.

Three relations are used to calculate throughput (i.e., information bit rate) for a space-based antenna system. One uses the received signal power C and required Eb/No in order to calculate throughput. Another relation uses channel bandwidth and received signal to noise power ratio (Shannon's limit) to calculate throughput. The third uses bandwidth, signal modulation, and a waveform shaping or roll-off factor to calculate throughput. All of these relationships can be referenced in Appendix A. These three throughput relationships help in analyzing the effectiveness of a larger antenna. As will be seen, a large increase in space-borne antenna size will not do much for current ship configurations. However, the future disadvantaged user will benefit immensely from a larger space-borne antenna as will future ship configurations.

Appendix B shows the graphs of the throughputs based on the three relations mentioned earlier and antenna size. When examining these graphs, it is important to note that the maximum data throughput that can be achieved for a given antenna size can be no greater than the lowest throughput indicated by the three curves on the graph. Beginning with the Intelsat 702 and DSCS III SLEP ship-to-ship and shore-to-ship graphs, an examination reveals that they all present a similar picture. If there were no bandwidth limitations, the throughput could be vastly improved by increasing the size of the satellite antenna. However, this is not currently practical. The throughput theoretically could be improved somewhat up to Shannon's channel capacity limit, but the practical achievable throughput is much lower than this limit. Increasing signal power only improves the bit error rate beyond this threshold (Wadsworth). Larger antennas for this application provide little improvement in capability. Only small changes in antenna size make any difference. In fact, the throughput is optimized with a

satellite antenna diameter somewhere between the Intelsat or DSCS III antenna and a five-meter antenna. Of note, the DSCS III SLEP graphs and disadvantaged user graphs all show an antenna diameter of 0.711 meters for the first antenna diameter. This is the transmitting antenna diameter, but both the transmitting and receiving antennas were used in the analysis. Therefore, the graphical representation of these scenarios is not completely accurate, but they give a good approximation of throughput capabilities for the actual DSCS III SLEP antenna used. So, a small change in size maximizes throughput, but inflatable antennas could still be used to reduce weight, save cost, and provide numerous pre-deployment stowage options. However, the disadvantaged user who has a quarter of a meter antenna benefits greatly from larger space antennas.

The disadvantaged user has many limitations. Disadvantaged users are mobile so it is difficult to carry heavy and bulky equipment, and they have little power to transmit signals. With this in mind, two models were set up using the DSCS III SLEP satellite. The two models developed are a disadvantaged user to a disadvantaged user model and a ground to a disadvantaged user model. The maximum transmit power of a disadvantaged user was set at five watts. A soldier on the ground could carry a communications unit that meets these criteria. Appendix B can also be referenced for the disadvantaged user graphs and spreadsheet models. From that data, a disadvantaged user could send data to a disadvantaged user via a forty-meter space borne antenna with a data rate of approximately thirteen Mbps. That value is about eight T-1 lines, and this is not even the practical limit. With a larger space antenna, even more throughput could be achieved. A shore link to a disadvantaged user would provide the full potential throughput with a space antenna somewhere greater than forty meters in diameter. For a forty meter

antenna, the data rate is roughly twenty-seven T-1 lines. So, the throughput capability of a disadvantaged user would be tremendous. However, there is a drawback to using this larger antenna.

The geographical area of a satellite footprint is diminished with increasing satellite antenna size. In fact, frequency and antenna size affect footprint size, but since the frequencies are fixed in these models, only antenna size affects the footprint size. Now, some clarification is in order. The access field of view of a satellite is unchanged regardless of antenna size or frequency. The coverage field of view is what changes. So, a ground site would be in the field of view of what the satellite can see regardless of antenna size or frequency, but it may not be in the field of view of the satellite beam that can send or receive data. This would become a large factor in the disadvantaged user scenario. For example, for both disadvantaged user scenarios, the up-link footprint goes from approximately 1,500,000 square kilometers to 1,000 square kilometers if a forty meter antenna is used. For the down-link, the footprint goes from approximately 20,000,000 square kilometers to 5,000 square kilometers if a forty meter antenna is used. These are large differences. An accurate pointing system would have to be used on the ground and on the satellite. However, this is a small price to pay for such a large improvement in throughput. In fact, 1,000 square kilometers may be a major theater of war, especially in this age of low intensity conflict. The communications link produced by the satellite would be limited to those users in a certain geographical location, but the signal power provided to those users would be substantial, allowing many users to share that signal power and still maintain high data rates. With these advantages, the application of inflatable technology is extremely attractive.

Even though disadvantaged users with small antenna benefit greatly from a larger satellite antenna, it cannot hurt other users from using them as well, as long as accurate pointing schemes and mechanisms were present. A current ship configuration will have its throughput maximized if, for example, a forty meter satellite antenna were used. It would just need to be in the satellite's footprint. With beam pointing from the satellite and accurate tracking and pointing of the ship antenna, this is possible. In fact, ships could use the smaller quarter of a meter antennas. The space on a ship is limited, so any savings in antenna size are attractive. Using inflatable structures makes this concept a possibility. Large antennas will be able to be used in space due to the advantages and savings inflatable structures provide. More research and work is needed, though, to further validate this technology.

C. OPERATIONAL USE OF SPACE INFLATABLE STRUCTURE TECHNOLOGY

Inflatable space structures are a promising technology that has received renewed interest in recent years. These structures are made of thin, flexible materials that can be inflated into a predetermined, manufactured shape. Research and development began on these structures in the 1950's. Goodyear developed technology demonstrations on structures such as an inflatable search radar antenna, a lenticular inflatable paragoric reflector, an inflatable pyramidal horn, and a radar calibration sphere. All of these demonstrations were developed in the late 1950's, but they were not the first flight-tested inflatable structures (Freeland and Helms, 1999, p. 4-7). The first flight-tested inflatable

structures were balloons that were part of NASA's Echo program. Echo was a passive communications relay program, and seven balloons were launched between 1958 and 1964. Over twenty years passed before another inflatable structure was successfully used in space, except for the inflatable re-entry vehicle decoys used beginning in the late 1960's (Katuin, 1999, p. 1). These decoys were used to simulate the radar and IR signatures of re-entry vehicles. Interestingly, though, they were the first flight-tested inflatable structures that were configured in a shape other than a sphere (Freeland and Helms, 1999, p. 9). It wasn't until the mid-1980's until new inflatable structures were flight-tested.

In 1984, NASA unsuccessfully deployed an inflatable calibration target for a Ku-band radar. Then, in 1985, the Soviet Union used two inflatable balloons in its Venus missions, Vega 1 and Vega 2 (Katuin, 1999, p. 1). Over ten years passed before inflatable structures were used again, but there were significant technology demonstrations in the 1980's. For example, the European Space Agency developed a 6-meter inflatable very long baseline interferometry antenna, an inflatable telescope sunshade support structure, and a 10 by 12 meter inflatable land mobile communications reflector antenna. L'Garde, Inc. and the United States Air Force developed an inflatable large offset reflector structure in the late 1980's (Freeland and Helms, 1999, p. 10-13). However, it wasn't until 1996 that another inflatable structure was launched into orbit. On May 20, 1996, NASA launched the Inflatable Antenna Experiment (IAE) from the Space Shuttle Endeavour. The IAE was a 14-meter diameter antenna that was used to test the potential of using inflatable structures as antennas (Katuin, 1999, p. 1). The mission was a success, and there are more inflatable missions on the horizon.

One newly developed inflatable structure is part of a United States Air Force project that will use lasers to track an inflated sphere target. The sphere has a 12-meter diameter with a skin thickness that is thinner than a human hair and is silver in color. L'Garde, Inc. constructed the sphere in four months, and its cost was $500,000. (Robbins, 1999, p. 1). A near future use of this technology is an inflatable solar array that will be part of the DS4/Champollion mission in 2003. This mission will be the first to land on and study the center of a comet (Acree, p. 15). Inflatable technology has a long and mostly successful history, and there is current work being done with this technology as well. In fact, inflatable technology is rapidly developing, and its uses are almost endless.

There are many potential applications for inflatable structures in space. Among these are space suits, habitats, antennas, attenuation systems, reflectors, covers and sun shields, solar arrays, and radars (ILC Dover, 1999, p. 8). Other possible uses are for rovers with inflatable wheels, sail occulters, infrared telescopes, and radiometers (Chmielewski, 1999, p. 17, 21). Science instrument support structures, solar cell support structures, large lightweight trusses, and solar collectors and concentrators are also possible uses (Freeland and Helms, 1999, p. 18). The Department of Defense, NASA, and commercial industry are even working on developing phased array antennas (Katuin, 1999, p. 6). In fact, the Air Force Research Laboratory initiated analytical and experimental evaluation of membrane phased array antennas in fiscal year 1998 (Acree, p. 1). Other types of more conventional structures could be used to try to achieve most of these applications, but there is a reason why there is considerable interest in using

inflatable space structures. Inflatable space structures have distinct advantages over conventional space structures.

Inflatable structures have low system mass, low development and production cost, low packing volume, packing flexibility, reduced system complexity (high reliability), controlled deployment, components that can be rigidized, long life, and design flexibility (many different configurations and shapes are possible) (ILC Dover, 1999, p. 10). These are all advantageous attributes for a space structure to possess, but perhaps the most advantageous attribute, that has not been mentioned yet, is low cost.

Inflatable space structures offer cost savings to a space system. Lower mass and stowed launcher volume may allow a smaller launch vehicle to be used. This will save a space system a considerable amount of money since a large portion of a space system's cost comes from its launch platform. In fact, a stowed inflatable space structure is ten to one hundred times smaller than a stowed mechanically deployed structure, and its mass can be up to ten times smaller than a conventional structure (Acree, p. 6). For example, in 1992 fiscal dollars, if using an inflatable space structure allowed a satellite to be launched in an Atlas G or a Centaur instead of a Titan IV, eighty-two million dollars would be saved in launch costs (Larson and Wertz, 1992, p. 731). Inflatable space structures offer possibilities like this. They are also inherently cheaper than conventional space structures. For example, an operational version of the IAE could be developed for approximately ten million dollars (in 1996), but a conventional space structure with the same capabilities as the IAE may cost as much as two hundred million dollars (Gipson, 1996, p. 1). Overall, inflatable space structures are ten to one hundred times cheaper than conventional structures (Acree, p. 6). It is postulated that in 2003, a UHF to X-band

antenna with millimeter surface accuracy will have a recurring cost of seven million dollars for a 10-meter antenna and ten million dollars for a 25-meter antenna (Acree, p. 4). These cost reductions are attractive, but there are even more advantages and attractive qualities that inflatable space structures offer to space systems.

Inflatable space structures are not susceptible to acoustics and vibrations caused by launches, and they can be deployed without using extravehicular activity. They also have excellent dynamics while in orbit, and they tend to have relatively small surface errors in orbit since gas pressure tends to perfect bodies of revolution (Friese and Thomas, p. 1). Also, inflatable structures "offer better thermal control opportunities than open structures. The radiative exchange between the sides of the inflatable can sharply reduce temperature non-uniformities" (Thomas and Friese, p. 1). Another advantage is the availability of materials and their abilities to be rigidized (inflated and then hardened into a firm shape). Some materials used for producing inflatable structures are polyesters, fluoroplastics, and polymides. An example of a polyester is polyethylene terephthalate. Examples of fluoroplastics are Teflon (PTFE and CTFE), fluorinated ethylene propylene (FEP), and polyvinylidene fluoride (PVDF). An example of a polymide is Kapton. Also, all of these types of materials are either thermosets or thermoplastics. These traits allow some forms of rigidization to be possible.

A thermoset is a material that when heated maintains its shape, and the process is not repeatable. A thermoplastic is a material that will melt when heated and solidify when cooled. This process is repeatable (Bradford, 1999, p. 4). Some methods that use these traits and other means for rigidization are fabric impregnation of resin that is cured by ultraviolet light exposure, fabric impregnation of water soluble resin that causes

rigidization upon water evaporation, fabric impregnation with a resin that rigidizes when cooled below its glass transition temperature, application of heat to cure plastic resin, and application of strain to aluminum laminate beyond its yield point (Freeland, Bilyeu, and Mikulas, p. 5). Rigidization may be desirable because some space inflatable structures, if not rigidized, will require relatively high pressures to maintain their shape. If leaks develop from holes caused by meteoroids, for example, the amount of gas needed to keep the structure's shape may not be practical. Larger inflatable structures that will not require high pressures for inflation will not have the same problem. Their inflation pressure will be around 10^-7 psi (ILC Dover, 1999, p. 11). In fact, "the operating pressure of large antennas is sufficiently low so that they can operate in the meteoroid environment for many years. The replacement-inflatant weight is not excessive" (Friese and Thomas, p. 2). So, rigidization is not necessary for these structures. However, if surface accuracy is important to a particular inflatable structure, then shape control may be necessary to maintain its shape.

There are many sources of surface error for an inflatable structure. Some of them are "material stiffness properties and areal variation, material thickness and areal variation, creep, moisture effects, material 'wrinkling' or creasing due to handling and packaging, fabrication, analytical shape prediction, edge support conditions, pressure level, thermal distortion, and gravitational effects in earth testing" (Bilyeu, Freeland, and Mikulas, p. 9). With so many sources of error, a capable actuation system may be needed for certain applications of inflatable space structures. Some possible actuation methods are adjusting edge radial displacements, controlling internal pressure, using thermal gradients across the structure surface, and incorporating piezoelectric materials into the

body of the structure (Freeland, Bilyeu, and Mikulas, p. 11). Piezoelectric materials, materials that change shape in the presence of an electric charge or produce an electric charge when their shape changes (Shields, p. 7), offer a particularly attractive actuation method because not only could they be used to change the shape of the structure, they could also be used to sense when surface errors arise. This could lead to an active control system.

There are a few ways this active control system could be activated to produce an active control system. Two of these methods involve using an electron gun to control a piezoelectric film and using discrete electrode coatings on a piezoelectric film (Bradford, p. 2). The electron gun would scan the film, inducing an electric charge where needed to maintain the structure's shape (Clayton, p. 2). This scheme doesn't account for feedback of the structure's shape. Leads or some other device would have to be connected to the structure. The discrete electrode coatings, or patches of coated piezoelectric material, could be connected to a control system via leads or some other device that could deliver electric charge and sense it also. This seems to be the most practical. Another method would entail piezo-induced strains on the tie rods, if they exist, of a structure. The implementation of this method would be similar to that of the discrete electrode coatings (Salama et al, p. 5). Also, these types of materials are widely available. Of the previously mentioned materials, PVDF, at least, can have the piezo effect induced into it by permanently polarizing its dipoles by applying a high voltage at high temperature. In general, polymers can undergo this treatment to make them piezoelectric (Salama et al, p. 2). Of note, research has been done to develop materials with a large piezoelectric response suitable for inflatable structure shape control. This research produced several

compositions of pervoskite $PbZr_{1-x}Ti_xO_3$ (PZT) for NASA for use in shape control applications (Neurgaonkar and Nelson, p. 1, 4, and 31).

Inflatable space structures are a developing, attractive technology that will allow missions that were impractical or impossible with conventional technology to become possible. The only other technology that claims that it is an effective alternative to inflatable technology for developing structures in space is space robots used for the assembly of structures. This claim does not take weight or stowed volume into account (Kimura et al, p. 14). If robots did assemble structures, the structure's components would still have to be placed into orbit. If these components weigh the same as conventional components, then there would be no savings in launch cost. Inflatable space structures are an attractive technology that has many applications and much work is being done in this field today.

Current and past funding levels for inflatable research and development are telling signs that there is a considerable amount of interest and enthusiasm regarding this technology. In fiscal year 1997, ten million dollars was spent at the Jet Propulsion Laboratory, NASA centers, the Department of Defense, and industry on inflatable research and development (Chmielewski, 1999, p. 8). In fiscal year 1998, this number grew to twelve million dollars (Chmielewski, 1999, p. 9). In fiscal year 1999, the funding number grew to twenty and a half million dollars (Chmielewski, 1999, p. 10). It is projected that, beginning in fiscal year 2000, inflatable structure funding will double every year (Chmielewski, 1999, p. 22). So, with funding on the increase, many industry organizations are becoming involved in the research and development of inflatable structures.

NASA and the Department of Defense are two of the main players in this technology field, but the number of corporations involved is growing. In 1995, L'Garde, Inc., SRS, Aerospace Recovery Systems, ILC Dover, and Thiokol were the main private organizations that had demonstrated large inflatable structure technology capability (Satter and Freeland, 1995, p. 1). In 1999, Winzen Engineering Inc., Sigma Labs Inc., ITN Energy Systems Inc., Vertigo Inc., Millimeter Wave Technology Inc., United Applied Technologies Inc., Adherent Technologies Inc., Energen Inc., Triton Systems Inc., Aeroplas Corp., and Raven Technologies could be added to the list of organizations with promising inflatable structures technology (Freeland and Helms, 1999, p. 16). All of these corporations are contributing to the body of knowledge of inflatable structures. Their work is paving the way for future uses of inflatable technology.

The current work being conducted in this technology field is the validation of inflatable structures. For example, the Air Force Research Laboratory is conducting work on controlled deployment (of structures from 8 meters to 200 meters), the validation of analytical models and tests, controlled structure interactions (pointing, for example), creating precision surfaces, and enhancing application performance. Other areas that this lab plans to address are creating rigidizing structures for space, developing membranes with good lifetime performance, and enhancing lifetime system performance (Acree, p. 28). With efforts like these, missions proposed for the future will become realities.

NASA has even set some goals for its inflatable structures program. These goals for the mid-term (2000 – 2005) are to develop technology for solar sails, antennas, rovers and to transition sunshields, solar arrays, and radars to industry (Chmielewski, 1999, p. 3). Its far-term goals (2005 – 2020) are to transition solar sails and antennas to industry

and to develop the Gossamer spacecraft architecture (NASA program that uses inflatable technology) (Chmielewski, 1999, p. 3). In fact, NASA is proposing that inflatable structures will be able to assist in a list of varied missions. These are imaging remote galaxies, detecting life on extrasolar planets, monitoring the earth using high resolution, imaging extrasolar planets, imaging active galactic nuclei, sending video from deep space, monitoring earth's environment, investigating planet subsurfaces, communicating optically, providing solar power in deep space, taking short time travel trips, non-Keplerian viewing, transporting cargo to Mars, and developing infrared astronomy (Chmielewski, 1999, p. 2). With goals and aspirations like these, NASA is pushing the development of this technology, and hopefully its near future timetable of inflatable projects may occur according to plan.

As of 1999, NASA planned to have a number of inflatable structures in space through 2020. Some of these are a radar by 2003, the NGST sunshield by 2007, solar sails for a Mercury orbiter by 2007, the Arise satellite by 2008, an interstellar probe by 2010, deep space antennas by 2010, and large optics by 2020 (Chmielewski, 1999, p. 5). This list is ambitious, but with current trends, it may not be unrealistic. However, there is still much work to be done.

Some of the areas that the Air Force Research Lab plans to do work in are areas of general improvement that need to be done to help validate this technology. ILC Dover lists five areas of potential improvement. They are testing and developing rigidizable materials, controlled deployment mechanisms, structural designs, adaptive structure designs, and manufacturing methods (ILC Dover, 1999, p. 38). With continuing effort, these improvements will be made and this technology will become completely validated.

III. EXPERIMENT

A. INFLATABLE STRUCTURE EXPERIMENTAL SET-UP

To begin to explain the work done at the Naval Postgraduate School (NPS), this section will discuss the equipment and procedure used for this experiment. The facility used was the Spacecraft Research and Design Center (SRDC) in Halligan Hall at NPS. The procedure used for this experiment was adapted from the work of Dr. Moktar Salama and Dr. C. P. Kuo of the Jet Propulsion Laboratory (JPL). Parts of the procedure were developed exclusively for this experiment, though. To begin this chapter, however, an in depth look at the equipment used for this experiment will be presented.

The pieces of equipment used for this experiment were procured from various sources. They were made in-house, purchased from industry, borrowed from other departments at NPS, or taken from the existing inventory of the SRDC. The major pieces of equipment used were a polyvinylidene fluoride (PVDF or Kynar) membrane, a polyvinyl chloride (PVC) drum with clamp, a tank of pressurized nitrogen gas, a low pressure air regulator, a voltage source and computer interface used for taking measurements (d-Space), an amplifier, copper tape, a displacement measurement laser, a low current power source, an oscilloscope, and various wires and tubes to connect it all together. The PVDF was the principle piece of equipment used since its response to different voltages and pressures was being studied. Figure 2 shows the drum, PVDF, and laser set-up.



Figure 2. Experimental Set-Up.

Membranes were purchased from a company called Measurement Specialties, Inc. The PVDF membranes are 52 micrometers (0.0020488 in) thick cut in a circular pattern with a 26.65 cm (10.5 in) diameter. A lead for a voltage source attachment was extended from the circular pattern, making the membrane look somewhat like an apple with its stem. The membranes are piezoelectric, poled to create a mechanical response (contraction or expansion) in the "3" or thickness direction when an electric field is applied. On both sides of each membrane is a thin coating of NiCu alloy, used as a conductor to apply an electric field to the membrane. To conduct the experiment, one membrane was attached to a PVC drum. A schematic of the experiment and its components can be seen in Figure 3.



Figure 3. Schematic of Experiment.

The drum has two basic parts. These parts are the base and the lip. The base is a cylinder that is open on one end and closed on the other. The outer diameter of the cylinder is 22.84 cm (9 in) and the inner diameter is 20.30 cm (8 in). The depth of the cylinder is 12.70 cm (5 in). The lip is rigidly attached to the cylinder on its open end and has an outer diameter of 26.65 cm (10.5 in) and an inner diameter of 21.57 cm (8.5 in).

The lip's thickness is 0.63 cm (.25 in). The lip has twenty-four 0.32 cm (0.125 in) diameter holes spaced evenly around it so that a clamp can be fastened to the lip. Placing the membrane between the lip and clamp secures the membrane so that the area from 10.79 cm (4.25 in) from the center of the membrane to the outer edge of the membrane for all 360 degrees of the circle is rigidly fixed. Twenty-four screws and nuts were used to attach the clamp. This didn't make the drum and membrane airtight, but it was made tight enough to hold enough nitrogen so that an air regulator could maintain a constant pressure.

A tank of nitrogen gas was used to provide the gas needed to pressurize the drum and membrane. A low-pressure gas regulator was attached to the nitrogen tank to supply the needed pressure to the drum and membrane. The regulator used was a Matheson ® Gas Products regulator model number 8-2. It is rated to receive pressures up to 20.7 MPa (3000 psi) and deliver pressures up to 20.7 KPa (3 psi). The tank offered enough nitrogen for the experiment, and the regulator supplied the proper amount of pressure to the membrane. Varying pressures caused varying displacements in the shape of the membrane, but applying an electric field to the piezoelectric membrane would also cause membrane displacements.

To apply an electric field, a voltage source was used. This was accomplished using d-Space. A program written by Christian Taranti of NPS controlled the voltages delivered to the experiment (0 to 8.5 volts). Since the response of hundreds of volts applied to the membrane was desired, a high gain amplifier was used. The amplifier, a Trek HV power supply amplifier, model 50/750, with a gain of one hundred, was used to increase the voltage applied to the membrane. To connect these pieces of equipment to

the membrane, two strips of copper tape were applied, one on each side, to the "stem" of the membrane. Leads were soldered onto the copper tape, and wires were used to connect the voltage source to the amplifier to the soldered leads of the copper tape. With the copper tape adhesive attached to both sides of the membrane, a positive and negative lead could be attached to the membrane. In this experiment, either the positive or the negative lead was attached to the side of the membrane facing away from the inside of the drum, and then the other lead was attached to the side of the membrane facing toward the inside of the drum. This will be important later for the discussion about the reaction of the membrane to the applied electric field. So, when an electric field was applied to the membrane, further displacements occurred. To measure these displacements, a laser measurement system was used.

A laser made by Matsushita Electric Works, Ltd. was used in this experiment. This laser is class II (685 nm wavelength) with a beam projector and receiver in one unit. The model used was an ANR12151, which has a measurable range of +/- 50 mm. The output of the laser measurement system ranges from –5 Volts to +5 Volts. So, a 1 mV reading would theoretically equate to a 10-micrometer displacement. To operate this laser, a Power Designs Inc. transistorized power supply, model number 2015R, was used. It provides a voltage range of 0-20 Volts DC at 0-1.5 Amps. For this laser, the power supply was set at 15 Volts DC at 0.3 Amps. For a stationary target, like this one, this laser will produce the best resolution (20-micrometers) when the lowest speed selector switch setting (10 Hz) is used. Therefore, the 10 Hz setting was used for this experiment. To measure the displacements, the drum and membrane were fastened to a table so that the membrane was perpendicular to the table. The laser was attached to a structure that

placed the projector of the laser facing at the center of the membrane. So, deflections of the center of the membrane could be observed. See Figure 2 for more detail.

To display the displacement information, a Hewlett Packard 500 MHz oscilloscope, model number 54610B, was connected to the laser measurement system. A voltage signal from the laser could be seen on the screen of the oscilloscope when the laser was measuring displacements. The average voltage of the laser signal (256 setting on the Average selector) was used as the reading for general observation purposes. The d-Space system was used to collect the data from the laser measurement device. The same program that set the application voltage was also used to collect the displacement data. Two minutes were allowed to pass to let the membrane settle, and then measurements were taken for intervals of one minute. Approximately 60,000 measurements were taken per minute. These 60,000 measurements were averaged to create a super-measurement. When three super-measurements had been taken that were within a defined (arbitrary) tolerance range (one sixth of $\sqrt{((\Sigma v^2)/n)-((\Sigma v)/n)^2}$ n = number of measurements, v = measured voltage from laser) they were averaged and reported. This tolerance range approximated a steady state value. If one of these super-measurements did not fall within this tolerance range, the oldest one was disregarded, and a new super-measurement was taken until three super-measurements fell within the tolerance range. The three super-measurements were then averaged for a final reading.

Better results may have been found by using more sophisticated equipment that could be set and read more accurately. A laser that has a more fine resolution could be used, or sensors better able to detect micrometer deflections, like eddy current sensors, could be used. A more accurate low-pressure gas regulator or an airtight drum and

membrane apparatus could also be used. Of note, some errors may have been introduced when a 2.54 cm (1 in) diameter circle of VHT brand high-temperature white auto paint (SP-101) was placed on the center of the membrane facing the laser measurement system. This was done because without it, the membrane face, silver in color and very reflective, would not scatter the laser beam enough so that the laser receiver could sense any return from the membrane surface. White reflects light well, and the paint helped scatter the light. This paint was applied at the point of laser beam contact with the membrane so that the laser receiver could sense a return. Therefore, the results of a similar experiment could be more accurate if less is done to the membrane physically and more sophisticated equipment is used.

When taking experimental data, the readings provided by the laser measurement system did not appear to be linear and were therefore not reliable. So, before any measurements were recorded, the laser was calibrated in the lab, and, using this calibration data, a MATLAB m-file, also written by Christian Taranti, was used to convert laser voltage readings into distances.

For each of ten pressure settings (0.1 psi, 0.2 psi, etc.) the laser measurement device was used to measure the deflection of the membrane under pressure loads alone. This was done so that the analytical model could be compared to the experimental results for pressure loading only. This is displayed in the next chapter. To begin the study of the membrane's piezoelectric response to an applied voltage, the pressure inside the drum and membrane apparatus was set using the low-pressure regulator and nitrogen gas tank. Starting at 690 Pa (0.1 psi) and increasing by increments of 1380 Pa (0.2 psi), the pressure was increased to 4830 Pa (0.7 psi). At each pressure, voltage was applied to the

membrane. The voltages ranged from 0-850 Volts, applied at increments of 50 Volts. The actual voltages delivered, however, were 0, 50, 99.5, 148.9, 198.4, 247.9, 297.2, 346.7, 396.1, 445.6, 495.1, 544.4, 594.0, 643.3, 692.9, 742.3, 791.6, 841.1 volts due to line losses. Further data manipulation was conducted in an Excel spreadsheet to calculate the distance the membrane moved from a reference of zero applied voltage at a given pressure with increasing applied voltages.

Several errors, besides that introduced by the white paint, was introduced into the measurements. The laser measurement device has a +/- 0.8 % error, and lighting conditions, laser resolution, inaccurate pressure settings, temperature (gas expansion or contraction), line losses, or noise (vibration) could have contributed to differences in readings. The following section will examine the results of the experiment and analyze the data.

B. INFLATABLE STRUCTURE EXPERIMENTAL RESULTS

This section will discuss the results of the experiment mentioned in the previous section. As mentioned previously, the laser measurement system is not the most accurate sensor that could be used to measure the displacement of the PVDF membrane. However, for every pressure used in the experiment, a general displacement trend was observed for both polarity settings. The membrane's displacement increased or decreased (slightly) by increasing the applied voltage. In other words, the membrane's center got closer to or further away from the laser measurement system when voltage was

applied to it. The data recorded and the graphs constructed from this data can be viewed in Appendix C.

As mentioned earlier, the membrane is coated on both sides by a thin metal layer. The positive electrode is indicated by a plus sign written on it (provided by Measurement Specialties, Inc.). The negative voltage lead was applied to this positive electrode. Voltage was applied creating an electric field with a negative polarity in the direction of the positive electrode (side of membrane facing the laser measurement system) and a positive polarity in the direction of the negative electrode (side of membrane facing the inside of the drum). The displacement of the membrane due to this electric field was in the direction of the laser measurement system. The positive and negative voltage leads were also reversed in position, but the response of the membrane to this configuration resulted only in displacement at 0.1 psig. At this pressure, the force pushing on the membrane was not so great as to hinder the movement of the membrane due to the piezoelectric effect. All other pressures tested did not allow such movement, perhaps due to an increased tension in the membrane that could not be overcome by piezoelectric induced movements. The results will be shown later.

Not initially being given the poling direction (defined as the direction from negative voltage lead to the positive voltage lead in the poling process) of the membrane by Measurement Specialties, Inc., it was derived from the information obtained through experimentation and other information provided by Measurement Specialties, Inc. A voltage applied to a piezoelectric ceramic material that is opposite in polarity to the poling direction results in a compression of the membrane in its thickness ("3" direction) and expansion of the membrane in its length and width directions ("1" and "2"

directions). This movement appears to be what occurred in this experiment when the negative lead of the voltage source was attached to the positive electrode. The internal pressure of the drum pushed the membrane out further when higher and higher voltages were applied. This occurred because the membrane had increasing amounts of slack (less taught) in the length and width directions. So, the membrane was capable of being pushed out more by the internal pressure. If the poling direction were in the direction of the applied voltage polarity, the thickness of the membrane would increase, contracting the length and width of the membrane. This would make it more taught and less capable of being pushed out by the internal pressure of the drum. In fact, the membrane would not be pushed out toward the laser measurement system in this set-up but would in fact either remain in its position or retreat from the laser measurement system. This appears to be what occurred when the positive lead of the voltage source was attached to the positive electrode. However, after receiving poling information from Measurement Specialties, Inc., the poling direction of the membrane was derived.

The poling direction of the film, in the thickness "3" direction, is in the negative electrode direction (away from the laser measurement device). This was determined using the following information. For piezofilms, the d constant ("ratio of strain developed along a specific axis to the value of electric field applied parallel to a given axis" (Shields, p. 13 – 14)) is negative in the "3" direction. This is just the opposite of the d constant of a piezoceramic. A positive "applied voltage produces a negative strain (i.e., the film gets thinner)" (Measurement Specialties, Inc., p. 3). The positive lead was placed on the side of the membrane that the poling direction pointed toward (the side facing away from the laser measurement device), and the film got thinner. The positive

electrode plus sign seems to have no correlation to the poling direction, unless it indicates the opposite of the poling direction. Knowing why the membrane behaved the way that it did, it is now appropriate to examine the amplitudes of the displacements.

Table 1 shows the displacement of the membrane at each internal pressure due to the piezoelectric effect induced by an applied voltage of 850 volts.

Internal Pressure of Drum (psi)	Total Displacement (micrometers)
0.1	169.786
0.3	92.03
0.5	183.6914
0.7	151.3092

Table 1. Displacement of Membrane due to Piezoelectric Effect (850 volts) and Pressure

These values are based on data collected and recorded by d-Space for each of the four pressure settings. They represent the displacement due to the application of 850 volts. The expected results are a larger displacement of the membrane for larger applied voltages. This was observed and can be seen in Figures 4, 5, 6, and 7.



Figure 4. Deflection of Membrane due to Piezoelectric effect (0.1 psi) – Negative Lead Attached to Positive Sign Side



Figure 5. Deflection of Membrane due to Piezoelectric effect (0.3 psi) – Negative Lead Attached to Positive Sign Side



Figure 6. Deflection of Membrane due to Piezoelectric effect (0.5 psi) – Negative Lead Attached to Positive Sign Side



Figure 7. Deflection of Membrane due to Piezoelectric effect (0.7 psi) – Negative Lead Attached to Positive Sign Side

The displacement of the membrane at each pressure setting shows a general increase in the laser measurement system direction for each pressure setting. All of the graphs show a displacement in the same direction. For the measurements collected with the positive voltage lead on the positive electrode (plus sign side), the results showed that the membrane did not move in either direction, except for 0.1 psig, for reasons mentioned earlier. Figures 8, 9, 10, and 11 show this.



Figure 8. Deflection of Membrane due to Piezoelectric effect (0.1 psi) – Positive Lead Attached to Positive Sign Side



Figure 9. Deflection of Membrane due to Piezoelectric effect (0.3 psi) – Positive Lead Attached to Positive Sign Side



Figure 10. Deflection of Membrane due to Piezoelectric effect (0.5 psi) – Positive Lead Attached to Positive Sign Side



Figure 11. Deflection of Membrane due to Piezoelectric effect (0.7 psi) – Positive Lead Attached to Positive Sign Side

The resolution of the laser measurement device is only 20 micrometers, so the measurements for Figures 9, 10, and 11 show that the displacement was inside or very near this resolution. With this in mind, the membrane did not move for these pressure settings when the positive voltage lead was placed on the positive electrode of the membrane. With better measurement devices, however, better displacement readings could be obtained and then displacements could accurately be predicted for given pressure settings. With this knowledge, an actuation system could be developed to take advantage of these displacements.

An alternate method obtain values of displacement under this set of applied loads is through modeling the piezoelectric film as a thin shell. By using MSC/PATRAN and MSC/NASTRAN, or similar analytical modeling programs, this membrane can be

modeled and evaluated. Once the model responds like the experimental set-up to pressure and voltage, evaluation of the piezoelectric film in space application situations can be performed. The next chapter describes the efforts in accurate modeling of the piezoelectric film as a thin shell undergoing large displacements nad large rotations using the nonlinear incremental finite element options of MSC/NASTRAN software.

THIS PAGE INTENTIONALLY LEFT BLANK

IV. ANALYTICAL MODEL SET-UP AND RESULTS

The analytical model used in this research was created using MSC/PATRAN and MSC/NASTRAN software. The software was used to create the geometric model, and combinations of pressure and voltage that were observed in the experiment were applied to the model. This chapter describes the modeling aspects of the thin piezoelectric film.

MSC/PATRAN and MSC/NASTRAN are capable of modeling piezoelectric materials by using a thermal analogy. The piezo strain constants of the material are converted into coefficients of thermal expansion. This is done using the following equation: $\alpha_{eq} = d / t_{piezo}$ (d = piezo strain constant, t = thickness). The coefficient of thermal expansion (α_{eq}) can then be prescribed to the experimental model as a material property in the analysis. The values of the voltage applied corresponds to the temperature that is to be used in the MSC/NASTRAN model (in this model, degrees fahrenheit). The values of the thermal coefficients of expansion are presented in Appendix D. There is a value for the "1" direction and the "2" direction. However, in MSC/PATRAN, as a first approximation of the study, the average of the two coefficients of thermal expansion was used in an isotropic setting. This approximation, as seen later, introduces a small percentage of error in the response of the film to applied loads.

MSC/PATRAN is a graphical user interface package used to model structural and thermal problems. It generates an interface to run MSC/NASTRAN analysis. The structural and thermal aspects were modeled using MSC/PATRAN. The model from MSC/PATRAN was then used to create an input file, (.bdf or .dat) for MSC/NASTRAN. MSC/NASTRAN, a multi-disciplinary finite element analysis tool, is used in computing

the response in the form of displacements, rotations, stresses, etc., based on input geometry, boundary conditions, and loads.

> The finite element method offers virtually unlimited problem generality by permitting the use of elements of various regular shapes. These elements can be combined to approximate any irregular boundary. In similar fashion, loads and constraints of any type can be applied (Miller, p. 3).

The piezoelectric fim (approximate thickness of 0.002 in) modeled as a thin-shell undergoes large displacements and large rotations (also note that E is of the order of 500,000 psi). For the given pressure loadings and the temperature loadings, the displacements of the film are several thousand times the thickness. This behavior requires the use of a nonlinear approach as displacements and rotations are large (linear strain-displacement approximations are violated) and as such MSC/NASTRAN has the capability to analyze such problems. The input deck generated by MSC/NASTRAN is changed (or edited) to incorporate the analysis parameters for computing the response of the thin shell to the applied loadings. Before any solutions could be obtained, though, inputs into the MSC/PATRAN model had to be made.

The MSC/PATRAN model was constructed using 216 finite elements. This was accomplished by placing 36 mesh seeds about the perimeter of of an 8.5 in membrane. This size was selected for the analytical model corresponding to the diameter of the membrane that is not rigidly clamped by the lip and drum of the experiment. Figure 12 shows the finite element model developed in MSC/NASTRAN.



Figure 12. Finite Element Model Produced in MSC/PATRAN

Another assumption made was the modulus of elasticity of the membrane. Measurement Specialties, Inc. gives a range of the modulus of elasticity of PVDF at a 52 micrometer thickness from 2 – 4 Gpa (290,000 psi to 580,000 psi). A modulus of elasticity of 537,500 psi was used in the analytical model.

Once the .dat file was generated, it was manipulated to solve a non-linear problem for multiple pressure and temperature combinations. The code solved for displacements due to each pressure setting and one temperature. So, the .dat file was changed for each temperature and run in MSC/NASTRAN. The MSC/NASTRAN analysis provided .fo6 files that included the displacements of the first nine elements of the finite element model of the membrane. These displacement vectors were compiled and placed in a word processor file (these values are in inches). The displacement vectors and the .dat file can be seen in Appendix D.

Figure 13 presents the results of the maximum displacement of the center as the pressure is increased. As can be seen, the maximum displacement at 0.1 psig is about a thousand times the thickness of the membrane. As mentioned earlier, the observed values have 'rounding off' errors in getting the measured displacements. The MSC/NASTRAN results agree well with the finite element results published by JPL. They also agree well with measured deflections of the membrane under solely pressure loads. Of note, the reference starting point for all three curves in the graph in Figure 13 is the membrane displacement at 0.1 psig as calculated by the MSC/NASTRAN code developed here at NPS. This was done to show the relative displacements of the three measurement attempts from a common reference.



Figure 13. Displacements of Membrane with only Internal Pressure Applied

The results of the analytical model when temperatures were applied, matched nicely with the experimental results. When different temperatures were put into the code,

the resulting displacements followed the same trends observed in the experiment. Graphs of these results can be seen in Appendix D. Two examples, Figures 14 and 15 follow.



Figure 14. Analytical Model Results of Displacement of Membrane Exposed to .1 psig and Positive Temperatures.



Figure 15. Analytical Model Results of Displacement of Membrane Exposed to .1 psig and Negative Temperatures.

Decreasing a negative temperature caused a decrease in the displacement of the membrane. An increase in temperature resulted in increases in displacement. In the experiment, an increase in voltage with the negative lead of the voltage source attached to the positive electrode of the membrane increased the displacement of the membrane. An increase in voltage with the positive lead of the voltage source attached to the positive electrode of the membrane did not change the displacement of the membrane. The latter experimental configuration corresponds to the decreasing temperature configuration for the analytical model. The model shows a negative displacement due to decreasing temperature, but the experiment showed that the membrane was not capable of moving in that direction with internal pressures higher than 0.1 psig, most likely due to increased tension in the membrane due to the higher pressure loads. The analytical model does make intuitive sense, because if the temperature of the membrane were reduced, it would not expand, but it would contract. This would correspond to a piezoelectric material becoming thicker in the "3" direction and shorter in the"1" and "2" directions. The increasing temperature configuration in the analytical model corresponds to the experimental configuration of the negative lead of the voltage source attached to the positive electrode of the membrane. An increasing temperature would expand the membrane, and this corresponds to a membrane becoming thinner in the "3" direction and longer in the "1" and "2" directions. Of note, if a positive temperature is applied to the membrane before a pressure load is, the rigidly bounded membrane will buckle. NASTRAN is then incapable of proceeding further. A pressure load needs to be applied first, giving stiffness to the membrane, allowing the temperature loads to be applied without buckling the membrane.

In the experiment, as has been mentioned before, there are a few things that may have contributed to inaccuracies in the results of the experiment. Also, there may be inaccuracies in the results obtained by the model. Inaccuracies may have been introduced because the average of the coefficients of thermal expansion may not be an accurate way to implement the temperature analogy, or the modulus of elasticity may not be accurate for the membrane used in this experiment.

A milestone in this research was establishing a nonlinear MSC/NASTRAN model that uses pressure and temperature loadings to calculate the displacements of an extremely thin membrane. Future work could be done to introduce membranes of larger size into the space environment. Also, the model can be used to determine the response of larger inflated structures to analogous voltage inputs. Optimum placement of piezoelectric films on large inflatable structures for desired responses could also be accomplished. This work can be used as a starting place for such future work.

THIS PAGE INTENTIONALLY LEFT BLANK

V. CONCLUSIONS

Inflatable thin film space-borne structures are revolutionary in terms of mass, stowed volume, and capability. The Navy and the Department of Defense should investigate using these materials in future space-borne communications platforms. It has been shown that a lot of work has been done and is going to be done with this technology, and its attributes far outweigh any drawbacks (which are very few in number). The enhanced communications capabilities that large antennas made of these materials offer are phenomenal. However, this technology is not quite ready for use in this application.

Surface errors in the shape of large parabolic antennas caused by the space environment can degrade the performance of these antennas, therefore some form of shape control has to be implemented to maintain the ideal shape of these antennas. Using piezoelectric material is one solution to this problem. The research done for this thesis shows that piezoelectric thin films are plausible materials to be used to help maintain shape. Not only can they be used to change an inflatable structure's shape, they can also be used to sense when the ideal shape has been changed. Through experimentation, it has been shown that the shape change of a piezoelectric thin film under pressure is repeatable. By developing a nonlinear MSC/NASTRAN model of a thin film under pressure and thermal loads, it has been shown that computer models can be constructed that will help predict and optimize piezoelectric thin film usage.

This thesis continued with the work of Dr. Salama, Dr. Kuo, B. Wada, and M. Thomas. Their work was very similar, but the research reported here placed a membrane

of a different size under a higher pressure. Displacements were observed and calculated that, without the influence of voltage or temperature, were very similar in nature to those reported by Salama, Kuo, Wada, and Thomas. They also reported that the out-of-plane displacement of their membrane due to an applied voltage of 300 volts was about .0012 in. The experiment conducted for this research produced an out-of-plane displacement of about .006 in for an applied voltage of 300 volts. The analytical model produced an out-of-plane displacement of about .0020 in for an applied voltage of 300 volts. However, the out-of-plane displacements for this model were obtained with a different configuration than those obtained by the experiment. They are both approximately, however, in the same range as the results obtained by Salama, Kuo, Wada, and Thomas. They stated that this out-of-plane displacement should scale directly with the diameter of the membrane (their diameter was 10 in). The experimental results for this thesis do not support this statement ((8.5 in / 10 in)*.0012 in = .0010 in, not .006 in). Again, the laser measurement device is not the best instrument that could be used in this experiment, but there could also be error in the results of Salama, Kuo, Wada, and Thomas.

Future work that can be done at NPS includes using better measurement devices to measure surface deflections of the membrane and developing analytical models of large inflatable structures and predicting their behavior and performance. Also, conducting temperature experiments on the membrane and drum to see if this has an effect on deflection and testing for the modes and natural frequencies of the membrane could be pursued. There is a lot of work left to be done on this technology, and the Navy and the Department of Defense should keep a watchful eye on the progress of the developments of this technology.

The Navy and the Department of Defense could benefit greatly from using inflatable antennas on communications satellites. They are light and compact when stowed, both of which help reduced the size of the launch vehicle and subsequently the cost of the program. The enhanced capabilities that larger antennas bring to warfighters, especially disadvantaged users with limited power and antenna size are incredible. With information superiority becoming more and more important, this capability is becoming more and more valuable. Planning ahead now and investing in this technology will ensure its growth and rapid maturity. Using this technology is just one piece of the puzzle that will bring true information superiority to all Department of Defense personnel. Inflatable space structures will be a part of the future, and hopefully, they will be a part of the Navy's and the Department of Defense's future as well.

THIS PAGE INTENTIONALLY LEFT BLANK

APPENDIX A. EQUATIONS USED FOR ANTENNA OPERATIONAL ANALYSIS

Equation	Source
Wavelength = C / frequency	Larson and Wertz, p. 242
antenna gain = $\pi^2 D_r^2 \eta / \lambda^2$	Larson and Wertz, p. 521
degraded antenna gain = $\eta(\pi D_r/\lambda)^2 e^{[-(4\pi\varepsilon/\lambda)^2]}$	Cassapakis, Love, and Palisoc, p. 456
EIRP = $P_t + G_t - L_{line}$ (in dB)	Baldwin, p. 36
FSPL = 32.4 + 20log(Freq(MHz)) + 20log(D(km)) (in dB)	Baldwin, p. 36
No = 10log(K) + 10log(T_e) (in dB)	Tomasi, p. 748
C = EIRP – FSPL + $G_r - L_{line}$ (in dB)	Baldwin, p. 36
C/No = C – No (in dB)	Tomasi, p. 749
N = bandwidth + No (in dB)	Tomasi, p. 748
C/N = C – N (in dB)	decibel mathematics
Beamwidth = $21*10^9$ / frequency*D_r (degrees)	Douglas, p. 74
D (km) = sin(λ_{FO})(6378)/sin(nadir ang+ beamwidth)	derived
L_F (km) = $K_L(\lambda_{FO}-\lambda_{FI})$	Larson and Wertz, p. 163
W_F(km) = $R_E \sin^{-1}$(Dsin(beamwidth)/ R_E)	Larson and Wertz, p. 164
F_A (km) = (π / 4) L_F W_F	Larson and Wertz, p. 165
C/No (overall) = $(C/No)_u(C/No)_d/[(C/No)_u+(C/No)_d]$	Tomasi, p. 758

Throughput (bps) = alog[(C/No – Eb/No – required margin)/10] Baldwin, p. 36

C/N (overall) = $(C/N)_u(C/N)_d/[(C/N)_u+(C/N)_d]$ Tomasi, p. 758

Shannon's Capacity Limit = bandwidth*$\log_2(1+C/N)$ Baldwin, p. 16

Practical throughput = bandwidth*$\log_2(M)/(1 + R)$ M-ary PSKs (no coding)

Key:

C = speed of light ($3*10^8$ m/s)
λ = wavelength
η = antenna efficiency
D_r = diameter of receiver
ε = root mean square surface error
EIRP = Effective Isotropic Radiated Power
P_t = transmitter power
G_t = transmitter gain
FSPL = Free Space Path Loss
D = slant range
G_r = receiver gain
L_{line} = line losses
k = Boltzmann's Constant ($1.38*10^{-23}$ J/deg Kelvin)
T_e = equivalent temperature
C = received power
No = noise density
K_L = 111.319543
L_F = footprint length
W_F = footprint width
F_A = footprint area
R = roll-off factor
M = number of modulation symbols (e.g., M = 2 for BPSK)

APPENDIX B. ANTENNA ANALYSIS SPREADSHEETS AND GRAPHS

The material contained in this appendix displays the analysis performed on the link budgets of different ground and space-borne antennas. Graphs display the throughputs possible for different scenarios using the different antennas available. Six different scenarios are displayed.

Thesis Antenna Spreadsheet
disadvantaged user to disadvantaged user link

uplink

altitude of satellite (km)	35786	35786	35786	35786	35786	35786	35786	35786	35786
diameter of disadvantaged user antenna (m)	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25
transmitted power (dBW)	7	7	7	7	7	7	7	7	7
frequency (Hz)	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09
wavelength (m)	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02
disadvantaged user antenna efficiency	5.50E-01	5.50E-01	5.50E-01	5.50E-01	5.50E-01	5.50E-01	5.50E-01	5.50E-01	5.50E-01
gain of disadvantaged user antenna (dB)	24.248585	24.248585	24.248585	24.248585	24.248585	24.248585	24.248585	24.248585	24.248585
EIRPof ground antenna (dBW)	30.248585	30.248585	30.248585	30.248585	30.248585	30.248585	30.248585	30.248585	30.248585
line losses of disadvantaged antenna (dB)	1.000000	1.000000	1.000000	1.000000	1.000000	1.000000	1.000000	1.000000	1.000000
diameter of satellite antenna (m)	1.14	5	10	15	20	25	30	35	40
satellite antenna efficiency	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55
gain of spacecraft antenna (dB)	37.427882	50.269185	56.289785	59.811610	62.310385	64.248585	65.832210	67.171146	68.330985
rms surface error (m)	0.00E+00	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03
degraded (actual) gain of spacecraft (dB)	37.427882	50.03141159	56.0520115	59.5738367	62.0726114	64.0108117	65.5944366	66.9333724	68.0932113
bandwidth (Hz)	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07
free space path loss (dB)	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02
atmospheric attenuation (dB)	3	3	3	3	3	3	3	3	3
line losses of receiver (dB)	2	2	2	2	2	2	2	2	2
equivalent temperature (K) on satellite	2710	2710	2710	2710	2710	2710	2710	2710	2710
No (dB)	-194.27031	-194.270307	-194.270307	-194.270307	-194.270307	-194.27031	-194.2703071	-194.27031	-194.27031
received power (C) (dBW)	-139.326132	-126.682040	-120.659799	-117.137670	-114.638789	-112.700540	-111.116888	-109.777936	-108.618087
required margin (dB)	3	3	3	3	3	3	3	3	3
C/No (dB)	5.494E+01	6.759E+01	7.361E+01	7.713E+01	7.963E+01	8.157E+01	8.315E+01	8.449E+01	8.565E+01
N (dB)	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02
C/N (dB)	-2.435E+01	-1.171E+01	-5.684E+00	-2.162E+00	3.373E-01	2.276E+00	3.859E+00	5.198E+00	6.358E+00
spacecraft-centered nadir angle (deg)	0	0	0	0	0	0	0	0	0
beamwidth (deg)	2.193E+00	5.000E-01	2.500E-01	1.667E-01	1.250E-01	1.000E-01	8.333E-02	7.143E-02	6.250E-02
lambda (lo) (deg)	12.4601678	2.807219145	1.40293648	0.935208	0.70138422	0.56109931	0.467579111	0.40078021	0.35068161
lambda (li) (deg)	0	0	0	0	0	0	0	0	0
slant range (km)	35962.5645	35795.01673	35788.2526	35787.001	35786.563	35786.3603	35786.25023	35786.1838	35786.1408
Lf (km)	1387.06019	312.4983523	156.174248	104.106927	78.0777709	62.4613191	52.05069295	44.6146697	39.0377167
Wf (km)	1.387E+03	3.125E+02	1.562E+02	1.041E+02	7.808E+01	6.246E+01	5.205E+01	4.461E+01	3.904E+01
Fa (km^2)	1.511E+06	7.670E+04	1.916E+04	8.512E+03	4.788E+03	3.064E+03	2.128E+03	1.563E+03	1.197E+03

DSCS III antenna diameter
= .7112 m
DSCS III SLEP parameter

DSCS III S mm
0

downlink									
altitude of satellite (km)	35786	35786	35786	35786	35786	35786	35786	35786	35786
diameter of satellite antenna (m)	0.711	5	10	15	20	25	30	35	40
transmitted power (dBW)	6.99	6.99	6.99	6.99	6.99	6.99	6.99	6.99	6.99
line losses of transmitter (dB)	1	1	1	1	1	1	1	1	1
frequency (Hz)	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09
wavelength (m)	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02
antenna efficiency	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55
ideal gain of satellite antenna (dB)	27.086669	44.028677	50.049277	53.571103	56.069877	58.008078	59.591702	60.930638	62.090477
rms surface error (m)	0.00E+00	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03
degraded (actual) gain of satellite (dB)	27.0866694	43.97216911	49.992769	53.5145942	56.0133689	57.9515692	59.53519412	60.8741299	62.0339689
EIRPof spacecraft (dBW)	33.0766694	49.96216911	55.982769	59.5045942	62.0033689	63.9415692	65.52519412	66.8641299	68.0239689
diameter of disadvantaged user antenna (m)	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25
gain of ship antenna (dB)	18.008078	18.008078	18.008078	18.008078	18.008078	18.008078	18.008078	18.008078	18.008078
bandwidth (Hz)	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07
free space path loss (dB)	1.963E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02
atmospheric attenuation (dB)	3	3	3	3	3	3	3	3	3
line losses of receiver (dB)	2	2	2	2	2	2	2	2	2
equivalent temperature (K) on ship	290	290	290	290	290	290	290	290	290
No (dB)	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602
received power (C) (dBW)	-150.218187	-132.758327	-126.730797	-123.207692	-120.708470	-118.770063	-117.186325	-115.847322	-114.687439
required margin (dB)	3	3	3	3	3	3	3	3	3
C/No (dB)	53.757833	71.217693	77.245223	80.768328	83.267550	85.205957	86.789695	88.128698	89.288581
N (dB)	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02
C/N (dB)	-2.554E+01	-8.076E+00	-2.049E+00	1.474E+00	3.973E+00	5.912E+00	7.496E+00	8.835E+00	9.994E+00
C/No for entire link (dB)	5.130E+01	6.602E+01	7.205E+01	7.557E+01	7.807E+01	8.001E+01	8.159E+01	8.293E+01	8.409E+01
Eb/No (dB)	10	10	10	10	10	10	10	10	10
spacecraft-centered nadir angle (deg)	0	0	0	0	0	0	0	0	0
beamwidth (deg)	7.213E+00	1.026E+00	5.128E-01	3.419E-01	2.564E-01	2.051E-01	1.709E-01	1.465E-01	1.282E-01
lambda (fo) (deg)	48.8869961	5.770279287	2.87929486	1.91881237	1.43892115	1.15106729	0.959191226	0.82214762	0.71936992
lambda (fi) (deg)	0	0	0	0	0	0	0	0	0
slant range (km)	38273.0255	35824.05692	35795.4855	35790.2134	35788.3696	35787.5164	35787.05301	35786.7736	35786.5923
Lf (km)	5442.07807	642.3448532	320.521787	213.601316	160.180045	128.136284	106.776729	91.5210977	80.079931
Wf (km)	5.442E+03	6.423E+02	3.205E+02	2.136E+02	1.602E+02	1.281E+02	1.068E+02	9.152E+01	8.008E+01
Fa (km^2)	2.326E+07	3.241E+05	8.069E+04	3.583E+04	2.015E+04	1.290E+04	8.954E+03	6.578E+03	5.036E+03
modulation	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK
throughput (Mbps)	0.00676133	0.200635757	0.80314204	1.80731867	3.21316587	5.02068369	7.229872133	9.84073119	12.8532609
C/N for entire link	-2.799E+01	-1.327E+01	-7.246E+00	-3.724E+00	-1.225E+00	7.134E-01	2.297E+00	3.636E+00	4.796E+00
r	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01
Shannon's Limit (Mbps)	0.194	5.644	21.180	43.367	68.922	95.486	121.671	146.780	170.524
Practical achieveable throughput (Mbps)	60.714	60.714	60.714	60.714	60.714	60.714	60.714	60.714	60.714

Disadvantaged User to Disadvantaged User Throughput Based on Antenna Gain and Bandwidth



Thesis Antenna Spreadsheet
shore to disadvantaged user link

uplink

altitude of satellite (km)	35786	35786	35786	35786	35786	35786	35786	35786	35786
diameter of ground antenna (m)	18.29	18.29	18.29	18.29	18.29	18.29	18.29	18.29	18.29
transmitted power (dBW)	40	40	40	40	40	40	40	40	40
frequency (Hz)	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09
wavelength (m)	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02
EIRPof ground antenna (dBW)	97	97	97	97	97	97	97	97	97
diameter of satellite antenna (m)	1.14	5	10	15	20	25	30	35	40
satellite antenna efficiency	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55
gain of spacecraft antenna (dB)	37.427882	50.269185	56.289785	59.811610	62.310385	64.248585	65.832210	67.171146	68.330985
rms surface error (m)	0.00E+00	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03
degraded (actual) gain of spacecraft (dB)	37.427882	50.0314116	56.0520115	59.57383669	62.07261142	64.0108117	65.5944366	66.9333724	68.0932113
bandwidth (Hz)	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07
free space path loss (dB)	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02
atmospheric attenuation (dB)	3	3	3	3	3	3	3	3	3
line losses of receiver (dB)	2	2	2	2	2	2	2	2	2
equivalent temperature (K) on satellite	2710	2710	2710	2710	2710	2710	2710	2710	2710
No (dB)	-194.2703071	-194.270307	-194.270307	-194.2703071	-194.2703071	-194.27031	-194.2703071	-194.270307	-194.270307
received power (C) (dBW)	-72.574717	-59.930626	-53.908384	-50.386255	-47.887374	-45.949125	-44.365473	-43.026521	-41.866672
required margin (dB)	3	3	3	3	3	3	3	3	3
C/No (dB)	1.217E+02	1.343E+02	1.404E+02	1.439E+02	1.464E+02	1.483E+02	1.499E+02	1.512E+02	1.524E+02
N (dB)	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02
C/N (dB)	4.240E+01	5.505E+01	6.107E+01	6.459E+01	6.709E+01	6.903E+01	7.061E+01	7.195E+01	7.311E+01
spacecraft-centered nadir angle (deg)	0	0	0	0	0	0	0	0	0
beamwidth (deg)	2.193E+00	5.000E-01	2.500E-01	1.667E-01	1.250E-01	1.000E-01	8.333E-02	7.143E-02	6.250E-02
lambda (fo) (deg)	12.46016784	2.80721914	1.40293648	0.935207998	0.70138422	0.56109931	0.467579111	0.40078021	0.35068161
lambda (fi) (deg)	0	0	0	0	0	0	0	0	0
slant range (km)	35962.56448	35795.0167	35788.2526	35787.00101	35786.56304	35786.3603	35786.25023	35786.1838	35786.1408
Lf (km)	1387.06019	312.498352	156.174248	104.1069269	78.07777088	62.4613191	52.05069295	44.6146697	39.0377167
Wf (km)	1.387E+03	3.125E+02	1.562E+02	1.041E+02	7.808E+01	6.246E+01	5.205E+01	4.461E+01	3.904E+01
Fa (km^2)	1.511E+06	7.670E+04	1.916E+04	8.512E+03	4.788E+03	3.064E+03	2.128E+03	1.563E+03	1.197E+03

DSCS III antenna diameter
= .7112 m
DSCS III SLEP parameter

DSCS III S mm
0

downlink									
altitude of satellite (km)	35786	35786	35786	35786	35786	35786	35786	35786	35786
diameter of satellite antenna (m)	0.711	5	10	15	20	25	30	35	40
transmitted power (dBW)	6.99	6.99	6.99	6.99	6.99	6.99	6.99	6.99	6.99
line losses of transmitter (dB)	1	1	1	1	1	1	1	1	1
frequency (Hz)	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09
wavelength (m)	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02
antenna efficiency	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55
ideal gain of satellite antenna (dB)	27.086669	44.028677	50.049277	53.571103	56.069877	58.008078	59.591702	60.930638	62.090477
rms surface error (m)	0.00E+00	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03
degraded (actual) gain of satellite (dB)	27.08666939	43.9721691	49.992769	53.51459421	56.01336894	57.9515692	59.53519412	60.8741299	62.0339689
EIRPof spacecraft (dBW)	33.07666939	49.9621691	55.982769	59.50459421	62.00336894	63.9415692	65.52519412	66.8641299	68.0239689
diameter of disadvantaged user antenna (m)	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25
gain of ship antenna (dB)	18.008078	18.008078	18.008078	18.008078	18.008078	18.008078	18.008078	18.008078	18.008078
bandwidth (Hz)	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07
free space path loss (dB)	1.963E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02
atmospheric attenuation (dB)	3	3	3	3	3	3	3	3	3
line losses of receiver (dB)	2	2	2	2	2	2	2	2	2
equivalent temperature (K) on ship	290	290	290	290	290	290	290	290	290
No (dB)	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602
received power (C) (dBW)	-150.218187	-132.758327	-126.730797	-123.207692	-120.708470	-118.770063	-117.186325	-115.847322	-114.687439
required margin (dB)	3	3	3	3	3	3	3	3	3
C/No (dB)	5.376E+01	7.122E+01	7.725E+01	8.077E+01	8.327E+01	8.521E+01	8.679E+01	8.813E+01	8.929E+01
N (dB)	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02
C/N (dB)	-2.554E+01	-8.076E+00	-2.049E+00	1.474E+00	3.973E+00	5.912E+00	7.496E+00	8.835E+00	9.994E+00
C/No for entire link (dB)	5.376E+01	7.122E+01	7.725E+01	8.077E+01	8.327E+01	8.521E+01	8.679E+01	8.813E+01	8.929E+01
Eb/No (dB)	10	10	10	10	10	10	10	10	10
spacecraft-centered nadir angle (deg)	0	0	0	0	0	0	0	0	0
beamwidth (deg)	7.213E+00	1.026E+00	5.128E-01	3.419E-01	2.564E-01	2.051E-01	1.709E-01	1.465E-01	1.282E-01
lambda (fo) (deg)	48.88699612	5.77027929	2.87929486	1.91881237	1.438921148	1.15106729	0.959191226	0.82214762	0.71936992
lambda (fi) (deg)	0	0	0	0	0	0	0	0	0
slant range (km)	38273.0255	35824.0569	35795.4855	35790.21344	35788.3696	35787.5164	35787.05301	35786.7736	35786.5923
Lf (km)	5442.078066	642.344853	320.521787	213.6013162	160.1800446	128.136284	106.776729	91.5210977	80.079931
Wf (km)	5.442E+03	6.423E+02	3.205E+02	2.136E+02	1.602E+02	1.281E+02	1.068E+02	9.152E+01	8.008E+01
Fa (km^2)	2.326E+07	3.241E+05	8.069E+04	3.583E+04	2.015E+04	1.290E+04	8.954E+03	6.578E+03	5.036E+03
modulation	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK
throughput (Mbps)	0.011906476	0.66339029	2.65779892	5.981809483	10.63542377	16.618642	23.93146425	32.5738905	42.5459208
C/N for entire link	-2.554E+01	-8.076E+00	-2.049E+00	1.474E+00	3.973E+00	5.912E+00	7.496E+00	8.835E+00	9.994E+00
r	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01
Shannon's Limit (Mbps)	0.342	17.748	59.453	107.570	153.503	194.912	231.736	264.527	293.908
Practical achieveable throughput (Mbps)	60.714	60.714	60.714	60.714	60.714	60.714	60.714	60.714	60.714

Shore to Disadavantaged User Throughputs Based on Antenna Gain and Bandwidth



Thesis Antenna Spreadsheet
ship to ship link

uplink

altitude of satellite (km)	35786	35786	35786	35786	35786	35786	35786	35786	35786
diameter of ship antenna (m)	2.36	2.36	2.36	2.36	2.36	2.36	2.36	2.36	2.36
transmitted power (dBW)	33.01	33.01	33.01	33.01	33.01	33.01	33.01	33.01	33.01
frequency (Hz)	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09
wavelength (m)	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02
EIRPof ship antenna (dBW)	72	72	72	72	72	72	72	72	72
diameter of satellite antenna (m)	1.14	5	10	15	20	25	30	35	40
satellite antenna efficiency	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55
gain of spacecraft antenna (dB)	37.427882	50.269185	56.289785	59.811610	62.310385	64.248585	65.832210	67.171146	68.330985
rms surface error (m)	0.00E+00	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03
degraded (actual) gain of spacecraft (dB)	37.427882	50.03141159	56.05201151	59.5738367	62.0726114	64.0108117	65.5944366	66.9333724	68.09321133
bandwidth (Hz)	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07
free space path loss (dB)	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02
atmospheric attenuation (dB)	3	3	3	3	3	3	3	3	3
line losses of receiver (dB)	2	2	2	2	2	2	2	2	2
equivalent temperature (K) on satellite	2710	2710	2710	2710	2710	2710	2710	2710	2710
No (dB)	-194.2703071	-194.2703071	-194.270307	-194.270307	-194.270307	-194.270307	-194.270307	-194.270307	-194.270307
received power (C) (dBW)	-97.574717	-84.930626	-78.908384	-75.386255	-72.887374	-70.949125	-69.365473	-68.026521	-66.866672
required margin (dB)	3	3	3	3	3	3	3	3	3
C/No (dB)	9.670E+01	1.093E+02	1.154E+02	1.189E+02	1.214E+02	1.233E+02	1.249E+02	1.262E+02	1.274E+02
N (dB)	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02
C/N (dB)	1.740E+01	3.005E+01	3.607E+01	3.959E+01	4.209E+01	4.403E+01	4.561E+01	4.695E+01	4.811E+01
spacecraft-centered nadir angle (deg)	0	0	0	0	0	0	0	0	0
beamwidth (deg)	2.193E+00	5.000E-01	2.500E-01	1.667E-01	1.250E-01	1.000E-01	8.333E-02	7.143E-02	6.250E-02
lambda (fo) (deg)	12.46016784	2.807219145	1.402936478	0.935208	0.70138422	0.56109931	0.46757911	0.40078021	0.350681611
lambda (fi) (deg)	0	0	0	0	0	0	0	0	0
slant range (km)	35962.56448	35795.01673	35788.25257	35787.001	35786.563	35786.3603	35786.2502	35786.1838	35786.14075
Lf (km)	1387.06019	312.4983523	156.1742476	104.106927	78.0777709	62.4613191	52.050693	44.6146697	39.03771673
Wf (km)	1.387E+03	3.125E+02	1.562E+02	1.041E+02	7.808E+01	6.246E+01	5.205E+01	4.461E+01	3.904E+01
Fa (km^2)	1.511E+06	7.670E+04	1.916E+04	8.512E+03	4.788E+03	3.064E+03	2.128E+03	1.563E+03	1.197E+03

DSCS III antenna diameter
= .7112 m
DSCS III SLEP parameter

DSCS III SLfmm
38.709677

downlink									
altitude of satellite (km)	35786	35786	35786	35786	35786	35786	35786	35786	35786
diameter of satellite antenna (m)	0.711	5	10	15	20	25	30	35	40
transmitted power (dBW)	6.99	6.99	6.99	6.99	6.99	6.99	6.99	6.99	6.99
line losses of transmitter (dB)	1	1	1	1	1	1	1	1	1
frequency (Hz)	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09
wavelength (m)	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02
antenna efficiency	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55
ideal gain of satellite antenna (dB)	27.086669	44.028677	50.049277	53.571103	56.069877	58.008078	59.591702	60.930638	62.090477
rms surface error (m)	0.00E+00	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03
degraded (actual) gain of satellite (dB)	27.08666939	43.97216911	49.99276903	53.5145942	56.0133689	57.9515692	59.5351941	60.8741299	62.03396885
EIRPof spacecraft (dBW)	33.07666939	49.96216911	55.98276903	59.5045942	62.0033689	63.9415692	65.5251941	66.8641299	68.02396885
diameter of ship antenna (m)	2.36	2.36	2.36	2.36	2.36	2.36	2.36	2.36	2.36
gain of ship antenna (dB)	37.507517	37.507517	37.507517	37.507517	37.507517	37.507517	37.507517	37.507517	37.507517
bandwidth (Hz)	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07
free space path loss (dB)	1.963E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02
atmospheric attenuation (dB)	3	3	3	3	3	3	3	3	3
line losses of receiver (dB)	2	2	2	2	2	2	2	2	2
equivalent temperature (K) on ship	290	290	290	290	290	290	290	290	290
No (dB)	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602
received power (C) (dBW)	-130.718747	-113.258887	-107.231357	-103.708252	-101.209030	-99.270623	-97.686885	-96.347882	-95.187999
required margin (dB)	3	3	3	3	3	3	3	3	3
C/No (dB)	7.326E+01	9.072E+01	9.674E+01	1.003E+02	1.028E+02	1.047E+02	1.063E+02	1.076E+02	1.088E+02
N (dB)	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02
C/N (dB)	-6.037E+00	1.142E+01	1.745E+01	2.097E+01	2.347E+01	2.541E+01	2.699E+01	2.833E+01	2.949E+01
C/No for entire link (dB)	7.324E+01	9.066E+01	9.669E+01	1.002E+02	1.027E+02	1.046E+02	1.062E+02	1.076E+02	1.087E+02
Eb/No (dB)	10	10	10	10	10	10	10	10	10
spacecraft-centered nadir angle (deg)	0	0	0	0	0	0	0	0	0
beamwidth (deg)	7.213E+00	1.026E+00	5.128E-01	3.419E-01	2.564E-01	2.051E-01	1.709E-01	1.465E-01	1.282E-01
lambda (fo) (deg)	48.88699612	5.770279287	2.879294855	1.91881237	1.43892115	1.15106729	0.95919123	0.82214762	0.719369923
lambda (fi) (deg)	0	0	0	0	0	0	0	0	0
slant range (km)	38273.0255	35824.05692	35795.48552	35790.2134	35788.3696	35787.5164	35787.053	35786.7736	35786.59229
Lf (km)	5442.078066	642.3448532	320.5217875	213.601316	160.180045	128.136284	106.776729	91.5210977	80.07993104
Wf (km)	5.442E+03	6.423E+02	3.205E+02	2.136E+02	1.602E+02	1.281E+02	1.068E+02	9.152E+01	8.008E+01
Fa (km^2)	2.326E+07	3.241E+05	8.069E+04	3.583E+04	2.015E+04	1.290E+04	8.954E+03	6.578E+03	5.036E+03
modulation	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK
throughput (Mbps) (unlimited bandwidth)	1.056243516	58.31630551	233.6338915	525.829535	934.903392	1460.85548	2103.68581	2863.39438	3739.981183
C/N for entire link	-6.057E+00	1.136E+01	1.739E+01	2.091E+01	2.341E+01	2.535E+01	2.694E+01	2.827E+01	2.943E+01
r	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01
Shannon's Limit (Mbps)	27.162	329.516	493.280	591.533	661.670	716.203	760.813	798.556	831.264
Practical achieveable throughput (Mbps)	60.714	60.714	60.714	60.714	60.714	60.714	60.714	60.714	60.714

DSCS III SLEP Theoretical Throughputs based on a 85 MHz Bandwidth (Ship to Ship)



Close-Up of DSCS III SLEP Theoretical Throughputs based on a 85 MHz Bandwidth (Ship to Ship)



Thesis Antenna Spreadsheet
ship to ship link

uplink

altitude of satellite (km)	35786	35786	35786	35786	35786	35786	35786	35786	35786
diameter of ship antenna (m)	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7
transmitted power (dBW)	26.02	26.02	26.02	26.02	26.02	26.02	26.02	26.02	26.02
frequency (Hz)	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09
wavelength (m)	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02
line losses of transmitter (dB)	1.00E+00	1.00E+00	1.00E+00	1.00E+00	1.00E+00	1.00E+00	1.00E+00	1.00E+00	1.00E+00
gain of ship antenna (dB)	42.445816	42.445816	42.445816	42.445816	42.445816	42.445816	42.445816	42.445816	42.445816
EIRPof ship antenna (dBW)	67.47	67.47	67.47	67.47	67.47	67.47	67.47	67.47	67.47
diameter of satellite antenna (m)	0.711	5	10	15	20	25	30	35	40
satellite and ship antenna efficiency	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55
gain of spacecraft antenna (dB)	30.855933	47.797941	53.818541	57.340366	59.839141	61.777341	63.360966	64.699902	65.859741
rms surface error (m)	0.00E+00	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03
degraded (actual) gain of spacecraft (dB)	30.85593283	47.6633428	53.6839427	57.20576789	59.7045426	61.6427429	63.2263678	64.56530359	65.7251425
bandwidth (Hz)	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07
free space path loss (dB)	1.997E+02	1.995E+02	1.995E+02	1.995E+02	1.995E+02	1.995E+02	1.995E+02	1.995E+02	1.995E+02
atmospheric attenuation (dB)	3	3	3	3	3	3	3	3	3
line losses of receiver (dB)	2	2	2	2	2	2	2	2	2
equivalent temperature (K) on satellite	3853	3853	3853	3853	3853	3853	3853	3853	3853
No (dB)	-192.7420099	-192.74201	-192.74201	-192.7420099	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201
received power (C) (dBW)	-106.374086	-89.363314	-83.339812	-79.817450	-77.318487	-75.380200	-73.796528	-72.457564	-71.297706
required margin (dB)	3	3	3	3	3	3	3	3	3
C/No (dB)	8.637E+01	1.034E+02	1.094E+02	1.129E+02	1.154E+02	1.174E+02	1.189E+02	1.203E+02	1.214E+02
N (dB)	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02
C/N (dB)	1.080E+01	2.782E+01	3.384E+01	3.736E+01	3.986E+01	4.180E+01	4.338E+01	4.472E+01	4.588E+01
spacecraft-centered nadir angle (deg)	0	0	0	0	0	0	0	0	0
beamwidth (deg)	4.673E+00	6.646E-01	3.323E-01	2.215E-01	1.661E-01	1.329E-01	1.108E-01	9.494E-02	8.307E-02
lambda (fo) (deg)	27.91661303	3.73294692	1.86489081	1.243065606	0.93224806	0.74577951	0.62147436	0.532687878	0.46609938
lambda (fi) (deg)	0	0	0	0	0	0	0	0	0
slant range (km)	36650.05792	35801.9401	35789.98	35787.76847	35786.9947	35786.6366	35786.4421	35786.32477	35786.2487
Lf (km)	3107.664604	415.549945	207.598792	138.3774952	103.777428	83.0198347	69.1822416	59.29857114	51.8859698
Wf (km)	3.108E+03	4.155E+02	2.076E+02	1.384E+02	1.038E+02	8.302E+01	6.918E+01	5.930E+01	5.188E+01
Fa (km^2)	7.585E+06	1.356E+05	3.385E+04	1.504E+04	8.458E+03	5.413E+03	3.759E+03	2.762E+03	2.114E+03

Intelsat 702 antenna diameter
= .7112 m
Intelsat 702 parameter

73.26007 mm

downlink									
altitude of satellite (km)	35786	35786	35786	35786	35786	35786	35786	35786	35786
diameter of satellite antenna (m)	0.711	5	10	15	20	25	30	35	40
transmitted power (dBW)	12.04	12.04	12.04	12.04	12.04	12.04	12.04	12.04	12.04
line losses of transmitter (dB)	1	1	1	1	1	1	1	1	1
frequency (Hz)	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09
wavelength (m)	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02
antenna efficiency	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55
ideal gain of satellite antenna (dB)	27.086669	44.028677	50.049277	53.571103	56.069877	58.008078	59.591702	60.930638	62.090477
rms surface error (m)	0.00E+00	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03
degraded (actual) gain of satellite (dB)	27.08666939	43.9721691	49.992769	53.51459421	56.0133689	57.9515692	59.5351941	60.87412991	62.0339689
EIRPof spacecraft (dBW)	38.12666939	55.0121691	61.032769	64.55459421	67.0533689	68.9915692	70.5751941	71.91412991	73.0739689
diameter of ship antenna (m)	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7
gain of ship antenna (dB)	38.676553	38.676553	38.676553	38.676553	38.676553	38.676553	38.676553	38.676553	38.676553
bandwidth (Hz)	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07
free space path loss (dB)	1.963E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02
atmospheric attenuation (dB)	3	3	3	3	3	3	3	3	3
line losses of receiver (dB)	2	2	2	2	2	2	2	2	2
equivalent temperature (K) on ship	290	290	290	290	290	290	290	290	290
No (dB)	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602
received power (C) (dBW)	-124.499712	-107.039852	-101.012322	-97.489217	-94.989995	-93.051587	-91.467850	-90.128846	-88.968964
required margin (dB)	3	3	3	3	3	3	3	3	3
C/No (dB)	7.948E+01	9.694E+01	1.030E+02	1.065E+02	1.090E+02	1.109E+02	1.125E+02	1.138E+02	1.150E+02
N (dB)	-1.284E+02	-1.284E+02	-1.284E+02	-1.284E+02	-1.284E+02	-1.284E+02	-1.284E+02	-1.284E+02	-1.284E+02
C/N (dB)	3.913E+00	2.137E+01	2.740E+01	3.092E+01	3.342E+01	3.536E+01	3.695E+01	3.828E+01	3.944E+01
C/No for entire link (dB)	7.867E+01	9.605E+01	1.021E+02	1.056E+02	1.081E+02	1.100E+02	1.116E+02	1.130E+02	1.141E+02
Eb/No (dB)	10	10	10	10	10	10	10	10	10
spacecraft-centered nadir angle (deg)	0	0	0	0	0	0	0	0	0
beamwidth (deg)	7.213E+00	1.026E+00	5.128E-01	3.419E-01	2.564E-01	2.051E-01	1.709E-01	1.465E-01	1.282E-01
lambda (fo) (deg)	48.88699612	5.77027929	2.87929486	1.91881237	1.43892115	1.15106729	0.95919123	0.822147623	0.71936992
lambda (fi) (deg)	0	0	0	0	0	0	0	0	0
slant range (km)	38273.0255	35824.0569	35795.4855	35790.21344	35788.3696	35787.5164	35787.053	35786.77362	35786.5923
Lf (km)	5442.078066	642.344853	320.521787	213.6013162	160.180045	128.136284	106.776729	91.52109769	80.079931
Wf (km)	5.442E+03	6.423E+02	3.205E+02	2.136E+02	1.602E+02	1.281E+02	1.068E+02	9.152E+01	8.008E+01
Fa (km^2)	2.326E+07	3.241E+05	8.069E+04	3.583E+04	2.015E+04	1.290E+04	8.954E+03	6.578E+03	5.036E+03
modulation	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK
throughput (Mbps)	3.688071766	201.754767	808.169216	1818.85893	3233.82439	5053.06567	7276.58277	9904.375696	12936.4445
C/N for entire link	3.105E+00	2.049E+01	2.651E+01	3.003E+01	3.253E+01	3.447E+01	3.606E+01	3.740E+01	3.856E+01
r	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01
Shannon's Limit (Mbps)	57.816	245.444	317.171	359.238	389.103	412.273	431.207	447.217	461.086
Practical achieveable throughput (Mbps)	25.714	25.714	25.714	25.714	25.714	25.714	25.714	25.714	25.714

Intelsat 702 Theoretical Throughputs based on a 36MHz Bandwidth (Ship to Ship)



Close-up of Intelsat 702 Theoretical Throughputs Based on a 36 MHz Bandwidth (Ship to Ship)



Thesis Antenna Spreadsheet
shore to ship link

uplink

altitude of satellite (km)	35786	35786	35786	35786	35786	35786	35786	35786	35786
diameter of ground antenna (m)	18.29	18.29	18.29	18.29	18.29	18.29	18.29	18.29	18.29
transmitted power (dBW)	40	40	40	40	40	40	40	40	40
frequency (Hz)	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09	8.400E+09
wavelength (m)	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02	3.57E-02
EIRPof ground antenna (dBW)	97	97	97	97	97	97	97	97	97
diameter of satellite antenna (m)	1.14	5	10	15	20	25	30	35	40
satellite antenna efficiency	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55
gain of spacecraft antenna (dB)	37.427882	50.269185	56.289785	59.811610	62.310385	64.248585	65.832210	67.171146	68.330985
rms surface error (m)	0.00E+00	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03
degraded (actual) gain of spacecraft (dB)	37.427882	50.03141159	56.0520115	59.5738367	62.07261142	64.01081168	65.5944366	66.9333724	68.09321133
bandwidth (Hz)	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07
free space path loss (dB)	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02	2.020E+02
atmospheric attenuation (dB)	3	3	3	3	3	3	3	3	3
line losses of receiver (dB)	2	2	2	2	2	2	2	2	2
equivalent temperature (K) on satellite	2710	2710	2710	2710	2710	2710	2710	2710	2710
No (dB)	-194.270307	-194.2703071	-194.270307	-194.27031	-194.270307	-194.270307	-194.27031	-194.27031	-194.270307
received power (C) (dBW)	-72.574717	-59.930626	-53.908384	-50.386255	-47.887374	-45.949125	-44.365473	-43.026521	-41.866672
required margin (dB)	3	3	3	3	3	3	3	3	3
C/No (dB)	1.217E+02	1.343E+02	1.404E+02	1.439E+02	1.464E+02	1.483E+02	1.499E+02	1.512E+02	1.524E+02
N (dB)	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02	-1.150E+02
C/N (dB)	4.240E+01	5.505E+01	6.107E+01	6.459E+01	6.709E+01	6.903E+01	7.061E+01	7.195E+01	7.311E+01
spacecraft-centered nadir angle (deg)	0	0	0	0	0	0	0	0	0
beamwidth (deg)	2.193E+00	5.000E-01	2.500E-01	1.667E-01	1.250E-01	1.000E-01	8.333E-02	7.143E-02	6.250E-02
lambda (fo) (deg)	12.4601678	2.807219145	1.40293648	0.935208	0.70138422	0.561099313	0.46757911	0.40078021	0.350681611
lambda (fi) (deg)	0	0	0	0	0	0	0	0	0
slant range (km)	35962.5645	35795.01673	35788.2526	35787.001	35786.56304	35786.36034	35786.2502	35786.1838	35786.14075
Lf (km)	1387.06019	312.4983523	156.174248	104.106927	78.07777088	62.4613191	52.050693	44.6146697	39.03771673
Wf (km)	1.387E+03	3.125E+02	1.562E+02	1.041E+02	7.808E+01	6.246E+01	5.205E+01	4.461E+01	3.904E+01
Fa (km^2)	1.511E+06	7.670E+04	1.916E+04	8.512E+03	4.788E+03	3.064E+03	2.128E+03	1.563E+03	1.197E+03

DSCS III antenna diameter
= .7112 m
DSCS III SLEP parameter

DSCS III S mm
0

downlink									
altitude of satellite (km)	35786	35786	35786	35786	35786	35786	35786	35786	35786
diameter of satellite antenna (m)	0.711	5	10	15	20	25	30	35	40
transmitted power (dBW)	6.99	6.99	6.99	6.99	6.99	6.99	6.99	6.99	6.99
line losses of transmitter (dB)	1	1	1	1	1	1	1	1	1
frequency (Hz)	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09
wavelength (m)	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02
antenna efficiency	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55
ideal gain of satellite antenna (dB)	27.086669	44.028677	50.049277	53.571103	56.069877	58.008078	59.591702	60.930638	62.090477
rms surface error (m)	0.00E+00	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03
degraded (actual) gain of satellite (dB)	27.0866694	43.97216911	49.992769	53.5145942	56.01336894	57.9515692	59.5351941	60.8741299	62.03396885
EIRPof spacecraft (dBW)	33.0766694	49.96216911	55.982769	59.5045942	62.00336894	63.9415692	65.5251941	66.8641299	68.02396885
diameter of ship antenna (m)	2.36	2.36	2.36	2.36	2.36	2.36	2.36	2.36	2.36
gain of ship antenna (dB)	37.507517	37.507517	37.507517	37.507517	37.507517	37.507517	37.507517	37.507517	37.507517
bandwidth (Hz)	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07	8.50E+07
free space path loss (dB)	1.963E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02
atmospheric attenuation (dB)	3	3	3	3	3	3	3	3	3
line losses of receiver (dB)	2	2	2	2	2	2	2	2	2
equivalent temperature (K) on ship	290	290	290	290	290	290	290	290	290
No (dB)	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602
received power (C) (dBW)	-130.718747	-113.258887	-107.231357	-103.708252	-101.209030	-99.270623	-97.686885	-96.347882	-95.187999
required margin (dB)	3	3	3	3	3	3	3	3	3
C/No (dB)	7.326E+01	9.072E+01	9.674E+01	1.003E+02	1.028E+02	1.047E+02	1.063E+02	1.076E+02	1.088E+02
N (dB)	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02	-1.247E+02
C/N (dB)	-6.037E+00	1.142E+01	1.745E+01	2.097E+01	2.347E+01	2.541E+01	2.699E+01	2.833E+01	2.949E+01
C/No for entire link (dB)	7.326E+01	9.072E+01	9.674E+01	1.003E+02	1.028E+02	1.047E+02	1.063E+02	1.076E+02	1.088E+02
Eb/No (dB)	10	10	10	10	10	10	10	10	10
spacecraft-centered nadir angle (deg)	0	0	0	0	0	0	0	0	0
beamwidth (deg)	7.213E+00	1.026E+00	5.128E-01	3.419E-01	2.564E-01	2.051E-01	1.709E-01	1.465E-01	1.282E-01
lambda (fo) (deg)	48.8869961	5.770279287	2.87929486	1.91881237	1.438921148	1.151067287	0.95919123	0.82214762	0.719369923
lambda (fi) (deg)	0	0	0	0	0	0	0	0	0
slant range (km)	38273.0255	35824.05692	35795.4855	35790.2134	35788.3696	35787.51641	35787.053	35786.7736	35786.59229
Lf (km)	5442.07807	642.3448532	320.521787	213.601316	160.1800446	128.1362844	106.776729	91.5210977	80.07993104
Wf (km)	5.442E+03	6.423E+02	3.205E+02	2.136E+02	1.602E+02	1.281E+02	1.068E+02	9.152E+01	8.008E+01
Fa (km^2)	2.326E+07	3.241E+05	8.069E+04	3.583E+04	2.015E+04	1.290E+04	8.954E+03	6.578E+03	5.036E+03
modulation	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK
throughput (Mbps)	1.06101387	59.11455888	236.835848	533.037657	947.7201446	1480.883331	2132.52722	2902.65182	3791.257117
C/N for entire link	-6.037E+00	1.142E+01	1.745E+01	2.097E+01	2.347E+01	2.541E+01	2.699E+01	2.833E+01	2.949E+01
r	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01
Shannon's Limit (Mbps)	27.272	331.071	494.919	593.189	663.332	717.868	762.479	800.223	832.932
Practical achieveable throughput (Mbps)	60.714	60.714	60.714	60.714	60.714	60.714	60.714	60.714	60.714

DSCS III SLEP Theoretical Throughputs Based on a 85 MHz Bandwidth (Shore to Ship)



Close-Up of DSCS III SLEP Theoretical Throughputs based on a 85 MHz Bandwidth (Shore to Ship)



Thesis Antenna Spreadsheet
shore to ship link

uplink

altitude of satellite (km)	35786	35786	35786	35786	35786	35786	35786	35786	35786
diameter of ground antenna (m)	18.29	18.29	18.29	18.29	18.29	18.29	18.29	18.29	18.29
transmitted power (dBW)	40	40	40	40	40	40	40	40	40
frequency (Hz)	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09	6.320E+09
wavelength (m)	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02	4.75E-02
gain of ground antenna (dB)	59.062815	59.062815	59.062815	59.062815	59.062815	59.062815	59.062815	59.062815	59.062815
EIRPof ground antenna (dBW)	97.00	97.00	97.00	97.00	97.00	97.00	97.00	97.00	97.00
diameter of satellite antenna (m)	0.711	5	10	15	20	25	30	35	40
satellite antenna efficiency	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55
gain of spacecraft antenna (dB)	30.855933	47.797941	53.818541	57.340366	59.839141	61.777341	63.360966	64.699902	65.859741
rms surface error (m)	0.00E+00	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03
degraded (actual) gain of spacecraft (dB)	30.8559328	47.6633428	53.6839427	57.2057679	59.7045426	61.6427429	63.2263678	64.56530359	65.7251425
bandwidth (Hz)	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07
free space path loss (dB)	1.997E+02	1.995E+02	1.995E+02	1.995E+02	1.995E+02	1.995E+02	1.995E+02	1.995E+02	1.995E+02
atmospheric attenuation (dB)	3	3	3	3	3	3	3	3	3
line losses of receiver (dB)	2	2	2	2	2	2	2	2	2
equivalent temperature (K) on satellite	3853	3853	3853	3853	3853	3853	3853	3853	3853
No (dB)	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201	-192.74201
received power (C) (dBW)	-76.839902	-59.829130	-53.805628	-50.283266	-47.784304	-45.846016	-44.262344	-42.923380	-41.763523
required margin (dB)	3	3	3	3	3	3	3	3	3
C/No (dB)	1.159E+02	1.329E+02	1.389E+02	1.425E+02	1.450E+02	1.469E+02	1.485E+02	1.498E+02	1.510E+02
N (dB)	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02	-1.172E+02
C/N (dB)	4.034E+01	5.735E+01	6.337E+01	6.690E+01	6.939E+01	7.133E+01	7.292E+01	7.426E+01	7.542E+01
spacecraft-centered nadir angle (deg)	0	0	0	0	0	0	0	0	0
beamwidth (deg)	4.673E+00	6.646E-01	3.323E-01	2.215E-01	1.661E-01	1.329E-01	1.108E-01	9.494E-02	8.307E-02
lambda (fo) (deg)	27.916613	3.73294692	1.86489081	1.24306561	0.93224806	0.74577951	0.62147436	0.532687878	0.46609938
lambda (fi) (deg)	0	0	0	0	0	0	0	0	0
slant range (km)	36650.0579	35801.9401	35789.98	35787.7685	35786.9947	35786.6366	35786.4421	35786.32477	35786.2487
Lf (km)	3107.6646	415.549945	207.598792	138.377495	103.777428	83.0198347	69.1822416	59.29857114	51.8859698
Wf (km)	3.108E+03	4.155E+02	2.076E+02	1.384E+02	1.038E+02	8.302E+01	6.918E+01	5.930E+01	5.188E+01
Fa (km^2)	7.585E+06	1.356E+05	3.385E+04	1.504E+04	8.458E+03	5.413E+03	3.759E+03	2.762E+03	2.114E+03

Intelsat 702 antenna diameter
= .7112 m
Intelsat 702 parameter

73.26007 mm

downlink									
altitude of satellite (km)	35786	35786	35786	35786	35786	35786	35786	35786	35786
diameter of satellite antenna (m)	0.711	5	10	15	20	25	30	35	40
transmitted power (dBW)	12.04	12.04	12.04	12.04	12.04	12.04	12.04	12.04	12.04
line losses of transmitter (dB)	1	1	1	1	1	1	1	1	1
frequency (Hz)	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09	4.095E+09
wavelength (m)	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02	7.33E-02
antenna efficiency	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55	0.55
ideal gain of satellite antenna (dB)	27.086669	44.028677	50.049277	53.571103	56.069877	58.008078	59.591702	60.930638	62.090477
rms surface error (m)	0.00E+00	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03	1.00E-03
degraded (actual) gain of satellite (dB)	27.0866694	43.9721691	49.992769	53.5145942	56.0133689	57.9515692	59.5351941	60.87412991	62.0339689
EIRPof spacecraft (dBW)	38.1266694	55.0121691	61.032769	64.5545942	67.0533689	68.9915692	70.5751941	71.91412991	73.0739689
diameter of ship antenna (m)	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7
gain of ship antenna (dB)	38.676553	38.676553	38.676553	38.676553	38.676553	38.676553	38.676553	38.676553	38.676553
bandwidth (Hz)	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07	3.60E+07
free space path loss (dB)	1.963E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02	1.957E+02
atmospheric attenuation (dB)	3	3	3	3	3	3	3	3	3
line losses of receiver (dB)	2	2	2	2	2	2	2	2	2
equivalent temperature (K) on ship	290	290	290	290	290	290	290	290	290
No (dB)	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602	-203.97602
received power (C) (dBW)	-124.499712	-107.039852	-101.012322	-97.489217	-94.989995	-93.051587	-91.467850	-90.128846	-88.968964
required margin (dB)	3	3	3	3	3	3	3	3	3
C/No (dB)	7.948E+01	9.694E+01	1.030E+02	1.065E+02	1.090E+02	1.109E+02	1.125E+02	1.138E+02	1.150E+02
N (dB)	-1.284E+02	-1.284E+02	-1.284E+02	-1.284E+02	-1.284E+02	-1.284E+02	-1.284E+02	-1.284E+02	-1.284E+02
C/N (dB)	3.913E+00	2.137E+01	2.740E+01	3.092E+01	3.342E+01	3.536E+01	3.695E+01	3.828E+01	3.944E+01
C/No for entire link (dB)	7.948E+01	9.694E+01	1.030E+02	1.065E+02	1.090E+02	1.109E+02	1.125E+02	1.138E+02	1.150E+02
Eb/No (dB)	10	10	10	10	10	10	10	10	10
spacecraft-centered nadir angle (deg)	0	0	0	0	0	0	0	0	0
beamwidth (deg)	7.213E+00	1.026E+00	5.128E-01	3.419E-01	2.564E-01	2.051E-01	1.709E-01	1.465E-01	1.282E-01
lambda (fo) (deg)	48.8869961	5.77027929	2.87929486	1.91881237	1.43892115	1.15106729	0.95919123	0.822147623	0.71936992
lambda (fi) (deg)	0	0	0	0	0	0	0	0	0
slant range (km)	38273.0255	35824.0569	35795.4855	35790.2134	35788.3696	35787.5164	35787.053	35786.77362	35786.5923
Lf (km)	5442.07807	642.344853	320.521787	213.601316	160.180045	128.136284	106.776729	91.52109769	80.079931
Wf (km)	5.442E+03	6.423E+02	3.205E+02	2.136E+02	1.602E+02	1.281E+02	1.068E+02	9.152E+01	8.008E+01
Fa (km^2)	2.326E+07	3.241E+05	8.069E+04	3.583E+04	2.015E+04	1.290E+04	8.954E+03	6.578E+03	5.036E+03
modulation	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK	BPSK
throughput (Mbps)	4.44152299	247.461233	991.425487	2231.36449	3967.2789	6199.16881	8927.03424	12150.87519	15870.6917
C/N for entire link	3.912E+00	2.137E+01	2.740E+01	3.092E+01	3.342E+01	3.536E+01	3.694E+01	3.828E+01	3.944E+01
r	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01	4.000E-01
Shannon's Limit (Mbps)	64.493	255.964	327.764	369.844	399.714	422.887	441.822	457.832	471.702
Practical achieveable throughput (Mbps)	25.714	25.714	25.714	25.714	25.714	25.714	25.714	25.714	25.714

Intelsat 702 Theoretical Throughputs Based on a 36 MHz Bandwidth (Shore to Ship)



Close-Up of Intelsat 702 Theoretical Throughputs Based on a 36 MHz Bandwidth (Shore to Ship)



THIS PAGE INTENTIONALLY LEFT BLANK

APPENDIX C. LABORATORY EXPERIMENTAL RESULTS AND GRAPHS OF THESE RESULTS

This appendix contains all of the raw data collected during the experiment conducted on the PVDF membrane. Data processing results are also displayed to the right of the raw data. The graphs that follow are based on this processed data.

Deflection of Membrane from Nominal Pressure Setting by Piezoelectric Effect (positive values mean the membrane is bulging outward toward the laser)

Volts	.1 psi - Positive Lead on Plus Sign micrometers	.1 psi - Negative Lead on Plus Sign micrometers	.3 psi - Positive Lead on Plus Sign micrometers	.3 psi - Negative Lead on Plus Sign micrometers
0	0	0	0	0
50	40.2301	26.2694	3.7946	-13.914
100	26.4153	46.6023	3.3081	-21.0658
150	13.4269	46.6023	0.3405	-11.822
200	-14.9357	45.1917	4.0865	-24.131
250	-14.5465	49.2289	-0.5838	-27.8773
300	-36.6837	60.2216	6.2757	-29.3855
350	-46.5122	69.9493	0.0486	-17.125
400	-60.2337	71.3598	0.2432	-0.973
450	-70.9876	88.8202	3.3568	7.8811
500	-84.5156	97.5743	5.4	8.4648
550	-87.6787	102.3889	8.4648	-3.6974
600	-90.2579	121.8899	12.0161	6.373
650	-90.1605	123.3488	8.9513	16.1511
700	-78.5301	132.88	11.9188	25.5884
750	-63.0073	132.1992	15.9565	45.0944
800	-65.343	137.9858	21.7454	43.1487
850	-53.5675	169.786	11.5783	45.2889

	.5 psi - Positive Lead on Plus Sign micrometers	.5 psi - Negative Lead on Plus Sign micrometers	.7 psi - Positive Lead on Plus Sign micrometers	.7 psi - Negative Lead on Plus Sign micrometers
0	0	0	0	0
50	11.5783	11.3837	-6.3731	2.6757
100	13.9133	18.0969	0.6324	12.0647
150	12.5026	81.7194	7.7351	29.6259
200	8.4648	96.5043	10.508	40.3761
250	11.0918	116.2003	18.9726	29.6259
300	16.9781	146.7385	20.0428	51.2232
350	16.443	157.5817	20.8211	43.0514
400	25.1992	156.901	16.0538	64.7937
450	26.9018	160.9367	25.3451	71.3598
500	22.7183	165.1669	29.5286	73.8889
550	26.3667	164.4862	23.0588	85.7075
600	26.3667	170.3208	20.8211	99.4223
650	30.161	171.4877	12.989	102.4862
700	30.842	172.4116	19.459	115.8598
750	30.7933	170.8557	3.4541	127.8713
800	30.9879	177.5167	6.9081	137.6454
850	30.3069	183.6914	12.4539	151.3092

Deflection of Membrane due to Piezoelectric Effect (0.1 psi) - Positive Lead Attached to Positive Sign Side



Deflection of Membrane due to Piezoelectric Effect (0.3 psi) - Positive Lead Attached to Positive Sign Side




Deflection of Membrane due to Piezoelectric Effect (0.5 psi) - Positive Lead Attached to Positve Sign Side
Micrometers
35
30
25
20
15
10
5
0
0 50 100 150 200 250 300 350 400 450 500 550 600 650 700 750 800 850
Volts
Deflection of Membrane

Deflection of Membrane due to Piezoelectric Effect (0.7 psi) - Positive Lead Attached Positive Sign Side



Deflection of Membrane due to Piezoelectric Effect (0.1 psi) - Negative Lead Attached to Positive Sign Side




Deflection of Membrane due to Piezoelectric Effect (0.3 psi) - Negative Lead Attached to Positive Sign Side
Micrometers
100
90
80
70
60
50
40
30
20
10
0
0
50
100
150
200
250
300
350
400
450
500
550
600
650
700
750
800
850
Volts
Deflection of Membrane


Deflection of Membrane due to Piezoelectric Effect (0.5 psi) - Negative Lead Attached Positive Sign Side
Micrometers
200
180
160
140
120
100
80
60
40
20
0
0 50 100 150 200 250 300 350 400 450 500 550 600 650 700 750 800 850
Volts
Deflection of Membrane


Deflection of Membrane due to Piezoelectirc Effect (0.7 psi) - Negative Lead Attached Positive Sign Side
Micrometers
160
140
120
100
80
60
40
20
0
0
50
100
150
200
250
300
350
400
450
500
550
600
650
700
750
800
850
Volts
Deflection of Membrane

APPENDIX D. ANALYTICAL MODEL INFORMATION

This appendix contains four main parts. They all pertain to the analytical model produced using NASTRAN and PATRAN. The four parts are:

1. inputs necessary for the thermal analogy to model the piezoelectric effect
2. graphical displays of computer model results
3. the NASTRAN input file used to model the membrane
4. compilation of the displacement vectors of the first nine elements (starting at the center of the membrane and proceeding radially outward for six elements, then starting over at the center at element eight) for all combinations of pressures and temperatures

This data is completely computer generated.

Voltage	d 31(in/in)/(V/in)	E 3 (V/in)	alpha 31 ((in/in)/(deg F)	T (deg F)	d 32(in/in)/(V/in)	E 3 (V/in)	alpha 32 ((in/in)/(deg F)	T (deg F)
0.00E+00	9.06E-10	0	4.42E-07	0.00E+00	1.182E-10	0	5.76923E-08	0.00E+00
5.00E+01	9.06E-10	24404.53	4.42E-07	5.00E+01	1.182E-10	24404.53	5.76923E-08	5.00E+01
1.00E+02	9.06E-10	48809.06	4.42E-07	1.00E+02	1.182E-10	48809.06	5.76923E-08	1.00E+02
1.50E+02	9.06E-10	73213.59	4.42E-07	1.50E+02	1.182E-10	73213.59	5.76923E-08	1.50E+02
2.00E+02	9.06E-10	97618.12	4.42E-07	2.00E+02	1.182E-10	97618.12	5.76923E-08	2.00E+02
2.50E+02	9.06E-10	122022.6	4.42E-07	2.50E+02	1.182E-10	122022.6	5.76923E-08	2.50E+02
3.00E+02	9.06E-10	146427.2	4.42E-07	3.00E+02	1.182E-10	146427.2	5.76923E-08	3.00E+02
3.50E+02	9.06E-10	170831.7	4.42E-07	3.50E+02	1.182E-10	170831.7	5.76923E-08	3.50E+02
4.00E+02	9.06E-10	195236.2	4.42E-07	4.00E+02	1.182E-10	195236.2	5.76923E-08	4.00E+02
4.50E+02	9.06E-10	219640.8	4.42E-07	4.50E+02	1.182E-10	219640.8	5.76923E-08	4.50E+02
5.00E+02	9.06E-10	244045.3	4.42E-07	5.00E+02	1.182E-10	244045.3	5.76923E-08	5.00E+02
5.50E+02	9.06E-10	268449.8	4.42E-07	5.50E+02	1.182E-10	268449.8	5.76923E-08	5.50E+02
6.00E+02	9.06E-10	292854.4	4.42E-07	6.00E+02	1.182E-10	292854.4	5.76923E-08	6.00E+02
6.50E+02	9.06E-10	317258.9	4.42E-07	6.50E+02	1.182E-10	317258.9	5.76923E-08	6.50E+02
7.00E+02	9.06E-10	341663.4	4.42E-07	7.00E+02	1.182E-10	341663.4	5.76923E-08	7.00E+02
7.50E+02	9.06E-10	366067.9	4.42E-07	7.50E+02	1.182E-10	366067.9	5.76923E-08	7.50E+02
8.00E+02	9.06E-10	390472.5	4.42E-07	8.00E+02	1.182E-10	390472.5	5.76923E-08	8.00E+02
8.50E+02	9.06E-10	414877	4.42E-07	8.50E+02	1.182E-10	414877	5.76923E-08	8.50E+02


Displacement of Membrane at .1 psig NASTRAN
Micrometers
6450
6400
6350
6300
6250
6200
6150
6100
6050
0
-50
-100
-150
-200
-250
-300
-350
-400
-450
-500
-550
-600
-650
-700
-750
-800
-850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at .2 psig NASTRAN
8100
8050
8000
7950
7900
7850
7800
7750
Micrometers
0
-50
-100
-150
-200
-250
-300
-350
-400
-450
-500
-550
-600
-650
-700
-750
-800
-850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at .3 psig NASTRAN
Micrometers
9250
9200
9150
9100
9050
9000
8950
0
-50
-100
-150
-200
-250
-300
-350
-400
-450
-500
-550
-600
-650
-700
-750
-800
-850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at .4 psig NASTRAN
Micrometers
10200
10150
10100
10050
10000
9950
9900
0
-50
-100
-150
-200
-250
-300
-350
-400
-450
-500
-550
-600
-650
-700
-750
-800
-850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at .5 psig NASTRAN
10950
10900
10850
10800
10750
10700
Micrometers
0
-50
-100
-150
-200
-250
-300
-350
-400
-450
-500
-550
-600
-650
-700
-750
-800
-850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at .6 psig NASTRAN
Micrometers
11620
11600
11580
11560
11540
11520
11500
11480
11460
11440
11420
0
-50
-100
-150
-200
-250
-300
-350
-400
-450
-500
-550
-600
-650
-700
-750
-800
-850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at .7 psig NASTRAN
Micrometers
12240
12220
12200
12180
12160
12140
12120
12100
12080
12060
12040
0
-50
-100
-150
-200
-250
-300
-350
-400
-450
-500
-550
-600
-650
-700
-750
-800
-850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membranes at .8 psig NASTRAN
12780
12760
12740
12720
12700
12680
12660
12640
12620
12600
Micrometers
0
-50
-100
-150
-200
-250
-300
-350
-400
-450
-500
-550
-600
-650
-700
-750
-800
-850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at .9 psig NASTRAN
Micrometers
13300
13280
13260
13240
13220
13200
13180
13160
13140
13120
13100
0
-50
-100
-150
-200
-250
-300
-350
-400
-450
-500
-550
-600
-650
-700
-750
-800
-850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at 1 psig NASTRAN
Micrometers
13760
13740
13720
13700
13680
13660
13640
13620
13600
13580
0
-50
-100
-150
-200
-250
-300
-350
-400
-450
-500
-550
-600
-650
-700
-750
-800
-850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at .1 psig NASTRAN
Micrometers
6650
6600
6550
6500
6450
6400
6350
6300
6250
0
50
100
150
200
250
300
350
400
450
500
550
600
650
700
750
800
850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at .2 psig NASTRAN
Micrometers
8250
8200
8150
8100
8050
8000
7950
0
50
100
150
200
250
300
350
400
450
500
550
600
650
700
750
800
850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at .3 psig NASTRAN
Micrometers
9400
9350
9300
9250
9200
9150
9100
0
50
100
150
200
250
300
350
400
450
500
550
600
650
700
750
800
850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at .4 psig NASTRAN
10300
10250
10200
10150
10100
10050
Micrometers
0
50
100
150
200
250
300
350
400
450
500
550
600
650
700
750
800
850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at .5 psig NASTRAN
Micrometers
11100
11050
11000
10950
10900
10850
0
50
100
150
200
250
300
350
400
450
500
550
600
650
700
750
800
850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at .6 psig NASTRAN
Micrometers
11740
11720
11700
11680
11660
11640
11620
11600
11580
11560
11540
0
50
100
150
200
250
300
350
400
450
500
550
600
650
700
750
800
850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at .7 psig NASTRAN
Micrometers
12340
12320
12300
12280
12260
12240
12220
12200
12180
12160
12140
0
50
100
150
200
250
300
350
400
450
500
550
600
650
700
750
800
850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at .8 psig NASTRAN
Micrometers
12900
12880
12860
12840
12820
12800
12780
12760
12740
12720
12700
0
50
100
150
200
250
300
350
400
450
500
550
600
650
700
750
800
850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at .8 psig NASTRAN
Micrometers
13400
13380
13360
13340
13320
13300
13280
13260
13240
13220
0
50
100
150
200
250
300
350
400
450
500
550
600
650
700
750
800
850
Volts (Equivalent Degrees Fahrenheit)
Series1


Displacement of Membrane at 1 psig NASTRAN
Micrometers
13860
13840
13820
13800
13780
13760
13740
13720
13700
13680
0
50
100
150
200
250
300
350
400
450
500
550
600
650
700
750
800
850
Volts (Equivalent Degrees Fahrenheit)
Series1

```
$ NASTRAN input file created by the MSC MSC/NASTRAN input file
$ translator ( MSC/PATRAN Version 8.5 ) on July      06, 2000 at
$ 12:55:22.
$ASSIGN OUTPUT2 = 'dinky.op2', UNIT = 12
$ Direct Text Input for File Management Section
$ Linear Static Analysis, Database
SOL 106
TIME 600
$ Direct Text Input for Executive Control
CEND
SEALL = ALL
SUPER = ALL
TITLE = LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE
ECHO = SORT
MAXLINES = 999999999
SET 45 = 1,2,3,4,5,6,7,8,9
DISP = 45
TEMP(INIT) = 1
$
$ Direct Text Input for Global Case Control Data
   SPC = 2
SUBCASE 4
LOAD = 33
LABEL = Small Mechanical Load
NLPARM = 108
$$$$
$$$$Subcase 5
$$$TEMP(LOAD) = 55
$$$NLPARM=108
$$$LABEL = THERMAL LOADS AT 200
$stress=all
SUBCASE 10
    LOAD = 100
TEMP(LOAD) = 55
    LABEL = ONE TENTH, -50 DEG
    NLPARM = 108
SUBCASE 20
    LOAD = 200
TEMP(LOAD) = 55
    LABEL = TWO TENTHS, -50 DEG
    NLPARM = 108
SUBCASE 30
    LOAD = 300
TEMP(LOAD) = 55
    LABEL = THREE TENTHS, -50 DEG
    NLPARM = 108
SUBCASE 40
    LOAD = 400
TEMP(LOAD) = 55
    LABEL = FOUR TENTHS, -50 DEG
    NLPARM = 108
SUBCASE 50
    LOAD = 500
TEMP(LOAD) = 55
    LABEL = FIVE TENTHS, -50 DEG
    NLPARM = 108
SUBCASE 60
    LOAD = 600
TEMP(LOAD) = 55
    LABEL = SIX TENTHS, -50 DEG
    NLPARM = 108
SUBCASE 70
    LOAD = 700
TEMP(LOAD) = 55
    LABEL = SEVEN TENTHS, -50 DEG
    NLPARM = 108
SUBCASE 80
    LOAD = 800
TEMP(LOAD) = 55
    LABEL = EIGHT TENTHS, -50 DEG
    NLPARM = 108
SUBCASE 90
    LOAD = 900
TEMP(LOAD) = 55
    LABEL = NINE TENTHS, -50 DEG
    NLPARM = 108
SUBCASE 101
    LOAD = 1000
TEMP(LOAD) = 55
    LABEL = ONE, -50 DEG
    NLPARM = 108
$   TEMPERATURE(BOTH) = 2
$   DISPLACEMENT(SORT1,REAL)=ALL
$   SPCFORCES(SORT1,REAL)=ALL
$   STRESS(SORT1,REAL,VONMISES,BILIN)=ALL
$ Direct Text Input for this Subcase
BEGIN BULK
PARAM    POST    -1
PARAM    PATVER  3.
$PARAM    AUTOSPC YES
$PARAM    INREL   0
$PARAM    ALTRED  NO
PARAM   COUPMASS -1
PARAM,K6ROT,1000.
PARAM    WTMASS  1.
PARAM,NOCOMPS,-1
PARAM   PRTMAXIM YES
$ Direct Text Input for Bulk Data
$ Elements and Element Properties for region : membrane
```

```
$12345678901234567890123456789012345678901234567890
$23456789012345678901234567890123456789012345678901234567890
PSHELL   1       1       .002047   1     1.25
$$PSHELL,1,1,0.002047,1,1.0
$ Pset: "membrane" will be imported as: "pshell.1"
CTRIA3   1       1       1       2       8
CQUAD4   2       1       2       3       9       8
CQUAD4   3       1       3       4       10      9
CQUAD4   4       1       4       5       11      10
CQUAD4   5       1       5       6       12      11
CQUAD4   6       1       6       7       13      12
CTRIA3   7       1       1       8       14
CQUAD4   8       1       8       9       15      14
CQUAD4   9       1       9       10      16      15
CQUAD4   10      1       10      11      17      16
CQUAD4   11      1       11      12      18      17
CQUAD4   12      1       12      13      19      18
CTRIA3   13      1       1       14      20
CQUAD4   14      1       14      15      21      20
CQUAD4   15      1       15      16      22      21
CQUAD4   16      1       16      17      23      22
CQUAD4   17      1       17      18      24      23
CQUAD4   18      1       18      19      25      24
CTRIA3   19      1       1       20      26
CQUAD4   20      1       20      21      27      26
CQUAD4   21      1       21      22      28      27
CQUAD4   22      1       22      23      29      28
CQUAD4   23      1       23      24      30      29
CQUAD4   24      1       24      25      31      30
CTRIA3   25      1       1       26      32
CQUAD4   26      1       26      27      33      32
CQUAD4   27      1       27      28      34      33
CQUAD4   28      1       28      29      35      34
CQUAD4   29      1       29      30      36      35
CQUAD4   30      1       30      31      37      36
CTRIA3   31      1       1       32      38
CQUAD4   32      1       32      33      39      38
CQUAD4   33      1       33      34      40      39
CQUAD4   34      1       34      35      41      40
CQUAD4   35      1       35      36      42      41
CQUAD4   36      1       36      37      43      42
CTRIA3   37      1       1       38      44
CQUAD4   38      1       38      39      45      44
CQUAD4   39      1       39      40      46      45
CQUAD4   40      1       40      41      47      46
CQUAD4   41      1       41      42      48      47
CQUAD4   42      1       42      43      49      48
CTRIA3   43      1       1       44      50
CQUAD4   44      1       44      45      51      50
CQUAD4   45      1       45      46      52      51
CQUAD4   46      1       46      47      53      52
CQUAD4   47      1       47      48      54      53
CQUAD4   48      1       48      49      55      54
CTRIA3   49      1       1       50      56
CQUAD4   50      1       50      51      57      56
CQUAD4   51      1       51      52      58      57
CQUAD4   52      1       52      53      59      58
CQUAD4   53      1       53      54      60      59
CQUAD4   54      1       54      55      61      60
CTRIA3   55      1       1       56      62
CQUAD4   56      1       56      57      63      62
CQUAD4   57      1       57      58      64      63
CQUAD4   58      1       58      59      65      64
CQUAD4   59      1       59      60      66      65
CQUAD4   60      1       60      61      67      66
CTRIA3   61      1       1       62      68
CQUAD4   62      1       62      63      69      68
CQUAD4   63      1       63      64      70      69
CQUAD4   64      1       64      65      71      70
CQUAD4   65      1       65      66      72      71
CQUAD4   66      1       66      67      73      72
CTRIA3   67      1       1       68      74
CQUAD4   68      1       68      69      75      74
CQUAD4   69      1       69      70      76      75
CQUAD4   70      1       70      71      77      76
CQUAD4   71      1       71      72      78      77
CQUAD4   72      1       72      73      79      78
CTRIA3   73      1       1       74      80
CQUAD4   74      1       74      75      81      80
CQUAD4   75      1       75      76      82      81
CQUAD4   76      1       76      77      83      82
CQUAD4   77      1       77      78      84      83
CQUAD4   78      1       78      79      85      84
CTRIA3   79      1       1       80      86
CQUAD4   80      1       80      81      87      86
CQUAD4   81      1       81      82      88      87
CQUAD4   82      1       82      83      89      88
CQUAD4   83      1       83      84      90      89
CQUAD4   84      1       84      85      91      90
CTRIA3   85      1       1       86      92
CQUAD4   86      1       86      87      93      92
CQUAD4   87      1       87      88      94      93
CQUAD4   88      1       88      89      95      94
CQUAD4   89      1       89      90      96      95
CQUAD4   90      1       90      91      97      96
CTRIA3   91      1       1       92      98
CQUAD4   92      1       92      93      99      98
CQUAD4   93      1       93      94      100     99
CQUAD4   94      1       94      95      101     100
```

```
CQUAD4  95      1       95      96      102     101
CQUAD4  96      1       96      97      103     102
CTRIA3  97      1       1       98      104
CQUAD4  98      1       98      99      105     104
CQUAD4  99      1       99      100     106     105
CQUAD4  100     1       100     101     107     106
CQUAD4  101     1       101     102     108     107
CQUAD4  102     1       102     103     109     108
CTRIA3  103     1       1       104     110
CQUAD4  104     1       104     105     111     110
CQUAD4  105     1       105     106     112     111
CQUAD4  106     1       106     107     113     112
CQUAD4  107     1       107     108     114     113
CQUAD4  108     1       108     109     115     114
CTRIA3  109     1       1       110     116
CQUAD4  110     1       110     111     117     116
CQUAD4  111     1       111     112     118     117
CQUAD4  112     1       112     113     119     118
CQUAD4  113     1       113     114     120     119
CQUAD4  114     1       114     115     121     120
CTRIA3  115     1       1       116     122
CQUAD4  116     1       116     117     123     122
CQUAD4  117     1       117     118     124     123
CQUAD4  118     1       118     119     125     124
CQUAD4  119     1       119     120     126     125
CQUAD4  120     1       120     121     127     126
CTRIA3  121     1       1       122     128
CQUAD4  122     1       122     123     129     128
CQUAD4  123     1       123     124     130     129
CQUAD4  124     1       124     125     131     130
CQUAD4  125     1       125     126     132     131
CQUAD4  126     1       126     127     133     132
CTRIA3  127     1       1       128     134
CQUAD4  128     1       128     129     135     134
CQUAD4  129     1       129     130     136     135
CQUAD4  130     1       130     131     137     136
CQUAD4  131     1       131     132     138     137
CQUAD4  132     1       132     133     139     138
CTRIA3  133     1       1       134     140
CQUAD4  134     1       134     135     141     140
CQUAD4  135     1       135     136     142     141
CQUAD4  136     1       136     137     143     142
CQUAD4  137     1       137     138     144     143
CQUAD4  138     1       138     139     145     144
CTRIA3  139     1       1       140     146
CQUAD4  140     1       140     141     147     146
CQUAD4  141     1       141     142     148     147
CQUAD4  142     1       142     143     149     148
CQUAD4  143     1       143     144     150     149
CQUAD4  144     1       144     145     151     150
CTRIA3  145     1       1       146     152
CQUAD4  146     1       146     147     153     152
CQUAD4  147     1       147     148     154     153
CQUAD4  148     1       148     149     155     154
CQUAD4  149     1       149     150     156     155
CQUAD4  150     1       150     151     157     156
CTRIA3  151     1       1       152     158
CQUAD4  152     1       152     153     159     158
CQUAD4  153     1       153     154     160     159
CQUAD4  154     1       154     155     161     160
CQUAD4  155     1       155     156     162     161
CQUAD4  156     1       156     157     163     162
CTRIA3  157     1       1       158     164
CQUAD4  158     1       158     159     165     164
CQUAD4  159     1       159     160     166     165
CQUAD4  160     1       160     161     167     166
CQUAD4  161     1       161     162     168     167
CQUAD4  162     1       162     163     169     168
CTRIA3  163     1       1       164     170
CQUAD4  164     1       164     165     171     170
CQUAD4  165     1       165     166     172     171
CQUAD4  166     1       166     167     173     172
CQUAD4  167     1       167     168     174     173
CQUAD4  168     1       168     169     175     174
CTRIA3  169     1       1       170     176
CQUAD4  170     1       170     171     177     176
CQUAD4  171     1       171     172     178     177
CQUAD4  172     1       172     173     179     178
CQUAD4  173     1       173     174     180     179
CQUAD4  174     1       174     175     181     180
CTRIA3  175     1       1       176     182
CQUAD4  176     1       176     177     183     182
CQUAD4  177     1       177     178     184     183
CQUAD4  178     1       178     179     185     184
CQUAD4  179     1       179     180     186     185
CQUAD4  180     1       180     181     187     186
CTRIA3  181     1       1       182     188
CQUAD4  182     1       182     183     189     188
CQUAD4  183     1       183     184     190     189
CQUAD4  184     1       184     185     191     190
CQUAD4  185     1       185     186     192     191
CQUAD4  186     1       186     187     193     192
CTRIA3  187     1       1       188     194
CQUAD4  188     1       188     189     195     194
CQUAD4  189     1       189     190     196     195
CQUAD4  190     1       190     191     197     196
CQUAD4  191     1       191     192     198     197
CQUAD4  192     1       192     193     199     198
CTRIA3  193     1       1       194     200
```

```
CQUAD4   194      1       194      195      201      200
CQUAD4   195      1       195      196      202      201
CQUAD4   196      1       196      197      203      202
CQUAD4   197      1       197      198      204      203
CQUAD4   198      1       198      199      205      204
CTRIA3   199      1       1        200      206
CQUAD4   200      1       200      201      207      206
CQUAD4   201      1       201      202      208      207
CQUAD4   202      1       202      203      209      208
CQUAD4   203      1       203      204      210      209
CQUAD4   204      1       204      205      211      210
CTRIA3   205      1       1        206      212
CQUAD4   206      1       206      207      213      212
CQUAD4   207      1       207      208      214      213
CQUAD4   208      1       208      209      215      214
CQUAD4   209      1       209      210      216      215
CQUAD4   210      1       210      211      217      216
CTRIA3   211      1       1        212      218
CQUAD4   212      1       212      213      219      218
CQUAD4   213      1       213      214      220      219
CQUAD4   214      1       214      215      221      220
CQUAD4   215      1       215      216      222      221
CQUAD4   216      1       216      217      223      222
$ Referenced Material Records
$ Material Record : kynar
$ Description of Material : Date: 01-Jun-00          Time: 15:44:27
$MAT1     1       580156.          .387     .064307 2.498-7 0.
MAT1      1       537500.          .387     .064307 2.498-7 0.
$ Nodes of the Entire Model
GRID      1               0.       0.       0.
GRID      2               .708333  0.       0.
GRID      3               1.41666  0.       0.
GRID      4               2.125    0.       0.
GRID      5               2.83333  0.       0.
GRID      6               3.54166  0.       0.
GRID      7               4.25     0.       0.
GRID      8               .697572  .123001  0.
GRID      9               1.39514  .246002  0.
GRID      10              2.09271  .369003  0.
GRID      11              2.79028  .492005  0.
GRID      12              3.48786  .615007  0.
GRID      13              4.18543  .738009  0.
GRID      14              .665615  .242264  0.
GRID      15              1.33123  .484529  0.
GRID      16              1.99684  .726795  0.
GRID      17              2.66246  .969061  0.
GRID      18              3.32807  1.21132  0.
GRID      19              3.99369  1.45359  0.
GRID      20              .613434  .354167  0.
GRID      21              1.22686  .708335  0.
GRID      22              1.84030  1.06250  0.
GRID      23              2.45373  1.41667  0.
GRID      24              3.06716  1.77084  0.
GRID      25              3.68060  2.12501  0.
GRID      26              .542615  .455308  0.
GRID      27              1.08522  .910617  0.
GRID      28              1.62784  1.36592  0.
GRID      29              2.17045  1.82123  0.
GRID      30              2.71306  2.27654  0.
GRID      31              3.25567  2.73186  0.
GRID      32              .455307  .542615  0.
GRID      33              .910614  1.08523  0.
GRID      34              1.36592  1.62784  0.
GRID      35              1.82122  2.17046  0.
GRID      36              2.27652  2.71308  0.
GRID      37              2.73183  3.25570  0.
GRID      38              .354166  .613435  0.
GRID      39              .708331  1.22687  0.
GRID      40              1.06249  1.84030  0.
GRID      41              1.41665  2.45374  0.
GRID      42              1.77081  3.06718  0.
GRID      43              2.12497  3.68062  0.
GRID      44              .242263  .665616  0.
GRID      45              .484526  1.33123  0.
GRID      46              .726786  1.99684  0.
GRID      47              .969045  2.66246  0.
GRID      48              1.21130  3.32808  0.
GRID      49              1.45356  3.99370  0.
GRID      50              .123     .697572  0.
GRID      51              .245998  1.39514  0.
GRID      52              .368994  2.09271  0.
GRID      53              .491989  2.79029  0.
GRID      54              .614982  3.48786  0.
GRID      55              .737973  4.18543  0.
GRID      56             -1.092-6  .708333  0.
GRID      57             -4.041-6  1.41666  0.
GRID      58             -8.846-6  2.125    0.
GRID      59             -1.604-5  2.83333  0.
GRID      60             -2.469-5  3.54166  0.
GRID      61             -3.599-5  4.25     0.
GRID      62              -.123002 .697572  0.
GRID      63              -.246006 1.39514  0.
GRID      64              -.369012 2.09271  0.
GRID      65              -.492021 2.79028  0.
GRID      66              -.615032 3.48785  0.
GRID      67              -.738045 4.18542  0.
GRID      68              -.242265 .665615  0.
GRID      69              -.484533 1.33123  0.
GRID      70              -.726803 1.99684  0.
```

```
GRID      71            -.969076 2.66245 0.
GRID      72            -1.21135 3.32806 0.
GRID      73            -1.45362 3.99367 0.
GRID      74            -.354168 .613434 0.
GRID      75            -.708338 1.22686 0.
GRID      76            -1.06251 1.84029 0.
GRID      77            -1.41668 2.45372 0.
GRID      78            -1.77086 3.06715 0.
GRID      79            -2.12504 3.68058 0.
GRID      80            -.455309 .542614 0.
GRID      81            -.91062  1.08522 0.
GRID      82            -1.36593 1.62783 0.
GRID      83            -1.82124 2.17044 0.
GRID      84            -2.27656 2.71305 0.
GRID      85            -2.73188 3.25565 0.
GRID      86            -.542616 .455307 0.
GRID      87            -1.08523 .910611 0.
GRID      88            -1.62785 1.36591 0.
GRID      89            -2.17047 1.82121 0.
GRID      90            -2.71309 2.27651 0.
GRID      91            -3.25572 2.73180 0.
GRID      92            -.613435 .354165 0.
GRID      93            -1.22687 .708328 0.
GRID      94            -1.84031 1.06248 0.
GRID      95            -2.45375 1.41664 0.
GRID      96            -3.06719 1.77079 0.
GRID      97            -3.68063 2.12494 0.
GRID      98            -.665616 .242263 0.
GRID      99            -1.33123 .484522 0.
GRID      100           -1.99685 .726778 0.
GRID      101           -2.66247 .96903  0.
GRID      102           -3.32809 1.21128 0.
GRID      103           -3.99371 1.45352 0.
GRID      104           -.697572 .122999 0.
GRID      105           -1.39514 .245994 0.
GRID      106           -2.09271 .368986 0.
GRID      107           -2.79029 .491973 0.
GRID      108           -3.48786 .614958 0.
GRID      109           -4.18544 .737938 0.
GRID      110           -.708333-2.184-6 0.
GRID      111           -1.41666-8.082-6 0.
GRID      112           -2.125   -1.769-5 0.
GRID      113           -2.83333-3.208-5 0.
GRID      114           -3.54166-4.938-5 0.
GRID      115           -4.25    -7.199-5 0.
GRID      116           -.697572-.123003 0.
GRID      117           -1.39514-.24601  0.
GRID      118           -2.09271-.369022 0.
GRID      119           -2.79028-.492036 0.
GRID      120           -3.48785-.615055 0.
GRID      121           -4.18542-.738079 0.
GRID      122           -.665615-.242266 0.
GRID      123           -1.33122-.484537 0.
GRID      124           -1.99684-.726812 0.
GRID      125           -2.66245-.969091 0.
GRID      126           -3.32805-1.21137 0.
GRID      127           -3.99366-1.45366 0.
GRID      128           -.613433-.354169 0.
GRID      129           -1.22686-.708341 0.
GRID      130           -1.84029-1.06251 0.
GRID      131           -2.45372-1.41669 0.
GRID      132           -3.06714-1.77088 0.
GRID      133           -3.68056-2.12507 0.
GRID      134           -.542613-.45531  0.
GRID      135           -1.08522-.910623 0.
GRID      136           -1.62783-1.36594 0.
GRID      137           -2.17043-1.82126 0.
GRID      138           -2.71303-2.27658 0.
GRID      139           -3.25563-2.73191 0.
GRID      140           -.455306-.542617 0.
GRID      141           -.910608-1.08523 0.
GRID      142           -1.36590-1.62785 0.
GRID      143           -1.8212 -2.17048 0.
GRID      144           -2.27649-2.71311 0.
GRID      145           -2.73177-3.25574 0.
GRID      146           -.354164-.613436 0.
GRID      147           -.708324-1.22687 0.
GRID      148           -1.06247-1.84031 0.
GRID      149           -1.41662-2.45376 0.
GRID      150           -1.77077-3.06720 0.
GRID      151           -2.12491-3.68065 0.
GRID      152           -.242262-.665617 0.
GRID      153           -.484518-1.33123 0.
GRID      154           -.726769-1.99685 0.
GRID      155           -.969015-2.66247 0.
GRID      156           -1.21125-3.32810 0.
GRID      157           -1.45349-3.99372 0.
GRID      158           -.122998-.697573 0.
GRID      159           -.24599 -1.39514 0.
GRID      160           -.368977-2.09272 0.
GRID      161           -.491958-2.79029 0.
GRID      162           -.614933-3.48787 0.
GRID      163           -.737903-4.18545 0.
GRID      164            3.010-6-.708333 0.
GRID      165            1.185-5-1.41666 0.
GRID      166            2.654-5-2.125   0.
GRID      167            4.706-5-2.83333 0.
GRID      168            7.341-5-3.54166 0.
GRID      169            1.056-4-4.25    0.
```

```
GRID     170             .123004-.697572 0.
GRID     171             .246014-1.39514 0.
GRID     172             .369029-2.09271 0.
GRID     173             .492052-2.79028 0.
GRID     174             .615079-3.48784 0.
GRID     175             .738114-4.18541 0.
GRID     176             .242267-.665614 0.
GRID     177             .484541-1.33122 0.
GRID     178             .72682 -1.99683 0.
GRID     179             .969105-2.66244 0.
GRID     180             1.21139-3.32805 0.
GRID     181             1.45369-3.99365 0.
GRID     182             .354169-.613433 0.
GRID     183             .708345-1.22686 0.
GRID     184             1.06252-1.84028 0.
GRID     185             1.41671-2.45371 0.
GRID     186             1.77090-3.06713 0.
GRID     187             2.12510-3.68054 0.
GRID     188             .455311-.542613 0.
GRID     189             .910626-1.08522 0.
GRID     190             1.36594-1.62782 0.
GRID     191             1.82127-2.17042 0.
GRID     192             2.27660-2.71302 0.
GRID     193             2.73194-3.25561 0.
GRID     194             .542617-.455305 0.
GRID     195             1.08523-.910605 0.
GRID     196             1.62786-1.3659  0.
GRID     197             2.17049-1.82118 0.
GRID     198             2.71313-2.27647 0.
GRID     199             3.25576-2.73175 0.
GRID     200             .613437-.354163 0.
GRID     201             1.22687-.708321 0.
GRID     202             1.84032-1.06247 0.
GRID     203             2.45376-1.41661 0.
GRID     204             3.06721-1.77075 0.
GRID     205             3.68067-2.12488 0.
GRID     206             .665617-.242261 0.
GRID     207             1.33123-.484515 0.
GRID     208             1.99685-.726761 0.
GRID     209             2.66248-.969002 0.
GRID     210             3.32810-1.21123 0.
GRID     211             3.99373-1.45346 0.
GRID     212             .697573-.122997 0.
GRID     213             1.39514-.245986 0.
GRID     214             2.09272-.368968 0.
GRID     215             2.79029-.491943 0.
GRID     216             3.48787-.61491  0.
GRID     217             4.18545-.73787  0.
GRID     218             .708333 1.238-7 0.
GRID     219             1.41666 2.476-7 0.
GRID     220             2.125   3.715-7 0.
GRID     221             2.83333 4.953-7 0.
GRID     222             3.54166 6.192-7 0.
GRID     223             4.25    7.430-7 0.
$ Loads for Load Case : loadcase1
$SPCADD   2       1
$23456789012345678901234567890123456789012345678901234567890
LOAD     100     1.      1.      10
LOAD     33      1.      1.      11
LOAD     200     1.      1.      20
LOAD     300     1.      1.      30
LOAD     400     1.      1.      40
LOAD     500     1.      1.      50
LOAD     600     1.      1.      60
LOAD     700     1.      1.      70
LOAD     800     1.      1.      80
LOAD     900     1.      1.      90
LOAD     1000    1.      1.      101
PLOAD4   11      1       .10                             THRU    216
PLOAD4   10      1       .1                              THRU    216
PLOAD4   20      1       .2                              THRU    216
PLOAD4   30      1       .3                              THRU    216
PLOAD4   40      1       .4                              THRU    216
PLOAD4   50      1       .5                              THRU    216
PLOAD4   60      1       .6                              THRU    216
PLOAD4   70      1       .7                              THRU    216
PLOAD4   80      1       .8                              THRU    216
PLOAD4   90      1       .9                              THRU    216
PLOAD4   101     1       1.0                             THRU    216
$ Static Plate Element Temperatures of Load Set : temperature
TEMPD    1       0
TEMPD,55,-50.0
$+       A 2       THRU    216
$ Displacement Constraints of Load Set : constraint
SPC1     2       123456  7       13      19      25      31      37      +       B
+       B 43     49      55      61      67      73      79      85      +       C
+       C 91     97      103     109     115     121     127     133     +       D
+       D 139    145     151     157     163     169     175     181     +       E
+       E 187    193     199     205     211     217     223
$ Pressure Loads of Load Set : pressure.1
PARAM,LGDISP,1
NLPARM,108,20
$NLPARM,107,8,,ITER
$ Referenced Coordinate Frames
ENDDATA
```

ONE TENTH, ZERO DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.341992E-03	7.401508E-08	2.133318E-01	4.767032E-06	-3.194503E-03	-5.698712E-07
2	G	3.587988E-03	7.349566E-03	2.514677E-01	-1.103176E-01	-1.476892E-02	5.080811E-03
3	G	4.534828E-03	8.846126E-03	2.499020E-01	-8.563810E-02	1.971927E-02	6.239635E-04
4	G	5.228249E-03	8.234358E-03	2.196153E-01	-6.538023E-02	7.205004E-02	-2.608204E-03
5	G	4.716984E-03	6.243060E-03	1.661580E-01	-4.700415E-02	6.834459E-02	-2.289620E-03
6	G	2.905966E-03	3.391708E-03	9.238727E-02	-5.754874E-02	1.687762E-01	-6.500938E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.094946E-03	6.582240E-03	2.393183E-01	-8.740198E-02	-2.736874E-02	6.174818E-03
9	G	3.969544E-03	7.959296E-03	2.311131E-01	-6.769782E-02	2.627526E-02	3.668207E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, ZERO DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.699800E-03	1.900756E-07	2.688976E-01	1.839473E-05	1.517781E-02	-1.255206E-06
2	G	5.657619E-03	1.171388E-02	3.170216E-01	-1.449520E-01	-1.793619E-02	7.857751E-03
3	G	7.199376E-03	1.407835E-02	3.150148E-01	-1.108159E-01	2.398902E-02	1.075015E-03
4	G	8.308156E-03	1.309270E-02	2.767770E-01	-8.485006E-02	9.233310E-02	-4.319508E-03
5	G	7.475621E-03	9.907982E-03	2.091379E-01	-5.601881E-02	8.507415E-02	-3.609077E-03
6	G	4.664267E-03	5.411784E-03	1.167564E-01	-7.577603E-02	2.122634E-01	-1.049676E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.905153E-03	1.043558E-02	3.012488E-01	-1.115717E-01	-3.500446E-02	9.848427E-03
9	G	6.283277E-03	1.261670E-02	2.908130E-01	-8.601391E-02	3.350478E-02	5.465528E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, ZERO DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.827071E-03	3.296506E-07	3.079243E-01	3.776644E-05	3.347854E-02	-1.804291E-06
2	G	7.381059E-03	1.537338E-02	3.629159E-01	-1.692394E-01	-2.032832E-02	1.019281E-02
3	G	9.427924E-03	1.846821E-02	3.606077E-01	-1.285687E-01	2.704221E-02	1.458444E-03
4	G	1.088789E-02	1.716879E-02	3.168018E-01	-9.846851E-02	1.064855E-01	-5.772921E-03
5	G	9.785834E-03	1.298225E-02	2.392366E-01	-6.223028E-02	9.684050E-02	-4.719901E-03
6	G	6.145012E-03	7.111489E-03	1.338336E-01	-8.868869E-02	2.424940E-01	-1.388027E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.415361E-03	1.365929E-02	3.446157E-01	-1.283657E-01	-4.029152E-02	1.293319E-02
9	G	8.215570E-03	1.651759E-02	3.326161E-01	-9.873720E-02	3.847246E-02	7.060374E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, ZERO DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.824279E-03	4.875732E-07	3.390261E-01	6.160066E-05	5.096036E-02	-2.113337E-06
2	G	8.910754E-03	1.863601E-02	3.993870E-01	-1.884515E-01	-2.228624E-02	1.228464E-02
3	G	1.141145E-02	2.238498E-02	3.968402E-01	-1.426764E-01	2.949344E-02	1.803628E-03
4	G	1.318708E-02	2.080704E-02	3.486135E-01	-1.092386E-01	1.176858E-01	-7.074701E-03
5	G	1.184594E-02	1.572718E-02	2.631682E-01	-6.716432E-02	1.062277E-01	-5.714348E-03
6	G	7.469765E-03	8.631983E-03	1.474169E-01	-9.904365E-02	2.663847E-01	-1.692065E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.756472E-03	1.653108E-02	3.790943E-01	-1.416347E-01	-4.442729E-02	1.568392E-02
9	G	9.934303E-03	1.999619E-02	3.658510E-01	-1.087726E-01	4.236004E-02	8.567687E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, ZERO DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.733309E-03	6.604511E-07	3.653156E-01	8.914154E-05	6.754070E-02	-2.123406E-06
2	G	1.030995E-02	2.163025E-02	4.301342E-01	-2.045407E-01	-2.394332E-02	1.421139E-02
3	G	1.322947E-02	2.598237E-02	4.273852E-01	-1.545321E-01	3.156491E-02	2.124286E-03
4	G	1.529706E-02	2.415056E-02	3.754366E-01	-1.182674E-01	1.270934E-01	-8.271642E-03
5	G	1.373792E-02	1.825094E-02	2.833554E-01	-7.133682E-02	1.141674E-01	-6.630572E-03
6	G	8.689254E-03	1.003195E-02	1.588780E-01	-1.078429E-01	2.864297E-01	-1.973036E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.983096E-03	1.916613E-02	4.081779E-01	-1.527627E-01	-4.784866E-02	1.820671E-02
9	G	1.150918E-02	2.319106E-02	3.938858E-01	-1.171724E-01	4.559385E-02	1.002825E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, ZERO DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.576771E-03	8.463200E-07	3.883161E-01	1.198958E-04	8.326672E-02	-1.794408E-06
2	G	1.161256E-02	2.442559E-02	4.569698E-01	-2.184867E-01	-2.537364E-02	1.601396E-02
3	G	1.492490E-02	2.934340E-02	4.540426E-01	-1.648382E-01	3.336866E-02	2.427868E-03
4	G	1.726710E-02	2.727639E-02	3.988505E-01	-1.261049E-01	1.352782E-01	-9.389993E-03
5	G	1.550585E-02	2.061162E-02	3.009839E-01	-7.499430E-02	1.211151E-01	-7.488977E-03
6	G	9.830929E-03	1.134300E-02	1.688890E-01	-1.155808E-01	3.038500E-01	-2.237032E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.012471E-02	2.162636E-02	4.335753E-01	-1.624303E-01	-5.077100E-02	2.055860E-02
9	G	1.297765E-02	2.617656E-02	4.183674E-01	-1.244550E-01	4.838090E-02	1.146241E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, ZERO DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.368637E-03	1.043875E-06	4.089008E-01	1.534995E-04	9.821242E-02	-1.097446E-06
2	G	1.283945E-02	2.706503E-02	4.809326E-01	-2.308585E-01	-2.662448E-02	1.771732E-02
3	G	1.652423E-02	3.251937E-02	4.778447E-01	-1.740040E-01	3.497084E-02	2.718891E-03
4	G	1.912758E-02	3.023202E-02	4.197606E-01	-1.330689E-01	1.425671E-01	-1.044636E-02
5	G	1.717687E-02	2.284497E-02	3.167335E-01	-7.827581E-02	1.273323E-01	-8.302107E-03
6	G	1.091176E-02	1.258460E-02	1.778352E-01	-1.225415E-01	3.193446E-01	-2.487816E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.119955E-02	2.394984E-02	4.562658E-01	-1.710281E-01	-5.331921E-02	2.277482E-02
9	G	1.436278E-02	2.899843E-02	4.402396E-01	-1.309180E-01	5.083937E-02	1.288188E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, ZERO DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.118314E-03	1.252067E-06	4.276222E-01	1.896795E-04	1.124524E-01	-1.115805E-08
2	G	1.400462E-02	2.957748E-02	5.026800E-01	-2.420164E-01	-2.772826E-02	1.933831E-02
3	G	1.804524E-02	3.554473E-02	4.994448E-01	-1.822887E-01	3.641428E-02	3.000361E-03
4	G	2.089888E-02	3.304930E-02	4.387399E-01	-1.393600E-01	1.491668E-01	-1.145202E-02
5	G	1.876916E-02	2.497493E-02	3.310342E-01	-8.126815E-02	1.329847E-01	-9.078379E-03
6	G	1.194312E-02	1.376981E-02	1.859604E-01	-1.289042E-01	3.333558E-01	-2.727912E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.221985E-02	2.616216E-02	4.768688E-01	-1.788021E-01	-5.557397E-02	2.487925E-02
9	G	1.568006E-02	3.168732E-02	4.600995E-01	-1.367493E-01	5.304433E-02	1.429357E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, ZERO DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.832514E-03	1.470081E-06	4.448548E-01	2.282205E-04	1.260549E-01	1.480952E-06
2	G	1.511807E-02	3.198354E-02	5.226576E-01	-2.522050E-01	-2.870859E-02	2.088898E-02
3	G	1.950064E-02	3.844401E-02	5.192854E-01	-1.898682E-01	3.772863E-02	3.274368E-03
4	G	2.259555E-02	3.575092E-02	4.561765E-01	-1.451146E-01	1.552172E-01	-1.241510E-02
5	G	2.029565E-02	2.701854E-02	3.441771E-01	-8.402963E-02	1.381845E-01	-9.823789E-03
6	G	1.293314E-02	1.490792E-02	1.934295E-01	-1.347904E-01	3.461829E-01	-2.959114E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.319438E-02	2.828150E-02	4.958042E-01	-1.859184E-01	-5.759095E-02	2.688901E-02
9	G	1.694051E-02	3.426507E-02	4.783516E-01	-1.420764E-01	5.504677E-02	1.570176E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, ZERO DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.051625E-02	1.697254E-06	4.608655E-01	2.689482E-04	1.390801E-01	3.391936E-06
2	G	1.618723E-02	3.429857E-02	5.411828E-01	-2.615984E-01	-2.958344E-02	2.237843E-02
3	G	2.089988E-02	4.123551E-02	5.376822E-01	-1.968684E-01	3.893548E-02	3.542423E-03
4	G	2.422840E-02	3.835374E-02	4.723471E-01	-1.504295E-01	1.608177E-01	-1.334169E-02
5	G	2.176594E-02	2.898846E-02	3.563698E-01	-8.660164E-02	1.430123E-01	-1.054280E-02
6	G	1.388785E-02	1.600586E-02	2.003604E-01	-1.402865E-01	3.580391E-01	-3.182759E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.412965E-02	3.032140E-02	5.133712E-01	-1.924952E-01	-5.941056E-02	2.881701E-02
9	G	1.815236E-02	3.674791E-02	4.952843E-01	-1.469900E-01	5.688317E-02	1.710918E-03

ONE TENTH, -50 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.340110E-03	7.428115E-08	2.128451E-01	4.820706E-06	-3.093266E-03	-5.687948E-07
2	G	3.573806E-03	7.377742E-03	2.511588E-01	-1.115135E-01	-1.483492E-02	5.071481E-03
3	G	4.521884E-03	8.881387E-03	2.496999E-01	-8.697136E-02	1.952435E-02	6.339154E-04
4	G	5.216466E-03	8.264905E-03	2.194424E-01	-6.612002E-02	7.222390E-02	-2.638099E-03
5	G	4.708288E-03	6.271722E-03	1.660596E-01	-4.742451E-02	6.795779E-02	-2.273157E-03
6	G	2.902673E-03	3.413449E-03	9.238085E-02	-5.830716E-02	1.688848E-01	-6.558518E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.085376E-03	6.596376E-03	2.388850E-01	-8.812183E-02	-2.740703E-02	6.182708E-03
9	G	3.952518E-03	7.971100E-03	2.306560E-01	-6.821154E-02	2.621001E-02	3.656474E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -50 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.695489E-03	1.901606E-07	2.684774E-01	1.843426E-05	1.522711E-02	-1.252465E-06
2	G	5.646479E-03	1.172431E-02	3.166179E-01	-1.450697E-01	-1.782726E-02	7.848052E-03
3	G	7.180028E-03	1.409234E-02	3.146470E-01	-1.108860E-01	2.377016E-02	1.094783E-03
4	G	8.284997E-03	1.310903E-02	2.764712E-01	-8.492364E-02	9.239355E-02	-4.330716E-03
5	G	7.455591E-03	9.927552E-03	2.089401E-01	-5.601626E-02	8.470047E-02	-3.592703E-03
6	G	4.654681E-03	5.430381E-03	1.166949E-01	-7.620370E-02	2.122201E-01	-1.053437E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.893503E-03	1.044339E-02	3.008387E-01	-1.116107E-01	-3.509798E-02	9.864526E-03
9	G	6.264481E-03	1.262562E-02	2.904265E-01	-8.607171E-02	3.352496E-02	5.432384E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -50 DEG SUBCASE 30
LOAD STEP = 4.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.822721E-03	3.299782E-07	3.075567E-01	3.783335E-05	3.353043E-02	-1.799412E-06
2	G	7.369811E-03	1.538384E-02	3.625630E-01	-1.693538E-01	-2.022869E-02	1.018174E-02
3	G	9.408536E-03	1.848219E-02	3.602862E-01	-1.286347E-01	2.684639E-02	1.478984E-03
4	G	1.086471E-02	1.718508E-02	3.165345E-01	-9.854170E-02	1.065437E-01	-5.785028E-03
5	G	9.765700E-03	1.300166E-02	2.390625E-01	-6.221803E-02	9.651127E-02	-4.703567E-03
6	G	6.135495E-03	7.130122E-03	1.337804E-01	-8.906911E-02	2.424554E-01	-1.391827E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.403677E-03	1.366700E-02	3.442564E-01	-1.284023E-01	-4.037400E-02	1.294937E-02
9	G	8.196723E-03	1.652636E-02	3.322772E-01	-9.879033E-02	3.849163E-02	7.025059E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -50 DEG SUBCASE 40
LOAD STEP = 5.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.819908E-03	4.878975E-07	3.386915E-01	6.168208E-05	5.101324E-02	-2.106644E-06
2	G	8.899365E-03	1.864665E-02	3.990668E-01	-1.885721E-01	-2.219472E-02	1.227260E-02
3	G	1.139207E-02	2.239911E-02	3.965490E-01	-1.427500E-01	2.931394E-02	1.824474E-03
4	G	1.316395E-02	2.082337E-02	3.483711E-01	-1.093134E-01	1.177421E-01	-7.087563E-03
5	G	1.182582E-02	1.574654E-02	2.630098E-01	-6.714895E-02	1.059271E-01	-5.698006E-03
6	G	7.460356E-03	8.650656E-03	1.473690E-01	-9.939503E-02	2.663496E-01	-1.695908E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.744778E-03	1.653871E-02	3.787669E-01	-1.416744E-01	-4.450060E-02	1.569982E-02
9	G	9.915403E-03	2.000480E-02	3.655417E-01	-1.088242E-01	4.237664E-02	8.532427E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -50 DEG SUBCASE 50
LOAD STEP = 6.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.728907E-03	6.608419E-07	3.650045E-01	8.924057E-05	6.759333E-02	-2.114550E-06
2	G	1.029848E-02	2.164088E-02	4.298367E-01	-2.046583E-01	-2.385704E-02	1.419874E-02
3	G	1.321006E-02	2.599648E-02	4.271145E-01	-1.546037E-01	3.139688E-02	2.145426E-03
4	G	1.527392E-02	2.416683E-02	3.752113E-01	-1.183401E-01	1.271475E-01	-8.284899E-03
5	G	1.371773E-02	1.827020E-02	2.832076E-01	-7.131873E-02	1.138874E-01	-6.614246E-03
6	G	8.679868E-03	1.005063E-02	1.588336E-01	-1.081717E-01	2.863965E-01	-1.976893E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.971375E-03	1.917369E-02	4.078732E-01	-1.528009E-01	-4.791618E-02	1.822251E-02
9	G	1.149023E-02	2.319956E-02	3.935978E-01	-1.172212E-01	4.560918E-02	9.992832E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -50 DEG SUBCASE 60
LOAD STEP = 7.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.572337E-03	8.467820E-07	3.880230E-01	1.200103E-04	8.331862E-02	-1.783222E-06
2	G	1.160104E-02	2.443619E-02	4.566893E-01	-2.186005E-01	-2.529143E-02	1.600087E-02
3	G	1.490546E-02	2.935746E-02	4.537874E-01	-1.649071E-01	3.320949E-02	2.449239E-03
4	G	1.724393E-02	2.729259E-02	3.986380E-01	-1.261755E-01	1.353302E-01	-9.403517E-03
5	G	1.548560E-02	2.063078E-02	3.008443E-01	-7.497447E-02	1.208511E-01	-7.472665E-03
6	G	9.821549E-03	1.136167E-02	1.688472E-01	-1.158920E-01	3.038180E-01	-2.240897E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.011296E-02	2.163383E-02	4.332880E-01	-1.624668E-01	-5.083411E-02	2.057432E-02
9	G	1.295867E-02	2.618497E-02	4.180957E-01	-1.245012E-01	4.839526E-02	1.142697E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -50 DEG SUBCASE 70
LOAD STEP = 8.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.364175E-03	1.044396E-06	4.086220E-01	1.536290E-04	9.826335E-02	-1.083836E-06
2	G	1.282787E-02	2.707558E-02	4.806656E-01	-2.309684E-01	-2.654559E-02	1.770389E-02
3	G	1.650475E-02	3.253337E-02	4.776019E-01	-1.740701E-01	3.481886E-02	2.740447E-03
4	G	1.910436E-02	3.024815E-02	4.195584E-01	-1.331373E-01	1.426173E-01	-1.046007E-02
5	G	1.715656E-02	2.286404E-02	3.166003E-01	-7.825480E-02	1.270811E-01	-8.285803E-03
6	G	1.090237E-02	1.260325E-02	1.777954E-01	-1.228383E-01	3.193135E-01	-2.491684E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.118777E-02	2.395725E-02	4.559923E-01	-1.710629E-01	-5.337878E-02	2.279046E-02
9	G	1.434376E-02	2.900675E-02	4.399810E-01	-1.309619E-01	5.085292E-02	1.284652E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -50 DEG SUBCASE 80
LOAD STEP = 9.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.113822E-03	1.252646E-06	4.273553E-01	1.898231E-04	1.125023E-01	4.977331E-09
2	G	1.399301E-02	2.958797E-02	5.024242E-01	-2.421227E-01	-2.765216E-02	1.932460E-02
3	G	1.802573E-02	3.555866E-02	4.992120E-01	-1.823522E-01	3.626829E-02	3.022067E-03
4	G	2.087563E-02	3.306536E-02	4.385461E-01	-1.394264E-01	1.492154E-01	-1.146588E-02
5	G	1.874879E-02	2.499392E-02	3.309062E-01	-8.124633E-02	1.327440E-01	-9.062080E-03
6	G	1.193373E-02	1.378845E-02	1.859221E-01	-1.291890E-01	3.333254E-01	-2.731781E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.220805E-02	2.616949E-02	4.766067E-01	-1.788354E-01	-5.563058E-02	2.489480E-02
9	G	1.566101E-02	3.169556E-02	4.598516E-01	-1.367913E-01	5.305718E-02	1.425836E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -50 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.827995E-03	1.470714E-06	4.445979E-01	2.283776E-04	1.261036E-01	1.499701E-06
2	G	1.510642E-02	3.199397E-02	5.224112E-01	-2.523078E-01	-2.863491E-02	2.087505E-02
3	G	1.948109E-02	3.845786E-02	5.190611E-01	-1.899295E-01	3.758777E-02	3.296199E-03
4	G	2.257226E-02	3.576690E-02	4.559897E-01	-1.451791E-01	1.552642E-01	-1.242907E-02
5	G	2.027521E-02	2.703745E-02	3.440535E-01	-8.400726E-02	1.379530E-01	-9.807492E-03
6	G	1.292373E-02	1.492654E-02	1.933926E-01	-1.350649E-01	3.461531E-01	-2.962984E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.318255E-02	2.828877E-02	4.955517E-01	-1.859503E-01	-5.764504E-02	2.690448E-02
9	G	1.692144E-02	3.427324E-02	4.781128E-01	-1.421166E-01	5.505901E-02	1.566675E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -50 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.051170E-02	1.697941E-06	4.606173E-01	2.691182E-04	1.391278E-01	3.413375E-06
2	G	1.617554E-02	3.430895E-02	5.409444E-01	-2.616982E-01	-2.951188E-02	2.236431E-02
3	G	2.088029E-02	4.124929E-02	5.374652E-01	-1.969276E-01	3.879909E-02	3.564358E-03
4	G	2.420507E-02	3.836966E-02	4.721664E-01	-1.504922E-01	1.608635E-01	-1.335573E-02
5	G	2.174545E-02	2.900730E-02	3.562501E-01	-8.657888E-02	1.427885E-01	-1.052650E-02
6	G	1.387843E-02	1.602445E-02	2.003246E-01	-1.405521E-01	3.580098E-01	-3.186629E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.411779E-02	3.032861E-02	5.131269E-01	-1.925259E-01	-5.946245E-02	2.883240E-02
9	G	1.813325E-02	3.675601E-02	4.950534E-01	-1.470286E-01	5.689486E-02	1.707441E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

ONE TENTH, -100 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.337973E-03	7.494951E-08	2.123175E-01	4.909183E-06	-2.985408E-03	-5.697601E-07
2	G	3.558577E-03	7.407735E-03	2.508172E-01	-1.127651E-01	-1.490065E-02	5.061528E-03
3	G	4.507627E-03	8.919111E-03	2.494726E-01	-8.837102E-02	1.930935E-02	6.452446E-04
4	G	5.203352E-03	8.297700E-03	2.192494E-01	-6.690559E-02	7.240685E-02	-2.670262E-03
5	G	4.698484E-03	6.302553E-03	1.659484E-01	-4.786848E-02	6.754102E-02	-2.255370E-03
6	G	2.898776E-03	3.436888E-03	9.237087E-02	-5.911401E-02	1.689950E-01	-6.620207E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.074961E-03	6.611493E-03	2.384136E-01	-8.887411E-02	-2.745105E-02	6.191441E-03
9	G	3.934066E-03	7.983810E-03	2.301606E-01	-6.875311E-02	2.614201E-02	3.643246E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

TWO TENTHS, -100 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.691157E-03	1.905202E-07	2.680572E-01	1.847643E-05	1.527627E-02	-1.248713E-06
2	G	5.635408E-03	1.173461E-02	3.162127E-01	-1.451740E-01	-1.771712E-02	7.838580E-03
3	G	7.160627E-03	1.410619E-02	3.142774E-01	-1.109430E-01	2.355055E-02	1.114703E-03
4	G	8.261741E-03	1.312533E-02	2.761639E-01	-8.499318E-02	9.245283E-02	-4.341727E-03
5	G	7.435414E-03	9.947084E-03	2.087409E-01	-5.601097E-02	8.432796E-02	-3.576442E-03
6	G	4.644937E-03	5.448967E-03	1.166323E-01	-7.662639E-02	2.121746E-01	-1.057166E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.881834E-03	1.045123E-02	3.004286E-01	-1.116431E-01	-3.519308E-02	9.880900E-03
9	G	6.245694E-03	1.263463E-02	2.900405E-01	-8.612657E-02	3.354646E-02	5.398593E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

THREE TENTHS, -100 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.818393E-03	3.303268E-07	3.071887E-01	3.789037E-05	3.358318E-02	-1.794215E-06
2	G	7.358482E-03	1.539462E-02	3.622115E-01	-1.694845E-01	-2.013173E-02	1.017058E-02
3	G	9.389227E-03	1.849651E-02	3.599668E-01	-1.287184E-01	2.665234E-02	1.499262E-03
4	G	1.084166E-02	1.720156E-02	3.162685E-01	-9.862070E-02	1.066026E-01	-5.797445E-03
5	G	9.745697E-03	1.302121E-02	2.388895E-01	-6.220870E-02	9.618243E-02	-4.687210E-03
6	G	6.126054E-03	7.148823E-03	1.337277E-01	-8.945189E-02	2.424180E-01	-1.395661E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.392026E-03	1.367477E-02	3.438969E-01	-1.284474E-01	-4.045379E-02	1.296521E-02
9	G	8.177868E-03	1.653513E-02	3.319375E-01	-9.884719E-02	3.850844E-02	6.991255E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

FOUR TENTHS, -100 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.815549E-03	4.882976E-07	3.383566E-01	6.176219E-05	5.106654E-02	-2.099691E-06
2	G	8.887932E-03	1.865747E-02	3.987474E-01	-1.887014E-01	-2.210472E-02	1.226054E-02
3	G	1.137274E-02	2.241346E-02	3.962588E-01	-1.428327E-01	2.913562E-02	1.845148E-03
4	G	1.314090E-02	2.083980E-02	3.481293E-01	-1.093907E-01	1.177987E-01	-7.100588E-03
5	G	1.180575E-02	1.576597E-02	2.628518E-01	-6.713477E-02	1.056267E-01	-5.681665E-03
6	G	7.450973E-03	8.669370E-03	1.473214E-01	-9.974714E-02	2.663150E-01	-1.699767E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.733103E-03	1.654639E-02	3.784393E-01	-1.417183E-01	-4.457231E-02	1.571552E-02
9	G	9.896498E-03	2.001343E-02	3.652318E-01	-1.088776E-01	4.239183E-02	8.498236E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

FIVE TENTHS, -100 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.724511E-03	6.612528E-07	3.646933E-01	8.933952E-05	6.764618E-02	-2.105637E-06
2	G	1.028700E-02	2.165163E-02	4.295394E-01	-2.047803E-01	-2.377161E-02	1.418610E-02
3	G	1.319068E-02	2.601072E-02	4.268444E-01	-1.546800E-01	3.122950E-02	2.166471E-03
4	G	1.525081E-02	2.418317E-02	3.749863E-01	-1.184143E-01	1.272016E-01	-8.298245E-03
5	G	1.369757E-02	1.828950E-02	2.830600E-01	-7.130133E-02	1.136077E-01	-6.597931E-03
6	G	8.670487E-03	1.006933E-02	1.587893E-01	-1.085007E-01	2.863633E-01	-1.980759E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.959666E-03	1.918127E-02	4.075684E-01	-1.528413E-01	-4.798283E-02	1.823821E-02
9	G	1.147129E-02	2.320808E-02	3.933094E-01	-1.172708E-01	4.562372E-02	9.958071E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

SIX TENTHS, -100 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.567908E-03	8.472538E-07	3.877298E-01	1.201250E-04	8.337066E-02	-1.772012E-06
2	G	1.158950E-02	2.444687E-02	4.564089E-01	-2.187168E-01	-2.520978E-02	1.598779E-02
3	G	1.488603E-02	2.937162E-02	4.535326E-01	-1.649788E-01	3.305077E-02	2.470545E-03
4	G	1.722077E-02	2.730885E-02	3.984258E-01	-1.262469E-01	1.353822E-01	-9.417096E-03
5	G	1.546536E-02	2.064998E-02	3.007046E-01	-7.495505E-02	1.205873E-01	-7.456366E-03
6	G	9.812166E-03	1.138036E-02	1.688054E-01	-1.162030E-01	3.037859E-01	-2.244765E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.010122E-02	2.164133E-02	4.330005E-01	-1.625046E-01	-5.089664E-02	2.058996E-02
9	G	1.293969E-02	2.619340E-02	4.178238E-01	-1.245479E-01	4.840908E-02	1.139202E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

SEVEN TENTHS, -100 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.359713E-03	1.044926E-06	4.083432E-01	1.537585E-04	9.831440E-02	-1.070209E-06
2	G	1.281629E-02	2.708620E-02	4.803988E-01	-2.310800E-01	-2.646712E-02	1.769048E-02
3	G	1.648528E-02	3.254744E-02	4.773592E-01	-1.741381E-01	3.466722E-02	2.761953E-03
4	G	1.908116E-02	3.026432E-02	4.193563E-01	-1.332062E-01	1.426674E-01	-1.047382E-02
5	G	1.713625E-02	2.288314E-02	3.164670E-01	-7.823407E-02	1.268301E-01	-8.269516E-03
6	G	1.089298E-02	1.262193E-02	1.777555E-01	-1.231348E-01	3.192823E-01	-2.495554E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.117600E-02	2.396467E-02	4.557187E-01	-1.710986E-01	-5.343791E-02	2.280604E-02
9	G	1.432475E-02	2.901509E-02	4.397222E-01	-1.310061E-01	5.086607E-02	1.281156E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

EIGHT TENTHS, -100 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.109332E-03	1.253231E-06	4.270884E-01	1.899668E-04	1.125522E-01	2.112483E-08
2	G	1.398139E-02	2.959852E-02	5.021684E-01	-2.422301E-01	-2.757640E-02	1.931092E-02
3	G	1.800622E-02	3.557264E-02	4.989793E-01	-1.824172E-01	3.612259E-02	3.043732E-03
4	G	2.085239E-02	3.308145E-02	4.383523E-01	-1.394931E-01	1.492638E-01	-1.147975E-02
5	G	1.872842E-02	2.501293E-02	3.307782E-01	-8.122472E-02	1.325037E-01	-9.045799E-03
6	G	1.192433E-02	1.380710E-02	1.858838E-01	-1.294734E-01	3.332949E-01	-2.735650E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.219625E-02	2.617685E-02	4.763445E-01	-1.788693E-01	-5.568686E-02	2.491031E-02
9	G	1.564196E-02	3.170382E-02	4.596036E-01	-1.368334E-01	5.306972E-02	1.422349E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 265

NINE TENTHS, -100 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.823477E-03	1.471353E-06	4.443410E-01	2.285347E-04	1.261525E-01	1.518459E-06
2	G	1.509476E-02	3.200445E-02	5.221648E-01	-2.524115E-01	-2.856151E-02	2.086115E-02
3	G	1.946155E-02	3.847177E-02	5.188370E-01	-1.899918E-01	3.744717E-02	3.317993E-03
4	G	2.254898E-02	3.578291E-02	4.558030E-01	-1.452438E-01	1.553112E-01	-1.244304E-02
5	G	2.025479E-02	2.705638E-02	3.439300E-01	-8.398504E-02	1.377216E-01	-9.791214E-03
6	G	1.291432E-02	1.494517E-02	1.933557E-01	-1.353390E-01	3.461232E-01	-2.966852E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.317072E-02	2.829606E-02	4.952992E-01	-1.859828E-01	-5.769885E-02	2.691992E-02
9	G	1.690236E-02	3.428142E-02	4.778739E-01	-1.421570E-01	5.507099E-02	1.563205E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 266

ONE, -100 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.050716E-02	1.698633E-06	4.603690E-01	2.692883E-04	1.391755E-01	3.434821E-06
2	G	1.616384E-02	3.431936E-02	5.407061E-01	-2.617986E-01	-2.944057E-02	2.235022E-02
3	G	2.086071E-02	4.126310E-02	5.372483E-01	-1.969875E-01	3.866293E-02	3.586259E-03
4	G	2.418175E-02	3.838560E-02	4.719857E-01	-1.505552E-01	1.609090E-01	-1.336978E-02
5	G	2.172497E-02	2.902616E-02	3.561304E-01	-8.655624E-02	1.425650E-01	-1.051022E-02
6	G	1.386900E-02	1.604306E-02	2.002888E-01	-1.408173E-01	3.579803E-01	-3.190494E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.410594E-02	3.033584E-02	5.128826E-01	-1.925571E-01	-5.951411E-02	2.884776E-02
9	G	1.811415E-02	3.676413E-02	4.948224E-01	-1.470674E-01	5.690632E-02	1.703992E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -150 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.329357E-03	7.437726E-08	2.117432E-01	4.830657E-06	-3.062573E-03	-5.652146E-07
2	G	3.554602E-03	7.382452E-03	2.499540E-01	-1.108043E-01	-1.442291E-02	5.059672E-03
3	G	4.477409E-03	8.890040E-03	2.485298E-01	-8.601610E-02	1.895038E-02	6.768920E-04
4	G	5.159586E-03	8.284648E-03	2.184707E-01	-6.563790E-02	7.223493E-02	-2.638176E-03
5	G	4.658239E-03	6.303390E-03	1.654289E-01	-4.711042E-02	6.696173E-02	-2.240450E-03
6	G	2.877196E-03	3.447597E-03	9.215534E-02	-5.912841E-02	1.686269E-01	-6.614641E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.060283E-03	6.606536E-03	2.377721E-01	-8.760615E-02	-2.769051E-02	6.220341E-03
9	G	3.913347E-03	7.986764E-03	2.296523E-01	-6.793053E-02	2.631566E-02	3.592006E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -150 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.686817E-03	1.903182E-07	2.676367E-01	1.849735E-05	1.532557E-02	-1.245954E-06
2	G	5.624424E-03	1.174474E-02	3.158057E-01	-1.452613E-01	-1.760436E-02	7.829248E-03
3	G	7.141180E-03	1.411988E-02	3.139054E-01	-1.109813E-01	2.332847E-02	1.134883E-03
4	G	8.238425E-03	1.314163E-02	2.758557E-01	-8.505850E-02	9.251013E-02	-4.352503E-03
5	G	7.415195E-03	9.966651E-03	2.085413E-01	-5.600548E-02	8.395544E-02	-3.560192E-03
6	G	4.635133E-03	5.467578E-03	1.165695E-01	-7.704809E-02	2.121285E-01	-1.060899E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.870153E-03	1.045910E-02	3.000183E-01	-1.116668E-01	-3.529124E-02	9.897561E-03
9	G	6.226935E-03	1.264375E-02	2.896551E-01	-8.617808E-02	3.356984E-02	5.363917E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -150 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.814030E-03	3.251841E-07	3.068205E-01	3.753560E-05	3.363425E-02	-1.796317E-06
2	G	7.347537E-03	1.540439E-02	3.618525E-01	-1.695409E-01	-2.002201E-02	1.015977E-02
3	G	9.369682E-03	1.850986E-02	3.596382E-01	-1.287229E-01	2.644521E-02	1.521028E-03
4	G	1.081836E-02	1.721783E-02	3.159991E-01	-9.868506E-02	1.066554E-01	-5.808874E-03
5	G	9.725576E-03	1.304074E-02	2.387155E-01	-6.219887E-02	9.585211E-02	-4.670788E-03
6	G	6.116510E-03	7.167524E-03	1.336745E-01	-8.983377E-02	2.423800E-01	-1.399505E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.380294E-03	1.368252E-02	3.435376E-01	-1.284556E-01	-4.054826E-02	1.298240E-02
9	G	8.159135E-03	1.654421E-02	3.316016E-01	-9.889132E-02	3.853524E-02	6.951347E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -150 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.811173E-03	4.886369E-07	3.380218E-01	6.184368E-05	5.111982E-02	-2.092935E-06
2	G	8.876565E-03	1.866814E-02	3.984268E-01	-1.888199E-01	-2.201346E-02	1.224863E-02
3	G	1.135335E-02	2.242764E-02	3.959672E-01	-1.429043E-01	2.895646E-02	1.865994E-03
4	G	1.311776E-02	2.085618E-02	3.478866E-01	-1.094648E-01	1.178543E-01	-7.113407E-03
5	G	1.178558E-02	1.578537E-02	2.626931E-01	-6.711914E-02	1.053268E-01	-5.665388E-03
6	G	7.441477E-03	8.688073E-03	1.472733E-01	-1.000967E-01	2.662792E-01	-1.703605E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.721408E-03	1.655408E-02	3.781117E-01	-1.417571E-01	-4.464569E-02	1.573151E-02
9	G	9.877605E-03	2.002212E-02	3.649224E-01	-1.089289E-01	4.240833E-02	8.463067E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -150 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.720106E-03	6.616519E-07	3.643821E-01	8.943871E-05	6.769919E-02	-2.096743E-06
2	G	1.027555E-02	2.166231E-02	4.292416E-01	-2.048970E-01	-2.368563E-02	1.417355E-02
3	G	1.317127E-02	2.602490E-02	4.265735E-01	-1.547509E-01	3.106178E-02	2.187601E-03
4	G	1.522766E-02	2.419949E-02	3.747607E-01	-1.184869E-01	1.272552E-01	-8.311487E-03
5	G	1.367735E-02	1.830881E-02	2.829121E-01	-7.128321E-02	1.133282E-01	-6.581658E-03
6	G	8.661034E-03	1.008803E-02	1.587447E-01	-1.088282E-01	2.863295E-01	-1.984614E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.947946E-03	1.918888E-02	4.072635E-01	-1.528792E-01	-4.805029E-02	1.825406E-02
9	G	1.145235E-02	2.321666E-02	3.930213E-01	-1.173195E-01	4.563889E-02	9.922792E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -150 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.563472E-03	8.477174E-07	3.874366E-01	1.202402E-04	8.342290E-02	-1.760800E-06
2	G	1.157799E-02	2.445752E-02	4.561283E-01	-2.188301E-01	-2.512785E-02	1.597478E-02
3	G	1.486659E-02	2.938574E-02	4.532773E-01	-1.650473E-01	3.289188E-02	2.491906E-03
4	G	1.719759E-02	2.732510E-02	3.982132E-01	-1.263174E-01	1.354339E-01	-9.430614E-03
5	G	1.544509E-02	2.066919E-02	3.005648E-01	-7.493524E-02	1.203236E-01	-7.440100E-03
6	G	9.802728E-03	1.139905E-02	1.687634E-01	-1.165131E-01	3.037534E-01	-2.248629E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.008948E-02	2.164886E-02	4.327130E-01	-1.625410E-01	-5.095967E-02	2.060572E-02
9	G	1.292071E-02	2.620186E-02	4.175520E-01	-1.245941E-01	4.842327E-02	1.135673E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -150 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.355249E-03	1.045449E-06	4.080644E-01	1.538888E-04	9.836563E-02	-1.056563E-06
2	G	1.280473E-02	2.709679E-02	4.801317E-01	-2.311895E-01	-2.638847E-02	1.767712E-02
3	G	1.646580E-02	3.256149E-02	4.771162E-01	-1.742041E-01	3.451546E-02	2.783500E-03
4	G	1.905794E-02	3.028050E-02	4.191539E-01	-1.332746E-01	1.427173E-01	-1.048753E-02
5	G	1.711592E-02	2.290226E-02	3.163337E-01	-7.821310E-02	1.265792E-01	-8.253254E-03
6	G	1.088355E-02	1.264060E-02	1.777156E-01	-1.234307E-01	3.192509E-01	-2.499422E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.116422E-02	2.397212E-02	4.554450E-01	-1.711334E-01	-5.349740E-02	2.282171E-02
9	G	1.430574E-02	2.902346E-02	4.394634E-01	-1.310501E-01	5.087947E-02	1.277633E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -150 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.104838E-03	1.253812E-06	4.268213E-01	1.901112E-04	1.126024E-01	3.730487E-08
2	G	1.396978E-02	2.960906E-02	5.019125E-01	-2.423361E-01	-2.750053E-02	1.929727E-02
3	G	1.798671E-02	3.558661E-02	4.987465E-01	-1.824807E-01	3.597681E-02	3.065430E-03
4	G	2.082913E-02	3.309755E-02	4.381584E-01	-1.395595E-01	1.493121E-01	-1.149361E-02
5	G	1.870802E-02	2.503196E-02	3.306501E-01	-8.120295E-02	1.322634E-01	-9.029538E-03
6	G	1.191489E-02	1.382576E-02	1.858455E-01	-1.297574E-01	3.332642E-01	-2.739521E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.218444E-02	2.618423E-02	4.760823E-01	-1.789027E-01	-5.574339E-02	2.492590E-02
9	G	1.562292E-02	3.171211E-02	4.593556E-01	-1.368754E-01	5.308243E-02	1.418841E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -150 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.818955E-03	1.471989E-06	4.440840E-01	2.286926E-04	1.262015E-01	1.537260E-06
2	G	1.508311E-02	3.201493E-02	5.219182E-01	-2.525143E-01	-2.848804E-02	2.084726E-02
3	G	1.944200E-02	3.848566E-02	5.186126E-01	-1.900531E-01	3.730650E-02	3.339815E-03
4	G	2.252568E-02	3.579894E-02	4.556162E-01	-1.453084E-01	1.553580E-01	-1.245701E-02
5	G	2.023434E-02	2.707533E-02	3.438064E-01	-8.396272E-02	1.374903E-01	-9.774952E-03
6	G	1.290488E-02	1.496381E-02	1.933187E-01	-1.356129E-01	3.460931E-01	-2.970723E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.315889E-02	2.830337E-02	4.950466E-01	-1.860148E-01	-5.775286E-02	2.693542E-02
9	G	1.688329E-02	3.428964E-02	4.776351E-01	-1.421972E-01	5.508309E-02	1.559716E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -150 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.050261E-02	1.699322E-06	4.601206E-01	2.694591E-04	1.392234E-01	3.456320E-06
2	G	1.615215E-02	3.432978E-02	5.404676E-01	-2.618983E-01	-2.936919E-02	2.233615E-02
3	G	2.084113E-02	4.127693E-02	5.370312E-01	-1.970467E-01	3.852671E-02	3.608186E-03
4	G	2.415842E-02	3.840156E-02	4.718050E-01	-1.506180E-01	1.609545E-01	-1.338383E-02
5	G	2.170447E-02	2.904503E-02	3.560107E-01	-8.653355E-02	1.423415E-01	-1.049396E-02
6	G	1.385955E-02	1.606168E-02	2.002529E-01	-1.410823E-01	3.579507E-01	-3.194365E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.409408E-02	3.034309E-02	5.126384E-01	-1.925879E-01	-5.956592E-02	2.886317E-02
9	G	1.809505E-02	3.677227E-02	4.945914E-01	-1.471060E-01	5.691789E-02	1.700527E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -200 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.325145E-03	7.450133E-08	2.112128E-01	4.852360E-06	-3.017707E-03	-5.637214E-07
2	G	3.543497E-03	7.393614E-03	2.494490E-01	-1.109679E-01	-1.430976E-02	5.052850E-03
3	G	4.458285E-03	8.904914E-03	2.480719E-01	-8.614436E-02	1.869600E-02	6.945065E-04
4	G	5.136708E-03	8.301627E-03	2.180888E-01	-6.572475E-02	7.229453E-02	-2.648136E-03
5	G	4.638614E-03	6.323676E-03	1.651854E-01	-4.714686E-02	6.650320E-02	-2.224147E-03
6	G	2.867461E-03	3.466329E-03	9.207732E-02	-5.965106E-02	1.685755E-01	-6.652638E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.048743E-03	6.614806E-03	2.372560E-01	-8.767575E-02	-2.779697E-02	6.235649E-03
9	G	3.894632E-03	7.996119E-03	2.291646E-01	-6.800894E-02	2.632786E-02	3.567292E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256
TWO TENTHS, -200 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.682544E-03	1.905734E-07	2.672155E-01	1.854526E-05	1.537727E-02	-1.242979E-06
2	G	5.613167E-03	1.175579E-02	3.154044E-01	-1.454095E-01	-1.750137E-02	7.819555E-03
3	G	7.121970E-03	1.413456E-02	3.135413E-01	-1.110846E-01	2.311382E-02	1.154171E-03
4	G	8.215481E-03	1.315839E-02	2.755522E-01	-8.514321E-02	9.257090E-02	-4.364204E-03
5	G	7.395362E-03	9.986543E-03	2.083453E-01	-5.600919E-02	8.358337E-02	-3.543831E-03
6	G	4.625593E-03	5.486342E-03	1.165089E-01	-7.747866E-02	2.120869E-01	-1.064724E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.858560E-03	1.046712E-02	2.996074E-01	-1.117226E-01	-3.537972E-02	9.913184E-03
9	G	6.208139E-03	1.265278E-02	2.892666E-01	-8.624350E-02	3.358529E-02	5.333286E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -200 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.809710E-03	3.259699E-07	3.064521E-01	3.763924E-05	3.368774E-02	-1.790909E-06
2	G	7.336203E-03	1.541532E-02	3.615010E-01	-1.696751E-01	-1.992615E-02	1.014869E-02
3	G	9.350399E-03	1.852436E-02	3.593191E-01	-1.288104E-01	2.625190E-02	1.541222E-03
4	G	1.079535E-02	1.723446E-02	3.157334E-01	-9.876554E-02	1.067136E-01	-5.821362E-03
5	G	9.705601E-03	1.306040E-02	2.385427E-01	-6.219085E-02	9.552394E-02	-4.654460E-03
6	G	6.107036E-03	7.186289E-03	1.336219E-01	-9.021625E-02	2.423425E-01	-1.403355E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.368657E-03	1.369038E-02	3.431777E-01	-1.285028E-01	-4.062732E-02	1.299818E-02
9	G	8.140288E-03	1.655307E-02	3.312614E-01	-9.894916E-02	3.855113E-02	6.918191E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -200 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.806813E-03	4.889875E-07	3.376867E-01	6.192640E-05	5.117357E-02	-2.086160E-06
2	G	8.865143E-03	1.867904E-02	3.981071E-01	-1.889490E-01	-2.192397E-02	1.223667E-02
3	G	1.133402E-02	2.244207E-02	3.956768E-01	-1.429871E-01	2.877855E-02	1.886650E-03
4	G	1.309470E-02	2.087269E-02	3.476447E-01	-1.095423E-01	1.179103E-01	-7.126434E-03
5	G	1.176550E-02	1.580487E-02	2.625349E-01	-6.710525E-02	1.050271E-01	-5.649099E-03
6	G	7.432031E-03	8.706826E-03	1.472255E-01	-1.004475E-01	2.662439E-01	-1.707466E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.709738E-03	1.656182E-02	3.777839E-01	-1.418013E-01	-4.471721E-02	1.574725E-02
9	G	9.858708E-03	2.003082E-02	3.646124E-01	-1.089824E-01	4.242320E-02	8.429107E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -200 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.715709E-03	6.620672E-07	3.640707E-01	8.953828E-05	6.775243E-02	-2.087806E-06
2	G	1.026407E-02	2.167313E-02	4.289442E-01	-2.050193E-01	-2.360067E-02	1.416099E-02
3	G	1.315189E-02	2.603922E-02	4.263033E-01	-1.548277E-01	3.089481E-02	2.208617E-03
4	G	1.520455E-02	2.421590E-02	3.745356E-01	-1.185612E-01	1.273089E-01	-8.324843E-03
5	G	1.365718E-02	1.832817E-02	2.827644E-01	-7.126600E-02	1.130491E-01	-6.565391E-03
6	G	8.651598E-03	1.010677E-02	1.587003E-01	-1.091561E-01	2.862959E-01	-1.988480E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.936241E-03	1.919652E-02	4.069586E-01	-1.529199E-01	-4.811667E-02	1.826977E-02
9	G	1.143342E-02	2.322524E-02	3.927328E-01	-1.173693E-01	4.565309E-02	9.888312E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -200 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.559042E-03	8.481928E-07	3.871433E-01	1.203556E-04	8.347527E-02	-1.749561E-06
2	G	1.156646E-02	2.446826E-02	4.558479E-01	-2.189467E-01	-2.504660E-02	1.596178E-02
3	G	1.484717E-02	2.939996E-02	4.530224E-01	-1.651195E-01	3.273351E-02	2.513185E-03
4	G	1.717443E-02	2.734142E-02	3.980008E-01	-1.263889E-01	1.354855E-01	-9.444203E-03
5	G	1.542484E-02	2.068844E-02	3.004251E-01	-7.491597E-02	1.200603E-01	-7.423847E-03
6	G	9.793295E-03	1.141777E-02	1.687214E-01	-1.168232E-01	3.037210E-01	-2.252498E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.007774E-02	2.165641E-02	4.324254E-01	-1.625791E-01	-5.102198E-02	2.062138E-02
9	G	1.290174E-02	2.621035E-02	4.172800E-01	-1.246409E-01	4.843680E-02	1.132203E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -200 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.350787E-03	1.045982E-06	4.077854E-01	1.540190E-04	9.841696E-02	-1.042901E-06
2	G	1.279316E-02	2.710746E-02	4.798647E-01	-2.313013E-01	-2.631034E-02	1.766377E-02
3	G	1.644634E-02	3.257562E-02	4.768734E-01	-1.742725E-01	3.436412E-02	2.804983E-03
4	G	1.903475E-02	3.029673E-02	4.189517E-01	-1.333436E-01	1.427671E-01	-1.050129E-02
5	G	1.709560E-02	2.292140E-02	3.162003E-01	-7.819250E-02	1.263286E-01	-8.237008E-03
6	G	1.087411E-02	1.265930E-02	1.776756E-01	-1.237264E-01	3.192193E-01	-2.503292E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.115245E-02	2.397959E-02	4.551713E-01	-1.711694E-01	-5.355635E-02	2.283731E-02
9	G	1.428673E-02	2.903185E-02	4.392045E-01	-1.310944E-01	5.089237E-02	1.274160E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -200 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.100347E-03	1.254400E-06	4.265543E-01	1.902556E-04	1.126526E-01	5.349411E-08
2	G	1.395816E-02	2.961965E-02	5.016567E-01	-2.424437E-01	-2.742507E-02	1.928365E-02
3	G	1.796721E-02	3.560065E-02	4.985138E-01	-1.825460E-01	3.583137E-02	3.087074E-03
4	G	2.080589E-02	3.311370E-02	4.379645E-01	-1.396264E-01	1.493602E-01	-1.150750E-02
5	G	1.868764E-02	2.505101E-02	3.305221E-01	-8.118144E-02	1.320233E-01	-9.013296E-03
6	G	1.190545E-02	1.384443E-02	1.858071E-01	-1.300412E-01	3.332334E-01	-2.743390E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.217264E-02	2.619163E-02	4.758200E-01	-1.789369E-01	-5.579950E-02	2.494142E-02
9	G	1.560388E-02	3.172042E-02	4.591075E-01	-1.369177E-01	5.309474E-02	1.415376E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -200 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.814437E-03	1.472632E-06	4.438269E-01	2.288505E-04	1.262505E-01	1.556066E-06
2	G	1.507146E-02	3.202546E-02	5.216718E-01	-2.526182E-01	-2.841490E-02	2.083342E-02
3	G	1.942246E-02	3.849962E-02	5.183883E-01	-1.901156E-01	3.716613E-02	3.361591E-03
4	G	2.250241E-02	3.581501E-02	4.554294E-01	-1.453732E-01	1.554047E-01	-1.247099E-02
5	G	2.021390E-02	2.709430E-02	3.436828E-01	-8.394060E-02	1.372593E-01	-9.758710E-03
6	G	1.289542E-02	1.498246E-02	1.932816E-01	-1.358864E-01	3.460628E-01	-2.974590E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.314706E-02	2.831070E-02	4.947939E-01	-1.860475E-01	-5.780651E-02	2.695087E-02
9	G	1.686422E-02	3.429786E-02	4.773961E-01	-1.422376E-01	5.509487E-02	1.556266E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -200 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.049806E-02	1.700017E-06	4.598722E-01	2.696298E-04	1.392713E-01	3.477820E-06
2	G	1.614046E-02	3.434024E-02	5.402293E-01	-2.619988E-01	-2.929811E-02	2.232211E-02
3	G	2.082155E-02	4.129080E-02	5.368142E-01	-1.971070E-01	3.839075E-02	3.630070E-03
4	G	2.413510E-02	3.841754E-02	4.716242E-01	-1.506810E-01	1.609999E-01	-1.339789E-02
5	G	2.168398E-02	2.906392E-02	3.558909E-01	-8.651098E-02	1.421183E-01	-1.047772E-02
6	G	1.385009E-02	1.608031E-02	2.002170E-01	-1.413469E-01	3.579210E-01	-3.198231E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.408223E-02	3.035035E-02	5.123940E-01	-1.926192E-01	-5.961743E-02	2.887855E-02
9	G	1.807595E-02	3.678042E-02	4.943602E-01	-1.471448E-01	5.692917E-02	1.697097E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -250 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.320932E-03	7.463038E-08	2.106818E-01	4.874085E-06	-2.970313E-03	-5.619806E-07
2	G	3.532331E-03	7.405038E-03	2.489449E-01	-1.111462E-01	-1.420031E-02	5.045667E-03
3	G	4.439197E-03	8.920093E-03	2.476158E-01	-8.629019E-02	1.844441E-02	7.121947E-04
4	G	5.113875E-03	8.318784E-03	2.177075E-01	-6.581748E-02	7.235470E-02	-2.658388E-03
5	G	4.618987E-03	6.344083E-03	1.649420E-01	-4.718475E-02	6.604616E-02	-2.207666E-03
6	G	2.857662E-03	3.485128E-03	9.199908E-02	-6.017214E-02	1.685231E-01	-6.688290E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.037208E-03	6.623178E-03	2.367392E-01	-8.775382E-02	-2.790111E-02	6.250920E-03
9	G	3.875895E-03	8.005532E-03	2.286754E-01	-6.809194E-02	2.633825E-02	3.542903E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -250 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.678284E-03	1.885241E-07	2.667924E-01	1.843549E-05	1.542881E-02	-1.238610E-06
2	G	5.601716E-03	1.176736E-02	3.150064E-01	-1.456029E-01	-1.740650E-02	7.809766E-03
3	G	7.102863E-03	1.414977E-02	3.131819E-01	-1.112372E-01	2.290610E-02	1.172803E-03
4	G	8.192702E-03	1.317539E-02	2.752510E-01	-8.524233E-02	9.263380E-02	-4.376611E-03
5	G	7.375674E-03	1.000658E-02	2.081508E-01	-5.601952E-02	8.321179E-02	-3.527544E-03
6	G	4.616120E-03	5.505166E-03	1.164491E-01	-7.791381E-02	2.120471E-01	-1.068636E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.846986E-03	1.047521E-02	2.991948E-01	-1.118033E-01	-3.546118E-02	9.928572E-03
9	G	6.189289E-03	1.266173E-02	2.888743E-01	-8.632021E-02	3.359534E-02	5.303946E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -250 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.805389E-03	3.316792E-07	3.060798E-01	3.812827E-05	3.374373E-02	-1.779553E-06
2	G	7.324293E-03	1.542751E-02	3.611553E-01	-1.699081E-01	-1.984781E-02	1.013709E-02
3	G	9.331335E-03	1.854010E-02	3.590081E-01	-1.290037E-01	2.607567E-02	1.559522E-03
4	G	1.077260E-02	1.725134E-02	3.154693E-01	-9.886760E-02	1.067775E-01	-5.835169E-03
5	G	9.685749E-03	1.308012E-02	2.383694E-01	-6.218661E-02	9.519698E-02	-4.638191E-03
6	G	6.097623E-03	7.205063E-03	1.335689E-01	-9.060080E-02	2.423039E-01	-1.407233E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.357061E-03	1.369822E-02	3.428131E-01	-1.285995E-01	-4.068710E-02	1.301228E-02
9	G	8.121215E-03	1.656145E-02	3.309118E-01	-9.902477E-02	3.855321E-02	6.892584E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -250 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.802449E-03	4.893259E-07	3.373516E-01	6.200936E-05	5.122748E-02	-2.079423E-06
2	G	8.853743E-03	1.868992E-02	3.977871E-01	-1.890754E-01	-2.183435E-02	1.222478E-02
3	G	1.131468E-02	2.245649E-02	3.953860E-01	-1.430673E-01	2.860061E-02	1.907338E-03
4	G	1.307162E-02	2.088923E-02	3.474025E-01	-1.096191E-01	1.179658E-01	-7.139410E-03
5	G	1.174538E-02	1.582438E-02	2.623765E-01	-6.709108E-02	1.047278E-01	-5.632846E-03
6	G	7.422531E-03	8.725591E-03	1.471774E-01	-1.007972E-01	2.662082E-01	-1.711322E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.698064E-03	1.656959E-02	3.774561E-01	-1.418442E-01	-4.478906E-02	1.576307E-02
9	G	9.839816E-03	2.003958E-02	3.643023E-01	-1.090354E-01	4.243826E-02	8.395010E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -250 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.711310E-03	6.624807E-07	3.637592E-01	8.963820E-05	6.780585E-02	-2.078865E-06
2	G	1.025260E-02	2.168395E-02	4.286467E-01	-2.051404E-01	-2.351577E-02	1.414848E-02
3	G	1.313251E-02	2.605356E-02	4.260328E-01	-1.549034E-01	3.072793E-02	2.229641E-03
4	G	1.518144E-02	2.423234E-02	3.743103E-01	-1.186352E-01	1.273623E-01	-8.338177E-03
5	G	1.363699E-02	1.834755E-02	2.826166E-01	-7.124867E-02	1.127702E-01	-6.549153E-03
6	G	8.642124E-03	1.012552E-02	1.586557E-01	-1.094832E-01	2.862620E-01	-1.992345E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.924535E-03	1.920418E-02	4.066535E-01	-1.529602E-01	-4.818316E-02	1.828553E-02
9	G	1.141448E-02	2.323386E-02	3.924443E-01	-1.174189E-01	4.566730E-02	9.853814E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -250 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.554611E-03	8.486675E-07	3.868498E-01	1.204713E-04	8.352781E-02	-1.738311E-06
2	G	1.155494E-02	2.447901E-02	4.555673E-01	-2.190627E-01	-2.496544E-02	1.594882E-02
3	G	1.482774E-02	2.941421E-02	4.527673E-01	-1.651911E-01	3.257523E-02	2.534469E-03
4	G	1.715128E-02	2.735776E-02	3.977884E-01	-1.264603E-01	1.355369E-01	-9.457780E-03
5	G	1.540457E-02	2.070770E-02	3.002853E-01	-7.489666E-02	1.197972E-01	-7.407617E-03
6	G	9.783830E-03	1.143650E-02	1.686794E-01	-1.171328E-01	3.036883E-01	-2.256366E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.006600E-02	2.166398E-02	4.321377E-01	-1.626170E-01	-5.108432E-02	2.063707E-02
9	G	1.288276E-02	2.621886E-02	4.170079E-01	-1.246876E-01	4.845031E-02	1.128734E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -250 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.346325E-03	1.046515E-06	4.075064E-01	1.541497E-04	9.846845E-02	-1.029221E-06
2	G	1.278159E-02	2.711814E-02	4.795977E-01	-2.314127E-01	-2.623229E-02	1.765046E-02
3	G	1.642687E-02	3.258977E-02	4.766306E-01	-1.743406E-01	3.421286E-02	2.826468E-03
4	G	1.901155E-02	3.031298E-02	4.187495E-01	-1.334126E-01	1.428167E-01	-1.051505E-02
5	G	1.707527E-02	2.294057E-02	3.160670E-01	-7.817189E-02	1.260781E-01	-8.220783E-03
6	G	1.086465E-02	1.267801E-02	1.776355E-01	-1.240217E-01	3.191876E-01	-2.507161E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.114069E-02	2.398709E-02	4.548975E-01	-1.712053E-01	-5.361531E-02	2.285293E-02
9	G	1.426772E-02	2.904027E-02	4.389455E-01	-1.311388E-01	5.090524E-02	1.270689E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -250 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.095855E-03	1.254989E-06	4.262871E-01	1.904004E-04	1.127029E-01	6.970729E-08
2	G	1.394655E-02	2.963027E-02	5.014008E-01	-2.425510E-01	-2.734969E-02	1.927006E-02
3	G	1.794770E-02	3.561472E-02	4.982809E-01	-1.826111E-01	3.568601E-02	3.108719E-03
4	G	2.078265E-02	3.312986E-02	4.377706E-01	-1.396932E-01	1.494083E-01	-1.152138E-02
5	G	1.866725E-02	2.507009E-02	3.303940E-01	-8.115994E-02	1.317835E-01	-8.997073E-03
6	G	1.189598E-02	1.386312E-02	1.857687E-01	-1.303245E-01	3.332025E-01	-2.747259E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.216085E-02	2.619904E-02	4.755576E-01	-1.789710E-01	-5.585559E-02	2.495697E-02
9	G	1.558484E-02	3.172875E-02	4.588593E-01	-1.369599E-01	5.310702E-02	1.411913E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -250 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.809917E-03	1.473275E-06	4.435698E-01	2.290088E-04	1.262997E-01	1.574900E-06
2	G	1.505981E-02	3.203600E-02	5.214252E-01	-2.527219E-01	-2.834184E-02	2.081959E-02
3	G	1.940292E-02	3.851359E-02	5.181640E-01	-1.901781E-01	3.702582E-02	3.383366E-03
4	G	2.247912E-02	3.583109E-02	4.552425E-01	-1.454380E-01	1.554513E-01	-1.248497E-02
5	G	2.019345E-02	2.711329E-02	3.435592E-01	-8.391847E-02	1.370284E-01	-9.742486E-03
6	G	1.288595E-02	1.500113E-02	1.932445E-01	-1.361596E-01	3.460325E-01	-2.978459E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.313524E-02	2.831805E-02	4.945412E-01	-1.860801E-01	-5.786016E-02	2.696634E-02
9	G	1.684515E-02	3.430612E-02	4.771570E-01	-1.422780E-01	5.510661E-02	1.552819E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -250 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.049352E-02	1.700713E-06	4.596237E-01	2.698010E-04	1.393193E-01	3.499352E-06
2	G	1.612878E-02	3.435071E-02	5.399908E-01	-2.620993E-01	-2.922709E-02	2.230809E-02
3	G	2.080198E-02	4.130469E-02	5.365972E-01	-1.971671E-01	3.825486E-02	3.651954E-03
4	G	2.411178E-02	3.843355E-02	4.714434E-01	-1.507441E-01	1.610451E-01	-1.341195E-02
5	G	2.166348E-02	2.908282E-02	3.557711E-01	-8.648844E-02	1.418951E-01	-1.046149E-02
6	G	1.384060E-02	1.609895E-02	2.001811E-01	-1.416113E-01	3.578911E-01	-3.202097E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.407038E-02	3.035763E-02	5.121496E-01	-1.926505E-01	-5.966892E-02	2.889393E-02
9	G	1.805685E-02	3.678860E-02	4.941291E-01	-1.471836E-01	5.694041E-02	1.693669E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -300 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.316669E-03	7.475861E-08	2.101518E-01	4.899284E-06	-2.923653E-03	-5.608063E-07
2	G	3.521375E-03	7.415888E-03	2.484362E-01	-1.112821E-01	-1.408487E-02	5.039105E-03
3	G	4.420004E-03	8.934611E-03	2.471527E-01	-8.638688E-02	1.819098E-02	7.299841E-04
4	G	5.090829E-03	8.335573E-03	2.173218E-01	-6.589039E-02	7.240821E-02	-2.667701E-03
5	G	4.599148E-03	6.364242E-03	1.646957E-01	-4.721436E-02	6.559100E-02	-2.191554E-03
6	G	2.847666E-03	3.503786E-03	9.191887E-02	-6.068237E-02	1.684658E-01	-6.725298E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.025678E-03	6.631402E-03	2.362224E-01	-8.780676E-02	-2.800854E-02	6.266480E-03
9	G	3.857235E-03	8.014949E-03	2.281882E-01	-6.815975E-02	2.635139E-02	3.518716E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -300 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.673996E-03	1.910591E-07	2.663724E-01	1.863860E-05	1.548181E-02	-1.236910E-06
2	G	5.590672E-03	1.177810E-02	3.146017E-01	-1.457074E-01	-1.729724E-02	7.800407E-03
3	G	7.083566E-03	1.416413E-02	3.128130E-01	-1.112938E-01	2.268621E-02	1.192656E-03
4	G	8.169603E-03	1.319213E-02	2.749451E-01	-8.531338E-02	9.269084E-02	-4.387623E-03
5	G	7.355652E-03	1.002649E-02	2.079530E-01	-5.601740E-02	8.284128E-02	-3.511222E-03
6	G	4.606365E-03	5.523964E-03	1.163871E-01	-7.833627E-02	2.120020E-01	-1.072378E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.835389E-03	1.048331E-02	2.987851E-01	-1.118357E-01	-3.555569E-02	9.944486E-03
9	G	6.170563E-03	1.267103E-02	2.884890E-01	-8.637503E-02	3.361492E-02	5.272790E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -300 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.801068E-03	3.252617E-07	3.057149E-01	3.766801E-05	3.379554E-02	-1.783049E-06
2	G	7.313522E-03	1.543739E-02	3.607984E-01	-1.699495E-01	-1.973660E-02	1.012669E-02
3	G	9.311859E-03	1.855360E-02	3.586811E-01	-1.289925E-01	2.586740E-02	1.581433E-03
4	G	1.074935E-02	1.726787E-02	3.152019E-01	-9.892787E-02	1.068294E-01	-5.846417E-03
5	G	9.665619E-03	1.309985E-02	2.381968E-01	-6.217523E-02	9.486917E-02	-4.621909E-03
6	G	6.087971E-03	7.223889E-03	1.335161E-01	-9.097851E-02	2.422662E-01	-1.411057E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.345398E-03	1.370622E-02	3.424575E-01	-1.286006E-01	-4.078369E-02	1.302968E-02
9	G	8.102600E-03	1.657090E-02	3.305802E-01	-9.906612E-02	3.858129E-02	6.852927E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -300 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.798093E-03	4.897053E-07	3.370163E-01	6.209256E-05	5.128177E-02	-2.072546E-06
2	G	8.842313E-03	1.870095E-02	3.974676E-01	-1.892077E-01	-2.174588E-02	1.221289E-02
3	G	1.129538E-02	2.247107E-02	3.950959E-01	-1.431539E-01	2.842355E-02	1.927907E-03
4	G	1.304859E-02	2.090585E-02	3.471608E-01	-1.096977E-01	1.180214E-01	-7.152503E-03
5	G	1.172531E-02	1.584397E-02	2.622184E-01	-6.707784E-02	1.044289E-01	-5.616602E-03
6	G	7.413041E-03	8.744391E-03	1.471295E-01	-1.011473E-01	2.661727E-01	-1.715189E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.686405E-03	1.657741E-02	3.771280E-01	-1.418903E-01	-4.485977E-02	1.577875E-02
9	G	9.820923E-03	2.004834E-02	3.639919E-01	-1.090897E-01	4.245229E-02	8.361682E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -300 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.706915E-03	6.629033E-07	3.634476E-01	8.973843E-05	6.785949E-02	-2.069897E-06
2	G	1.024112E-02	2.169487E-02	4.283493E-01	-2.052643E-01	-2.343149E-02	1.413599E-02
3	G	1.311315E-02	2.606799E-02	4.257627E-01	-1.549822E-01	3.056152E-02	2.250603E-03
4	G	1.515834E-02	2.424884E-02	3.740852E-01	-1.187102E-01	1.274156E-01	-8.351570E-03
5	G	1.361682E-02	1.836698E-02	2.824689E-01	-7.123186E-02	1.124916E-01	-6.532928E-03
6	G	8.632645E-03	1.014429E-02	1.586111E-01	-1.098103E-01	2.862281E-01	-1.996215E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.912839E-03	1.921188E-02	4.063483E-01	-1.530020E-01	-4.824905E-02	1.830122E-02
9	G	1.139555E-02	2.324251E-02	3.921556E-01	-1.174691E-01	4.568096E-02	9.819777E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -300 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.550181E-03	8.491492E-07	3.865563E-01	1.205873E-04	8.358051E-02	-1.727039E-06
2	G	1.154341E-02	2.448983E-02	4.552868E-01	-2.191803E-01	-2.488471E-02	1.593588E-02
3	G	1.480833E-02	2.942852E-02	4.525124E-01	-1.652647E-01	3.241730E-02	2.555707E-03
4	G	1.712813E-02	2.737415E-02	3.975760E-01	-1.265323E-01	1.355882E-01	-9.471395E-03
5	G	1.538432E-02	2.072701E-02	3.001456E-01	-7.487767E-02	1.195343E-01	-7.391405E-03
6	G	9.774355E-03	1.145525E-02	1.686373E-01	-1.174421E-01	3.036556E-01	-2.260237E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.005427E-02	2.167159E-02	4.318500E-01	-1.626558E-01	-5.114626E-02	2.065272E-02
9	G	1.286379E-02	2.622740E-02	4.167356E-01	-1.247348E-01	4.846342E-02	1.125302E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -300 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.341864E-03	1.047054E-06	4.072273E-01	1.542805E-04	9.852006E-02	-1.015523E-06
2	G	1.277001E-02	2.712888E-02	4.793307E-01	-2.315252E-01	-2.615458E-02	1.763718E-02
3	G	1.640742E-02	3.260398E-02	4.763878E-01	-1.744100E-01	3.406188E-02	2.847915E-03
4	G	1.898836E-02	3.032927E-02	4.185472E-01	-1.334820E-01	1.428662E-01	-1.052882E-02
5	G	1.705494E-02	2.295976E-02	3.159336E-01	-7.815149E-02	1.258280E-01	-8.204577E-03
6	G	1.085517E-02	1.269673E-02	1.775954E-01	-1.243166E-01	3.191558E-01	-2.511031E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.112892E-02	2.399461E-02	4.546236E-01	-1.712417E-01	-5.367396E-02	2.286852E-02
9	G	1.424872E-02	2.904871E-02	4.386864E-01	-1.311833E-01	5.091779E-02	1.267248E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -300 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.091364E-03	1.255583E-06	4.260199E-01	1.905454E-04	1.127534E-01	8.593555E-08
2	G	1.393494E-02	2.964092E-02	5.011449E-01	-2.426592E-01	-2.727458E-02	1.925650E-02
3	G	1.792821E-02	3.562883E-02	4.980482E-01	-1.826771E-01	3.554089E-02	3.130333E-03
4	G	2.075942E-02	3.314606E-02	4.375767E-01	-1.397603E-01	1.494561E-01	-1.153528E-02
5	G	1.864686E-02	2.508918E-02	3.302658E-01	-8.113860E-02	1.315438E-01	-8.980869E-03
6	G	1.188650E-02	1.388182E-02	1.857302E-01	-1.306075E-01	3.331713E-01	-2.751128E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.214906E-02	2.620648E-02	4.752952E-01	-1.790056E-01	-5.591145E-02	2.497249E-02
9	G	1.556581E-02	3.173710E-02	4.586110E-01	-1.370023E-01	5.311904E-02	1.408477E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -300 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.805398E-03	1.473923E-06	4.433127E-01	2.291672E-04	1.263490E-01	1.593748E-06
2	G	1.504816E-02	3.204658E-02	5.211788E-01	-2.528262E-01	-2.826901E-02	2.080580E-02
3	G	1.938339E-02	3.852761E-02	5.179397E-01	-1.902413E-01	3.688573E-02	3.405114E-03
4	G	2.245585E-02	3.584721E-02	4.550557E-01	-1.455031E-01	1.554977E-01	-1.249897E-02
5	G	2.017301E-02	2.713229E-02	3.434355E-01	-8.389647E-02	1.367977E-01	-9.726280E-03
6	G	1.287646E-02	1.501980E-02	1.932074E-01	-1.364324E-01	3.460020E-01	-2.982326E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.312342E-02	2.832541E-02	4.942884E-01	-1.861130E-01	-5.791359E-02	2.698179E-02
9	G	1.682608E-02	3.431439E-02	4.769179E-01	-1.423186E-01	5.511813E-02	1.549396E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -300 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.048897E-02	1.701413E-06	4.593752E-01	2.699723E-04	1.393674E-01	3.520899E-06
2	G	1.611709E-02	3.436121E-02	5.397523E-01	-2.622001E-01	-2.915629E-02	2.229410E-02
3	G	2.078241E-02	4.131861E-02	5.363801E-01	-1.972278E-01	3.811916E-02	3.673812E-03
4	G	2.408846E-02	3.844958E-02	4.712626E-01	-1.508072E-01	1.610902E-01	-1.342602E-02
5	G	2.164298E-02	2.910175E-02	3.556513E-01	-8.646598E-02	1.416722E-01	-1.044528E-02
6	G	1.383111E-02	1.611760E-02	2.001451E-01	-1.418753E-01	3.578611E-01	-3.205962E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.405853E-02	3.036493E-02	5.119051E-01	-1.926821E-01	-5.972024E-02	2.890931E-02
9	G	1.803776E-02	3.679679E-02	4.938978E-01	-1.472225E-01	5.695147E-02	1.690265E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -350 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.312457E-03	7.485583E-08	2.096203E-01	4.925781E-06	-2.872987E-03	-5.594613E-07
2	G	3.510286E-03	7.427397E-03	2.479310E-01	-1.114530E-01	-1.397600E-02	5.032715E-03
3	G	4.400928E-03	8.949907E-03	2.466954E-01	-8.652706E-02	1.793946E-02	7.473367E-04
4	G	5.068014E-03	8.352903E-03	2.169402E-01	-6.598334E-02	7.246548E-02	-2.677941E-03
5	G	4.579475E-03	6.384779E-03	1.644517E-01	-4.725303E-02	6.513751E-02	-2.175384E-03
6	G	2.837709E-03	3.522654E-03	9.183972E-02	-6.119790E-02	1.684113E-01	-6.763017E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.014166E-03	6.639925E-03	2.357052E-01	-8.788177E-02	-2.811258E-02	6.281768E-03
9	G	3.838546E-03	8.024569E-03	2.276989E-01	-6.824119E-02	2.636091E-02	3.494884E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -350 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.669722E-03	1.913565E-07	2.659505E-01	1.868937E-05	1.553466E-02	-1.233905E-06
2	G	5.579437E-03	1.178934E-02	3.142000E-01	-1.458566E-01	-1.719600E-02	7.790956E-03
3	G	7.064371E-03	1.417904E-02	3.124486E-01	-1.113991E-01	2.247311E-02	1.211864E-03
4	G	8.146666E-03	1.320910E-02	2.746414E-01	-8.539881E-02	9.274997E-02	-4.399336E-03
5	G	7.335776E-03	1.004654E-02	2.077566E-01	-5.602194E-02	8.247127E-02	-3.494973E-03
6	G	4.596677E-03	5.542822E-03	1.163259E-01	-7.876331E-02	2.119589E-01	-1.076208E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.823809E-03	1.049149E-02	2.983736E-01	-1.118928E-01	-3.564332E-02	9.960175E-03
9	G	6.151784E-03	1.268025E-02	2.880998E-01	-8.644105E-02	3.362919E-02	5.242876E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -350 DEG SUBCASE 30
LOAD STEP = 4.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.796747E-03	3.241819E-07	3.053461E-01	3.762563E-05	3.384986E-02	-1.780094E-06
2	G	7.302183E-03	1.544852E-02	3.604470E-01	-1.700882E-01	-1.964265E-02	1.011578E-02
3	G	9.292597E-03	1.856833E-02	3.583622E-01	-1.290856E-01	2.567590E-02	1.601484E-03
4	G	1.072635E-02	1.728465E-02	3.149361E-01	-9.900946E-02	1.068868E-01	-5.858966E-03
5	G	9.645611E-03	1.311964E-02	2.380237E-01	-6.216765E-02	9.454251E-02	-4.605682E-03
6	G	6.078380E-03	7.242724E-03	1.334631E-01	-9.135833E-02	2.422276E-01	-1.414908E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.333775E-03	1.371421E-02	3.420972E-01	-1.286506E-01	-4.086133E-02	1.304544E-02
9	G	8.083759E-03	1.657988E-02	3.302393E-01	-9.912498E-02	3.859578E-02	6.820686E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -350 DEG SUBCASE 40
LOAD STEP = 5.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.793731E-03	4.900643E-07	3.366809E-01	6.217619E-05	5.133621E-02	-2.065738E-06
2	G	8.830904E-03	1.871196E-02	3.971477E-01	-1.893373E-01	-2.165729E-02	1.220107E-02
3	G	1.127606E-02	2.248565E-02	3.948053E-01	-1.432378E-01	2.824644E-02	1.948511E-03
4	G	1.302554E-02	2.092249E-02	3.469187E-01	-1.097756E-01	1.180766E-01	-7.165544E-03
5	G	1.170520E-02	1.586356E-02	2.620601E-01	-6.706432E-02	1.041303E-01	-5.600395E-03
6	G	7.403498E-03	8.763202E-03	1.470814E-01	-1.014962E-01	2.661367E-01	-1.719052E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.674742E-03	1.658525E-02	3.767999E-01	-1.419351E-01	-4.493082E-02	1.579452E-02
9	G	9.802036E-03	2.005716E-02	3.636815E-01	-1.091435E-01	4.246651E-02	8.328207E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -350 DEG SUBCASE 50
LOAD STEP = 6.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.702518E-03	6.633241E-07	3.631360E-01	8.983901E-05	6.791331E-02	-2.060927E-06
2	G	1.022965E-02	2.170579E-02	4.280517E-01	-2.053870E-01	-2.334726E-02	1.412356E-02
3	G	1.309378E-02	2.608244E-02	4.254923E-01	-1.550600E-01	3.039519E-02	2.271574E-03
4	G	1.513524E-02	2.426536E-02	3.738600E-01	-1.187848E-01	1.274686E-01	-8.364941E-03
5	G	1.359662E-02	1.838643E-02	2.823210E-01	-7.121494E-02	1.122133E-01	-6.516734E-03
6	G	8.623126E-03	1.016308E-02	1.585664E-01	-1.101366E-01	2.861938E-01	-2.000082E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.901141E-03	1.921961E-02	4.060431E-01	-1.530433E-01	-4.831504E-02	1.831696E-02
9	G	1.137662E-02	2.325119E-02	3.918668E-01	-1.175192E-01	4.569464E-02	9.785724E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -350 DEG SUBCASE 60
LOAD STEP = 7.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.545751E-03	8.496301E-07	3.862627E-01	1.207037E-04	8.363338E-02	-1.715757E-06
2	G	1.153189E-02	2.450067E-02	4.550062E-01	-2.192973E-01	-2.480407E-02	1.592299E-02
3	G	1.478892E-02	2.944286E-02	4.522573E-01	-1.653376E-01	3.225946E-02	2.576948E-03
4	G	1.710498E-02	2.739056E-02	3.973635E-01	-1.266041E-01	1.356393E-01	-9.484997E-03
5	G	1.536405E-02	2.074633E-02	3.000057E-01	-7.485864E-02	1.192717E-01	-7.375218E-03
6	G	9.764848E-03	1.147401E-02	1.685952E-01	-1.177508E-01	3.036226E-01	-2.264106E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.004254E-02	2.167922E-02	4.315621E-01	-1.626943E-01	-5.120823E-02	2.066841E-02
9	G	1.284483E-02	2.623597E-02	4.164633E-01	-1.247818E-01	4.847651E-02	1.121870E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -350 DEG SUBCASE 70
LOAD STEP = 8.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.337401E-03	1.047593E-06	4.069482E-01	1.544118E-04	9.857182E-02	-1.001807E-06
2	G	1.275845E-02	2.713963E-02	4.790637E-01	-2.316373E-01	-2.607696E-02	1.762393E-02
3	G	1.638796E-02	3.261821E-02	4.761450E-01	-1.744791E-01	3.391099E-02	2.869364E-03
4	G	1.896516E-02	3.034558E-02	4.183449E-01	-1.335513E-01	1.429155E-01	-1.054259E-02
5	G	1.703461E-02	2.297897E-02	3.158001E-01	-7.813107E-02	1.255780E-01	-8.188393E-03
6	G	1.084567E-02	1.271547E-02	1.775553E-01	-1.246111E-01	3.191238E-01	-2.514901E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.111716E-02	2.400215E-02	4.543496E-01	-1.712781E-01	-5.373261E-02	2.288414E-02
9	G	1.422972E-02	2.905718E-02	4.384272E-01	-1.312279E-01	5.093031E-02	1.263810E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -350 DEG SUBCASE 80
LOAD STEP = 9.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.086872E-03	1.256178E-06	4.257527E-01	1.906908E-04	1.128040E-01	1.021879E-07
2	G	1.392333E-02	2.965159E-02	5.008889E-01	-2.427670E-01	-2.719956E-02	1.924296E-02
3	G	1.790871E-02	3.564296E-02	4.978154E-01	-1.827429E-01	3.539584E-02	3.151947E-03
4	G	2.073618E-02	3.316228E-02	4.373828E-01	-1.398273E-01	1.495039E-01	-1.154918E-02
5	G	1.862647E-02	2.510830E-02	3.301377E-01	-8.111725E-02	1.313043E-01	-8.964685E-03
6	G	1.187700E-02	1.390053E-02	1.856917E-01	-1.308901E-01	3.331401E-01	-2.754997E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.213726E-02	2.621394E-02	4.750327E-01	-1.790401E-01	-5.596730E-02	2.498803E-02
9	G	1.554677E-02	3.174549E-02	4.583627E-01	-1.370447E-01	5.313103E-02	1.405044E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -350 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.800877E-03	1.474571E-06	4.430555E-01	2.293261E-04	1.263984E-01	1.612626E-06
2	G	1.503651E-02	3.205717E-02	5.209322E-01	-2.529303E-01	-2.819626E-02	2.079203E-02
3	G	1.936385E-02	3.854164E-02	5.177153E-01	-1.903044E-01	3.674570E-02	3.426862E-03
4	G	2.243257E-02	3.586334E-02	4.548688E-01	-1.455681E-01	1.555440E-01	-1.251296E-02
5	G	2.015255E-02	2.715132E-02	3.433118E-01	-8.387449E-02	1.365672E-01	-9.710093E-03
6	G	1.286696E-02	1.503849E-02	1.931702E-01	-1.367049E-01	3.459714E-01	-2.986194E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.311159E-02	2.833280E-02	4.940356E-01	-1.861460E-01	-5.796701E-02	2.699725E-02
9	G	1.680702E-02	3.432268E-02	4.766788E-01	-1.423591E-01	5.512961E-02	1.545975E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -350 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.048443E-02	1.702114E-06	4.591266E-01	2.701441E-04	1.394157E-01	3.542479E-06
2	G	1.610541E-02	3.437173E-02	5.395138E-01	-2.623009E-01	-2.908555E-02	2.228014E-02
3	G	2.076284E-02	4.133256E-02	5.361630E-01	-1.972885E-01	3.798351E-02	3.695670E-03
4	G	2.406515E-02	3.846563E-02	4.710818E-01	-1.508704E-01	1.611353E-01	-1.344009E-02
5	G	2.162247E-02	2.912069E-02	3.555314E-01	-8.644354E-02	1.414494E-01	-1.042909E-02
6	G	1.382159E-02	1.613627E-02	2.001090E-01	-1.421390E-01	3.578310E-01	-3.209827E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.404668E-02	3.037225E-02	5.116606E-01	-1.927136E-01	-5.977153E-02	2.892469E-02
9	G	1.801866E-02	3.680501E-02	4.936665E-01	-1.472614E-01	5.696248E-02	1.686863E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -400 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.308255E-03	7.494755E-08	2.090882E-01	4.952560E-06	-2.820690E-03	-5.579416E-07
2	G	3.499173E-03	7.439137E-03	2.474265E-01	-1.116330E-01	-1.386989E-02	5.026489E-03
3	G	4.381892E-03	8.965499E-03	2.462397E-01	-8.668194E-02	1.768865E-02	7.645553E-04
4	G	5.045276E-03	8.370449E-03	2.165598E-01	-6.608344E-02	7.252375E-02	-2.688557E-03
5	G	4.559818E-03	6.405460E-03	1.642081E-01	-4.729382E-02	6.468567E-02	-2.159282E-03
6	G	2.827697E-03	3.541601E-03	9.176043E-02	-6.171228E-02	1.683564E-01	-6.800756E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.002666E-03	6.648575E-03	2.351877E-01	-8.796283E-02	-2.821519E-02	6.297006E-03
9	G	3.819854E-03	8.034292E-03	2.272086E-01	-6.832678E-02	2.636920E-02	3.471074E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -400 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.665449E-03	1.915687E-07	2.655284E-01	1.873404E-05	1.558788E-02	-1.230821E-06
2	G	5.568208E-03	1.180066E-02	3.137983E-01	-1.460064E-01	-1.709542E-02	7.781586E-03
3	G	7.045182E-03	1.419402E-02	3.120842E-01	-1.115054E-01	2.226060E-02	1.231041E-03
4	G	8.123734E-03	1.322614E-02	2.743376E-01	-8.548456E-02	9.280857E-02	-4.411058E-03
5	G	7.315885E-03	1.006665E-02	2.075602E-01	-5.602675E-02	8.210197E-02	-3.478763E-03
6	G	4.586940E-03	5.561711E-03	1.162645E-01	-7.918912E-02	2.119152E-01	-1.080039E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.812235E-03	1.049972E-02	2.979619E-01	-1.119504E-01	-3.573059E-02	9.975884E-03
9	G	6.133011E-03	1.268953E-02	2.877105E-01	-8.650734E-02	3.364302E-02	5.213219E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -400 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.792425E-03	3.214724E-07	3.049771E-01	3.745417E-05	3.390450E-02	-1.779322E-06
2	G	7.290816E-03	1.545979E-02	3.600962E-01	-1.702339E-01	-1.955030E-02	1.010491E-02
3	G	9.273359E-03	1.858319E-02	3.580440E-01	-1.291861E-01	2.548607E-02	1.621375E-03
4	G	1.070338E-02	1.730151E-02	3.146705E-01	-9.909234E-02	1.069444E-01	-5.871600E-03
5	G	9.625591E-03	1.313946E-02	2.378505E-01	-6.216011E-02	9.421655E-02	-4.589502E-03
6	G	6.068749E-03	7.261581E-03	1.334099E-01	-9.173707E-02	2.421885E-01	-1.418757E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.322161E-03	1.372223E-02	3.417366E-01	-1.287041E-01	-4.093736E-02	1.306110E-02
9	G	8.064911E-03	1.658888E-02	3.298979E-01	-9.918506E-02	3.860906E-02	6.789217E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258
FOUR TENTHS, -400 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.789370E-03	4.904277E-07	3.363454E-01	6.226011E-05	5.139089E-02	-2.058912E-06
2	G	8.819500E-03	1.872302E-02	3.968277E-01	-1.894671E-01	-2.156900E-02	1.218930E-02
3	G	1.125674E-02	2.250027E-02	3.945147E-01	-1.433220E-01	2.806960E-02	1.969098E-03
4	G	1.300249E-02	2.093918E-02	3.466766E-01	-1.098535E-01	1.181314E-01	-7.178590E-03
5	G	1.168508E-02	1.588319E-02	2.619017E-01	-6.705094E-02	1.038320E-01	-5.584215E-03
6	G	7.393923E-03	8.782032E-03	1.470332E-01	-1.018444E-01	2.661004E-01	-1.722915E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.663083E-03	1.659312E-02	3.764717E-01	-1.419801E-01	-4.500171E-02	1.581031E-02
9	G	9.783152E-03	2.006602E-02	3.633710E-01	-1.091974E-01	4.248053E-02	8.294894E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -400 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.698120E-03	6.637467E-07	3.628242E-01	8.993992E-05	6.796733E-02	-2.051945E-06
2	G	1.021819E-02	2.171674E-02	4.277541E-01	-2.055098E-01	-2.326327E-02	1.411116E-02
3	G	1.307441E-02	2.609693E-02	4.252218E-01	-1.551380E-01	3.022908E-02	2.292530E-03
4	G	1.511214E-02	2.428192E-02	3.736347E-01	-1.188595E-01	1.275214E-01	-8.378317E-03
5	G	1.357642E-02	1.840590E-02	2.821731E-01	-7.119813E-02	1.119353E-01	-6.500564E-03
6	G	8.613579E-03	1.018188E-02	1.585216E-01	-1.104623E-01	2.861593E-01	-2.003950E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.889445E-03	1.922737E-02	4.057377E-01	-1.530848E-01	-4.838090E-02	1.833270E-02
9	G	1.135769E-02	2.325991E-02	3.915779E-01	-1.175693E-01	4.570814E-02	9.751815E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -400 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.541319E-03	8.501127E-07	3.859691E-01	1.208205E-04	8.368642E-02	-1.704459E-06
2	G	1.152037E-02	2.451153E-02	4.547256E-01	-2.194144E-01	-2.472362E-02	1.591013E-02
3	G	1.476950E-02	2.945723E-02	4.520022E-01	-1.654108E-01	3.210180E-02	2.598176E-03
4	G	1.708183E-02	2.740701E-02	3.971510E-01	-1.266759E-01	1.356901E-01	-9.498605E-03
5	G	1.534377E-02	2.076568E-02	2.998658E-01	-7.483970E-02	1.190093E-01	-7.359053E-03
6	G	9.755315E-03	1.149278E-02	1.685529E-01	-1.180591E-01	3.035894E-01	-2.267976E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.003081E-02	2.168687E-02	4.312742E-01	-1.627330E-01	-5.127009E-02	2.068410E-02
9	G	1.282586E-02	2.624457E-02	4.161909E-01	-1.248289E-01	4.848946E-02	1.118452E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -400 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.332939E-03	1.048133E-06	4.066690E-01	1.545435E-04	9.862373E-02	-9.880730E-07
2	G	1.274688E-02	2.715041E-02	4.787965E-01	-2.317495E-01	-2.599951E-02	1.761071E-02
3	G	1.636851E-02	3.263247E-02	4.759021E-01	-1.745484E-01	3.376025E-02	2.890802E-03
4	G	1.894197E-02	3.036193E-02	4.181426E-01	-1.336206E-01	1.429647E-01	-1.055637E-02
5	G	1.701426E-02	2.299821E-02	3.156666E-01	-7.811073E-02	1.253282E-01	-8.172230E-03
6	G	1.083614E-02	1.273421E-02	1.775150E-01	-1.249052E-01	3.190916E-01	-2.518772E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.110540E-02	2.400971E-02	4.540756E-01	-1.713146E-01	-5.379117E-02	2.289976E-02
9	G	1.421072E-02	2.906568E-02	4.381680E-01	-1.312725E-01	5.094271E-02	1.260383E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -400 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.082381E-03	1.256774E-06	4.254853E-01	1.908366E-04	1.128547E-01	1.184614E-07
2	G	1.391173E-02	2.966229E-02	5.006329E-01	-2.428750E-01	-2.712469E-02	1.922946E-02
3	G	1.788922E-02	3.565712E-02	4.975825E-01	-1.828089E-01	3.525093E-02	3.173550E-03
4	G	2.071294E-02	3.317853E-02	4.371888E-01	-1.398944E-01	1.495515E-01	-1.156308E-02
5	G	1.860606E-02	2.512743E-02	3.300095E-01	-8.109596E-02	1.310650E-01	-8.948520E-03
6	G	1.186747E-02	1.391925E-02	1.856530E-01	-1.311724E-01	3.331087E-01	-2.758867E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.212547E-02	2.622142E-02	4.747701E-01	-1.790747E-01	-5.602306E-02	2.500358E-02
9	G	1.552774E-02	3.175389E-02	4.581144E-01	-1.370872E-01	5.314290E-02	1.401621E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -400 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.796358E-03	1.475222E-06	4.427982E-01	2.294853E-04	1.264479E-01	1.631528E-06
2	G	1.502486E-02	3.206779E-02	5.206856E-01	-2.530344E-01	-2.812365E-02	2.077829E-02
3	G	1.934432E-02	3.855571E-02	5.174910E-01	-1.903676E-01	3.660579E-02	3.448600E-03
4	G	2.240929E-02	3.587950E-02	4.546819E-01	-1.456332E-01	1.555902E-01	-1.252696E-02
5	G	2.013209E-02	2.717036E-02	3.431880E-01	-8.385254E-02	1.363368E-01	-9.693924E-03
6	G	1.285743E-02	1.505718E-02	1.931329E-01	-1.369771E-01	3.459406E-01	-2.990061E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.309977E-02	2.834020E-02	4.937827E-01	-1.861790E-01	-5.802036E-02	2.701272E-02
9	G	1.678795E-02	3.433100E-02	4.764395E-01	-1.423997E-01	5.514100E-02	1.542565E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -400 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.047988E-02	1.702817E-06	4.588780E-01	2.703163E-04	1.394640E-01	3.564086E-06
2	G	1.609373E-02	3.438227E-02	5.392752E-01	-2.624017E-01	-2.901493E-02	2.226620E-02
3	G	2.074327E-02	4.134653E-02	5.359460E-01	-1.973493E-01	3.784797E-02	3.717520E-03
4	G	2.404183E-02	3.848171E-02	4.709010E-01	-1.509336E-01	1.611802E-01	-1.345416E-02
5	G	2.160195E-02	2.913965E-02	3.554115E-01	-8.642115E-02	1.412267E-01	-1.041291E-02
6	G	1.381206E-02	1.615494E-02	2.000729E-01	-1.424024E-01	3.578008E-01	-3.213693E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.403483E-02	3.037958E-02	5.114161E-01	-1.927453E-01	-5.982276E-02	2.894008E-02
9	G	1.799957E-02	3.681325E-02	4.934352E-01	-1.473004E-01	5.697341E-02	1.683470E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -450 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.304088E-03	7.515781E-08	2.085542E-01	4.974300E-06	-2.776541E-03	-5.568507E-07
2	G	3.488095E-03	7.451091E-03	2.469207E-01	-1.118084E-01	-1.376341E-02	5.019781E-03
3	G	4.362812E-03	8.981237E-03	2.457813E-01	-8.681615E-02	1.744131E-02	7.825728E-04
4	G	5.022375E-03	8.388198E-03	2.161767E-01	-6.616744E-02	7.257900E-02	-2.698074E-03
5	G	4.540121E-03	6.426458E-03	1.639645E-01	-4.733540E-02	6.422859E-02	-2.142978E-03
6	G	2.817672E-03	3.560777E-03	9.168179E-02	-6.223441E-02	1.683041E-01	-6.839190E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.991151E-03	6.657483E-03	2.346693E-01	-8.804253E-02	-2.832149E-02	6.312940E-03
9	G	3.801164E-03	8.044388E-03	2.267190E-01	-6.841060E-02	2.637788E-02	3.448799E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -450 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.661242E-03	1.918983E-07	2.651055E-01	1.879017E-05	1.564352E-02	-1.227963E-06
2	G	5.556697E-03	1.181292E-02	3.134026E-01	-1.462186E-01	-1.700501E-02	7.771819E-03
3	G	7.026229E-03	1.421000E-02	3.117279E-01	-1.116785E-01	2.205599E-02	1.249330E-03
4	G	8.101170E-03	1.324366E-02	2.740387E-01	-8.558998E-02	9.287065E-02	-4.423741E-03
5	G	7.296368E-03	1.008708E-02	2.073672E-01	-5.604057E-02	8.173344E-02	-3.462453E-03
6	G	4.577451E-03	5.580750E-03	1.162053E-01	-7.962316E-02	2.118756E-01	-1.083957E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.800749E-03	1.050809E-02	2.975496E-01	-1.120409E-01	-3.580775E-02	9.990525E-03
9	G	6.114198E-03	1.269871E-02	2.873178E-01	-8.658780E-02	3.364861E-02	5.187748E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -450 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.788151E-03	3.324142E-07	3.046080E-01	3.834717E-05	3.396193E-02	-1.760349E-06
2	G	7.279094E-03	1.547213E-02	3.597524E-01	-1.704506E-01	-1.947058E-02	1.009372E-02
3	G	9.254361E-03	1.859914E-02	3.577344E-01	-1.293625E-01	2.530883E-02	1.639888E-03
4	G	1.068067E-02	1.731869E-02	3.144083E-01	-9.919026E-02	1.070067E-01	-5.885233E-03
5	G	9.605717E-03	1.315943E-02	2.376786E-01	-6.215456E-02	9.389264E-02	-4.573410E-03
6	G	6.059187E-03	7.280503E-03	1.333572E-01	-9.211653E-02	2.421498E-01	-1.422616E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.310639E-03	1.373037E-02	3.413756E-01	-1.287934E-01	-4.099940E-02	1.307545E-02
9	G	8.045966E-03	1.659768E-02	3.295526E-01	-9.925777E-02	3.861241E-02	6.763845E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -450 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.785025E-03	4.907810E-07	3.360096E-01	6.234580E-05	5.144604E-02	-2.052146E-06
2	G	8.808040E-03	1.873430E-02	3.965086E-01	-1.896074E-01	-2.148250E-02	1.217748E-02
3	G	1.123748E-02	2.251513E-02	3.942254E-01	-1.434174E-01	2.789405E-02	1.989497E-03
4	G	1.297953E-02	2.095599E-02	3.464352E-01	-1.099349E-01	1.181866E-01	-7.191845E-03
5	G	1.166504E-02	1.590292E-02	2.617438E-01	-6.703928E-02	1.035341E-01	-5.568025E-03
6	G	7.384393E-03	8.800912E-03	1.469853E-01	-1.021938E-01	2.660647E-01	-1.726799E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.651448E-03	1.660105E-02	3.761432E-01	-1.420305E-01	-4.507072E-02	1.582584E-02
9	G	9.764264E-03	2.007488E-02	3.630598E-01	-1.092535E-01	4.249289E-02	8.262810E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -450 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.693732E-03	6.641853E-07	3.625123E-01	9.004123E-05	6.802158E-02	-2.042921E-06
2	G	1.020669E-02	2.172784E-02	4.274569E-01	-2.056382E-01	-2.318031E-02	1.409876E-02
3	G	1.305508E-02	2.611157E-02	4.249520E-01	-1.552219E-01	3.006373E-02	2.313373E-03
4	G	1.508909E-02	2.429856E-02	3.734098E-01	-1.189360E-01	1.275742E-01	-8.391808E-03
5	G	1.355626E-02	1.842544E-02	2.820254E-01	-7.118223E-02	1.116576E-01	-6.484400E-03
6	G	8.604050E-03	1.020072E-02	1.584769E-01	-1.107884E-01	2.861250E-01	-2.007828E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.877765E-03	1.923516E-02	4.054322E-01	-1.531291E-01	-4.844568E-02	1.834830E-02
9	G	1.133877E-02	2.326864E-02	3.912886E-01	-1.176206E-01	4.572067E-02	9.718709E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -450 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.536894E-03	8.506073E-07	3.856753E-01	1.209374E-04	8.373959E-02	-1.693135E-06
2	G	1.150884E-02	2.452249E-02	4.544452E-01	-2.195349E-01	-2.464387E-02	1.589728E-02
3	G	1.475011E-02	2.947171E-02	4.517474E-01	-1.654876E-01	3.194468E-02	2.619324E-03
4	G	1.705872E-02	2.742351E-02	3.969387E-01	-1.267488E-01	1.357410E-01	-9.512282E-03
5	G	1.532352E-02	2.078507E-02	2.997260E-01	-7.482130E-02	1.187472E-01	-7.342902E-03
6	G	9.745788E-03	1.151158E-02	1.685107E-01	-1.183673E-01	3.035562E-01	-2.271851E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.001909E-02	2.169455E-02	4.309862E-01	-1.627735E-01	-5.133123E-02	2.069969E-02
9	G	1.280690E-02	2.625319E-02	4.159183E-01	-1.248767E-01	4.850174E-02	1.115094E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -450 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.328480E-03	1.048683E-06	4.063897E-01	1.546751E-04	9.867573E-02	-9.743221E-07
2	G	1.273531E-02	2.716126E-02	4.785295E-01	-2.318640E-01	-2.592258E-02	1.759752E-02
3	G	1.634907E-02	3.264682E-02	4.756594E-01	-1.746201E-01	3.360994E-02	2.912176E-03
4	G	1.891880E-02	3.037832E-02	4.179404E-01	-1.336906E-01	1.430137E-01	-1.057019E-02
5	G	1.699393E-02	2.301748E-02	3.155332E-01	-7.809075E-02	1.250787E-01	-8.156084E-03
6	G	1.082661E-02	1.275298E-02	1.774748E-01	-1.251991E-01	3.190593E-01	-2.522643E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.109365E-02	2.401730E-02	4.538015E-01	-1.713522E-01	-5.384918E-02	2.291531E-02
9	G	1.419172E-02	2.907419E-02	4.379086E-01	-1.313175E-01	5.095461E-02	1.257007E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -450 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.077892E-03	1.257378E-06	4.252180E-01	1.909823E-04	1.129055E-01	1.347442E-07
2	G	1.390011E-02	2.967304E-02	5.003771E-01	-2.429844E-01	-2.705023E-02	1.921598E-02
3	G	1.786974E-02	3.567134E-02	4.973498E-01	-1.828767E-01	3.510636E-02	3.195100E-03
4	G	2.068972E-02	3.319482E-02	4.369949E-01	-1.399620E-01	1.495990E-01	-1.157701E-02
5	G	1.858567E-02	2.514660E-02	3.298813E-01	-8.107492E-02	1.308260E-01	-8.932373E-03
6	G	1.185794E-02	1.393799E-02	1.856144E-01	-1.314543E-01	3.330772E-01	-2.762735E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.211369E-02	2.622893E-02	4.745075E-01	-1.791101E-01	-5.607839E-02	2.501908E-02
9	G	1.550871E-02	3.176231E-02	4.578658E-01	-1.371299E-01	5.315438E-02	1.398242E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -450 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.791840E-03	1.475879E-06	4.425409E-01	2.296445E-04	1.264975E-01	1.650433E-06
2	G	1.501322E-02	3.207845E-02	5.204390E-01	-2.531397E-01	-2.805137E-02	2.076458E-02
3	G	1.932480E-02	3.856982E-02	5.172666E-01	-1.904321E-01	3.646619E-02	3.470291E-03
4	G	2.238603E-02	3.589570E-02	4.544950E-01	-1.456985E-01	1.556363E-01	-1.254098E-02
5	G	2.011164E-02	2.718943E-02	3.430643E-01	-8.383079E-02	1.361067E-01	-9.677775E-03
6	G	1.284789E-02	1.507589E-02	1.930956E-01	-1.372488E-01	3.459097E-01	-2.993926E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.308796E-02	2.834763E-02	4.935298E-01	-1.862126E-01	-5.807335E-02	2.702815E-02
9	G	1.676889E-02	3.433933E-02	4.762002E-01	-1.424405E-01	5.515205E-02	1.539193E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -450 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.047533E-02	1.703526E-06	4.586293E-01	2.704884E-04	1.395124E-01	3.585693E-06
2	G	1.608205E-02	3.439285E-02	5.390367E-01	-2.625033E-01	-2.894461E-02	2.225229E-02
3	G	2.072371E-02	4.136055E-02	5.357289E-01	-1.974111E-01	3.771271E-02	3.739326E-03
4	G	2.401852E-02	3.849781E-02	4.707201E-01	-1.509971E-01	1.612249E-01	-1.346824E-02
5	G	2.158145E-02	2.915863E-02	3.552915E-01	-8.639888E-02	1.410043E-01	-1.039676E-02
6	G	1.380252E-02	1.617362E-02	2.000367E-01	-1.426653E-01	3.577704E-01	-3.217554E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.402299E-02	3.038693E-02	5.111715E-01	-1.927774E-01	-5.987368E-02	2.895543E-02
9	G	1.798048E-02	3.682150E-02	4.932038E-01	-1.473394E-01	5.698405E-02	1.680113E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -500 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.299862E-03	7.515276E-08	2.080212E-01	4.978161E-06	-2.726826E-03	-5.510882E-07
2	G	3.477071E-03	7.462800E-03	2.464132E-01	-1.119725E-01	-1.365458E-02	5.014147E-03
3	G	4.343722E-03	8.996816E-03	2.453219E-01	-8.695167E-02	1.718899E-02	7.991262E-04
4	G	4.999582E-03	8.405868E-03	2.157945E-01	-6.626406E-02	7.263131E-02	-2.709181E-03
5	G	4.520403E-03	6.447258E-03	1.637199E-01	-4.737791E-02	6.378037E-02	-2.126602E-03
6	G	2.807487E-03	3.579784E-03	9.160139E-02	-6.274306E-02	1.682469E-01	-6.876492E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.979649E-03	6.666231E-03	2.341504E-01	-8.811483E-02	-2.842436E-02	6.328108E-03
9	G	3.782498E-03	8.054296E-03	2.262283E-01	-6.849127E-02	2.638571E-02	3.423569E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -500 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.656902E-03	1.916278E-07	2.646835E-01	1.880115E-05	1.569548E-02	-1.224665E-06
2	G	5.545766E-03	1.182350E-02	3.129946E-01	-1.463089E-01	-1.689638E-02	7.763091E-03
3	G	7.006826E-03	1.422423E-02	3.113553E-01	-1.117221E-01	2.183751E-02	1.269281E-03
4	G	8.077881E-03	1.326044E-02	2.737299E-01	-8.565726E-02	9.292430E-02	-4.434540E-03
5	G	7.276057E-03	1.010703E-02	2.071668E-01	-5.603714E-02	8.136562E-02	-3.446469E-03
6	G	4.567314E-03	5.599580E-03	1.161411E-01	-8.003695E-02	2.118262E-01	-1.087704E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.789103E-03	1.051635E-02	2.971380E-01	-1.120679E-01	-3.590390E-02	1.000734E-02
9	G	6.095479E-03	1.270827E-02	2.869310E-01	-8.664090E-02	3.366925E-02	5.154744E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -500 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.783797E-03	3.338586E-07	3.042389E-01	3.851227E-05	3.401581E-02	-1.754121E-06
2	G	7.268087E-03	1.548252E-02	3.593948E-01	-1.705291E-01	-1.936719E-02	1.008331E-02
3	G	9.234907E-03	1.861315E-02	3.574077E-01	-1.293914E-01	2.510821E-02	1.661027E-03
4	G	1.065744E-02	1.733538E-02	3.141391E-01	-9.925894E-02	1.070584E-01	-5.896907E-03
5	G	9.585520E-03	1.317923E-02	2.375039E-01	-6.214558E-02	9.356624E-02	-4.557253E-03
6	G	6.049371E-03	7.299366E-03	1.333030E-01	-9.249187E-02	2.421091E-01	-1.426457E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.298953E-03	1.373843E-02	3.410153E-01	-1.288137E-01	-4.108819E-02	1.309239E-02
9	G	8.027227E-03	1.660702E-02	3.292146E-01	-9.930599E-02	3.863440E-02	6.727108E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -500 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.780647E-03	4.911277E-07	3.356740E-01	6.242961E-05	5.150095E-02	-2.045358E-06
2	G	8.796705E-03	1.874525E-02	3.961876E-01	-1.897270E-01	-2.139332E-02	1.216592E-02
3	G	1.121811E-02	2.252965E-02	3.939334E-01	-1.434914E-01	2.771673E-02	2.010220E-03
4	G	1.295639E-02	2.097267E-02	3.461922E-01	-1.100098E-01	1.182403E-01	-7.204693E-03
5	G	1.164481E-02	1.592255E-02	2.615846E-01	-6.702455E-02	1.032366E-01	-5.551941E-03
6	G	7.374675E-03	8.819750E-03	1.469364E-01	-1.025388E-01	2.660270E-01	-1.730641E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.639773E-03	1.660898E-02	3.758149E-01	-1.420708E-01	-4.514302E-02	1.584191E-02
9	G	9.745395E-03	2.008384E-02	3.627496E-01	-1.093054E-01	4.250794E-02	8.228751E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -500 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.689325E-03	6.645969E-07	3.622004E-01	9.014281E-05	6.807594E-02	-2.033949E-06
2	G	1.019527E-02	2.173876E-02	4.271586E-01	-2.057560E-01	-2.309602E-02	1.408651E-02
3	G	1.303568E-02	2.612603E-02	4.246809E-01	-1.552949E-01	2.989751E-02	2.334396E-03
4	G	1.506594E-02	2.431514E-02	3.731840E-01	-1.190093E-01	1.276263E-01	-8.405081E-03
5	G	1.353598E-02	1.844494E-02	2.818770E-01	-7.116479E-02	1.113801E-01	-6.468301E-03
6	G	8.594401E-03	1.021954E-02	1.584317E-01	-1.111122E-01	2.860897E-01	-2.011686E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.866061E-03	1.924297E-02	4.051268E-01	-1.531682E-01	-4.851222E-02	1.836422E-02
9	G	1.131985E-02	2.327744E-02	3.909999E-01	-1.176698E-01	4.573462E-02	9.684429E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -500 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.532456E-03	8.510837E-07	3.853815E-01	1.210550E-04	8.379299E-02	-1.681820E-06
2	G	1.149734E-02	2.453335E-02	4.541641E-01	-2.196490E-01	-2.456334E-02	1.588453E-02
3	G	1.473069E-02	2.948608E-02	4.514919E-01	-1.655578E-01	3.178703E-02	2.640592E-03
4	G	1.703554E-02	2.743999E-02	3.967259E-01	-1.268199E-01	1.357913E-01	-9.525833E-03
5	G	1.530319E-02	2.080444E-02	2.995858E-01	-7.480203E-02	1.184852E-01	-7.326793E-03
6	G	9.736177E-03	1.153038E-02	1.684682E-01	-1.186742E-01	3.035225E-01	-2.275716E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.000736E-02	2.170225E-02	4.306982E-01	-1.628109E-01	-5.139347E-02	2.071550E-02
9	G	1.278794E-02	2.626186E-02	4.156459E-01	-1.249233E-01	4.851491E-02	1.111654E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -500 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.324013E-03	1.049219E-06	4.061103E-01	1.548078E-04	9.872798E-02	-9.605506E-07
2	G	1.272377E-02	2.717204E-02	4.782622E-01	-2.319743E-01	-2.584512E-02	1.758438E-02
3	G	1.632960E-02	3.266110E-02	4.754162E-01	-1.746875E-01	3.345924E-02	2.933641E-03
4	G	1.889558E-02	3.039470E-02	4.177378E-01	-1.337595E-01	1.430625E-01	-1.058394E-02
5	G	1.697355E-02	2.303674E-02	3.153995E-01	-7.807024E-02	1.248292E-01	-8.139967E-03
6	G	1.081702E-02	1.277175E-02	1.774344E-01	-1.254922E-01	3.190267E-01	-2.526512E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.108189E-02	2.402490E-02	4.535274E-01	-1.713879E-01	-5.390799E-02	2.293103E-02
9	G	1.417273E-02	2.908275E-02	4.376493E-01	-1.313618E-01	5.096712E-02	1.253565E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -500 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.073395E-03	1.257971E-06	4.249506E-01	1.911292E-04	1.129565E-01	1.510723E-07
2	G	1.388852E-02	2.968375E-02	5.001209E-01	-2.430911E-01	-2.697539E-02	1.920254E-02
3	G	1.785023E-02	3.568552E-02	4.971167E-01	-1.829415E-01	3.496150E-02	3.216725E-03
4	G	2.066647E-02	3.321111E-02	4.368008E-01	-1.400288E-01	1.496463E-01	-1.159090E-02
5	G	1.856523E-02	2.516576E-02	3.297529E-01	-8.105355E-02	1.305869E-01	-8.916249E-03
6	G	1.184836E-02	1.395673E-02	1.855757E-01	-1.317359E-01	3.330455E-01	-2.766605E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.210190E-02	2.623645E-02	4.742449E-01	-1.791443E-01	-5.613431E-02	2.503470E-02
9	G	1.548968E-02	3.177077E-02	4.576174E-01	-1.371722E-01	5.316631E-02	1.394809E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -500 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.787316E-03	1.476527E-06	4.422835E-01	2.298049E-04	1.265473E-01	1.669404E-06
2	G	1.500158E-02	3.208909E-02	5.201922E-01	-2.532430E-01	-2.797880E-02	2.075089E-02
3	G	1.930526E-02	3.858392E-02	5.170421E-01	-1.904945E-01	3.632632E-02	3.492048E-03
4	G	2.236274E-02	3.591189E-02	4.543079E-01	-1.457635E-01	1.556823E-01	-1.255497E-02
5	G	2.009115E-02	2.720850E-02	3.429404E-01	-8.380880E-02	1.358765E-01	-9.661641E-03
6	G	1.283831E-02	1.509461E-02	1.930583E-01	-1.375205E-01	3.458787E-01	-2.997796E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.307614E-02	2.835507E-02	4.932768E-01	-1.862454E-01	-5.812681E-02	2.704368E-02
9	G	1.674983E-02	3.434770E-02	4.759610E-01	-1.424810E-01	5.516347E-02	1.535775E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -500 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.047078E-02	1.704229E-06	4.583807E-01	2.706617E-04	1.395610E-01	3.607381E-06
2	G	1.607038E-02	3.440342E-02	5.387980E-01	-2.626035E-01	-2.887404E-02	2.223839E-02
3	G	2.070414E-02	4.137455E-02	5.355116E-01	-1.974713E-01	3.757720E-02	3.761193E-03
4	G	2.399519E-02	3.851392E-02	4.705392E-01	-1.510603E-01	1.612697E-01	-1.348232E-02
5	G	2.156091E-02	2.917762E-02	3.551716E-01	-8.637647E-02	1.407818E-01	-1.038061E-02
6	G	1.379294E-02	1.619231E-02	2.000006E-01	-1.429284E-01	3.577400E-01	-3.221423E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.401114E-02	3.039430E-02	5.109268E-01	-1.928089E-01	-5.992500E-02	2.897088E-02
9	G	1.796139E-02	3.682978E-02	4.929724E-01	-1.473784E-01	5.699499E-02	1.676714E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -550 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.295661E-03	7.537840E-08	2.074880E-01	5.020152E-06	-2.679436E-03	-5.545637E-07
2	G	3.466067E-03	7.474671E-03	2.459067E-01	-1.121414E-01	-1.354922E-02	5.008161E-03
3	G	4.324663E-03	9.012480E-03	2.448625E-01	-8.708533E-02	1.694321E-02	8.167097E-04
4	G	4.976693E-03	8.423569E-03	2.154108E-01	-6.634987E-02	7.268287E-02	-2.718549E-03
5	G	4.500583E-03	6.468148E-03	1.634745E-01	-4.741664E-02	6.333075E-02	-2.110782E-03
6	G	2.797216E-03	3.598866E-03	9.152062E-02	-6.325019E-02	1.681881E-01	-6.915083E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.968170E-03	6.675127E-03	2.336319E-01	-8.819053E-02	-2.852671E-02	6.343790E-03
9	G	3.763860E-03	8.064387E-03	2.257381E-01	-6.857148E-02	2.639212E-02	3.402916E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -550 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.652629E-03	1.922329E-07	2.642608E-01	1.887295E-05	1.574992E-02	-1.221769E-06
2	G	5.534565E-03	1.183500E-02	3.125924E-01	-1.464588E-01	-1.679735E-02	7.753968E-03
3	G	6.987651E-03	1.423942E-02	3.109905E-01	-1.118290E-01	2.162649E-02	1.288380E-03
4	G	8.054951E-03	1.327768E-02	2.734257E-01	-8.574314E-02	9.298106E-02	-4.446246E-03
5	G	7.256120E-03	1.012729E-02	2.069699E-01	-5.604271E-02	8.099839E-02	-3.430375E-03
6	G	4.557427E-03	5.618561E-03	1.160791E-01	-8.045912E-02	2.117809E-01	-1.091540E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.777544E-03	1.052474E-02	2.967257E-01	-1.121263E-01	-3.599044E-02	1.002311E-02
9	G	6.076724E-03	1.271774E-02	2.865410E-01	-8.670744E-02	3.368194E-02	5.125852E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -550 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.779464E-03	3.237590E-07	3.038694E-01	3.776144E-05	3.407036E-02	-1.763257E-06
2	G	7.256863E-03	1.549358E-02	3.590412E-01	-1.706499E-01	-1.927164E-02	1.007274E-02
3	G	9.215605E-03	1.862786E-02	3.570863E-01	-1.294669E-01	2.491444E-02	1.681377E-03
4	G	1.063440E-02	1.735232E-02	3.138724E-01	-9.933815E-02	1.071130E-01	-5.909255E-03
5	G	9.565464E-03	1.319918E-02	2.373305E-01	-6.213906E-02	9.324086E-02	-4.541111E-03
6	G	6.039631E-03	7.318296E-03	1.332494E-01	-9.286890E-02	2.420693E-01	-1.430320E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.287323E-03	1.374655E-02	3.406545E-01	-1.288555E-01	-4.116887E-02	1.310853E-02
9	G	8.008433E-03	1.661626E-02	3.288741E-01	-9.936245E-02	3.865039E-02	6.694036E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -550 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.776286E-03	4.915153E-07	3.353381E-01	6.251411E-05	5.155633E-02	-2.038441E-06
2	G	8.785312E-03	1.875643E-02	3.958674E-01	-1.898576E-01	-2.130599E-02	1.215431E-02
3	G	1.119881E-02	2.254442E-02	3.936427E-01	-1.435770E-01	2.754075E-02	2.030746E-03
4	G	1.293335E-02	2.098948E-02	3.459499E-01	-1.100882E-01	1.182943E-01	-7.217756E-03
5	G	1.162466E-02	1.594228E-02	2.614259E-01	-6.701155E-02	1.029395E-01	-5.535847E-03
6	G	7.365003E-03	8.838637E-03	1.468878E-01	-1.028850E-01	2.659898E-01	-1.734505E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.628122E-03	1.661695E-02	3.754864E-01	-1.421166E-01	-4.521336E-02	1.585772E-02
9	G	9.726521E-03	2.009282E-02	3.624387E-01	-1.093597E-01	4.252127E-02	8.195970E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -550 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.684926E-03	6.650252E-07	3.618884E-01	9.024473E-05	6.813055E-02	-2.024933E-06
2	G	1.018381E-02	2.174982E-02	4.268608E-01	-2.058793E-01	-2.301277E-02	1.407424E-02
3	G	1.301633E-02	2.614064E-02	4.244103E-01	-1.553737E-01	2.973206E-02	2.355306E-03
4	G	1.504285E-02	2.433180E-02	3.729585E-01	-1.190843E-01	1.276784E-01	-8.418471E-03
5	G	1.351575E-02	1.846450E-02	2.817290E-01	-7.114827E-02	1.111030E-01	-6.452207E-03
6	G	8.584770E-03	1.023839E-02	1.583866E-01	-1.114363E-01	2.860545E-01	-2.015554E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.854373E-03	1.925081E-02	4.048212E-01	-1.532103E-01	-4.857767E-02	1.838000E-02
9	G	1.130093E-02	2.328626E-02	3.907107E-01	-1.177201E-01	4.574760E-02	9.650955E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -550 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.528024E-03	8.515719E-07	3.850877E-01	1.211727E-04	8.384653E-02	-1.670478E-06
2	G	1.148584E-02	2.454430E-02	4.538833E-01	-2.197665E-01	-2.448350E-02	1.587179E-02
3	G	1.471128E-02	2.950056E-02	4.512367E-01	-1.656318E-01	3.162991E-02	2.661780E-03
4	G	1.701239E-02	2.745653E-02	3.965132E-01	-1.268920E-01	1.358417E-01	-9.539453E-03
5	G	1.528289E-02	2.082386E-02	2.994458E-01	-7.478333E-02	1.182235E-01	-7.310698E-03
6	G	9.726569E-03	1.154919E-02	1.684257E-01	-1.189811E-01	3.034887E-01	-2.279586E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.995637E-03	2.170998E-02	4.304101E-01	-1.628501E-01	-5.145498E-02	2.073121E-02
9	G	1.276898E-02	2.627054E-02	4.153733E-01	-1.249706E-01	4.852742E-02	1.108274E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -550 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.319549E-03	1.049765E-06	4.058309E-01	1.549405E-04	9.878033E-02	-9.467619E-07
2	G	1.271221E-02	2.718290E-02	4.779949E-01	-2.320868E-01	-2.576819E-02	1.757127E-02
3	G	1.631015E-02	3.267545E-02	4.751732E-01	-1.747574E-01	3.330896E-02	2.955043E-03
4	G	1.887239E-02	3.041113E-02	4.175354E-01	-1.338291E-01	1.431112E-01	-1.059773E-02
5	G	1.695319E-02	2.305604E-02	3.152659E-01	-7.805009E-02	1.245800E-01	-8.123867E-03
6	G	1.080743E-02	1.279054E-02	1.773939E-01	-1.257851E-01	3.189940E-01	-2.530381E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.107013E-02	2.403253E-02	4.532532E-01	-1.714248E-01	-5.396625E-02	2.294667E-02
9	G	1.415373E-02	2.909133E-02	4.373899E-01	-1.314065E-01	5.097914E-02	1.250174E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -550 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.068903E-03	1.258573E-06	4.246831E-01	1.912760E-04	1.130076E-01	1.674099E-07
2	G	1.387692E-02	2.969452E-02	4.998647E-01	-2.431993E-01	-2.690096E-02	1.918913E-02
3	G	1.783074E-02	3.569977E-02	4.968838E-01	-1.830081E-01	3.481698E-02	3.238297E-03
4	G	2.064324E-02	3.322744E-02	4.366067E-01	-1.400961E-01	1.496935E-01	-1.160482E-02
5	G	1.854481E-02	2.518495E-02	3.296246E-01	-8.103243E-02	1.303482E-01	-8.900143E-03
6	G	1.183877E-02	1.397549E-02	1.855369E-01	-1.320171E-01	3.330137E-01	-2.770474E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.209011E-02	2.624399E-02	4.739822E-01	-1.791792E-01	-5.618981E-02	2.505026E-02
9	G	1.547065E-02	3.177924E-02	4.573689E-01	-1.372148E-01	5.317785E-02	1.391419E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -550 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.782795E-03	1.477183E-06	4.420261E-01	2.299652E-04	1.265972E-01	1.688378E-06
2	G	1.498995E-02	3.209977E-02	5.199455E-01	-2.533474E-01	-2.790657E-02	2.073723E-02
3	G	1.928573E-02	3.859806E-02	5.168176E-01	-1.905582E-01	3.618676E-02	3.513757E-03
4	G	2.233946E-02	3.592813E-02	4.541209E-01	-1.458287E-01	1.557281E-01	-1.256898E-02
5	G	2.007067E-02	2.722760E-02	3.428166E-01	-8.378701E-02	1.356465E-01	-9.645528E-03
6	G	1.282873E-02	1.511334E-02	1.930209E-01	-1.377917E-01	3.458476E-01	-3.001663E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.306433E-02	2.836253E-02	4.930238E-01	-1.862787E-01	-5.817992E-02	2.705917E-02
9	G	1.673078E-02	3.435608E-02	4.757216E-01	-1.425217E-01	5.517455E-02	1.532395E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -550 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.046624E-02	1.704937E-06	4.581319E-01	2.708349E-04	1.396096E-01	3.629069E-06
2	G	1.605870E-02	3.441402E-02	5.385594E-01	-2.627046E-01	-2.880377E-02	2.222452E-02
3	G	2.068458E-02	4.138859E-02	5.352945E-01	-1.975326E-01	3.744198E-02	3.783017E-03
4	G	2.397188E-02	3.853007E-02	4.703582E-01	-1.511237E-01	1.613143E-01	-1.349640E-02
5	G	2.154038E-02	2.919662E-02	3.550515E-01	-8.635420E-02	1.405596E-01	-1.036449E-02
6	G	1.378335E-02	1.621101E-02	1.999643E-01	-1.431909E-01	3.577095E-01	-3.225288E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.399930E-02	3.040168E-02	5.106822E-01	-1.928408E-01	-5.997601E-02	2.898628E-02
9	G	1.794230E-02	3.683808E-02	4.927409E-01	-1.474174E-01	5.700565E-02	1.673350E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -600 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.291474E-03	7.550521E-08	2.069545E-01	5.050520E-06	-2.628602E-03	-5.546576E-07
2	G	3.455011E-03	7.486895E-03	2.454016E-01	-1.123253E-01	-1.344750E-02	5.002198E-03
3	G	4.305667E-03	9.028614E-03	2.444059E-01	-8.723929E-02	1.669829E-02	8.340076E-04
4	G	4.953946E-03	8.441598E-03	2.150294E-01	-6.644751E-02	7.273548E-02	-2.728714E-03
5	G	4.480851E-03	6.489241E-03	1.632303E-01	-4.746044E-02	6.288357E-02	-2.094904E-03
6	G	2.786925E-03	3.618041E-03	9.144012E-02	-6.375752E-02	1.681302E-01	-6.952989E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.956713E-03	6.684167E-03	2.331132E-01	-8.827510E-02	-2.862779E-02	6.359392E-03
9	G	3.745222E-03	8.074575E-03	2.252470E-01	-6.865823E-02	2.639732E-02	3.381439E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -600 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.648356E-03	1.924721E-07	2.638379E-01	1.892123E-05	1.580471E-02	-1.218782E-06
2	G	5.523366E-03	1.184657E-02	3.121902E-01	-1.466102E-01	-1.669918E-02	7.744930E-03
3	G	6.968485E-03	1.425471E-02	3.106257E-01	-1.119381E-01	2.141618E-02	1.307438E-03
4	G	8.032030E-03	1.329500E-02	2.731215E-01	-8.582987E-02	9.303743E-02	-4.457983E-03
5	G	7.236168E-03	1.014762E-02	2.067729E-01	-5.604860E-02	8.063199E-02	-3.414326E-03
6	G	4.547490E-03	5.637572E-03	1.160168E-01	-8.087997E-02	2.117351E-01	-1.095376E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.765990E-03	1.053319E-02	2.963133E-01	-1.121857E-01	-3.607646E-02	1.003890E-02
9	G	6.057975E-03	1.272727E-02	2.861508E-01	-8.677454E-02	3.369413E-02	5.097218E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -600 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.775143E-03	3.243314E-07	3.034998E-01	3.784936E-05	3.412623E-02	-1.758146E-06
2	G	7.245555E-03	1.550495E-02	3.586893E-01	-1.707896E-01	-1.917966E-02	1.006215E-02
3	G	9.196364E-03	1.864287E-02	3.567670E-01	-1.295619E-01	2.472473E-02	1.701323E-03
4	G	1.061142E-02	1.736937E-02	3.136062E-01	-9.942049E-02	1.071686E-01	-5.921821E-03
5	G	9.545399E-03	1.321917E-02	2.371569E-01	-6.213238E-02	9.291663E-02	-4.525048E-03
6	G	6.029847E-03	7.337247E-03	1.331956E-01	-9.324441E-02	2.420288E-01	-1.434175E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.275718E-03	1.375474E-02	3.402935E-01	-1.289068E-01	-4.124551E-02	1.312436E-02
9	G	7.989615E-03	1.662548E-02	3.285325E-01	-9.942192E-02	3.866353E-02	6.662751E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -600 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.771924E-03	4.918817E-07	3.350022E-01	6.259945E-05	5.161196E-02	-2.031602E-06
2	G	8.773925E-03	1.876765E-02	3.955472E-01	-1.899881E-01	-2.121893E-02	1.214275E-02
3	G	1.117950E-02	2.255923E-02	3.933519E-01	-1.436627E-01	2.736503E-02	2.051259E-03
4	G	1.291031E-02	2.100634E-02	3.457075E-01	-1.101667E-01	1.183481E-01	-7.230821E-03
5	G	1.160450E-02	1.596204E-02	2.612672E-01	-6.699868E-02	1.026427E-01	-5.519781E-03
6	G	7.355298E-03	8.857543E-03	1.468391E-01	-1.032306E-01	2.659524E-01	-1.738369E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.616474E-03	1.662496E-02	3.751577E-01	-1.421626E-01	-4.528358E-02	1.587354E-02
9	G	9.707651E-03	2.010183E-02	3.621277E-01	-1.094140E-01	4.253441E-02	8.163330E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -600 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.680528E-03	6.654550E-07	3.615763E-01	9.034701E-05	6.818534E-02	-2.015906E-06
2	G	1.017236E-02	2.176091E-02	4.265630E-01	-2.060027E-01	-2.292976E-02	1.406202E-02
3	G	1.299697E-02	2.615529E-02	4.241397E-01	-1.554529E-01	2.956682E-02	2.376201E-03
4	G	1.501975E-02	2.434851E-02	3.727331E-01	-1.191594E-01	1.277303E-01	-8.431864E-03
5	G	1.349552E-02	1.848408E-02	2.815808E-01	-7.113186E-02	1.108261E-01	-6.436139E-03
6	G	8.575111E-03	1.025726E-02	1.583415E-01	-1.117598E-01	2.860191E-01	-2.019423E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.842688E-03	1.925868E-02	4.045155E-01	-1.532524E-01	-4.864299E-02	1.839578E-02
9	G	1.128202E-02	2.329511E-02	3.904215E-01	-1.177706E-01	4.576040E-02	9.617627E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -600 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.523592E-03	8.520619E-07	3.847937E-01	1.212909E-04	8.390024E-02	-1.659121E-06
2	G	1.147433E-02	2.455529E-02	4.536025E-01	-2.198841E-01	-2.440386E-02	1.585908E-02
3	G	1.469188E-02	2.951507E-02	4.509814E-01	-1.657059E-01	3.147298E-02	2.682955E-03
4	G	1.698925E-02	2.747311E-02	3.963006E-01	-1.269642E-01	1.358918E-01	-9.553078E-03
5	G	1.526258E-02	2.084331E-02	2.993057E-01	-7.476470E-02	1.179621E-01	-7.294626E-03
6	G	9.716937E-03	1.156803E-02	1.683832E-01	-1.192875E-01	3.034548E-01	-2.283456E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.983917E-03	2.171774E-02	4.301219E-01	-1.628894E-01	-5.151638E-02	2.074694E-02
9	G	1.275003E-02	2.627926E-02	4.151006E-01	-1.250179E-01	4.853978E-02	1.104907E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -600 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.315085E-03	1.050313E-06	4.055514E-01	1.550735E-04	9.883282E-02	-9.329551E-07
2	G	1.270066E-02	2.719379E-02	4.777276E-01	-2.321994E-01	-2.569142E-02	1.755818E-02
3	G	1.629071E-02	3.268984E-02	4.749302E-01	-1.748275E-01	3.315884E-02	2.976433E-03
4	G	1.884920E-02	3.042758E-02	4.173329E-01	-1.338987E-01	1.431598E-01	-1.061152E-02
5	G	1.693282E-02	2.307537E-02	3.151322E-01	-7.803001E-02	1.243311E-01	-8.107790E-03
6	G	1.079781E-02	1.280934E-02	1.773534E-01	-1.260776E-01	3.189612E-01	-2.534251E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.105838E-02	2.404019E-02	4.529790E-01	-1.714618E-01	-5.402440E-02	2.296232E-02
9	G	1.413474E-02	2.909993E-02	4.371304E-01	-1.314514E-01	5.099103E-02	1.246795E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -600 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.064409E-03	1.259177E-06	4.244155E-01	1.914232E-04	1.130589E-01	1.837689E-07
2	G	1.386533E-02	2.970531E-02	4.996086E-01	-2.433076E-01	-2.682668E-02	1.917574E-02
3	G	1.781126E-02	3.571405E-02	4.966508E-01	-1.830748E-01	3.467260E-02	3.259858E-03
4	G	2.062000E-02	3.324379E-02	4.364126E-01	-1.401634E-01	1.497406E-01	-1.161874E-02
5	G	1.852438E-02	2.520417E-02	3.294962E-01	-8.101136E-02	1.301096E-01	-8.884057E-03
6	G	1.182916E-02	1.399426E-02	1.854980E-01	-1.322979E-01	3.329816E-01	-2.774342E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.207833E-02	2.625155E-02	4.737194E-01	-1.792143E-01	-5.624522E-02	2.506584E-02
9	G	1.545163E-02	3.178774E-02	4.571202E-01	-1.372574E-01	5.318928E-02	1.388040E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -600 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.778273E-03	1.477841E-06	4.417686E-01	2.301259E-04	1.266471E-01	1.707377E-06
2	G	1.497831E-02	3.211048E-02	5.196987E-01	-2.534519E-01	-2.783448E-02	2.072360E-02
3	G	1.926621E-02	3.861223E-02	5.165932E-01	-1.906221E-01	3.604732E-02	3.535457E-03
4	G	2.231619E-02	3.594438E-02	4.539339E-01	-1.458940E-01	1.557738E-01	-1.258300E-02
5	G	2.005019E-02	2.724671E-02	3.426926E-01	-8.376526E-02	1.354168E-01	-9.629433E-03
6	G	1.281912E-02	1.513208E-02	1.929834E-01	-1.380626E-01	3.458163E-01	-3.005530E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.305251E-02	2.837001E-02	4.927707E-01	-1.863121E-01	-5.823294E-02	2.707466E-02
9	G	1.671172E-02	3.436449E-02	4.754822E-01	-1.425625E-01	5.518553E-02	1.529026E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -600 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.046169E-02	1.705648E-06	4.578831E-01	2.710085E-04	1.396583E-01	3.650784E-06
2	G	1.604703E-02	3.442465E-02	5.383207E-01	-2.628056E-01	-2.873362E-02	2.221068E-02
3	G	2.066501E-02	4.140267E-02	5.350772E-01	-1.975939E-01	3.730685E-02	3.804832E-03
4	G	2.394856E-02	3.854623E-02	4.701772E-01	-1.511871E-01	1.613588E-01	-1.351049E-02
5	G	2.151985E-02	2.921565E-02	3.549315E-01	-8.633197E-02	1.403375E-01	-1.034839E-02
6	G	1.377375E-02	1.622972E-02	1.999280E-01	-1.434532E-01	3.576788E-01	-3.229153E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.398746E-02	3.040909E-02	5.104374E-01	-1.928728E-01	-6.002694E-02	2.900169E-02
9	G	1.792322E-02	3.684640E-02	4.925094E-01	-1.474565E-01	5.701622E-02	1.669995E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -650 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.287252E-03	7.910892E-08	2.064204E-01	5.399912E-06	-2.577379E-03	-5.724411E-07
2	G	3.444084E-03	7.498775E-03	2.448924E-01	-1.124810E-01	-1.334117E-02	4.996710E-03
3	G	4.286566E-03	9.044335E-03	2.439437E-01	-8.736223E-02	1.645091E-02	8.511074E-04
4	G	4.931010E-03	8.459427E-03	2.146441E-01	-6.653176E-02	7.278421E-02	-2.738726E-03
5	G	4.460924E-03	6.510229E-03	1.629835E-01	-4.749802E-02	6.243654E-02	-2.078902E-03
6	G	2.776465E-03	3.637183E-03	9.135806E-02	-6.425864E-02	1.680687E-01	-6.990748E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.945235E-03	6.693173E-03	2.325933E-01	-8.834393E-02	-2.873055E-02	6.374983E-03
9	G	3.726599E-03	8.084839E-03	2.247560E-01	-6.873520E-02	2.640378E-02	3.359273E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -650 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.644084E-03	1.932423E-07	2.634148E-01	1.902012E-05	1.585981E-02	-1.217111E-06
2	G	5.512174E-03	1.185822E-02	3.117880E-01	-1.467629E-01	-1.660183E-02	7.735979E-03
3	G	6.949327E-03	1.427009E-02	3.102610E-01	-1.120493E-01	2.120656E-02	1.326465E-03
4	G	8.009116E-03	1.331239E-02	2.728174E-01	-8.591735E-02	9.309340E-02	-4.469746E-03
5	G	7.216203E-03	1.016800E-02	2.065758E-01	-5.605482E-02	8.026640E-02	-3.398323E-03
6	G	4.537503E-03	5.656614E-03	1.159544E-01	-8.129951E-02	2.116888E-01	-1.099211E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.754442E-03	1.054170E-02	2.959007E-01	-1.122462E-01	-3.616206E-02	1.005472E-02
9	G	6.039232E-03	1.273687E-02	2.857604E-01	-8.684220E-02	3.370585E-02	5.068778E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -650 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.770831E-03	3.334980E-07	3.031302E-01	3.861471E-05	3.418307E-02	-1.741293E-06
2	G	7.234218E-03	1.551648E-02	3.583382E-01	-1.709367E-01	-1.908915E-02	1.005155E-02
3	G	9.177148E-03	1.865803E-02	3.564485E-01	-1.296642E-01	2.453684E-02	1.721101E-03
4	G	1.058845E-02	1.738648E-02	3.133402E-01	-9.950395E-02	1.072241E-01	-5.934459E-03
5	G	9.525322E-03	1.323919E-02	2.369833E-01	-6.212578E-02	9.259318E-02	-4.509039E-03
6	G	6.020021E-03	7.356221E-03	1.331417E-01	-9.361879E-02	2.419879E-01	-1.438027E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.264127E-03	1.376298E-02	3.399324E-01	-1.289619E-01	-4.132046E-02	1.314008E-02
9	G	7.970792E-03	1.663472E-02	3.281905E-01	-9.948253E-02	3.867539E-02	6.632310E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -650 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.767562E-03	4.922269E-07	3.346661E-01	6.268568E-05	5.166781E-02	-2.024840E-06
2	G	8.762541E-03	1.877891E-02	3.952269E-01	-1.901189E-01	-2.113221E-02	1.213124E-02
3	G	1.116021E-02	2.257409E-02	3.930610E-01	-1.437489E-01	2.718959E-02	2.071751E-03
4	G	1.288726E-02	2.102323E-02	3.454651E-01	-1.102453E-01	1.184015E-01	-7.243892E-03
5	G	1.158433E-02	1.598183E-02	2.611085E-01	-6.698594E-02	1.023463E-01	-5.503745E-03
6	G	7.345560E-03	8.876468E-03	1.467903E-01	-1.035754E-01	2.659147E-01	-1.742234E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.604830E-03	1.663301E-02	3.748290E-01	-1.422088E-01	-4.535360E-02	1.588938E-02
9	G	9.688784E-03	2.011088E-02	3.618166E-01	-1.094684E-01	4.254732E-02	8.130876E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -650 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.676129E-03	6.658864E-07	3.612641E-01	9.044966E-05	6.824034E-02	-2.006868E-06
2	G	1.016091E-02	2.177204E-02	4.262651E-01	-2.061263E-01	-2.284700E-02	1.404985E-02
3	G	1.297762E-02	2.616999E-02	4.238690E-01	-1.555324E-01	2.940181E-02	2.397079E-03
4	G	1.499665E-02	2.436525E-02	3.725075E-01	-1.192346E-01	1.277819E-01	-8.445262E-03
5	G	1.347527E-02	1.850370E-02	2.814326E-01	-7.111554E-02	1.105496E-01	-6.420097E-03
6	G	8.565423E-03	1.027614E-02	1.582962E-01	-1.120828E-01	2.859834E-01	-2.023291E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.831005E-03	1.926658E-02	4.042097E-01	-1.532948E-01	-4.870817E-02	1.841157E-02
9	G	1.126311E-02	2.330399E-02	3.901321E-01	-1.178211E-01	4.577303E-02	9.584447E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -650 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.519160E-03	8.525539E-07	3.844997E-01	1.214093E-04	8.395411E-02	-1.647749E-06
2	G	1.146283E-02	2.456630E-02	4.533216E-01	-2.200018E-01	-2.432443E-02	1.584641E-02
3	G	1.467247E-02	2.952963E-02	4.507262E-01	-1.657803E-01	3.131622E-02	2.704116E-03
4	G	1.696610E-02	2.748971E-02	3.960879E-01	-1.270365E-01	1.359418E-01	-9.566707E-03
5	G	1.524227E-02	2.086277E-02	2.991655E-01	-7.474615E-02	1.177009E-01	-7.278577E-03
6	G	9.707280E-03	1.158687E-02	1.683406E-01	-1.195934E-01	3.034206E-01	-2.287326E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.972199E-03	2.172552E-02	4.298336E-01	-1.629288E-01	-5.157767E-02	2.076266E-02
9	G	1.273108E-02	2.628801E-02	4.148279E-01	-1.250653E-01	4.855198E-02	1.101554E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -650 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.310623E-03	1.050863E-06	4.052719E-01	1.552069E-04	9.888546E-02	-9.191298E-07
2	G	1.268911E-02	2.720470E-02	4.774602E-01	-2.323121E-01	-2.561483E-02	1.754514E-02
3	G	1.627126E-02	3.270427E-02	4.746871E-01	-1.748978E-01	3.300887E-02	2.997811E-03
4	G	1.882601E-02	3.044407E-02	4.171304E-01	-1.339684E-01	1.432081E-01	-1.062532E-02
5	G	1.691244E-02	2.309471E-02	3.149984E-01	-7.801001E-02	1.240823E-01	-8.091733E-03
6	G	1.078817E-02	1.282815E-02	1.773129E-01	-1.263696E-01	3.189282E-01	-2.538121E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.104663E-02	2.404786E-02	4.527047E-01	-1.714989E-01	-5.408246E-02	2.297798E-02
9	G	1.411575E-02	2.910855E-02	4.368709E-01	-1.314962E-01	5.100279E-02	1.243428E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -650 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.059916E-03	1.259782E-06	4.241479E-01	1.915708E-04	1.131102E-01	2.001494E-07
2	G	1.385374E-02	2.971613E-02	4.993524E-01	-2.434160E-01	-2.675255E-02	1.916239E-02
3	G	1.779177E-02	3.572836E-02	4.964178E-01	-1.831417E-01	3.452836E-02	3.281408E-03
4	G	2.059677E-02	3.326017E-02	4.362185E-01	-1.402308E-01	1.497875E-01	-1.163266E-02
5	G	1.850394E-02	2.522340E-02	3.293678E-01	-8.099036E-02	1.298712E-01	-8.867992E-03
6	G	1.181953E-02	1.401304E-02	1.854592E-01	-1.325784E-01	3.329495E-01	-2.778211E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.206654E-02	2.625914E-02	4.734566E-01	-1.792495E-01	-5.630053E-02	2.508141E-02
9	G	1.543261E-02	3.179626E-02	4.568716E-01	-1.373001E-01	5.320060E-02	1.384673E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -650 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.773752E-03	1.478501E-06	4.415111E-01	2.302869E-04	1.266972E-01	1.726401E-06
2	G	1.496668E-02	3.212121E-02	5.194520E-01	-2.535565E-01	-2.776252E-02	2.070999E-02
3	G	1.924668E-02	3.862643E-02	5.163686E-01	-1.906861E-01	3.590800E-02	3.557147E-03
4	G	2.229291E-02	3.596066E-02	4.537469E-01	-1.459594E-01	1.558194E-01	-1.259702E-02
5	G	2.002970E-02	2.726585E-02	3.425687E-01	-8.374356E-02	1.351872E-01	-9.613357E-03
6	G	1.280950E-02	1.515083E-02	1.929459E-01	-1.383332E-01	3.457849E-01	-3.009397E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.304070E-02	2.837751E-02	4.925176E-01	-1.863456E-01	-5.828589E-02	2.709015E-02
9	G	1.669267E-02	3.437291E-02	4.752427E-01	-1.426033E-01	5.519642E-02	1.525667E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -650 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.045714E-02	1.706360E-06	4.576343E-01	2.711824E-04	1.397072E-01	3.672527E-06
2	G	1.603536E-02	3.443529E-02	5.380820E-01	-2.629068E-01	-2.866358E-02	2.219687E-02
3	G	2.064545E-02	4.141676E-02	5.348600E-01	-1.976555E-01	3.717184E-02	3.826638E-03
4	G	2.392525E-02	3.856242E-02	4.699962E-01	-1.512506E-01	1.614031E-01	-1.352458E-02
5	G	2.149930E-02	2.923469E-02	3.548114E-01	-8.630978E-02	1.401155E-01	-1.033230E-02
6	G	1.376412E-02	1.624844E-02	1.998917E-01	-1.437151E-01	3.576480E-01	-3.233017E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.397562E-02	3.041651E-02	5.101926E-01	-1.929048E-01	-6.007781E-02	2.901710E-02
9	G	1.790413E-02	3.685474E-02	4.922778E-01	-1.474956E-01	5.702669E-02	1.666651E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -700 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.283061E-03	7.271444E-08	2.058859E-01	4.817924E-06	-2.525184E-03	-5.530223E-07
2	G	3.432868E-03	7.511606E-03	2.443911E-01	-1.127083E-01	-1.325129E-02	4.991211E-03
3	G	4.267682E-03	9.061085E-03	2.434921E-01	-8.757121E-02	1.621780E-02	8.673381E-04
4	G	4.908330E-03	8.477666E-03	2.142631E-01	-6.663544E-02	7.283894E-02	-2.749537E-03
5	G	4.441098E-03	6.531435E-03	1.627382E-01	-4.754052E-02	6.199282E-02	-2.063137E-03
6	G	2.765978E-03	3.656422E-03	9.127624E-02	-6.475849E-02	1.680076E-01	-7.028689E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.933813E-03	6.702396E-03	2.320735E-01	-8.845323E-02	-2.881933E-02	6.389588E-03
9	G	3.707904E-03	8.095055E-03	2.242609E-01	-6.882986E-02	2.640041E-02	3.341507E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -700 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.639812E-03	1.928396E-07	2.629915E-01	1.900381E-05	1.591541E-02	-1.212241E-06
2	G	5.500991E-03	1.186993E-02	3.113855E-01	-1.469153E-01	-1.650495E-02	7.727112E-03
3	G	6.930173E-03	1.428554E-02	3.098961E-01	-1.121602E-01	2.099739E-02	1.345463E-03
4	G	7.986202E-03	1.332985E-02	2.725131E-01	-8.600470E-02	9.314869E-02	-4.481496E-03
5	G	7.196222E-03	1.018843E-02	2.063785E-01	-5.606125E-02	7.990152E-02	-3.382360E-03
6	G	4.527465E-03	5.675685E-03	1.158917E-01	-8.171778E-02	2.116419E-01	-1.103048E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.742900E-03	1.055026E-02	2.954879E-01	-1.123066E-01	-3.624742E-02	1.007055E-02
9	G	6.020494E-03	1.274652E-02	2.853698E-01	-8.690979E-02	3.371719E-02	5.040659E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -700 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.766509E-03	3.340114E-07	3.027604E-01	3.870000E-05	3.423945E-02	-1.736160E-06
2	G	7.222942E-03	1.552789E-02	3.579858E-01	-1.710727E-01	-1.899725E-02	1.004110E-02
3	G	9.157904E-03	1.867311E-02	3.561286E-01	-1.297559E-01	2.434702E-02	1.741089E-03
4	G	1.056546E-02	1.740362E-02	3.130738E-01	-9.958604E-02	1.072785E-01	-5.946987E-03
5	G	9.505234E-03	1.325926E-02	2.368096E-01	-6.211956E-02	9.226983E-02	-4.493036E-03
6	G	6.010159E-03	7.375218E-03	1.330876E-01	-9.399265E-02	2.419468E-01	-1.441884E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.252526E-03	1.377125E-02	3.395711E-01	-1.290117E-01	-4.139753E-02	1.315601E-02
9	G	7.951991E-03	1.664405E-02	3.278488E-01	-9.954164E-02	3.868855E-02	6.601054E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258
FOUR TENTHS, -700 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.763200E-03	4.925960E-07	3.343300E-01	6.277172E-05	5.172390E-02	-2.017988E-06
2	G	8.751163E-03	1.879021E-02	3.949065E-01	-1.902498E-01	-2.104577E-02	1.211978E-02
3	G	1.114091E-02	2.258900E-02	3.927701E-01	-1.438354E-01	2.701442E-02	2.092228E-03
4	G	1.286422E-02	2.104018E-02	3.452227E-01	-1.103240E-01	1.184547E-01	-7.256964E-03
5	G	1.156416E-02	1.600166E-02	2.609496E-01	-6.697334E-02	1.020503E-01	-5.487738E-03
6	G	7.335790E-03	8.895412E-03	1.467414E-01	-1.039196E-01	2.658767E-01	-1.746098E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.593188E-03	1.664109E-02	3.745001E-01	-1.422552E-01	-4.542349E-02	1.590522E-02
9	G	9.669922E-03	2.011996E-02	3.615054E-01	-1.095229E-01	4.256003E-02	8.098573E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -700 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.671730E-03	6.663198E-07	3.609518E-01	9.055264E-05	6.829553E-02	-1.997819E-06
2	G	1.014947E-02	2.178320E-02	4.259671E-01	-2.062500E-01	-2.276448E-02	1.403771E-02
3	G	1.295826E-02	2.618473E-02	4.235984E-01	-1.556122E-01	2.923702E-02	2.417943E-03
4	G	1.497356E-02	2.438202E-02	3.722820E-01	-1.193100E-01	1.278334E-01	-8.458664E-03
5	G	1.345502E-02	1.852334E-02	2.812843E-01	-7.109933E-02	1.102733E-01	-6.404080E-03
6	G	8.555708E-03	1.029504E-02	1.582509E-01	-1.124052E-01	2.859476E-01	-2.027159E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.819325E-03	1.927451E-02	4.039039E-01	-1.533374E-01	-4.877321E-02	1.842737E-02
9	G	1.124420E-02	2.331291E-02	3.898427E-01	-1.178717E-01	4.578548E-02	9.551414E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -700 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.514727E-03	8.530476E-07	3.842055E-01	1.215281E-04	8.400816E-02	-1.636362E-06
2	G	1.145133E-02	2.457735E-02	4.530406E-01	-2.201196E-01	-2.424521E-02	1.583379E-02
3	G	1.465308E-02	2.954421E-02	4.504708E-01	-1.658550E-01	3.115966E-02	2.725264E-03
4	G	1.694296E-02	2.750635E-02	3.958751E-01	-1.271089E-01	1.359915E-01	-9.580340E-03
5	G	1.522195E-02	2.088227E-02	2.990253E-01	-7.472769E-02	1.174400E-01	-7.262552E-03
6	G	9.697597E-03	1.160574E-02	1.682979E-01	-1.198988E-01	3.033863E-01	-2.291195E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.960483E-03	2.173333E-02	4.295453E-01	-1.629684E-01	-5.163884E-02	2.077840E-02
9	G	1.271213E-02	2.629678E-02	4.145550E-01	-1.251128E-01	4.856405E-02	1.098214E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -700 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.306158E-03	1.051414E-06	4.049923E-01	1.553407E-04	9.893824E-02	-9.052860E-07
2	G	1.267756E-02	2.721564E-02	4.771928E-01	-2.324249E-01	-2.553841E-02	1.753212E-02
3	G	1.625182E-02	3.271873E-02	4.744440E-01	-1.749684E-01	3.285906E-02	3.019178E-03
4	G	1.880282E-02	3.046059E-02	4.169278E-01	-1.340382E-01	1.432563E-01	-1.063912E-02
5	G	1.689206E-02	2.311408E-02	3.148647E-01	-7.799006E-02	1.238338E-01	-8.075697E-03
6	G	1.077851E-02	1.284698E-02	1.772722E-01	-1.266613E-01	3.188950E-01	-2.541991E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.103488E-02	2.405556E-02	4.524303E-01	-1.715361E-01	-5.414042E-02	2.299364E-02
9	G	1.409677E-02	2.911721E-02	4.366112E-01	-1.315411E-01	5.101442E-02	1.240072E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -700 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.055423E-03	1.260390E-06	4.238803E-01	1.917187E-04	1.131617E-01	2.165516E-07
2	G	1.384214E-02	2.972698E-02	4.990962E-01	-2.435244E-01	-2.667857E-02	1.914907E-02
3	G	1.777229E-02	3.574270E-02	4.961848E-01	-1.832088E-01	3.438424E-02	3.302948E-03
4	G	2.057354E-02	3.327657E-02	4.360243E-01	-1.402983E-01	1.498343E-01	-1.164659E-02
5	G	1.848350E-02	2.524265E-02	3.292393E-01	-8.096941E-02	1.296329E-01	-8.851946E-03
6	G	1.180988E-02	1.403183E-02	1.854202E-01	-1.328585E-01	3.329172E-01	-2.782079E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.205476E-02	2.626674E-02	4.731937E-01	-1.792848E-01	-5.635576E-02	2.509700E-02
9	G	1.541359E-02	3.180480E-02	4.566228E-01	-1.373428E-01	5.321180E-02	1.381316E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -700 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.769230E-03	1.479162E-06	4.412536E-01	2.304483E-04	1.267474E-01	1.745449E-06
2	G	1.495505E-02	3.213197E-02	5.192052E-01	-2.536611E-01	-2.769068E-02	2.069642E-02
3	G	1.922716E-02	3.864066E-02	5.161440E-01	-1.907503E-01	3.576880E-02	3.578828E-03
4	G	2.226964E-02	3.597696E-02	4.535598E-01	-1.460248E-01	1.558649E-01	-1.261104E-02
5	G	2.000920E-02	2.728500E-02	3.424447E-01	-8.372191E-02	1.349578E-01	-9.597300E-03
6	G	1.279986E-02	1.516959E-02	1.929084E-01	-1.386034E-01	3.457533E-01	-3.013263E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.302889E-02	2.838503E-02	4.922644E-01	-1.863793E-01	-5.833876E-02	2.710565E-02
9	G	1.667362E-02	3.438136E-02	4.750031E-01	-1.426441E-01	5.520720E-02	1.522318E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -700 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.045259E-02	1.707074E-06	4.573854E-01	2.713567E-04	1.397562E-01	3.694297E-06
2	G	1.602369E-02	3.444596E-02	5.378432E-01	-2.630080E-01	-2.859366E-02	2.218308E-02
3	G	2.062589E-02	4.143089E-02	5.346427E-01	-1.977171E-01	3.703693E-02	3.848434E-03
4	G	2.390194E-02	3.857863E-02	4.698152E-01	-1.513141E-01	1.614474E-01	-1.353868E-02
5	G	2.147876E-02	2.925375E-02	3.546913E-01	-8.628764E-02	1.398937E-01	-1.031623E-02
6	G	1.375448E-02	1.626717E-02	1.998553E-01	-1.439768E-01	3.576170E-01	-3.236881E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.396378E-02	3.042395E-02	5.099478E-01	-1.929370E-01	-6.012860E-02	2.903252E-02
9	G	1.788505E-02	3.686310E-02	4.920462E-01	-1.475348E-01	5.703707E-02	1.663315E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -750 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.278889E-03	7.514779E-08	2.053510E-01	5.022590E-06	-2.471722E-03	-5.254731E-07
2	G	3.421840E-03	7.524222E-03	2.438858E-01	-1.128969E-01	-1.315226E-02	4.985532E-03
3	G	4.248729E-03	9.077728E-03	2.430362E-01	-8.773575E-02	1.597273E-02	8.847227E-04
4	G	4.885691E-03	8.496183E-03	2.138831E-01	-6.674550E-02	7.289003E-02	-2.760152E-03
5	G	4.421356E-03	6.552867E-03	1.624941E-01	-4.758956E-02	6.155096E-02	-2.047227E-03
6	G	2.755477E-03	3.675777E-03	9.119479E-02	-6.526110E-02	1.679476E-01	-7.066955E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.922378E-03	6.711755E-03	2.315539E-01	-8.854304E-02	-2.891976E-02	6.405245E-03
9	G	3.689295E-03	8.105586E-03	2.237683E-01	-6.892199E-02	2.640406E-02	3.320307E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -750 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.635541E-03	1.928652E-07	2.625679E-01	1.904706E-05	1.597142E-02	-1.209851E-06
2	G	5.489817E-03	1.188171E-02	3.109829E-01	-1.470677E-01	-1.640856E-02	7.718326E-03
3	G	6.911026E-03	1.430107E-02	3.095311E-01	-1.122712E-01	2.078874E-02	1.364427E-03
4	G	7.963289E-03	1.334737E-02	2.722086E-01	-8.609203E-02	9.320334E-02	-4.493240E-03
5	G	7.176223E-03	1.020891E-02	2.061811E-01	-5.606790E-02	7.953735E-02	-3.366439E-03
6	G	4.517375E-03	5.694787E-03	1.158289E-01	-8.213477E-02	2.115945E-01	-1.106885E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.731364E-03	1.055888E-02	2.950749E-01	-1.123673E-01	-3.633249E-02	1.008638E-02
9	G	6.001764E-03	1.275625E-02	2.849790E-01	-8.697741E-02	3.372810E-02	5.012862E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -750 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.762192E-03	3.336256E-07	3.023905E-01	3.871292E-05	3.429648E-02	-1.732318E-06
2	G	7.211570E-03	1.553963E-02	3.576353E-01	-1.712287E-01	-1.890940E-02	1.003063E-02
3	G	9.138719E-03	1.868851E-02	3.558110E-01	-1.298693E-01	2.416150E-02	1.760658E-03
4	G	1.054251E-02	1.742086E-02	3.128080E-01	-9.967161E-02	1.073342E-01	-5.959769E-03
5	G	9.485135E-03	1.327937E-02	2.366358E-01	-6.211311E-02	9.194758E-02	-4.477109E-03
6	G	6.000254E-03	7.394236E-03	1.330333E-01	-9.436497E-02	2.419050E-01	-1.445733E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.240948E-03	1.377958E-02	3.392097E-01	-1.290717E-01	-4.147027E-02	1.317162E-02
9	G	7.933160E-03	1.665336E-02	3.275059E-01	-9.960410E-02	3.869867E-02	6.571675E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -750 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.758838E-03	4.929673E-07	3.339937E-01	6.285802E-05	5.178022E-02	-2.011127E-06
2	G	8.739793E-03	1.880155E-02	3.945860E-01	-1.903806E-01	-2.095959E-02	1.210837E-02
3	G	1.112161E-02	2.260396E-02	3.924792E-01	-1.439218E-01	2.683947E-02	2.112693E-03
4	G	1.284118E-02	2.105716E-02	3.449802E-01	-1.104028E-01	1.185075E-01	-7.270036E-03
5	G	1.154397E-02	1.602151E-02	2.607907E-01	-6.696087E-02	1.017546E-01	-5.471759E-03
6	G	7.325988E-03	8.914375E-03	1.466924E-01	-1.042631E-01	2.658385E-01	-1.749962E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.581549E-03	1.664920E-02	3.741712E-01	-1.423017E-01	-4.549327E-02	1.592109E-02
9	G	9.651064E-03	2.012909E-02	3.611942E-01	-1.095774E-01	4.257258E-02	8.066396E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -750 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.667332E-03	6.667552E-07	3.606394E-01	9.065596E-05	6.835092E-02	-1.988757E-06
2	G	1.013803E-02	2.179440E-02	4.256690E-01	-2.063739E-01	-2.268221E-02	1.402562E-02
3	G	1.293892E-02	2.619950E-02	4.233277E-01	-1.556922E-01	2.907246E-02	2.438790E-03
4	G	1.495047E-02	2.439884E-02	3.720563E-01	-1.193854E-01	1.278846E-01	-8.472070E-03
5	G	1.343475E-02	1.854301E-02	2.811359E-01	-7.108321E-02	1.099974E-01	-6.388091E-03
6	G	8.545963E-03	1.031396E-02	1.582054E-01	-1.127271E-01	2.859115E-01	-2.031028E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.807647E-03	1.928247E-02	4.035980E-01	-1.533801E-01	-4.883812E-02	1.844318E-02
9	G	1.122529E-02	2.332186E-02	3.895532E-01	-1.179223E-01	4.579775E-02	9.518529E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260
SIX TENTHS, -750 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.510295E-03	8.535432E-07	3.839114E-01	1.216473E-04	8.406237E-02	-1.624960E-06
2	G	1.143984E-02	2.458843E-02	4.527597E-01	-2.202375E-01	-2.416618E-02	1.582119E-02
3	G	1.463368E-02	2.955884E-02	4.502155E-01	-1.659299E-01	3.100327E-02	2.746398E-03
4	G	1.691982E-02	2.752302E-02	3.956623E-01	-1.271814E-01	1.360411E-01	-9.593978E-03
5	G	1.520162E-02	2.090179E-02	2.988850E-01	-7.470931E-02	1.171793E-01	-7.246550E-03
6	G	9.687889E-03	1.162461E-02	1.682551E-01	-1.202038E-01	3.033518E-01	-2.295065E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.948769E-03	2.174116E-02	4.292569E-01	-1.630082E-01	-5.169989E-02	2.079414E-02
9	G	1.269318E-02	2.630559E-02	4.142821E-01	-1.251604E-01	4.857596E-02	1.094887E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -750 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.301694E-03	1.051968E-06	4.047126E-01	1.554748E-04	9.899118E-02	-8.914236E-07
2	G	1.266602E-02	2.722661E-02	4.769254E-01	-2.325378E-01	-2.546217E-02	1.751914E-02
3	G	1.623238E-02	3.273322E-02	4.742009E-01	-1.750391E-01	3.270940E-02	3.040532E-03
4	G	1.877963E-02	3.047713E-02	4.167252E-01	-1.341081E-01	1.433044E-01	-1.065293E-02
5	G	1.687166E-02	2.313346E-02	3.147309E-01	-7.797018E-02	1.235855E-01	-8.059684E-03
6	G	1.076883E-02	1.296582E-02	1.772316E-01	-1.269525E-01	3.188616E-01	-2.545860E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.102313E-02	2.406329E-02	4.521559E-01	-1.715735E-01	-5.419827E-02	2.300931E-02
9	G	1.407779E-02	2.912589E-02	4.363515E-01	-1.315861E-01	5.102593E-02	1.236729E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -750 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.050928E-03	1.260999E-06	4.236126E-01	1.918669E-04	1.132133E-01	2.329755E-07
2	G	1.383056E-02	2.973785E-02	4.988399E-01	-2.436330E-01	-2.660474E-02	1.913578E-02
3	G	1.775281E-02	3.575706E-02	4.959517E-01	-1.832761E-01	3.424027E-02	3.324477E-03
4	G	2.055031E-02	3.329301E-02	4.358301E-01	-1.403659E-01	1.498809E-01	-1.166052E-02
5	G	1.846305E-02	2.526193E-02	3.291108E-01	-8.094852E-02	1.293949E-01	-8.835920E-03
6	G	1.180021E-02	1.405063E-02	1.853812E-01	-1.331382E-01	3.328848E-01	-2.785947E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.204299E-02	2.627437E-02	4.729307E-01	-1.793202E-01	-5.641090E-02	2.511258E-02
9	G	1.539457E-02	3.181338E-02	4.563740E-01	-1.373856E-01	5.322288E-02	1.377970E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -750 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.764709E-03	1.479826E-06	4.409959E-01	2.306101E-04	1.267978E-01	1.764522E-06
2	G	1.494342E-02	3.214274E-02	5.189583E-01	-2.537659E-01	-2.761899E-02	2.068287E-02
3	G	1.920764E-02	3.865492E-02	5.159195E-01	-1.908147E-01	3.562971E-02	3.600499E-03
4	G	2.224636E-02	3.599329E-02	4.533726E-01	-1.460902E-01	1.559102E-01	-1.262507E-02
5	G	1.998870E-02	2.730417E-02	3.423207E-01	-8.370031E-02	1.347285E-01	-9.581261E-03
6	G	1.279019E-02	1.518836E-02	1.928708E-01	-1.388733E-01	3.457217E-01	-3.017129E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.301708E-02	2.839257E-02	4.920112E-01	-1.864130E-01	-5.839154E-02	2.712116E-02
9	G	1.665457E-02	3.438983E-02	4.747635E-01	-1.426850E-01	5.521788E-02	1.518979E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -750 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.044804E-02	1.707791E-06	4.571365E-01	2.715314E-04	1.398052E-01	3.716095E-06
2	G	1.601203E-02	3.445666E-02	5.376045E-01	-2.631093E-01	-2.852386E-02	2.216931E-02
3	G	2.060634E-02	4.144504E-02	5.344254E-01	-1.977790E-01	3.690212E-02	3.870222E-03
4	G	2.387862E-02	3.859486E-02	4.696342E-01	-1.513777E-01	1.614915E-01	-1.355278E-02
5	G	2.145821E-02	2.927283E-02	3.545712E-01	-8.626554E-02	1.396720E-01	-1.030018E-02
6	G	1.374482E-02	1.628591E-02	1.998189E-01	-1.442381E-01	3.575860E-01	-3.240745E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.395194E-02	3.043141E-02	5.097030E-01	-1.929693E-01	-6.017932E-02	2.904794E-02
9	G	1.786597E-02	3.687148E-02	4.918145E-01	-1.475740E-01	5.704737E-02	1.659990E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, -800 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.274634E-03	7.612573E-08	2.048162E-01	5.148670E-06	-2.418904E-03	-5.467502E-07
2	G	3.411162E-03	7.535812E-03	2.433703E-01	-1.130074E-01	-1.304096E-02	4.980474E-03
3	G	4.229523E-03	9.093167E-03	2.425659E-01	-8.780509E-02	1.572328E-02	9.021625E-04
4	G	4.862542E-03	8.514048E-03	2.134928E-01	-6.681153E-02	7.292970E-02	-2.769299E-03
5	G	4.401190E-03	6.573945E-03	1.622443E-01	-4.762139E-02	6.110731E-02	-2.031520E-03
6	G	2.744701E-03	3.694980E-03	9.111045E-02	-6.575089E-02	1.678804E-01	-7.104478E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.910909E-03	6.720882E-03	2.310326E-01	-8.858611E-02	-2.902829E-02	6.421582E-03
9	G	3.670756E-03	8.116199E-03	2.232785E-01	-6.898540E-02	2.641367E-02	3.297512E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -800 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.631270E-03	1.934207E-07	2.621442E-01	1.912171E-05	1.602782E-02	-1.207310E-06
2	G	5.478656E-03	1.189354E-02	3.105802E-01	-1.472196E-01	-1.631265E-02	7.709634E-03
3	G	6.891882E-03	1.431666E-02	3.091659E-01	-1.123821E-01	2.058046E-02	1.383380E-03
4	G	7.940378E-03	1.336497E-02	2.719041E-01	-8.617951E-02	9.325738E-02	-4.504980E-03
5	G	7.156210E-03	1.022945E-02	2.059836E-01	-5.607485E-02	7.917393E-02	-3.350560E-03
6	G	4.507235E-03	5.713919E-03	1.157658E-01	-8.255049E-02	2.115466E-01	-1.110723E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.719832E-03	1.056755E-02	2.946618E-01	-1.124280E-01	-3.641743E-02	1.010225E-02
9	G	5.983042E-03	1.276604E-02	2.845880E-01	-8.704510E-02	3.373874E-02	4.985234E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -800 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.757872E-03	3.324121E-07	3.020204E-01	3.865983E-05	3.435354E-02	-1.729629E-06
2	G	7.200258E-03	1.555127E-02	3.572836E-01	-1.713745E-01	-1.882023E-02	1.002029E-02
3	G	9.119511E-03	1.870384E-02	3.554921E-01	-1.299724E-01	2.397433E-02	1.780409E-03
4	G	1.051955E-02	1.743813E-02	3.125418E-01	-9.975559E-02	1.073887E-01	-5.972430E-03
5	G	9.465025E-03	1.329952E-02	2.364619E-01	-6.210705E-02	9.162544E-02	-4.461190E-03
6	G	5.990313E-03	7.413279E-03	1.329790E-01	-9.473679E-02	2.418630E-01	-1.449586E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.229363E-03	1.378794E-02	3.388481E-01	-1.291268E-01	-4.154494E-02	1.318742E-02
9	G	7.914351E-03	1.666275E-02	3.271635E-01	-9.966506E-02	3.870997E-02	6.541596E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -800 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.754476E-03	4.933397E-07	3.336573E-01	6.294475E-05	5.183679E-02	-2.004261E-06
2	G	8.728424E-03	1.881293E-02	3.942655E-01	-1.905118E-01	-2.087378E-02	1.209702E-02
3	G	1.110232E-02	2.261896E-02	3.921882E-01	-1.440090E-01	2.666487E-02	2.133132E-03
4	G	1.281814E-02	2.107418E-02	3.447376E-01	-1.104818E-01	1.185601E-01	-7.283117E-03
5	G	1.152377E-02	1.604141E-02	2.606317E-01	-6.694853E-02	1.014593E-01	-5.455812E-03
6	G	7.316152E-03	8.933356E-03	1.466433E-01	-1.046058E-01	2.657999E-01	-1.753827E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.569914E-03	1.665734E-02	3.738421E-01	-1.423485E-01	-4.556281E-02	1.593696E-02
9	G	9.632209E-03	2.013826E-02	3.608828E-01	-1.096321E-01	4.258485E-02	8.034436E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -800 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.662933E-03	6.671924E-07	3.603269E-01	9.075963E-05	6.840651E-02	-1.979684E-06
2	G	1.012660E-02	2.180564E-02	4.253710E-01	-2.064979E-01	-2.260019E-02	1.401358E-02
3	G	1.291957E-02	2.621432E-02	4.230569E-01	-1.557726E-01	2.890811E-02	2.459622E-03
4	G	1.492737E-02	2.441568E-02	3.718307E-01	-1.194609E-01	1.279355E-01	-8.485480E-03
5	G	1.341448E-02	1.856271E-02	2.809876E-01	-7.106721E-02	1.097217E-01	-6.372127E-03
6	G	8.536191E-03	1.033289E-02	1.581599E-01	-1.130483E-01	2.858752E-01	-2.034896E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.795971E-03	1.929045E-02	4.032920E-01	-1.534230E-01	-4.890289E-02	1.845899E-02
9	G	1.120639E-02	2.333084E-02	3.892636E-01	-1.179731E-01	4.580985E-02	9.485795E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -800 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.505862E-03	8.540407E-07	3.836171E-01	1.217668E-04	8.411674E-02	-1.613542E-06
2	G	1.142835E-02	2.459954E-02	4.524786E-01	-2.203556E-01	-2.408736E-02	1.580864E-02
3	G	1.461429E-02	2.957350E-02	4.499601E-01	-1.660050E-01	3.084708E-02	2.767518E-03
4	G	1.689668E-02	2.753972E-02	3.954495E-01	-1.272539E-01	1.360905E-01	-9.607619E-03
5	G	1.518128E-02	2.092133E-02	2.987447E-01	-7.469101E-02	1.169189E-01	-7.230572E-03
6	G	9.678156E-03	1.164350E-02	1.682123E-01	-1.205083E-01	3.033170E-01	-2.298934E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.937057E-03	2.174902E-02	4.289684E-01	-1.630481E-01	-5.176082E-02	2.080989E-02
9	G	1.267424E-02	2.631442E-02	4.140091E-01	-1.252080E-01	4.858772E-02	1.091574E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -800 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.297229E-03	1.052523E-06	4.044329E-01	1.556092E-04	9.904426E-02	-8.775427E-07
2	G	1.265448E-02	2.723761E-02	4.766580E-01	-2.326508E-01	-2.538610E-02	1.750619E-02
3	G	1.621294E-02	3.274774E-02	4.739577E-01	-1.751101E-01	3.255991E-02	3.061874E-03
4	G	1.875645E-02	3.049370E-02	4.165226E-01	-1.341780E-01	1.433523E-01	-1.066674E-02
5	G	1.685126E-02	2.315287E-02	3.145970E-01	-7.795038E-02	1.233374E-01	-8.043693E-03
6	G	1.075912E-02	1.288467E-02	1.771908E-01	-1.272433E-01	3.188281E-01	-2.549729E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.101138E-02	2.407103E-02	4.518813E-01	-1.716110E-01	-5.425603E-02	2.302498E-02
9	G	1.405881E-02	2.913459E-02	4.360918E-01	-1.316311E-01	5.103730E-02	1.233398E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -800 DEG SUBCASE 80
LOAD STEP = 9.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.046434E-03	1.261610E-06	4.233448E-01	1.920155E-04	1.132651E-01	2.494212E-07
2	G	1.381897E-02	2.974874E-02	4.985836E-01	-2.437416E-01	-2.653106E-02	1.912251E-02
3	G	1.773333E-02	3.577146E-02	4.957186E-01	-1.833436E-01	3.409643E-02	3.345995E-03
4	G	2.052707E-02	3.330946E-02	4.356359E-01	-1.404334E-01	1.499274E-01	-1.167446E-02
5	G	1.844260E-02	2.528122E-02	3.289823E-01	-8.092768E-02	1.291571E-01	-8.819915E-03
6	G	1.179052E-02	1.406945E-02	1.853421E-01	-1.334176E-01	3.328522E-01	-2.789815E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.203121E-02	2.628202E-02	4.726678E-01	-1.793557E-01	-5.646595E-02	2.512818E-02
9	G	1.537556E-02	3.182197E-02	4.561252E-01	-1.374284E-01	5.323386E-02	1.374636E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -800 DEG SUBCASE 90
LOAD STEP = 1.00000E+01

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.760186E-03	1.480491E-06	4.407383E-01	2.307722E-04	1.268482E-01	1.783620E-06
2	G	1.493179E-02	3.215354E-02	5.187113E-01	-2.538706E-01	-2.754742E-02	2.066934E-02
3	G	1.918812E-02	3.866920E-02	5.156949E-01	-1.908792E-01	3.549075E-02	3.622160E-03
4	G	2.222309E-02	3.600964E-02	4.531855E-01	-1.461558E-01	1.559554E-01	-1.263910E-02
5	G	1.996819E-02	2.732336E-02	3.421967E-01	-8.367875E-02	1.344994E-01	-9.565242E-03
6	G	1.278051E-02	1.520714E-02	1.928331E-01	-1.391428E-01	3.456899E-01	-3.020995E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.300527E-02	2.840013E-02	4.917579E-01	-1.864468E-01	-5.844425E-02	2.713667E-02
9	G	1.663552E-02	3.439832E-02	4.745239E-01	-1.427259E-01	5.522846E-02	1.515650E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 8, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, -800 DEG SUBCASE 101
LOAD STEP = 1.10000E+01

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.044349E-02	1.708509E-06	4.568875E-01	2.717064E-04	1.398544E-01	3.737921E-06
2	G	1.600036E-02	3.446737E-02	5.373657E-01	-2.632107E-01	-2.845417E-02	2.215558E-02
3	G	2.058678E-02	4.145921E-02	5.342081E-01	-1.978409E-01	3.676742E-02	3.892002E-03
4	G	2.385531E-02	3.861111E-02	4.694531E-01	-1.514413E-01	1.615356E-01	-1.356688E-02
5	G	2.143765E-02	2.929192E-02	3.544510E-01	-8.624348E-02	1.394505E-01	-1.028414E-02
6	G	1.373514E-02	1.630466E-02	1.997824E-01	-1.444991E-01	3.575548E-01	-3.244608E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.394010E-02	3.043889E-02	5.094581E-01	-1.930016E-01	-6.022996E-02	2.906337E-02
9	G	1.784690E-02	3.687988E-02	4.915828E-01	-1.476133E-01	5.705757E-02	1.656674E-03

ONE TENTH, -850 DEG SUBCASE 10
LOAD STEP = 2.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.270442E-03	7.627559E-08	2.042809E-01	5.174657E-06	-2.365638E-03	-5.453617E-07
2	G	3.400191E-03	7.548475E-03	2.428637E-01	-1.131925E-01	-1.294472E-02	4.975366E-03
3	G	4.210559E-03	9.109799E-03	2.421077E-01	-8.796486E-02	1.548423E-02	9.189713E-04
4	G	4.839766E-03	8.532519E-03	2.131094E-01	-6.690789E-02	7.297698E-02	-2.779592E-03
5	G	4.381250E-03	6.595381E-03	1.619977E-01	-4.766401E-02	6.066730E-02	-2.015819E-03
6	G	2.733972E-03	3.714354E-03	9.102726E-02	-6.624407E-02	1.678160E-01	-7.142470E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	2.899497E-03	6.730330E-03	2.305119E-01	-8.867331E-02	-2.912490E-02	6.437106E-03
9	G	3.652162E-03	8.126861E-03	2.227851E-01	-6.907176E-02	2.641450E-02	3.278067E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, -850 DEG SUBCASE 20
LOAD STEP = 3.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.627000E-03	1.940123E-07	2.617203E-01	1.917093E-05	1.608459E-02	-1.202626E-06
2	G	5.467513E-03	1.190541E-02	3.101772E-01	-1.473705E-01	-1.621710E-02	7.701037E-03
3	G	6.872741E-03	1.433231E-02	3.088004E-01	-1.124922E-01	2.037250E-02	1.402337E-03
4	G	7.917467E-03	1.338263E-02	2.715994E-01	-8.626711E-02	9.331074E-02	-4.516703E-03
5	G	7.136182E-03	1.025004E-02	2.057859E-01	-5.608220E-02	7.881123E-02	-3.334720E-03
6	G	4.497047E-03	5.733081E-03	1.157025E-01	-8.296502E-02	2.114981E-01	-1.114562E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.708305E-03	1.057628E-02	2.942485E-01	-1.124885E-01	-3.650242E-02	1.011820E-02
9	G	5.964329E-03	1.277590E-02	2.841969E-01	-8.711286E-02	3.374923E-02	4.957663E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, -850 DEG SUBCASE 30
LOAD STEP = 4.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.753550E-03	3.374733E-07	3.016502E-01	3.910557E-05	3.441067E-02	-1.717992E-06
2	G	7.189105E-03	1.556255E-02	3.569290E-01	-1.714908E-01	-1.872591E-02	1.001012E-02
3	G	9.100223E-03	1.871882E-02	3.551697E-01	-1.300438E-01	2.378175E-02	1.800718E-03
4	G	1.049651E-02	1.745538E-02	3.122745E-01	-9.983449E-02	1.074404E-01	-5.984700E-03
5	G	9.444899E-03	1.331971E-02	2.362879E-01	-6.210179E-02	9.130295E-02	-4.445244E-03
6	G	5.980339E-03	7.432348E-03	1.329245E-01	-9.510867E-02	2.418211E-01	-1.453455E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.217757E-03	1.379632E-02	3.384867E-01	-1.291674E-01	-4.162553E-02	1.320374E-02
9	G	7.895600E-03	1.667230E-02	3.268225E-01	-9.972121E-02	3.872508E-02	6.509271E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, -850 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.750115E-03	4.937203E-07	3.333208E-01	6.303169E-05	5.189360E-02	-1.997364E-06
2	G	8.717060E-03	1.882435E-02	3.939449E-01	-1.906433E-01	-2.078827E-02	1.208571E-02
3	G	1.108304E-02	2.263402E-02	3.918971E-01	-1.440965E-01	2.649054E-02	2.153553E-03
4	G	1.279510E-02	2.109125E-02	3.444951E-01	-1.105609E-01	1.186124E-01	-7.296201E-03
5	G	1.150357E-02	1.606133E-02	2.604726E-01	-6.693634E-02	1.011644E-01	-5.439894E-03
6	G	7.306284E-03	8.952356E-03	1.465940E-01	-1.049479E-01	2.657611E-01	-1.757691E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.558282E-03	1.666553E-02	3.735130E-01	-1.423956E-01	-4.563219E-02	1.595284E-02
9	G	9.613358E-03	2.014747E-02	3.605712E-01	-1.096869E-01	4.259691E-02	8.002642E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, -850 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.658534E-03	6.676315E-07	3.600144E-01	9.086364E-05	6.846229E-02	-1.970599E-06
2	G	1.011517E-02	2.181691E-02	4.250728E-01	-2.066221E-01	-2.251842E-02	1.400158E-02
3	G	1.290023E-02	2.622919E-02	4.227861E-01	-1.558532E-01	2.874400E-02	2.480438E-03
4	G	1.490428E-02	2.443257E-02	3.716050E-01	-1.195365E-01	1.279863E-01	-8.498894E-03
5	G	1.339420E-02	1.858244E-02	2.808391E-01	-7.105130E-02	1.094464E-01	-6.356189E-03
6	G	8.526389E-03	1.035184E-02	1.581143E-01	-1.133691E-01	2.858386E-01	-2.038764E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.784299E-03	1.929847E-02	4.029859E-01	-1.534661E-01	-4.896751E-02	1.847482E-02
9	G	1.118749E-02	2.333986E-02	3.889739E-01	-1.180239E-01	4.582176E-02	9.453209E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, -850 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.501429E-03	8.545401E-07	3.833228E-01	1.218867E-04	8.417130E-02	-1.602109E-06
2	G	1.141686E-02	2.461068E-02	4.521975E-01	-2.204738E-01	-2.400875E-02	1.579612E-02
3	G	1.459490E-02	2.958820E-02	4.497046E-01	-1.660804E-01	3.069106E-02	2.788624E-03
4	G	1.687354E-02	2.755645E-02	3.952366E-01	-1.273265E-01	1.361397E-01	-9.621264E-03
5	G	1.516093E-02	2.094090E-02	2.986044E-01	-7.467280E-02	1.166587E-01	-7.214619E-03
6	G	9.668398E-03	1.166240E-02	1.681693E-01	-1.208123E-01	3.032821E-01	-2.302803E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.925348E-03	2.175690E-02	4.286798E-01	-1.630881E-01	-5.182164E-02	2.082565E-02
9	G	1.265530E-02	2.632328E-02	4.137360E-01	-1.252557E-01	4.859934E-02	1.088273E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, -850 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.292765E-03	1.053080E-06	4.041531E-01	1.557440E-04	9.909748E-02	-8.636430E-07
2	G	1.264294E-02	2.724863E-02	4.763904E-01	-2.327639E-01	-2.531020E-02	1.749328E-02
3	G	1.619351E-02	3.276230E-02	4.737146E-01	-1.751812E-01	3.241057E-02	3.083204E-03
4	G	1.873326E-02	3.051031E-02	4.163200E-01	-1.342480E-01	1.434000E-01	-1.068055E-02
5	G	1.683086E-02	2.317230E-02	3.144631E-01	-7.793064E-02	1.230895E-01	-8.027723E-03
6	G	1.074939E-02	1.290353E-02	1.771500E-01	-1.275337E-01	3.187944E-01	-2.553598E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.099964E-02	2.407880E-02	4.516068E-01	-1.716487E-01	-5.431368E-02	2.304066E-02
9	G	1.403983E-02	2.914333E-02	4.358320E-01	-1.316762E-01	5.104855E-02	1.230079E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, -850 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.041940E-03	1.262223E-06	4.230770E-01	1.921645E-04	1.133170E-01	2.658888E-07
2	G	1.380739E-02	2.975966E-02	4.983272E-01	-2.438504E-01	-2.645754E-02	1.910928E-02
3	G	1.771385E-02	3.578589E-02	4.954855E-01	-1.834113E-01	3.395272E-02	3.367502E-03
4	G	2.050385E-02	3.332594E-02	4.354417E-01	-1.405011E-01	1.499738E-01	-1.168840E-02
5	G	1.842214E-02	2.530053E-02	3.288537E-01	-8.090691E-02	1.289194E-01	-8.803930E-03
6	G	1.178081E-02	1.408828E-02	1.853030E-01	-1.336966E-01	3.328195E-01	-2.793683E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.201943E-02	2.628968E-02	4.724047E-01	-1.793913E-01	-5.652091E-02	2.514378E-02
9	G	1.535654E-02	3.183059E-02	4.558763E-01	-1.374713E-01	5.324472E-02	1.371312E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 7, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, -850 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.755664E-03	1.481158E-06	4.404806E-01	2.309346E-04	1.268988E-01	1.802742E-06
2	G	1.492017E-02	3.216437E-02	5.184644E-01	-2.539755E-01	-2.747598E-02	2.065585E-02
3	G	1.916861E-02	3.868351E-02	5.154703E-01	-1.909439E-01	3.535190E-02	3.643811E-03
4	G	2.219982E-02	3.602602E-02	4.529983E-01	-1.462213E-01	1.560005E-01	-1.265313E-02
5	G	1.994768E-02	2.734256E-02	3.420726E-01	-8.365725E-02	1.342705E-01	-9.549242E-03
6	G	1.277081E-02	1.522594E-02	1.927954E-01	-1.394121E-01	3.456579E-01	-3.024861E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.299347E-02	2.840770E-02	4.915046E-01	-1.864807E-01	-5.849687E-02	2.715218E-02
9	G	1.661647E-02	3.440684E-02	4.742842E-01	-1.427669E-01	5.523895E-02	1.512332E-03

ONE, -850 DEG SUBCASE 101
LOAD STEP = 1.10000E+01

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.043894E-02	1.709229E-06	4.566384E-01	2.718818E-04	1.399036E-01	3.759774E-06
2	G	1.598870E-02	3.447810E-02	5.371268E-01	-2.633121E-01	-2.838461E-02	2.214186E-02
3	G	2.056723E-02	4.147341E-02	5.339908E-01	-1.979031E-01	3.663283E-02	3.913772E-03
4	G	2.383200E-02	3.862739E-02	4.692720E-01	-1.515050E-01	1.615795E-01	-1.358099E-02
5	G	2.141709E-02	2.931103E-02	3.543308E-01	-8.622146E-02	1.392292E-01	-1.026813E-02
6	G	1.372545E-02	1.632342E-02	1.997459E-01	-1.447599E-01	3.575235E-01	-3.248471E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.392827E-02	3.044638E-02	5.092131E-01	-1.930341E-01	-6.028054E-02	2.907880E-02
9	G	1.782782E-02	3.688830E-02	4.913510E-01	-1.476525E-01	5.706769E-02	1.653368E-03

ONE TENTH, ZERO DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.341992E-03	7.401508E-08	2.133318E-01	4.767032E-06	-3.194503E-03	-5.698712E-07
2	G	3.587988E-03	7.349566E-03	2.514677E-01	-1.103176E-01	-1.476892E-02	5.080811E-03
3	G	4.534828E-03	8.846126E-03	2.499020E-01	-8.563810E-02	1.971927E-02	6.239635E-04
4	G	5.228249E-03	8.234358E-03	2.196153E-01	-6.538023E-02	7.205004E-02	-2.608204E-03
5	G	4.716984E-03	6.243060E-03	1.661580E-01	-4.700415E-02	6.834459E-02	-2.289620E-03
6	G	2.905966E-03	3.391708E-03	9.238727E-02	-5.754874E-02	1.687762E-01	-6.500938E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.094946E-03	6.582240E-03	2.393183E-01	-8.740198E-02	-2.736874E-02	6.174818E-03
9	G	3.969544E-03	7.959296E-03	2.311131E-01	-6.769782E-02	2.627526E-02	3.668207E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, ZERO DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.699800E-03	1.900756E-07	2.688976E-01	1.839473E-05	1.517781E-02	-1.255206E-06
2	G	5.657619E-03	1.171388E-02	3.170216E-01	-1.449520E-01	-1.793619E-02	7.857751E-03
3	G	7.199376E-03	1.407835E-02	3.150148E-01	-1.108159E-01	2.398902E-02	1.075015E-03
4	G	8.308156E-03	1.309270E-02	2.767770E-01	-8.485006E-02	9.233310E-02	-4.319508E-03
5	G	7.475621E-03	9.907982E-03	2.091379E-01	-5.601881E-02	8.507415E-02	-3.609077E-03
6	G	4.664267E-03	5.411784E-03	1.167564E-01	-7.577603E-02	2.122634E-01	-1.049676E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.905153E-03	1.043558E-02	3.012488E-01	-1.115717E-01	-3.500446E-02	9.848427E-03
9	G	6.283277E-03	1.261670E-02	2.908130E-01	-8.601391E-02	3.350478E-02	5.465528E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, ZERO DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.827071E-03	3.296506E-07	3.079243E-01	3.776644E-05	3.347854E-02	-1.804291E-06
2	G	7.381059E-03	1.537338E-02	3.629159E-01	-1.692394E-01	-2.032832E-02	1.019281E-02
3	G	9.427924E-03	1.846821E-02	3.606077E-01	-1.285687E-01	2.704221E-02	1.458444E-03
4	G	1.088789E-02	1.716879E-02	3.168018E-01	-9.846851E-02	1.064855E-01	-5.772921E-03
5	G	9.785834E-03	1.298225E-02	2.392366E-01	-6.223028E-02	9.684050E-02	-4.719901E-03
6	G	6.145012E-03	7.111489E-03	1.338336E-01	-8.868869E-02	2.424940E-01	-1.388027E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.415361E-03	1.365929E-02	3.446157E-01	-1.283657E-01	-4.029152E-02	1.293319E-02
9	G	8.215570E-03	1.651759E-02	3.326161E-01	-9.873720E-02	3.847246E-02	7.060374E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, ZERO DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.824279E-03	4.875732E-07	3.390261E-01	6.160066E-05	5.096036E-02	-2.113337E-06
2	G	8.910754E-03	1.863601E-02	3.993870E-01	-1.884515E-01	-2.228624E-02	1.228464E-02
3	G	1.141145E-02	2.238498E-02	3.968402E-01	-1.426764E-01	2.949344E-02	1.803628E-03
4	G	1.318708E-02	2.080704E-02	3.486135E-01	-1.092386E-01	1.176858E-01	-7.074701E-03
5	G	1.184594E-02	1.572718E-02	2.631682E-01	-6.716432E-02	1.062277E-01	-5.714348E-03
6	G	7.469765E-03	8.631983E-03	1.474169E-01	-9.904365E-02	2.663847E-01	-1.692065E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.756472E-03	1.653108E-02	3.790943E-01	-1.416347E-01	-4.442729E-02	1.568392E-02
9	G	9.934303E-03	1.999619E-02	3.658510E-01	-1.087726E-01	4.236004E-02	8.567687E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, ZERO DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.733309E-03	6.604511E-07	3.653156E-01	8.914154E-05	6.754070E-02	-2.123406E-06
2	G	1.030995E-02	2.163025E-02	4.301342E-01	-2.045407E-01	-2.394332E-02	1.421139E-02
3	G	1.322947E-02	2.598237E-02	4.273852E-01	-1.545321E-01	3.156491E-02	2.124286E-03
4	G	1.529706E-02	2.415056E-02	3.754366E-01	-1.182674E-01	1.270934E-01	-8.271642E-03
5	G	1.373792E-02	1.825094E-02	2.833554E-01	-7.133682E-02	1.141674E-01	-6.630572E-03
6	G	8.689254E-03	1.003195E-02	1.588780E-01	-1.078429E-01	2.864297E-01	-1.973036E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.983096E-03	1.916613E-02	4.081779E-01	-1.527627E-01	-4.784866E-02	1.820671E-02
9	G	1.150918E-02	2.319106E-02	3.938858E-01	-1.171724E-01	4.559385E-02	1.002825E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, ZERO DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.576771E-03	8.463200E-07	3.883161E-01	1.198958E-04	8.326672E-02	-1.794408E-06
2	G	1.161256E-02	2.442559E-02	4.569698E-01	-2.184867E-01	-2.537364E-02	1.601396E-02
3	G	1.492490E-02	2.934340E-02	4.540426E-01	-1.648382E-01	3.336866E-02	2.427868E-03
4	G	1.726710E-02	2.727639E-02	3.988505E-01	-1.261049E-01	1.352782E-01	-9.389993E-03
5	G	1.550585E-02	2.061162E-02	3.009839E-01	-7.499430E-02	1.211151E-01	-7.488977E-03
6	G	9.830929E-03	1.134300E-02	1.688890E-01	-1.155808E-01	3.038500E-01	-2.237032E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.012471E-02	2.162636E-02	4.335753E-01	-1.624303E-01	-5.077100E-02	2.055860E-02
9	G	1.297765E-02	2.617656E-02	4.183674E-01	-1.244550E-01	4.838090E-02	1.146241E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, ZERO DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.368637E-03	1.043875E-06	4.089008E-01	1.534995E-04	9.821242E-02	-1.097446E-06
2	G	1.283945E-02	2.706503E-02	4.809326E-01	-2.308585E-01	-2.662448E-02	1.771732E-02
3	G	1.652423E-02	3.251937E-02	4.778447E-01	-1.740040E-01	3.497084E-02	2.718891E-03
4	G	1.912758E-02	3.023202E-02	4.197606E-01	-1.330689E-01	1.425671E-01	-1.044636E-02
5	G	1.717687E-02	2.284497E-02	3.167335E-01	-7.827581E-02	1.273323E-01	-8.302107E-03
6	G	1.091176E-02	1.258460E-02	1.778352E-01	-1.225415E-01	3.193446E-01	-2.487816E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.119955E-02	2.394984E-02	4.562658E-01	-1.710281E-01	-5.331921E-02	2.277482E-02
9	G	1.436278E-02	2.899843E-02	4.402396E-01	-1.309180E-01	5.083937E-02	1.288188E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, ZERO DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.118314E-03	1.252067E-06	4.276222E-01	1.896795E-04	1.124524E-01	-1.115805E-08
2	G	1.400462E-02	2.957748E-02	5.026800E-01	-2.420164E-01	-2.772826E-02	1.933831E-02
3	G	1.804524E-02	3.554473E-02	4.994448E-01	-1.822887E-01	3.641428E-02	3.000361E-03
4	G	2.089888E-02	3.304930E-02	4.387399E-01	-1.393600E-01	1.491668E-01	-1.145202E-02
5	G	1.876916E-02	2.497493E-02	3.310342E-01	-8.126815E-02	1.329847E-01	-9.078379E-03
6	G	1.194312E-02	1.376981E-02	1.859604E-01	-1.289042E-01	3.333558E-01	-2.727912E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.221985E-02	2.616216E-02	4.768688E-01	-1.788021E-01	-5.557397E-02	2.487925E-02
9	G	1.568006E-02	3.168732E-02	4.600995E-01	-1.367493E-01	5.304433E-02	1.429357E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, ZERO DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.832514E-03	1.470081E-06	4.448548E-01	2.282205E-04	1.260549E-01	1.480952E-06
2	G	1.511807E-02	3.198354E-02	5.226576E-01	-2.522050E-01	-2.870859E-02	2.088898E-02
3	G	1.950064E-02	3.844401E-02	5.192854E-01	-1.898682E-01	3.772863E-02	3.274368E-03
4	G	2.259555E-02	3.575092E-02	4.561765E-01	-1.451146E-01	1.552172E-01	-1.241510E-02
5	G	2.029565E-02	2.701854E-02	3.441771E-01	-8.402963E-02	1.381845E-01	-9.823789E-03
6	G	1.293314E-02	1.490792E-02	1.934295E-01	-1.347904E-01	3.461829E-01	-2.959114E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.319438E-02	2.828150E-02	4.958042E-01	-1.859184E-01	-5.759095E-02	2.688901E-02
9	G	1.694051E-02	3.426507E-02	4.783516E-01	-1.420764E-01	5.504677E-02	1.570176E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, ZERO DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.051625E-02	1.697254E-06	4.608655E-01	2.689482E-04	1.390801E-01	3.391936E-06
2	G	1.618723E-02	3.429857E-02	5.411828E-01	-2.615984E-01	-2.958344E-02	2.237843E-02
3	G	2.089988E-02	4.123551E-02	5.376822E-01	-1.968684E-01	3.893548E-02	3.542423E-03
4	G	2.422840E-02	3.835374E-02	4.723471E-01	-1.504295E-01	1.608177E-01	-1.334169E-02
5	G	2.176594E-02	2.898846E-02	3.563698E-01	-8.660164E-02	1.430123E-01	-1.054280E-02
6	G	1.388785E-02	1.600586E-02	2.003604E-01	-1.402865E-01	3.580391E-01	-3.182759E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.412965E-02	3.032140E-02	5.133712E-01	-1.924952E-01	-5.941056E-02	2.881701E-02
9	G	1.815236E-02	3.674791E-02	4.952843E-01	-1.469900E-01	5.688317E-02	1.710918E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

ONE TENTH, 50 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.344982E-03	7.372912E-08	2.138460E-01	4.721140E-06	-3.269909E-03	-5.707928E-07
2	G	3.600940E-03	7.329270E-03	2.518731E-01	-1.095916E-01	-1.478822E-02	5.089241E-03
3	G	4.550870E-03	8.820355E-03	2.502274E-01	-8.485451E-02	1.994637E-02	6.103521E-04
4	G	5.245470E-03	8.210093E-03	2.198898E-01	-6.494360E-02	7.192380E-02	-2.587451E-03
5	G	4.730938E-03	6.218150E-03	1.663262E-01	-4.676238E-02	6.877638E-02	-2.306383E-03
6	G	2.912157E-03	3.371158E-03	9.242661E-02	-5.688357E-02	1.687386E-01	-6.452031E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.105605E-03	6.570819E-03	2.397963E-01	-8.697853E-02	-2.729649E-02	6.163362E-03
9	G	3.987649E-03	7.948643E-03	2.315908E-01	-6.738293E-02	2.630314E-02	3.687229E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

TWO TENTHS, 50 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.703974E-03	1.895745E-07	2.693188E-01	1.833968E-05	1.512457E-02	-1.259003E-06
2	G	5.669242E-03	1.170201E-02	3.174151E-01	-1.447326E-01	-1.803124E-02	7.868384E-03
3	G	7.218304E-03	1.406285E-02	3.153686E-01	-1.106389E-01	2.419892E-02	1.056592E-03
4	G	8.330598E-03	1.307564E-02	2.770733E-01	-8.474120E-02	9.226575E-02	-4.306667E-03
5	G	7.494790E-03	9.887892E-03	2.093277E-01	-5.600226E-02	8.545002E-02	-3.625840E-03
6	G	4.673128E-03	5.392959E-03	1.168124E-01	-7.532460E-02	2.122953E-01	-1.045714E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.916652E-03	1.042766E-02	3.016593E-01	-1.114795E-01	-3.492519E-02	9.834217E-03
9	G	6.302128E-03	1.260809E-02	2.912040E-01	-8.593208E-02	3.349661E-02	5.492606E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

THREE TENTHS, 50 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.831350E-03	3.293509E-07	3.082924E-01	3.769924E-05	3.342521E-02	-1.809064E-06
2	G	7.392572E-03	1.536215E-02	3.632641E-01	-1.690759E-01	-2.042136E-02	1.020441E-02
3	G	9.447088E-03	1.845342E-02	3.609227E-01	-1.284512E-01	2.723373E-02	1.438638E-03
4	G	1.091069E-02	1.715213E-02	3.170648E-01	-9.837919E-02	1.064240E-01	-5.759921E-03
5	G	9.805522E-03	1.296258E-02	2.394071E-01	-6.223445E-02	9.717071E-02	-4.736444E-03
6	G	6.154139E-03	7.092744E-03	1.338844E-01	-8.829744E-02	2.425276E-01	-1.384126E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.426958E-03	1.365156E-02	3.449753E-01	-1.283043E-01	-4.021651E-02	1.291812E-02
9	G	8.234454E-03	1.650901E-02	3.329572E-01	-9.867344E-02	3.845945E-02	7.091786E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FOUR TENTHS, 50 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.828626E-03	4.872697E-07	3.393608E-01	6.151665E-05	5.090738E-02	-2.119924E-06
2	G	8.922231E-03	1.862514E-02	3.997057E-01	-1.883159E-01	-2.237591E-02	1.229687E-02
3	G	1.143075E-02	2.237059E-02	3.971294E-01	-1.425875E-01	2.967170E-02	1.783026E-03
4	G	1.321007E-02	2.079063E-02	3.488545E-01	-1.091593E-01	1.176283E-01	-7.061554E-03
5	G	1.186591E-02	1.570777E-02	2.633256E-01	-6.717757E-02	1.065288E-01	-5.730771E-03
6	G	7.479027E-03	8.613285E-03	1.474639E-01	-9.868883E-02	2.664182E-01	-1.688193E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.768138E-03	1.652346E-02	3.794217E-01	-1.415879E-01	-4.435632E-02	1.566841E-02
9	G	9.953219E-03	1.998766E-02	3.661610E-01	-1.087179E-01	4.234533E-02	8.601545E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

FIVE TENTHS, 50 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.737697E-03	6.600227E-07	3.656266E-01	8.904380E-05	6.748820E-02	-2.132352E-06
2	G	1.032147E-02	2.161949E-02	4.304310E-01	-2.044148E-01	-2.402863E-02	1.422415E-02
3	G	1.324883E-02	2.596812E-02	4.276547E-01	-1.544521E-01	3.173229E-02	2.103293E-03
4	G	1.532014E-02	2.413426E-02	3.756612E-01	-1.181922E-01	1.270386E-01	-8.258222E-03
5	G	1.375802E-02	1.823166E-02	2.835026E-01	-7.135382E-02	1.144477E-01	-6.646950E-03
6	G	8.698544E-03	1.001327E-02	1.589219E-01	-1.075122E-01	2.864622E-01	-1.969164E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	8.994799E-03	1.915860E-02	4.084826E-01	-1.527206E-01	-4.778250E-02	1.819116E-02
9	G	1.152813E-02	2.318262E-02	3.941741E-01	-1.171221E-01	4.557959E-02	1.006277E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SIX TENTHS, 50 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.581194E-03	8.458436E-07	3.886092E-01	1.197820E-04	8.321504E-02	-1.805600E-06
2	G	1.162412E-02	2.441492E-02	4.572498E-01	-2.183680E-01	-2.545530E-02	1.602713E-02
3	G	1.494432E-02	2.932926E-02	4.542971E-01	-1.647644E-01	3.352745E-02	2.406591E-03
4	G	1.729024E-02	2.726018E-02	3.990625E-01	-1.260330E-01	1.352257E-01	-9.376374E-03
5	G	1.552605E-02	2.059246E-02	3.011233E-01	-7.501353E-02	1.213794E-01	-7.505327E-03
6	G	9.840242E-03	1.132434E-02	1.689306E-01	-1.152686E-01	3.038815E-01	-2.233161E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.013645E-02	2.161890E-02	4.338627E-01	-1.623916E-01	-5.070873E-02	2.054305E-02
9	G	1.299663E-02	2.616820E-02	4.186393E-01	-1.244080E-01	4.836719E-02	1.149724E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

SEVEN TENTHS, 50 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.373094E-03	1.043343E-06	4.091794E-01	1.533709E-04	9.816170E-02	-1.111037E-06
2	G	1.285104E-02	2.705444E-02	4.811992E-01	-2.307455E-01	-2.670303E-02	1.773081E-02
3	G	1.654369E-02	3.250533E-02	4.780871E-01	-1.739347E-01	3.512258E-02	2.697402E-03
4	G	1.915076E-02	3.021589E-02	4.199625E-01	-1.329996E-01	1.425166E-01	-1.043259E-02
5	G	1.719715E-02	2.282590E-02	3.168666E-01	-7.829646E-02	1.275837E-01	-8.318437E-03
6	G	1.092109E-02	1.256595E-02	1.778749E-01	-1.222441E-01	3.193755E-01	-2.483946E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.121132E-02	2.394246E-02	4.565393E-01	-1.709919E-01	-5.326021E-02	2.275931E-02
9	G	1.438179E-02	2.899014E-02	4.404984E-01	-1.308735E-01	5.082625E-02	1.291679E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

EIGHT TENTHS, 50 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.122801E-03	1.251481E-06	4.278890E-01	1.895368E-04	1.124028E-01	-2.725551E-08
2	G	1.401626E-02	2.956696E-02	5.029356E-01	-2.419081E-01	-2.780411E-02	1.935205E-02
3	G	1.806474E-02	3.553078E-02	4.996772E-01	-1.822229E-01	3.656007E-02	2.978708E-03
4	G	2.092211E-02	3.303325E-02	4.389335E-01	-1.392932E-01	1.491181E-01	-1.143814E-02
5	G	1.878951E-02	2.495595E-02	3.311620E-01	-8.128972E-02	1.332253E-01	-9.094697E-03
6	G	1.195247E-02	1.375118E-02	1.859985E-01	-1.286191E-01	3.333861E-01	-2.724044E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.223165E-02	2.615484E-02	4.771309E-01	-1.787678E-01	-5.551777E-02	2.486379E-02
9	G	1.569910E-02	3.167911E-02	4.603474E-01	-1.367071E-01	5.303178E-02	1.432841E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

NINE TENTHS, 50 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.837030E-03	1.469442E-06	4.451116E-01	2.280643E-04	1.260063E-01	1.462256E-06
2	G	1.512974E-02	3.197308E-02	5.229038E-01	-2.521006E-01	-2.878208E-02	2.090293E-02
3	G	1.952018E-02	3.843015E-02	5.195095E-01	-1.898055E-01	3.786932E-02	3.252583E-03
4	G	2.261883E-02	3.573494E-02	4.563631E-01	-1.450498E-01	1.551700E-01	-1.240113E-02
5	G	2.031605E-02	2.699964E-02	3.443005E-01	-8.405184E-02	1.384161E-01	-9.840101E-03
6	G	1.294250E-02	1.488931E-02	1.934664E-01	-1.345158E-01	3.462127E-01	-2.955249E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.320621E-02	2.827425E-02	4.960567E-01	-1.858857E-01	-5.753719E-02	2.687362E-02
9	G	1.695959E-02	3.425693E-02	4.785904E-01	-1.420361E-01	5.503477E-02	1.573644E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 265

ONE, 50 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.052079E-02	1.696563E-06	4.611138E-01	2.687792E-04	1.390327E-01	3.370562E-06
2	G	1.619893E-02	3.428819E-02	5.414210E-01	-2.614976E-01	-2.965485E-02	2.239256E-02
3	G	2.091945E-02	4.122172E-02	5.378991E-01	-1.968081E-01	3.907171E-02	3.520532E-03
4	G	2.425172E-02	3.833784E-02	4.725277E-01	-1.503665E-01	1.607720E-01	-1.332765E-02
5	G	2.178640E-02	2.896964E-02	3.564894E-01	-8.662429E-02	1.432360E-01	-1.055911E-02
6	G	1.389723E-02	1.598726E-02	2.003961E-01	-1.400209E-01	3.580684E-01	-3.178896E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.414151E-02	3.031421E-02	5.136153E-01	-1.924639E-01	-5.935894E-02	2.880169E-02
9	G	1.817147E-02	3.673984E-02	4.955153E-01	-1.469513E-01	5.687167E-02	1.714366E-03

ONE TENTH, 100 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.346308E-03	7.315836E-08	2.143476E-01	4.636918E-06	-3.391188E-03	-5.705064E-07
2	G	3.616564E-03	7.295535E-03	2.521480E-01	-1.080737E-01	-1.467426E-02	5.099681E-03
3	G	4.562809E-03	8.778515E-03	2.503752E-01	-8.314878E-02	2.013658E-02	6.022101E-04
4	G	5.255025E-03	8.174803E-03	2.200199E-01	-6.401072E-02	7.170751E-02	-2.551846E-03
5	G	4.737286E-03	6.186046E-03	1.663934E-01	-4.622937E-02	6.917207E-02	-2.323524E-03
6	G	2.913811E-03	3.347543E-03	9.241429E-02	-5.601825E-02	1.685808E-01	-6.386887E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.115156E-03	6.554442E-03	2.402304E-01	-8.605577E-02	-2.727074E-02	6.156646E-03
9	G	4.005122E-03	7.935530E-03	2.320633E-01	-6.673310E-02	2.638878E-02	3.697436E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

TWO TENTHS, 100 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.708173E-03	1.840091E-07	2.697348E-01	1.788180E-05	1.507292E-02	-1.255223E-06
2	G	5.680357E-03	1.169128E-02	3.178137E-01	-1.446105E-01	-1.814258E-02	7.878458E-03
3	G	7.237460E-03	1.404849E-02	3.157307E-01	-1.105667E-01	2.442227E-02	1.036704E-03
4	G	8.353421E-03	1.305899E-02	2.773728E-01	-8.466130E-02	9.220309E-02	-4.295149E-03
5	G	7.514353E-03	9.868060E-03	2.095197E-01	-5.599876E-02	8.582520E-02	-3.642480E-03
6	G	4.682269E-03	5.374234E-03	1.168698E-01	-7.488492E-02	2.123306E-01	-1.041886E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.928184E-03	1.041977E-02	3.020646E-01	-1.114390E-01	-3.482983E-02	9.818718E-03
9	G	6.320811E-03	1.259911E-02	2.915854E-01	-8.587228E-02	3.347580E-02	5.524671E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

THREE TENTHS, 100 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.835729E-03	3.483844E-07	3.086623E-01	3.497380E-05	3.337522E-02	-2.329401E-06
2	G	7.404882E-03	1.534977E-02	3.636039E-01	-1.688070E-01	-2.045884E-02	1.021138E-02
3	G	9.466154E-03	1.843808E-02	3.612303E-01	-1.282386E-01	2.735849E-02	1.426965E-03
4	G	1.093451E-02	1.713703E-02	3.173424E-01	-9.838071E-02	1.063695E-01	-5.751423E-03
5	G	9.826409E-03	1.294387E-02	2.395884E-01	-6.226590E-02	9.750358E-02	-4.752915E-03
6	G	6.164168E-03	7.074482E-03	1.339424E-01	-8.794532E-02	2.425731E-01	-1.380619E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.438554E-03	1.364417E-02	3.453385E-01	-1.281950E-01	-4.017808E-02	1.290656E-02
9	G	8.253767E-03	1.650107E-02	3.333047E-01	-9.860296E-02	3.848257E-02	7.094024E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

FOUR TENTHS, 100 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.832965E-03	4.869472E-07	3.396954E-01	6.143744E-05	5.085446E-02	-2.126539E-06
2	G	8.933751E-03	1.861420E-02	4.000237E-01	-1.881740E-01	-2.246493E-02	1.230921E-02
3	G	1.145002E-02	2.235614E-02	3.974178E-01	-1.424921E-01	2.984951E-02	1.762529E-03
4	G	1.323303E-02	2.077421E-02	3.490951E-01	-1.090783E-01	1.175702E-01	-7.048291E-03
5	G	1.188583E-02	1.568835E-02	2.634825E-01	-6.719013E-02	1.068303E-01	-5.747240E-03
6	G	7.488214E-03	8.594590E-03	1.475106E-01	-9.833232E-02	2.664510E-01	-1.684310E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.779792E-03	1.651586E-02	3.797491E-01	-1.415380E-01	-4.428633E-02	1.565308E-02
9	G	9.972143E-03	1.997920E-02	3.664712E-01	-1.086622E-01	4.233133E-02	8.634869E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

FIVE TENTHS, 100 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.742080E-03	6.595982E-07	3.659376E-01	8.894584E-05	6.743587E-02	-2.141277E-06
2	G	1.033300E-02	2.160871E-02	4.307275E-01	-2.042864E-01	-2.411381E-02	1.423699E-02
3	G	1.326819E-02	2.595385E-02	4.279239E-01	-1.543696E-01	3.189964E-02	2.082332E-03
4	G	1.534319E-02	2.411796E-02	3.758855E-01	-1.181162E-01	1.269835E-01	-8.244753E-03
5	G	1.377808E-02	1.821239E-02	2.836495E-01	-7.137049E-02	1.147282E-01	-6.663362E-03
6	G	8.707782E-03	9.994596E-03	1.589656E-01	-1.071804E-01	2.864941E-01	-1.965287E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.006498E-03	1.915109E-02	4.087872E-01	-1.526774E-01	-4.771665E-02	1.817569E-02
9	G	1.154708E-02	2.317423E-02	3.944625E-01	-1.170714E-01	4.556552E-02	1.009712E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

SIX TENTHS, 100 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.585615E-03	8.453646E-07	3.889022E-01	1.196685E-04	8.316352E-02	-1.816783E-06
2	G	1.163568E-02	2.440424E-02	4.575296E-01	-2.182479E-01	-2.553693E-02	1.604035E-02
3	G	1.496373E-02	2.931513E-02	4.545513E-01	-1.646891E-01	3.368625E-02	2.385333E-03
4	G	1.731335E-02	2.724398E-02	3.992743E-01	-1.259606E-01	1.351730E-01	-9.362727E-03
5	G	1.554621E-02	2.057330E-02	3.012625E-01	-7.503260E-02	1.216438E-01	-7.521703E-03
6	G	9.849513E-03	1.130568E-02	1.689720E-01	-1.149557E-01	3.039127E-01	-2.229287E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.014819E-02	2.161147E-02	4.341500E-01	-1.623522E-01	-5.064663E-02	2.052756E-02
9	G	1.301562E-02	2.615988E-02	4.189112E-01	-1.243607E-01	4.835358E-02	1.153197E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 265

SEVEN TENTHS, 100 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.377548E-03	1.042809E-06	4.094581E-01	1.532427E-04	9.811117E-02	-1.124610E-06
2	G	1.286265E-02	2.704385E-02	4.814656E-01	-2.306315E-01	-2.678158E-02	1.774433E-02
3	G	1.656314E-02	3.249130E-02	4.783294E-01	-1.738645E-01	3.527433E-02	2.675928E-03
4	G	1.917393E-02	3.019978E-02	4.201643E-01	-1.329302E-01	1.424660E-01	-1.041880E-02
5	G	1.721740E-02	2.280684E-02	3.169996E-01	-7.831702E-02	1.278352E-01	-8.334791E-03
6	G	1.093038E-02	1.254731E-02	1.779145E-01	-1.219462E-01	3.194060E-01	-2.480075E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.122308E-02	2.393509E-02	4.568128E-01	-1.709552E-01	-5.320133E-02	2.274385E-02
9	G	1.440081E-02	2.898189E-02	4.407571E-01	-1.308290E-01	5.081318E-02	1.295162E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 266

EIGHT TENTHS, 100 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.127286E-03	1.250894E-06	4.281558E-01	1.893946E-04	1.123533E-01	-4.332662E-08
2	G	1.402789E-02	2.955644E-02	5.031911E-01	-2.417991E-01	-2.787998E-02	1.936582E-02
3	G	1.808424E-02	3.551684E-02	4.999096E-01	-1.821566E-01	3.670589E-02	2.957067E-03
4	G	2.094533E-02	3.301722E-02	4.391271E-01	-1.392261E-01	1.490692E-01	-1.142424E-02
5	G	1.880983E-02	2.493698E-02	3.312898E-01	-8.131126E-02	1.334661E-01	-9.111037E-03
6	G	1.196179E-02	1.373256E-02	1.860366E-01	-1.283336E-01	3.334161E-01	-2.720176E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.224345E-02	2.614754E-02	4.773930E-01	-1.787333E-01	-5.546166E-02	2.484837E-02
9	G	1.571815E-02	3.167093E-02	4.605953E-01	-1.366648E-01	5.301927E-02	1.436319E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 267

NINE TENTHS, 100 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.841545E-03	1.468802E-06	4.453684E-01	2.279087E-04	1.259579E-01	1.443594E-06
2	G	1.514141E-02	3.196264E-02	5.231500E-01	-2.519959E-01	-2.885560E-02	2.091691E-02
3	G	1.953972E-02	3.841630E-02	5.197335E-01	-1.897423E-01	3.801002E-02	3.230809E-03
4	G	2.264209E-02	3.571898E-02	4.565497E-01	-1.449849E-01	1.551228E-01	-1.238715E-02
5	G	2.033645E-02	2.698075E-02	3.444239E-01	-8.407404E-02	1.386478E-01	-9.856430E-03
6	G	1.295184E-02	1.487071E-02	1.935032E-01	-1.342409E-01	3.462422E-01	-2.951384E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.321803E-02	2.826701E-02	4.963092E-01	-1.858529E-01	-5.748349E-02	2.685826E-02
9	G	1.697867E-02	3.424882E-02	4.788292E-01	-1.419957E-01	5.502278E-02	1.577108E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 268

ONE, 100 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.052533E-02	1.695872E-06	4.613619E-01	2.686107E-04	1.389854E-01	3.349228E-06
2	G	1.621063E-02	3.427781E-02	5.416592E-01	-2.613965E-01	-2.972628E-02	2.240671E-02
3	G	2.093902E-02	4.120795E-02	5.381159E-01	-1.967476E-01	3.920795E-02	3.498649E-03
4	G	2.427502E-02	3.832196E-02	4.727083E-01	-1.503035E-01	1.607262E-01	-1.331361E-02
5	G	2.180685E-02	2.895083E-02	3.566090E-01	-8.664693E-02	1.434598E-01	-1.057543E-02
6	G	1.390659E-02	1.596868E-02	2.004318E-01	-1.397551E-01	3.580976E-01	-3.175035E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.415336E-02	3.030703E-02	5.138595E-01	-1.924326E-01	-5.930737E-02	2.878639E-02
9	G	1.819057E-02	3.673179E-02	4.957463E-01	-1.469126E-01	5.686019E-02	1.717809E-03

ONE TENTH, 150 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.354563E-03	7.366276E-08	2.149118E-01	4.696348E-06	-3.328901E-03	-5.742499E-07
2	G	3.621486E-03	7.317279E-03	2.529716E-01	-1.098151E-01	-1.511953E-02	5.103266E-03
3	G	4.592068E-03	8.802887E-03	2.512641E-01	-8.524304E-02	2.049389E-02	5.709227E-04
4	G	5.296557E-03	8.184847E-03	2.207512E-01	-6.510935E-02	7.185407E-02	-2.577779E-03
5	G	4.775199E-03	6.183512E-03	1.668808E-01	-4.689491E-02	6.973214E-02	-2.339091E-03
6	G	2.933926E-03	3.336375E-03	9.261449E-02	-5.595305E-02	1.689154E-01	-6.389252E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.129553E-03	6.558679E-03	2.408560E-01	-8.719178E-02	-2.704529E-02	6.129972E-03
9	G	4.025673E-03	7.932787E-03	2.325669E-01	-6.745957E-02	2.623035E-02	3.747195E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 150 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.712575E-03	1.894269E-07	2.701582E-01	1.826190E-05	1.502717E-02	-1.264309E-06
2	G	5.691628E-03	1.168124E-02	3.182202E-01	-1.444839E-01	-1.824957E-02	7.888268E-03
3	G	7.256961E-03	1.403500E-02	3.161014E-01	-1.104852E-01	2.463765E-02	1.017125E-03
4	G	8.376823E-03	1.304318E-02	2.776830E-01	-8.458919E-02	9.214108E-02	-4.284007E-03
5	G	7.534677E-03	9.848950E-03	2.097218E-01	-5.600616E-02	8.620033E-02	-3.658775E-03
6	G	4.691985E-03	5.355895E-03	1.169338E-01	-7.446147E-02	2.123782E-01	-1.038185E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.939951E-03	1.041229E-02	3.024785E-01	-1.113954E-01	-3.473910E-02	9.802400E-03
9	G	6.339755E-03	1.259060E-02	2.919766E-01	-8.581370E-02	3.345615E-02	5.559138E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 150 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.839993E-03	3.288491E-07	3.090273E-01	3.757990E-05	3.332148E-02	-1.818605E-06
2	G	7.415303E-03	1.534081E-02	3.639657E-01	-1.688086E-01	-2.061691E-02	1.022721E-02
3	G	9.485699E-03	1.842505E-02	3.615601E-01	-1.282794E-01	2.762326E-02	1.398076E-03
4	G	1.095675E-02	1.711948E-02	3.175957E-01	-9.822046E-02	1.063034E-01	-5.735007E-03
5	G	9.845399E-03	1.292373E-02	2.397522E-01	-6.225341E-02	9.783161E-02	-4.769385E-03
6	G	6.172716E-03	7.055494E-03	1.339885E-01	-8.752506E-02	2.425996E-01	-1.376457E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.450269E-03	1.363628E-02	3.456935E-01	-1.282124E-01	-4.005688E-02	1.288674E-02
9	G	8.272197E-03	1.649183E-02	3.336361E-01	-9.855925E-02	3.842499E-02	7.159968E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 150 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.837342E-03	4.865723E-07	3.400296E-01	6.135544E-05	5.080239E-02	-2.133453E-06
2	G	8.945124E-03	1.860377E-02	4.003441E-01	-1.880589E-01	-2.255802E-02	1.232134E-02
3	G	1.146943E-02	2.234224E-02	3.977095E-01	-1.424248E-01	3.003020E-02	1.741557E-03
4	G	1.325620E-02	2.075806E-02	3.493377E-01	-1.090056E-01	1.175133E-01	-7.035545E-03
5	G	1.190598E-02	1.566913E-02	2.636411E-01	-6.720678E-02	1.071319E-01	-5.763636E-03
6	G	7.497573E-03	8.575993E-03	1.475584E-01	-9.798019E-02	2.664857E-01	-1.680482E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.791505E-03	1.650834E-02	3.800761E-01	-1.415015E-01	-4.421180E-02	1.563709E-02
9	G	9.991050E-03	1.997068E-02	3.667799E-01	-1.086119E-01	4.231346E-02	8.671052E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 150 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.746485E-03	6.592109E-07	3.662484E-01	8.884835E-05	6.738384E-02	-2.150111E-06
2	G	1.034446E-02	2.159823E-02	4.310251E-01	-2.041718E-01	-2.420116E-02	1.424973E-02
3	G	1.328762E-02	2.593991E-02	4.281947E-01	-1.543016E-01	3.206852E-02	2.061103E-03
4	G	1.536636E-02	2.410183E-02	3.761109E-01	-1.180446E-01	1.269289E-01	-8.231565E-03
5	G	1.379827E-02	1.819324E-02	2.837973E-01	-7.138930E-02	1.150090E-01	-6.679747E-03
6	G	8.717111E-03	9.975981E-03	1.590099E-01	-1.068506E-01	2.865269E-01	-1.961438E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.018232E-03	1.914363E-02	4.090916E-01	-1.526410E-01	-4.764832E-02	1.815984E-02
9	G	1.156603E-02	2.316581E-02	3.947501E-01	-1.170234E-01	4.554931E-02	1.013325E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 150 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.590050E-03	8.449124E-07	3.891950E-01	1.195550E-04	8.311211E-02	-1.827921E-06
2	G	1.164721E-02	2.439377E-02	4.578101E-01	-2.181361E-01	-2.561997E-02	1.605353E-02
3	G	1.498318E-02	2.930121E-02	4.548065E-01	-1.646226E-01	3.384609E-02	2.363893E-03
4	G	1.733655E-02	2.722789E-02	3.994867E-01	-1.258908E-01	1.351205E-01	-9.349250E-03
5	G	1.556646E-02	2.055423E-02	3.014021E-01	-7.505291E-02	1.219086E-01	-7.538075E-03
6	G	9.858836E-03	1.128706E-02	1.690136E-01	-1.146434E-01	3.039443E-01	-2.225427E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.015995E-02	2.160407E-02	4.344371E-01	-1.623169E-01	-5.058291E-02	2.051182E-02
9	G	1.303461E-02	2.615155E-02	4.191825E-01	-1.243150E-01	4.833854E-02	1.156801E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 150 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.382013E-03	1.042297E-06	4.097366E-01	1.531141E-04	9.806063E-02	-1.138168E-06
2	G	1.287422E-02	2.703340E-02	4.817325E-01	-2.305230E-01	-2.686114E-02	1.775786E-02
3	G	1.658263E-02	3.247742E-02	4.785722E-01	-1.738001E-01	3.542689E-02	2.654313E-03
4	G	1.919716E-02	3.018375E-02	4.203665E-01	-1.328623E-01	1.424153E-01	-1.040512E-02
5	G	1.723771E-02	2.278785E-02	3.171327E-01	-7.833837E-02	1.280871E-01	-8.351152E-03
6	G	1.093971E-02	1.252870E-02	1.779542E-01	-1.216483E-01	3.194367E-01	-2.476209E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.123487E-02	2.392776E-02	4.570861E-01	-1.709213E-01	-5.314126E-02	2.272819E-02
9	G	1.441984E-02	2.897364E-02	4.410155E-01	-1.307854E-01	5.079908E-02	1.298751E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 150 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.131779E-03	1.250324E-06	4.284225E-01	1.892518E-04	1.123038E-01	-5.940598E-08
2	G	1.403951E-02	2.954604E-02	5.034468E-01	-2.416939E-01	-2.795664E-02	1.937961E-02
3	G	1.810377E-02	3.550302E-02	5.001423E-01	-1.820944E-01	3.685236E-02	2.935308E-03
4	G	2.096860E-02	3.300125E-02	4.393209E-01	-1.391602E-01	1.490203E-01	-1.141041E-02
5	G	1.883020E-02	2.491806E-02	3.314177E-01	-8.133333E-02	1.337073E-01	-9.127391E-03
6	G	1.197113E-02	1.371396E-02	1.860746E-01	-1.280479E-01	3.334461E-01	-2.716306E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.225526E-02	2.614027E-02	4.776550E-01	-1.787006E-01	-5.540462E-02	2.483280E-02
9	G	1.573721E-02	3.166275E-02	4.608430E-01	-1.366231E-01	5.300594E-02	1.439887E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 150 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.846064E-03	1.468177E-06	4.456252E-01	2.277524E-04	1.259095E-01	1.424906E-06
2	G	1.515307E-02	3.195228E-02	5.233963E-01	-2.518938E-01	-2.892977E-02	2.093092E-02
3	G	1.955928E-02	3.840254E-02	5.199577E-01	-1.896821E-01	3.815131E-02	3.208932E-03
4	G	2.266539E-02	3.570307E-02	4.567364E-01	-1.449207E-01	1.550754E-01	-1.237321E-02
5	G	2.035687E-02	2.696190E-02	3.445473E-01	-8.409661E-02	1.388799E-01	-9.872780E-03
6	G	1.296120E-02	1.485213E-02	1.935399E-01	-1.339653E-01	3.462717E-01	-2.947513E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.322987E-02	2.825980E-02	4.965615E-01	-1.858215E-01	-5.742903E-02	2.684277E-02
9	G	1.699775E-02	3.424071E-02	4.790678E-01	-1.419557E-01	5.501014E-02	1.580653E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 150 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.052988E-02	1.695193E-06	4.616101E-01	2.684416E-04	1.389380E-01	3.327855E-06
2	G	1.622233E-02	3.426750E-02	5.418974E-01	-2.612973E-01	-2.979827E-02	2.242091E-02
3	G	2.095861E-02	4.119426E-02	5.383328E-01	-1.966893E-01	3.934472E-02	3.476672E-03
4	G	2.429836E-02	3.830611E-02	4.728889E-01	-1.502410E-01	1.606801E-01	-1.329958E-02
5	G	2.182733E-02	2.893204E-02	3.567286E-01	-8.666985E-02	1.436840E-01	-1.059178E-02
6	G	1.391596E-02	1.595011E-02	2.004674E-01	-1.394885E-01	3.581266E-01	-3.171164E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.416523E-02	3.029988E-02	5.141035E-01	-1.924023E-01	-5.925516E-02	2.877099E-02
9	G	1.820968E-02	3.672376E-02	4.959770E-01	-1.468741E-01	5.684813E-02	1.721327E-03

ONE TENTH, 200 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.358828E-03	7.355487E-08	2.154434E-01	4.684988E-06	-3.362801E-03	-5.761007E-07
2	G	3.632650E-03	7.307108E-03	2.534819E-01	-1.096795E-01	-1.524501E-02	5.110674E-03
3	G	4.611491E-03	8.789221E-03	2.517288E-01	-8.515172E-02	2.075714E-02	5.528591E-04
4	G	5.319860E-03	8.168803E-03	2.211388E-01	-6.504311E-02	7.178964E-02	-2.568360E-03
5	G	4.795018E-03	6.163848E-03	1.671271E-01	-4.686970E-02	7.020464E-02	-2.355721E-03
6	G	2.943332E-03	3.317913E-03	9.269178E-02	-5.541647E-02	1.689633E-01	-6.350109E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.141251E-03	6.551024E-03	2.413739E-01	-8.714139E-02	-2.693313E-02	6.114659E-03
9	G	4.044584E-03	7.924038E-03	2.330549E-01	-6.739330E-02	2.621151E-02	3.774358E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 200 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.716719E-03	1.888906E-07	2.705789E-01	1.821163E-05	1.497423E-02	-1.268621E-06
2	G	5.703422E-03	1.166910E-02	3.186098E-01	-1.442316E-01	-1.834102E-02	7.899298E-03
3	G	7.275778E-03	1.401925E-02	3.164505E-01	-1.102743E-01	2.484437E-02	9.992043E-04
4	G	8.399097E-03	1.302614E-02	2.779767E-01	-8.447200E-02	9.206965E-02	-4.270735E-03
5	G	7.553637E-03	9.828915E-03	2.099097E-01	-5.598703E-02	8.657819E-02	-3.675682E-03
6	G	4.700567E-03	5.337120E-03	1.169882E-01	-7.400262E-02	2.124067E-01	-1.034199E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.951420E-03	1.040448E-02	3.028885E-01	-1.112869E-01	-3.466473E-02	9.788832E-03
9	G	6.358653E-03	1.258226E-02	2.923686E-01	-8.572534E-02	3.345108E-02	5.584656E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 200 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.844261E-03	3.265192E-07	3.093947E-01	3.734945E-05	3.326790E-02	-1.825553E-06
2	G	7.427104E-03	1.532900E-02	3.643081E-01	-1.685910E-01	-2.070095E-02	1.023906E-02
3	G	9.504713E-03	1.840973E-02	3.618683E-01	-1.281048E-01	2.780457E-02	1.379467E-03
4	G	1.097943E-02	1.710287E-02	3.178566E-01	-9.812324E-02	1.062364E-01	-5.721403E-03
5	G	9.865088E-03	1.290421E-02	2.399226E-01	-6.226011E-02	9.816133E-02	-4.785878E-03
6	G	6.181776E-03	7.036840E-03	1.340392E-01	-8.713431E-02	2.426335E-01	-1.372599E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.461823E-03	1.362863E-02	3.460529E-01	-1.281249E-01	-3.999297E-02	1.287267E-02
9	G	8.291194E-03	1.648359E-02	3.339798E-01	-9.848730E-02	3.841891E-02	7.187132E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 200 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.841684E-03	4.862183E-07	3.403639E-01	6.127398E-05	5.075003E-02	-2.140217E-06
2	G	8.956624E-03	1.859299E-02	4.006624E-01	-1.879218E-01	-2.264834E-02	1.233374E-02
3	G	1.148873E-02	2.232796E-02	3.979982E-01	-1.423348E-01	3.020914E-02	1.720930E-03
4	G	1.327918E-02	2.074175E-02	3.495784E-01	-1.089258E-01	1.174549E-01	-7.022371E-03
5	G	1.192590E-02	1.564980E-02	2.637981E-01	-6.721988E-02	1.074341E-01	-5.780150E-03
6	G	7.506717E-03	8.557346E-03	1.476050E-01	-9.762285E-02	2.665181E-01	-1.676605E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.803173E-03	1.650081E-02	3.804033E-01	-1.414543E-01	-4.414062E-02	1.562166E-02
9	G	1.000997E-02	1.996228E-02	3.670896E-01	-1.085571E-01	4.229835E-02	8.705228E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 200 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.750870E-03	6.587941E-07	3.665591E-01	8.875101E-05	6.733190E-02	-2.159005E-06
2	G	1.035600E-02	2.158754E-02	4.313215E-01	-2.040451E-01	-2.428700E-02	1.426264E-02
3	G	1.330698E-02	2.592576E-02	4.284639E-01	-1.542211E-01	3.223641E-02	2.040091E-03
4	G	1.538942E-02	2.408561E-02	3.763352E-01	-1.179692E-01	1.268734E-01	-8.218135E-03
5	G	1.381833E-02	1.817404E-02	2.839442E-01	-7.140635E-02	1.152901E-01	-6.696200E-03
6	G	8.726306E-03	9.957343E-03	1.590535E-01	-1.065180E-01	2.865586E-01	-1.957565E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.029939E-03	1.913618E-02	4.093960E-01	-1.525989E-01	-4.758198E-02	1.814435E-02
9	G	1.158499E-02	2.315747E-02	3.950382E-01	-1.169731E-01	4.553472E-02	1.016804E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 200 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.594471E-03	8.444396E-07	3.894878E-01	1.194421E-04	8.306091E-02	-1.839073E-06
2	G	1.165878E-02	2.438316E-02	4.580899E-01	-2.180170E-01	-2.570211E-02	1.606681E-02
3	G	1.500260E-02	2.928716E-02	4.550608E-01	-1.645487E-01	3.400532E-02	2.342595E-03
4	G	1.735968E-02	2.721176E-02	3.996986E-01	-1.258189E-01	1.350674E-01	-9.335631E-03
5	G	1.558663E-02	2.053513E-02	3.015413E-01	-7.507224E-02	1.221735E-01	-7.554492E-03
6	G	9.868067E-03	1.126844E-02	1.690550E-01	-1.143297E-01	3.039752E-01	-2.221555E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.017169E-02	2.159669E-02	4.347242E-01	-1.622783E-01	-5.052045E-02	2.049632E-02
9	G	1.305360E-02	2.614329E-02	4.194542E-01	-1.242680E-01	4.832452E-02	1.160310E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 200 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.386467E-03	1.041769E-06	4.100151E-01	1.529866E-04	9.801036E-02	-1.151706E-06
2	G	1.288582E-02	2.702288E-02	4.819990E-01	-2.304098E-01	-2.694011E-02	1.777144E-02
3	G	1.660210E-02	3.246347E-02	4.788145E-01	-1.737308E-01	3.557900E-02	2.632805E-03
4	G	1.922034E-02	3.016770E-02	4.205683E-01	-1.327931E-01	1.423644E-01	-1.039136E-02
5	G	1.725796E-02	2.276884E-02	3.172656E-01	-7.835913E-02	1.283390E-01	-8.367544E-03
6	G	1.094897E-02	1.251009E-02	1.779936E-01	-1.213497E-01	3.194670E-01	-2.472340E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.124664E-02	2.392044E-02	4.573594E-01	-1.708851E-01	-5.308209E-02	2.271272E-02
9	G	1.443886E-02	2.896544E-02	4.412740E-01	-1.307411E-01	5.078568E-02	1.302265E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 200 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.136263E-03	1.249742E-06	4.286892E-01	1.891103E-04	1.122545E-01	-7.543910E-08
2	G	1.405115E-02	2.953558E-02	5.037022E-01	-2.415854E-01	-2.803286E-02	1.939344E-02
3	G	1.812327E-02	3.548915E-02	5.003747E-01	-1.820288E-01	3.699848E-02	2.913637E-03
4	G	2.099183E-02	3.298527E-02	4.395144E-01	-1.390933E-01	1.489712E-01	-1.139654E-02
5	G	1.885052E-02	2.489913E-02	3.315454E-01	-8.135502E-02	1.339484E-01	-9.143766E-03
6	G	1.198041E-02	1.369537E-02	1.861126E-01	-1.277617E-01	3.334759E-01	-2.712439E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.226706E-02	2.613301E-02	4.779169E-01	-1.786665E-01	-5.534826E-02	2.481738E-02
9	G	1.575626E-02	3.165462E-02	4.610908E-01	-1.365809E-01	5.299314E-02	1.443394E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 200 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.850577E-03	1.467542E-06	4.458818E-01	2.275975E-04	1.258613E-01	1.406285E-06
2	G	1.516475E-02	3.194189E-02	5.236424E-01	-2.517894E-01	-2.900360E-02	2.094495E-02
3	G	1.957882E-02	3.838874E-02	5.201817E-01	-1.896195E-01	3.829228E-02	3.187131E-03
4	G	2.268866E-02	3.568717E-02	4.569229E-01	-1.448560E-01	1.550279E-01	-1.235925E-02
5	G	2.037725E-02	2.694305E-02	3.446706E-01	-8.411893E-02	1.391118E-01	-9.889145E-03
6	G	1.297050E-02	1.483355E-02	1.935766E-01	-1.336898E-01	3.463010E-01	-2.943649E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.324170E-02	2.825260E-02	4.968138E-01	-1.857890E-01	-5.737512E-02	2.682741E-02
9	G	1.701683E-02	3.423264E-02	4.793065E-01	-1.419154E-01	5.499790E-02	1.584143E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 200 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.053442E-02	1.694507E-06	4.618582E-01	2.682737E-04	1.388909E-01	3.306567E-06
2	G	1.623403E-02	3.425718E-02	5.421355E-01	-2.611965E-01	-2.986997E-02	2.243511E-02
3	G	2.097819E-02	4.118055E-02	5.385495E-01	-1.966292E-01	3.948121E-02	3.454765E-03
4	G	2.432167E-02	3.829027E-02	4.730695E-01	-1.501782E-01	1.606341E-01	-1.328555E-02
5	G	2.184778E-02	2.891327E-02	3.568482E-01	-8.669259E-02	1.439081E-01	-1.060814E-02
6	G	1.392529E-02	1.593155E-02	2.005030E-01	-1.392221E-01	3.581556E-01	-3.167303E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.417708E-02	3.029274E-02	5.143476E-01	-1.923712E-01	-5.920339E-02	2.875570E-02
9	G	1.822879E-02	3.671575E-02	4.962078E-01	-1.468355E-01	5.683643E-02	1.724796E-03

ONE TENTH, 250 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.363033E-03	7.343962E-08	2.159703E-01	4.665842E-06	-3.403791E-03	-5.777393E-07
2	G	3.643904E-03	7.296593E-03	2.539834E-01	-1.095093E-01	-1.536469E-02	5.118910E-03
3	G	4.630649E-03	8.775120E-03	2.521832E-01	-8.501925E-02	2.101760E-02	5.348585E-04
4	G	5.342728E-03	8.152617E-03	2.215182E-01	-6.495472E-02	7.172048E-02	-2.558138E-03
5	G	4.814449E-03	6.144236E-03	1.673685E-01	-4.683664E-02	7.067232E-02	-2.372622E-03
6	G	2.952478E-03	3.299581E-03	9.276688E-02	-5.487816E-02	1.690079E-01	-6.314811E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.152844E-03	6.543413E-03	2.418869E-01	-8.707152E-02	-2.682437E-02	6.099723E-03
9	G	4.063388E-03	7.915500E-03	2.335400E-01	-6.731428E-02	2.619459E-02	3.801831E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 250 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.721013E-03	1.876693E-07	2.709981E-01	1.806309E-05	1.492617E-02	-1.268161E-06
2	G	5.714573E-03	1.165900E-02	3.190134E-01	-1.441215E-01	-1.845442E-02	7.909453E-03
3	G	7.295143E-03	1.400564E-02	3.168182E-01	-1.102137E-01	2.506831E-02	9.791233E-04
4	G	8.422216E-03	1.301008E-02	2.782815E-01	-8.439799E-02	9.200720E-02	-4.259521E-03
5	G	7.573499E-03	9.809544E-03	2.101060E-01	-5.598822E-02	8.695560E-02	-3.692281E-03
6	G	4.709831E-03	5.318651E-03	1.170481E-01	-7.356627E-02	2.124461E-01	-1.030420E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.963083E-03	1.039693E-02	3.032975E-01	-1.112528E-01	-3.456799E-02	9.772852E-03
9	G	6.377453E-03	1.257362E-02	2.927535E-01	-8.566884E-02	3.342805E-02	5.619347E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 250 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.848585E-03	3.294755E-07	3.097619E-01	3.753616E-05	3.321725E-02	-1.826345E-06
2	G	7.438387E-03	1.531869E-02	3.646605E-01	-1.684768E-01	-2.080315E-02	1.025057E-02
3	G	9.524080E-03	1.839592E-02	3.621891E-01	-1.280400E-01	2.800407E-02	1.358714E-03
4	G	1.100250E-02	1.708670E-02	3.181224E-01	-9.804715E-02	1.061767E-01	-5.709176E-03
5	G	9.884978E-03	1.288487E-02	2.400948E-01	-6.226915E-02	9.849365E-02	-4.802479E-03
6	G	6.190944E-03	7.018265E-03	1.340908E-01	-8.674479E-02	2.426680E-01	-1.368752E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.473503E-03	1.362111E-02	3.464116E-01	-1.280889E-01	-3.990861E-02	1.285669E-02
9	G	8.310039E-03	1.647504E-02	3.343178E-01	-9.843343E-02	3.839834E-02	7.223327E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 250 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.846040E-03	4.858726E-07	3.406981E-01	6.119399E-05	5.069811E-02	-2.146970E-06
2	G	8.968079E-03	1.858240E-02	4.009814E-01	-1.877940E-01	-2.274017E-02	1.234609E-02
3	G	1.150808E-02	2.231390E-02	3.982881E-01	-1.422546E-01	3.038908E-02	1.700149E-03
4	G	1.330224E-02	2.072557E-02	3.498198E-01	-1.088492E-01	1.173968E-01	-7.009384E-03
5	G	1.194591E-02	1.563056E-02	2.639557E-01	-6.723475E-02	1.077364E-01	-5.796646E-03
6	G	7.515911E-03	8.538748E-03	1.476520E-01	-9.726696E-02	2.665512E-01	-1.672753E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.814863E-03	1.649334E-02	3.807302E-01	-1.414118E-01	-4.406792E-02	1.560602E-02
9	G	1.002890E-02	1.995388E-02	3.673987E-01	-1.085044E-01	4.228185E-02	8.740405E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 250 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.755263E-03	6.583928E-07	3.668698E-01	8.865409E-05	6.728020E-02	-2.167857E-06
2	G	1.036750E-02	2.157700E-02	4.316184E-01	-2.039240E-01	-2.437386E-02	1.427552E-02
3	G	1.332638E-02	2.591176E-02	4.287338E-01	-1.541465E-01	3.240503E-02	2.018962E-03
4	G	1.541253E-02	2.406949E-02	3.765600E-01	-1.178957E-01	1.268180E-01	-8.204821E-03
5	G	1.383844E-02	1.815490E-02	2.840914E-01	-7.142432E-02	1.155715E-01	-6.712656E-03
6	G	8.735521E-03	9.938740E-03	1.590973E-01	-1.061860E-01	2.865905E-01	-1.953703E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.041660E-03	1.912876E-02	4.097003E-01	-1.525595E-01	-4.751458E-02	1.812871E-02
9	G	1.160395E-02	2.314915E-02	3.953259E-01	-1.169239E-01	4.551916E-02	1.020362E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 250 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.598898E-03	8.439784E-07	3.897805E-01	1.193295E-04	8.300985E-02	-1.850199E-06
2	G	1.167033E-02	2.437266E-02	4.583699E-01	-2.179014E-01	-2.578493E-02	1.608010E-02
3	G	1.502204E-02	2.927322E-02	4.553154E-01	-1.644784E-01	3.416507E-02	2.321215E-03
4	G	1.738283E-02	2.719570E-02	3.999106E-01	-1.257480E-01	1.350144E-01	-9.322083E-03
5	G	1.560682E-02	2.051608E-02	3.016806E-01	-7.509211E-02	1.224387E-01	-7.570918E-03
6	G	9.877303E-03	1.124984E-02	1.690963E-01	-1.140160E-01	3.040062E-01	-2.217690E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.018344E-02	2.158933E-02	4.350112E-01	-1.622413E-01	-5.045727E-02	2.048072E-02
9	G	1.307259E-02	2.613503E-02	4.197256E-01	-1.242217E-01	4.830984E-02	1.163878E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 250 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.390925E-03	1.041250E-06	4.102935E-01	1.528591E-04	9.796018E-02	-1.165229E-06
2	G	1.289742E-02	2.701242E-02	4.822655E-01	-2.302988E-01	-2.701958E-02	1.778504E-02
3	G	1.662157E-02	3.244960E-02	4.790569E-01	-1.736640E-01	3.573152E-02	2.611233E-03
4	G	1.924354E-02	3.015169E-02	4.207702E-01	-1.327246E-01	1.423133E-01	-1.037764E-02
5	G	1.727822E-02	2.274987E-02	3.173986E-01	-7.838023E-02	1.285912E-01	-8.383950E-03
6	G	1.095823E-02	1.249150E-02	1.780331E-01	-1.210509E-01	3.194973E-01	-2.468472E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.125842E-02	2.391315E-02	4.576326E-01	-1.708502E-01	-5.302238E-02	2.269718E-02
9	G	1.445788E-02	2.895726E-02	4.415324E-01	-1.306971E-01	5.077178E-02	1.305829E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 250 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.140751E-03	1.249168E-06	4.289558E-01	1.889687E-04	1.122053E-01	-9.146328E-08
2	G	1.406279E-02	2.952518E-02	5.039577E-01	-2.414786E-01	-2.810949E-02	1.940729E-02
3	G	1.814279E-02	3.547534E-02	5.006071E-01	-1.819649E-01	3.714494E-02	2.891913E-03
4	G	2.101507E-02	3.296933E-02	4.397080E-01	-1.390270E-01	1.489219E-01	-1.138269E-02
5	G	1.887085E-02	2.488024E-02	3.316731E-01	-8.137695E-02	1.341898E-01	-9.160158E-03
6	G	1.198969E-02	1.367679E-02	1.861505E-01	-1.274752E-01	3.335055E-01	-2.708571E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.227887E-02	2.612578E-02	4.781788E-01	-1.786332E-01	-5.529148E-02	2.480190E-02
9	G	1.577532E-02	3.164650E-02	4.613384E-01	-1.365391E-01	5.297995E-02	1.446943E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 250 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.855093E-03	1.466914E-06	4.461384E-01	2.274424E-04	1.258131E-01	1.387669E-06
2	G	1.517642E-02	3.193155E-02	5.238886E-01	-2.516862E-01	-2.907776E-02	2.095901E-02
3	G	1.959837E-02	3.837501E-02	5.204057E-01	-1.895582E-01	3.843356E-02	3.165283E-03
4	G	2.271195E-02	3.567130E-02	4.571095E-01	-1.447916E-01	1.549802E-01	-1.234530E-02
5	G	2.039765E-02	2.692423E-02	3.447939E-01	-8.414143E-02	1.393441E-01	-9.905529E-03
6	G	1.297980E-02	1.481498E-02	1.936132E-01	-1.334138E-01	3.463302E-01	-2.939781E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.325354E-02	2.824542E-02	4.970661E-01	-1.857572E-01	-5.732085E-02	2.681200E-02
9	G	1.703592E-02	3.422458E-02	4.795450E-01	-1.418754E-01	5.498534E-02	1.587671E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 250 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.053896E-02	1.693826E-06	4.621062E-01	2.681058E-04	1.388438E-01	3.285279E-06
2	G	1.624574E-02	3.424689E-02	5.423737E-01	-2.610965E-01	-2.994197E-02	2.244934E-02
3	G	2.099777E-02	4.116688E-02	5.387663E-01	-1.965701E-01	3.961797E-02	3.432815E-03
4	G	2.434500E-02	3.827447E-02	4.732500E-01	-1.501155E-01	1.605879E-01	-1.327153E-02
5	G	2.186823E-02	2.889451E-02	3.569677E-01	-8.671547E-02	1.441324E-01	-1.062452E-02
6	G	1.393461E-02	1.591300E-02	2.005386E-01	-1.389552E-01	3.581844E-01	-3.163436E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.418895E-02	3.026561E-02	5.145916E-01	-1.923406E-01	-5.915133E-02	2.874036E-02
9	G	1.824790E-02	3.670775E-02	4.964386E-01	-1.467970E-01	5.682444E-02	1.728299E-03

ONE TENTH, 300 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.367231E-03	7.332545E-08	2.164965E-01	4.645270E-06	-3.444421E-03	-5.792397E-07
2	G	3.655146E-03	7.286183E-03	2.544847E-01	-1.093424E-01	-1.548555E-02	5.126880E-03
3	G	4.649807E-03	8.761142E-03	2.526376E-01	-8.489065E-02	2.127886E-02	5.170402E-04
4	G	5.365598E-03	8.136533E-03	2.218976E-01	-6.486823E-02	7.165094E-02	-2.548040E-03
5	G	4.833857E-03	6.124710E-03	1.676096E-01	-4.680381E-02	7.114077E-02	-2.389323E-03
6	G	2.961559E-03	3.281304E-03	9.284169E-02	-5.433842E-02	1.690515E-01	-6.277717E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.164432E-03	6.535877E-03	2.423992E-01	-8.700369E-02	-2.671536E-02	6.084937E-03
9	G	4.082184E-03	7.907037E-03	2.340243E-01	-6.723669E-02	2.617735E-02	3.829050E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 300 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.725439E-03	1.889507E-07	2.714158E-01	1.813912E-05	1.488237E-02	-1.273246E-06
2	G	5.725359E-03	1.165020E-02	3.194245E-01	-1.440907E-01	-1.857800E-02	7.918866E-03
3	G	7.314885E-03	1.399343E-02	3.171967E-01	-1.102358E-01	2.529720E-02	9.580322E-04
4	G	8.446011E-03	1.299481E-02	2.785947E-01	-8.435494E-02	9.194899E-02	-4.249698E-03
5	G	7.594205E-03	9.790799E-03	2.103101E-01	-5.600928E-02	8.733071E-02	-3.708508E-03
6	G	4.719755E-03	5.300478E-03	1.171133E-01	-7.315342E-02	2.124966E-01	-1.026866E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.974892E-03	1.038957E-02	3.037057E-01	-1.112604E-01	-3.446111E-02	9.755251E-03
9	G	6.396240E-03	1.256487E-02	2.931347E-01	-8.563216E-02	3.339537E-02	5.659220E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 300 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.852986E-03	3.283553E-07	3.101283E-01	3.739091E-05	3.316884E-02	-1.831720E-06
2	G	7.449308E-03	1.530956E-02	3.650196E-01	-1.684336E-01	-2.091648E-02	1.026163E-02
3	G	9.543752E-03	1.838334E-02	3.625188E-01	-1.280505E-01	2.821230E-02	1.336702E-03
4	G	1.102603E-02	1.707107E-02	3.183935E-01	-9.799135E-02	1.061213E-01	-5.698113E-03
5	G	9.905346E-03	1.286589E-02	2.402707E-01	-6.228699E-02	9.882587E-02	-4.818925E-03
6	G	6.200474E-03	6.999864E-03	1.341448E-01	-8.636558E-02	2.427074E-01	-1.365015E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.485301E-03	1.361371E-02	3.467694E-01	-1.280889E-01	-3.981226E-02	1.283924E-02
9	G	8.328821E-03	1.646632E-02	3.346521E-01	-9.839413E-02	3.836816E-02	7.265609E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 300 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.850434E-03	4.857433E-07	3.410318E-01	6.111067E-05	5.064701E-02	-2.152988E-06
2	G	8.979396E-03	1.857231E-02	4.013026E-01	-1.876912E-01	-2.283575E-02	1.235824E-02
3	G	1.152756E-02	2.230036E-02	3.985811E-01	-1.422006E-01	3.057159E-02	1.678923E-03
4	G	1.332551E-02	2.070965E-02	3.500633E-01	-1.087805E-01	1.173398E-01	-6.996883E-03
5	G	1.196615E-02	1.561151E-02	2.641148E-01	-6.725361E-02	1.080389E-01	-5.813071E-03
6	G	7.525272E-03	8.520246E-03	1.477000E-01	-9.691537E-02	2.665863E-01	-1.668954E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.826608E-03	1.648592E-02	3.810567E-01	-1.413818E-01	-4.399104E-02	1.558977E-02
9	G	1.004780E-02	1.994544E-02	3.677065E-01	-1.084568E-01	4.226176E-02	8.778234E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 300 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.759678E-03	6.579987E-07	3.671802E-01	8.855948E-05	6.722878E-02	-2.176700E-06
2	G	1.037893E-02	2.156675E-02	4.319165E-01	-2.038171E-01	-2.446296E-02	1.428832E-02
3	G	1.334585E-02	2.589808E-02	4.290054E-01	-1.540870E-01	3.257529E-02	1.997545E-03
4	G	1.543577E-02	2.405353E-02	3.767858E-01	-1.178264E-01	1.267631E-01	-8.191791E-03
5	G	1.385868E-02	1.813587E-02	2.842394E-01	-7.144435E-02	1.158531E-01	-6.729087E-03
6	G	8.744824E-03	9.920197E-03	1.591415E-01	-1.058557E-01	2.866232E-01	-1.949869E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.053417E-03	1.912139E-02	4.100043E-01	-1.525272E-01	-4.744458E-02	1.811268E-02
9	G	1.162290E-02	2.314080E-02	3.956128E-01	-1.168775E-01	4.550137E-02	1.024107E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 300 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.603341E-03	8.435464E-07	3.900730E-01	1.192166E-04	8.295889E-02	-1.861275E-06
2	G	1.168183E-02	2.436238E-02	4.586506E-01	-2.177948E-01	-2.586929E-02	1.609335E-02
3	G	1.504153E-02	2.925951E-02	4.555710E-01	-1.644178E-01	3.432596E-02	2.299629E-03
4	G	1.740608E-02	2.717976E-02	4.001232E-01	-1.256798E-01	1.349615E-01	-9.308717E-03
5	G	1.562710E-02	2.049710E-02	3.018203E-01	-7.511331E-02	1.227042E-01	-7.587337E-03
6	G	9.886597E-03	1.123128E-02	1.691380E-01	-1.137031E-01	3.040375E-01	-2.213838E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.019522E-02	2.158201E-02	4.352980E-01	-1.622089E-01	-5.039230E-02	2.046484E-02
9	G	1.309158E-02	2.612677E-02	4.199965E-01	-1.241771E-01	4.829361E-02	1.167591E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 300 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.395394E-03	1.040754E-06	4.105718E-01	1.527310E-04	9.791000E-02	-1.178735E-06
2	G	1.290898E-02	2.700212E-02	4.825325E-01	-2.301937E-01	-2.710015E-02	1.779864E-02
3	G	1.664109E-02	3.243589E-02	4.793001E-01	-1.736036E-01	3.588490E-02	2.589505E-03
4	G	1.926681E-02	3.013578E-02	4.209725E-01	-1.326578E-01	1.422623E-01	-1.036403E-02
5	G	1.729855E-02	2.273095E-02	3.175318E-01	-7.840219E-02	1.288438E-01	-8.400363E-03
6	G	1.096752E-02	1.247294E-02	1.780727E-01	-1.207521E-01	3.195276E-01	-2.464609E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.127022E-02	2.390589E-02	4.579057E-01	-1.708181E-01	-5.296138E-02	2.268143E-02
9	G	1.447691E-02	2.894907E-02	4.417904E-01	-1.306543E-01	5.075677E-02	1.309507E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 300 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.145248E-03	1.248612E-06	4.292223E-01	1.888263E-04	1.121561E-01	-1.074963E-07
2	G	1.407440E-02	2.951490E-02	5.042135E-01	-2.413757E-01	-2.818697E-02	1.942116E-02
3	G	1.816233E-02	3.546166E-02	5.008400E-01	-1.819055E-01	3.729211E-02	2.870061E-03
4	G	2.103836E-02	3.295346E-02	4.399018E-01	-1.389618E-01	1.488726E-01	-1.136891E-02
5	G	1.889123E-02	2.486138E-02	3.318010E-01	-8.139946E-02	1.344316E-01	-9.176566E-03
6	G	1.199899E-02	1.365823E-02	1.861885E-01	-1.271884E-01	3.335351E-01	-2.704701E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.229070E-02	2.611857E-02	4.784405E-01	-1.786019E-01	-5.523369E-02	2.478626E-02
9	G	1.579438E-02	3.163838E-02	4.615857E-01	-1.364979E-01	5.296589E-02	1.450590E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 300 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.859617E-03	1.466301E-06	4.463950E-01	2.272865E-04	1.257649E-01	1.369025E-06
2	G	1.518807E-02	3.192129E-02	5.241349E-01	-2.515858E-01	-2.915262E-02	2.097310E-02
3	G	1.961795E-02	3.836136E-02	5.206300E-01	-1.895001E-01	3.857545E-02	3.143323E-03
4	G	2.273527E-02	3.565548E-02	4.572962E-01	-1.447279E-01	1.549324E-01	-1.233139E-02
5	G	2.041808E-02	2.690544E-02	3.449173E-01	-8.416432E-02	1.395768E-01	-9.921934E-03
6	G	1.298912E-02	1.479644E-02	1.936498E-01	-1.331372E-01	3.463593E-01	-2.935907E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.326539E-02	2.823826E-02	4.973182E-01	-1.857268E-01	-5.726577E-02	2.679646E-02
9	G	1.705501E-02	3.421653E-02	4.797833E-01	-1.418357E-01	5.497207E-02	1.591287E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 300 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.054351E-02	1.693159E-06	4.623542E-01	2.679370E-04	1.387966E-01	3.263949E-06
2	G	1.625744E-02	3.423667E-02	5.426119E-01	-2.609986E-01	-3.001457E-02	2.246363E-02
3	G	2.101739E-02	4.115329E-02	5.389833E-01	-1.965135E-01	3.975530E-02	3.410762E-03
4	G	2.436835E-02	3.825870E-02	4.734306E-01	-1.500534E-01	1.605414E-01	-1.325752E-02
5	G	2.188871E-02	2.887578E-02	3.570872E-01	-8.673865E-02	1.443572E-01	-1.064092E-02
6	G	1.394394E-02	1.589447E-02	2.005741E-01	-1.386875E-01	3.582129E-01	-3.159559E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.420082E-02	3.027851E-02	5.148355E-01	-1.923111E-01	-5.909856E-02	2.872492E-02
9	G	1.826702E-02	3.669976E-02	4.966691E-01	-1.467588E-01	5.681183E-02	1.731883E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 350 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.371495E-03	7.320489E-08	2.170217E-01	4.630460E-06	-3.476444E-03	-5.806948E-07
2	G	3.666557E-03	7.275717E-03	2.549841E-01	-1.091455E-01	-1.559989E-02	5.135071E-03
3	G	4.668949E-03	8.747096E-03	2.530893E-01	-8.472092E-02	2.153227E-02	4.999061E-04
4	G	5.388543E-03	8.120810E-03	2.222783E-01	-6.478049E-02	7.157630E-02	-2.537698E-03
5	G	4.853522E-03	6.105624E-03	1.678543E-01	-4.678436E-02	7.160768E-02	-2.406012E-03
6	G	2.970786E-03	3.263273E-03	9.291868E-02	-5.381036E-02	1.691005E-01	-6.241180E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.176010E-03	6.528637E-03	2.429127E-01	-8.692455E-02	-2.661762E-02	6.071128E-03
9	G	4.101096E-03	7.899066E-03	2.345122E-01	-6.715883E-02	2.616498E-02	3.852794E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 350 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.729725E-03	1.887200E-07	2.718346E-01	1.808593E-05	1.482835E-02	-1.275194E-06
2	G	5.736610E-03	1.164003E-02	3.198259E-01	-1.439630E-01	-1.868842E-02	7.928989E-03
3	G	7.334214E-03	1.397976E-02	3.175620E-01	-1.101564E-01	2.551834E-02	9.383397E-04
4	G	8.469090E-03	1.297885E-02	2.788986E-01	-8.427811E-02	9.188408E-02	-4.238381E-03
5	G	7.614023E-03	9.771534E-03	2.105061E-01	-5.601090E-02	8.770895E-02	-3.725113E-03
6	G	4.728916E-03	5.282075E-03	1.171728E-01	-7.271501E-02	2.125353E-01	-1.023089E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.986551E-03	1.038213E-02	3.041144E-01	-1.112177E-01	-3.436704E-02	9.739504E-03
9	G	6.415078E-03	1.255643E-02	2.935203E-01	-8.557276E-02	3.337402E-02	5.693221E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 350 DEG SUBCASE 30
LOAD STEP = 4.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.857322E-03	3.278347E-07	3.104949E-01	3.733337E-05	3.311871E-02	-1.837423E-06
2	G	7.460625E-03	1.529932E-02	3.653711E-01	-1.683142E-01	-2.101783E-02	1.027318E-02
3	G	9.563133E-03	1.836963E-02	3.628388E-01	-1.279804E-01	2.840982E-02	1.316117E-03
4	G	1.104917E-02	1.705508E-02	3.186597E-01	-9.791681E-02	1.060603E-01	-5.685914E-03
5	G	9.925346E-03	1.284671E-02	2.404437E-01	-6.229918E-02	9.915807E-02	-4.835480E-03
6	G	6.209685E-03	6.981382E-03	1.341969E-01	-8.597846E-02	2.427431E-01	-1.361213E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.496992E-03	1.360627E-02	3.471277E-01	-1.280508E-01	-3.972953E-02	1.282332E-02
9	G	8.347698E-03	1.645789E-02	3.349902E-01	-9.834041E-02	3.834802E-02	7.301614E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 350 DEG SUBCASE 40
LOAD STEP = 5.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.854804E-03	4.852837E-07	3.413655E-01	6.103665E-05	5.059585E-02	-2.160220E-06
2	G	8.990797E-03	1.856199E-02	4.016224E-01	-1.875743E-01	-2.292969E-02	1.237059E-02
3	G	1.154697E-02	2.228660E-02	3.988722E-01	-1.421323E-01	3.075313E-02	1.657910E-03
4	G	1.334866E-02	2.069364E-02	3.503054E-01	-1.087073E-01	1.172818E-01	-6.984108E-03
5	G	1.198623E-02	1.559240E-02	2.642729E-01	-6.727016E-02	1.083418E-01	-5.829583E-03
6	G	7.534479E-03	8.501718E-03	1.477472E-01	-9.656009E-02	2.666197E-01	-1.665123E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.838324E-03	1.647852E-02	3.813833E-01	-1.413450E-01	-4.391624E-02	1.557388E-02
9	G	1.006672E-02	1.993708E-02	3.680149E-01	-1.084064E-01	4.224337E-02	8.814840E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 350 DEG SUBCASE 50
LOAD STEP = 6.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.764079E-03	6.576447E-07	3.674905E-01	8.846173E-05	6.717764E-02	-2.185476E-06
2	G	1.039041E-02	2.155637E-02	4.322136E-01	-2.037011E-01	-2.455098E-02	1.430125E-02
3	G	1.336528E-02	2.588426E-02	4.292757E-01	-1.540181E-01	3.274478E-02	1.976296E-03
4	G	1.545893E-02	2.403752E-02	3.770108E-01	-1.177546E-01	1.267076E-01	-8.178585E-03
5	G	1.387882E-02	1.811682E-02	2.843868E-01	-7.146326E-02	1.161350E-01	-6.745568E-03
6	G	8.754029E-03	9.901644E-03	1.591853E-01	-1.055235E-01	2.866550E-01	-1.946019E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.065155E-03	1.911404E-02	4.103083E-01	-1.524906E-01	-4.737612E-02	1.809693E-02
9	G	1.164186E-02	2.313253E-02	3.959001E-01	-1.168294E-01	4.548479E-02	1.027749E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 350 DEG SUBCASE 60
LOAD STEP = 7.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.607771E-03	8.430965E-07	3.903655E-01	1.191050E-04	8.290831E-02	-1.872445E-06
2	G	1.169337E-02	2.435198E-02	4.589307E-01	-2.176818E-01	-2.595287E-02	1.610669E-02
3	G	1.506099E-02	2.924569E-02	4.558258E-01	-1.643505E-01	3.448630E-02	2.278172E-03
4	G	1.742926E-02	2.716378E-02	4.003354E-01	-1.256098E-01	1.349082E-01	-9.295225E-03
5	G	1.564730E-02	2.047811E-02	3.019596E-01	-7.513366E-02	1.229699E-01	-7.603799E-03
6	G	9.895806E-03	1.121272E-02	1.691793E-01	-1.133889E-01	3.040682E-01	-2.209977E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.020698E-02	2.157471E-02	4.355848E-01	-1.621734E-01	-5.032849E-02	2.044918E-02
9	G	1.311058E-02	2.611857E-02	4.202676E-01	-1.241314E-01	4.827828E-02	1.171218E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 350 DEG SUBCASE 70
LOAD STEP = 8.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.399854E-03	1.040245E-06	4.108500E-01	1.526046E-04	9.786027E-02	-1.192336E-06
2	G	1.292057E-02	2.699176E-02	4.827991E-01	-2.300845E-01	-2.718023E-02	1.781230E-02
3	G	1.666059E-02	3.242211E-02	4.795426E-01	-1.735389E-01	3.603790E-02	2.567872E-03
4	G	1.929003E-02	3.011985E-02	4.211745E-01	-1.325899E-01	1.422110E-01	-1.035035E-02
5	G	1.731882E-02	2.271203E-02	3.176647E-01	-7.842363E-02	1.290964E-01	-8.416805E-03
6	G	1.097675E-02	1.245438E-02	1.781121E-01	-1.204526E-01	3.195576E-01	-2.460743E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.128201E-02	2.389864E-02	4.581787E-01	-1.707841E-01	-5.290119E-02	2.266585E-02
9	G	1.449594E-02	2.894093E-02	4.420485E-01	-1.306107E-01	5.074237E-02	1.313120E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 350 DEG SUBCASE 80
LOAD STEP = 9.00000E+00

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.149737E-03	1.248046E-06	4.294887E-01	1.886860E-04	1.121073E-01	-1.236320E-07
2	G	1.408604E-02	2.950457E-02	5.044689E-01	-2.412701E-01	-2.826409E-02	1.943508E-02
3	G	1.818186E-02	3.544793E-02	5.010725E-01	-1.818432E-01	3.743899E-02	2.848284E-03
4	G	2.106162E-02	3.293759E-02	4.400954E-01	-1.388958E-01	1.488231E-01	-1.135508E-02
5	G	1.891157E-02	2.484253E-02	3.319287E-01	-8.142164E-02	1.346735E-01	-9.192995E-03
6	G	1.200824E-02	1.363968E-02	1.862263E-01	-1.269012E-01	3.335645E-01	-2.700833E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.230252E-02	2.611138E-02	4.787022E-01	-1.785693E-01	-5.517653E-02	2.477075E-02
9	G	1.581343E-02	3.163031E-02	4.618331E-01	-1.364563E-01	5.295229E-02	1.454182E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 350 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.864134E-03	1.465681E-06	4.466515E-01	2.271329E-04	1.257172E-01	1.350265E-06
2	G	1.519975E-02	3.191101E-02	5.243810E-01	-2.514834E-01	-2.922722E-02	2.098723E-02
3	G	1.963751E-02	3.834770E-02	5.208541E-01	-1.894400E-01	3.871709E-02	3.121427E-03
4	G	2.275857E-02	3.563965E-02	4.574828E-01	-1.446638E-01	1.548845E-01	-1.231746E-02
5	G	2.043847E-02	2.688665E-02	3.450406E-01	-8.418700E-02	1.398095E-01	-9.938353E-03
6	G	1.299839E-02	1.477790E-02	1.936864E-01	-1.328605E-01	3.463882E-01	-2.932038E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.327723E-02	2.823112E-02	4.975703E-01	-1.856954E-01	-5.721118E-02	2.678104E-02
9	G	1.707410E-02	3.420852E-02	4.800217E-01	-1.417958E-01	5.495916E-02	1.594854E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 350 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.054806E-02	1.692485E-06	4.626021E-01	2.677707E-04	1.387500E-01	3.242490E-06
2	G	1.626915E-02	3.422644E-02	5.428500E-01	-2.608993E-01	-3.008695E-02	2.247793E-02
3	G	2.103698E-02	4.113968E-02	5.392001E-01	-1.964553E-01	3.989239E-02	3.388768E-03
4	G	2.439168E-02	3.824294E-02	4.736111E-01	-1.499910E-01	1.604950E-01	-1.324351E-02
5	G	2.190916E-02	2.885706E-02	3.572066E-01	-8.676167E-02	1.445820E-01	-1.065734E-02
6	G	1.395323E-02	1.587594E-02	2.006095E-01	-1.384199E-01	3.582415E-01	-3.155690E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.421269E-02	3.027142E-02	5.150793E-01	-1.922809E-01	-5.904621E-02	2.870956E-02
9	G	1.828614E-02	3.669181E-02	4.968997E-01	-1.467205E-01	5.679954E-02	1.735423E-03

ONE TENTH, 400 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.375595E-03	7.316699E-08	2.175462E-01	4.605499E-06	-3.526167E-03	-5.823217E-07
2	G	3.676803E-03	7.267762E-03	2.555033E-01	-1.091997E-01	-1.576805E-02	5.143355E-03
3	G	4.688556E-03	8.735888E-03	2.535690E-01	-8.486806E-02	2.183642E-02	4.777535E-04
4	G	5.411728E-03	8.105053E-03	2.226620E-01	-6.474157E-02	7.153090E-02	-2.530499E-03
5	G	4.872420E-03	6.085756E-03	1.680888E-01	-4.672921E-02	7.208692E-02	-2.423175E-03
6	G	2.979317E-03	3.244825E-03	9.298830E-02	-5.324136E-02	1.691299E-01	-6.203623E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.187724E-03	6.521059E-03	2.434190E-01	-8.696756E-02	-2.645250E-02	6.051285E-03
9	G	4.119399E-03	7.889617E-03	2.349769E-01	-6.711987E-02	2.611279E-02	3.898758E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 400 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.733935E-03	1.885501E-07	2.722536E-01	1.805493E-05	1.478611E-02	-1.279221E-06
2	G	5.748134E-03	1.162900E-02	3.202210E-01	-1.437745E-01	-1.879212E-02	7.940109E-03
3	G	7.353284E-03	1.396521E-02	3.179187E-01	-1.100140E-01	2.573429E-02	9.192888E-04
4	G	8.491748E-03	1.296247E-02	2.791967E-01	-8.418063E-02	9.181464E-02	-4.225964E-03
5	G	7.633354E-03	9.751987E-03	2.106973E-01	-5.600208E-02	8.808847E-02	-3.742016E-03
6	G	4.737653E-03	5.263553E-03	1.172291E-01	-7.226331E-02	2.125671E-01	-1.019221E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	4.998117E-03	1.037460E-02	3.045231E-01	-1.111432E-01	-3.428253E-02	9.724974E-03
9	G	6.433945E-03	1.254815E-02	2.939083E-01	-8.549895E-02	3.335973E-02	5.723552E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 400 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.861585E-03	3.278584E-07	3.108619E-01	3.726604E-05	3.306700E-02	-1.841065E-06
2	G	7.472223E-03	1.528826E-02	3.657176E-01	-1.681421E-01	-2.111217E-02	1.028525E-02
3	G	9.582272E-03	1.835506E-02	3.631519E-01	-1.278556E-01	2.860260E-02	1.296369E-03
4	G	1.107191E-02	1.703870E-02	3.189213E-01	-9.782568E-02	1.059956E-01	-5.672789E-03
5	G	9.944879E-03	1.282728E-02	2.406130E-01	-6.230319E-02	9.949146E-02	-4.852245E-03
6	G	6.218484E-03	6.962782E-03	1.342463E-01	-8.557986E-02	2.427735E-01	-1.357308E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.508590E-03	1.359880E-02	3.474863E-01	-1.279864E-01	-3.965485E-02	1.280859E-02
9	G	8.366616E-03	1.644967E-02	3.353307E-01	-9.827553E-02	3.833449E-02	7.333368E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 400 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.859133E-03	4.848964E-07	3.416995E-01	6.095717E-05	5.054416E-02	-2.167042E-06
2	G	9.002356E-03	1.855123E-02	4.019397E-01	-1.874304E-01	-2.302005E-02	1.238324E-02
3	G	1.156625E-02	2.227236E-02	3.991598E-01	-1.420357E-01	3.093221E-02	1.637372E-03
4	G	1.337159E-02	2.067743E-02	3.505453E-01	-1.086259E-01	1.172219E-01	-6.970818E-03
5	G	1.200605E-02	1.557316E-02	2.644292E-01	-6.728283E-02	1.086453E-01	-5.846215E-03
6	G	7.543447E-03	8.483130E-03	1.477931E-01	-9.619916E-02	2.666505E-01	-1.661240E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.849985E-03	1.647112E-02	3.817101E-01	-1.412949E-01	-4.384582E-02	1.555870E-02
9	G	1.008567E-02	1.992885E-02	3.683245E-01	-1.083505E-01	4.222854E-02	8.848775E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 400 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.768455E-03	6.572263E-07	3.678010E-01	8.836527E-05	6.712630E-02	-2.194291E-06
2	G	1.040198E-02	2.154575E-02	4.325095E-01	-2.035712E-01	-2.463720E-02	1.431434E-02
3	G	1.338463E-02	2.587019E-02	4.295443E-01	-1.539348E-01	3.291308E-02	1.955305E-03
4	G	1.548196E-02	2.402142E-02	3.772346E-01	-1.176785E-01	1.266510E-01	-8.165105E-03
5	G	1.389881E-02	1.809770E-02	2.845333E-01	-7.148017E-02	1.164171E-01	-6.762124E-03
6	G	8.763085E-03	9.883063E-03	1.592285E-01	-1.051883E-01	2.866855E-01	-1.942143E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.076860E-03	1.910670E-02	4.106124E-01	-1.524473E-01	-4.730994E-02	1.808158E-02
9	G	1.166084E-02	2.312433E-02	3.961880E-01	-1.167787E-01	4.547007E-02	1.031235E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 400 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.612186E-03	8.426235E-07	3.906581E-01	1.189931E-04	8.285762E-02	-1.883469E-06
2	G	1.170497E-02	2.434145E-02	4.592100E-01	-2.175609E-01	-2.603541E-02	1.612013E-02
3	G	1.508040E-02	2.923174E-02	4.560797E-01	-1.642751E-01	3.464593E-02	2.256881E-03
4	G	1.745237E-02	2.714775E-02	4.005468E-01	-1.255375E-01	1.348544E-01	-9.281583E-03
5	G	1.566741E-02	2.045910E-02	3.020985E-01	-7.515299E-02	1.232357E-01	-7.620305E-03
6	G	9.904919E-03	1.119415E-02	1.692202E-01	-1.130732E-01	3.040983E-01	-2.206105E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.021872E-02	2.156743E-02	4.358717E-01	-1.621342E-01	-5.026603E-02	2.043379E-02
9	G	1.312958E-02	2.611042E-02	4.205391E-01	-1.240842E-01	4.826406E-02	1.174741E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 400 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.404304E-03	1.039718E-06	4.111282E-01	1.524780E-04	9.781041E-02	-1.205694E-06
2	G	1.293220E-02	2.698131E-02	4.830652E-01	-2.299702E-01	-2.725959E-02	1.782601E-02
3	G	1.668005E-02	3.240825E-02	4.797845E-01	-1.734689E-01	3.619039E-02	2.546361E-03
4	G	1.931319E-02	3.010390E-02	4.213760E-01	-1.325206E-01	1.421595E-01	-1.033658E-02
5	G	1.733903E-02	2.269310E-02	3.177974E-01	-7.844444E-02	1.293490E-01	-8.433278E-03
6	G	1.098591E-02	1.243582E-02	1.781513E-01	-1.201524E-01	3.195872E-01	-2.456874E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.129379E-02	2.389141E-02	4.584518E-01	-1.707478E-01	-5.284194E-02	2.265045E-02
9	G	1.451497E-02	2.893284E-02	4.423069E-01	-1.305663E-01	5.072873E-02	1.316653E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 400 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.154217E-03	1.247467E-06	4.297552E-01	1.885452E-04	1.120584E-01	-1.394339E-07
2	G	1.409769E-02	2.949419E-02	5.047241E-01	-2.411610E-01	-2.834068E-02	1.944901E-02
3	G	1.820136E-02	3.543415E-02	5.013046E-01	-1.817772E-01	3.758544E-02	2.826607E-03
4	G	2.108484E-02	3.292170E-02	4.402887E-01	-1.388290E-01	1.487734E-01	-1.134121E-02
5	G	1.893185E-02	2.482368E-02	3.320562E-01	-8.144341E-02	1.349152E-01	-9.209444E-03
6	G	1.201743E-02	1.362113E-02	1.862641E-01	-1.266137E-01	3.335938E-01	-2.696968E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.231432E-02	2.610420E-02	4.789639E-01	-1.785352E-01	-5.512005E-02	2.475539E-02
9	G	1.583249E-02	3.162227E-02	4.620808E-01	-1.364142E-01	5.293924E-02	1.457708E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 400 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.868643E-03	1.465050E-06	4.469080E-01	2.269785E-04	1.256693E-01	1.331924E-06
2	G	1.521143E-02	3.190069E-02	5.246270E-01	-2.513787E-01	-2.930137E-02	2.100135E-02
3	G	1.965705E-02	3.833400E-02	5.210778E-01	-1.893772E-01	3.885837E-02	3.099621E-03
4	G	2.278183E-02	3.562384E-02	4.576691E-01	-1.445992E-01	1.548366E-01	-1.230351E-02
5	G	2.045882E-02	2.686787E-02	3.451637E-01	-8.420940E-02	1.400420E-01	-9.954786E-03
6	G	1.300761E-02	1.475936E-02	1.937229E-01	-1.325838E-01	3.464170E-01	-2.928176E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.328906E-02	2.822400E-02	4.978225E-01	-1.856630E-01	-5.715714E-02	2.676572E-02
9	G	1.709319E-02	3.420053E-02	4.802602E-01	-1.417556E-01	5.494669E-02	1.598363E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 400 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.055259E-02	1.691803E-06	4.628499E-01	2.676033E-04	1.387030E-01	3.221526E-06
2	G	1.628086E-02	3.421618E-02	5.430880E-01	-2.607983E-01	-3.015894E-02	2.249220E-02
3	G	2.105656E-02	4.112605E-02	5.394167E-01	-1.963952E-01	4.002913E-02	3.366856E-03
4	G	2.441499E-02	3.822718E-02	4.737915E-01	-1.499283E-01	1.604486E-01	-1.322949E-02
5	G	2.192957E-02	2.883835E-02	3.573260E-01	-8.678450E-02	1.448065E-01	-1.067376E-02
6	G	1.396248E-02	1.585742E-02	2.006450E-01	-1.381525E-01	3.582700E-01	-3.151833E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.422455E-02	3.026435E-02	5.153232E-01	-1.922499E-01	-5.899432E-02	2.869431E-02
9	G	1.830526E-02	3.668388E-02	4.971303E-01	-1.466819E-01	5.678761E-02	1.738909E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 450 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.379892E-03	7.311164E-08	2.180728E-01	4.583238E-06	-3.564603E-03	-5.839285E-07
2	G	3.688897E-03	7.255931E-03	2.559908E-01	-1.088630E-01	-1.585575E-02	5.151126E-03
3	G	4.707457E-03	8.720363E-03	2.540043E-01	-8.452626E-02	2.206690E-02	4.638024E-04
4	G	5.434502E-03	8.089309E-03	2.230393E-01	-6.462518E-02	7.143810E-02	-2.517711E-03
5	G	4.892296E-03	6.066959E-03	1.683361E-01	-4.672045E-02	7.255284E-02	-2.439747E-03
6	G	2.988612E-03	3.226925E-03	9.306674E-02	-5.271930E-02	1.691831E-01	-6.167647E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.199272E-03	6.513967E-03	2.439357E-01	-8.681699E-02	-2.638813E-02	6.041190E-03
9	G	4.138685E-03	7.882405E-03	2.354764E-01	-6.701649E-02	2.612170E-02	3.912791E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 450 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.738055E-03	1.882692E-07	2.726732E-01	1.801215E-05	1.473438E-02	-1.282869E-06
2	G	5.760032E-03	1.161694E-02	3.206082E-01	-1.435075E-01	-1.888414E-02	7.951583E-03
3	G	7.372047E-03	1.394958E-02	3.182650E-01	-1.097892E-01	2.594177E-02	9.015515E-04
4	G	8.513919E-03	1.294565E-02	2.794884E-01	-8.405951E-02	9.173942E-02	-4.212505E-03
5	G	7.652112E-03	9.732138E-03	2.108834E-01	-5.598137E-02	8.846994E-02	-3.759125E-03
6	G	4.745886E-03	5.244903E-03	1.172817E-01	-7.179528E-02	2.125914E-01	-1.015221E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.009577E-03	1.036703E-02	3.049321E-01	-1.110283E-01	-3.420929E-02	9.711836E-03
9	G	6.452877E-03	1.254015E-02	2.943000E-01	-8.540792E-02	3.335472E-02	5.749034E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 450 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.865836E-03	3.277619E-07	3.112286E-01	3.724157E-05	3.301457E-02	-1.846221E-06
2	G	7.484106E-03	1.527649E-02	3.660582E-01	-1.679138E-01	-2.119611E-02	1.029740E-02
3	G	9.601242E-03	1.833982E-02	3.634581E-01	-1.276698E-01	2.878427E-02	1.277917E-03
4	G	1.109451E-02	1.702225E-02	3.191809E-01	-9.772547E-02	1.059258E-01	-5.659017E-03
5	G	9.964416E-03	1.280789E-02	2.407822E-01	-6.230897E-02	9.982358E-02	-4.868921E-03
6	G	6.227275E-03	6.944221E-03	1.342958E-01	-8.518291E-02	2.428046E-01	-1.353437E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.520138E-03	1.359133E-02	3.478452E-01	-1.278943E-01	-3.959193E-02	1.279484E-02
9	G	8.385642E-03	1.644170E-02	3.356743E-01	-9.820157E-02	3.832860E-02	7.360468E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 450 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.863461E-03	4.845360E-07	3.420333E-01	6.087674E-05	5.049273E-02	-2.173812E-06
2	G	9.013922E-03	1.854048E-02	4.022568E-01	-1.872858E-01	-2.311064E-02	1.239595E-02
3	G	1.158552E-02	2.225816E-02	3.994472E-01	-1.419387E-01	3.111153E-02	1.616829E-03
4	G	1.339451E-02	2.066126E-02	3.507850E-01	-1.085443E-01	1.171616E-01	-6.957519E-03
5	G	1.202585E-02	1.555394E-02	2.645853E-01	-6.729543E-02	1.089492E-01	-5.862878E-03
6	G	7.552375E-03	8.464560E-03	1.478389E-01	-9.583732E-02	2.666810E-01	-1.657355E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.861647E-03	1.646375E-02	3.820367E-01	-1.412446E-01	-4.377534E-02	1.554354E-02
9	G	1.010461E-02	1.992066E-02	3.686340E-01	-1.082946E-01	4.221359E-02	8.882809E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 450 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.772830E-03	6.568052E-07	3.681113E-01	8.826962E-05	6.707528E-02	-2.203164E-06
2	G	1.041356E-02	2.153515E-02	4.328052E-01	-2.034410E-01	-2.472361E-02	1.432748E-02
3	G	1.340398E-02	2.585615E-02	4.298128E-01	-1.538513E-01	3.308154E-02	1.934310E-03
4	G	1.550500E-02	2.400534E-02	3.774584E-01	-1.176024E-01	1.265942E-01	-8.151620E-03
5	G	1.391879E-02	1.807861E-02	2.846797E-01	-7.149711E-02	1.166995E-01	-6.778704E-03
6	G	8.772109E-03	9.864498E-03	1.592715E-01	-1.048526E-01	2.867158E-01	-1.938267E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.088566E-03	1.909938E-02	4.109164E-01	-1.524039E-01	-4.724374E-02	1.806626E-02
9	G	1.167981E-02	2.311617E-02	3.964759E-01	-1.167280E-01	4.545525E-02	1.034728E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 450 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.616600E-03	8.421514E-07	3.909505E-01	1.188821E-04	8.280727E-02	-1.894563E-06
2	G	1.171657E-02	2.433095E-02	4.594893E-01	-2.174399E-01	-2.611815E-02	1.613361E-02
3	G	1.509981E-02	2.921781E-02	4.563334E-01	-1.641997E-01	3.480573E-02	2.235579E-03
4	G	1.747548E-02	2.713175E-02	4.007583E-01	-1.254652E-01	1.348003E-01	-9.267941E-03
5	G	1.568751E-02	2.044010E-02	3.022372E-01	-7.517235E-02	1.235017E-01	-7.636834E-03
6	G	9.914004E-03	1.117559E-02	1.692611E-01	-1.127570E-01	3.041281E-01	-2.202233E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.023046E-02	2.156017E-02	4.361585E-01	-1.620950E-01	-5.020352E-02	2.041841E-02
9	G	1.314859E-02	2.610230E-02	4.208105E-01	-1.240371E-01	4.824972E-02	1.178274E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 450 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.408753E-03	1.039193E-06	4.114064E-01	1.523524E-04	9.776089E-02	-1.219147E-06
2	G	1.294383E-02	2.697088E-02	4.833313E-01	-2.298559E-01	-2.733912E-02	1.783976E-02
3	G	1.669950E-02	3.239441E-02	4.800264E-01	-1.733990E-01	3.634302E-02	2.524841E-03
4	G	1.933636E-02	3.008797E-02	4.215775E-01	-1.324513E-01	1.421077E-01	-1.032281E-02
5	G	1.735922E-02	2.267419E-02	3.179300E-01	-7.846528E-02	1.296018E-01	-8.449771E-03
6	G	1.099504E-02	1.241727E-02	1.781904E-01	-1.198517E-01	3.196166E-01	-2.453006E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.130556E-02	2.388420E-02	4.587249E-01	-1.707115E-01	-5.278263E-02	2.263507E-02
9	G	1.453401E-02	2.892477E-02	4.425653E-01	-1.305220E-01	5.071499E-02	1.320195E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 450 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.158698E-03	1.246889E-06	4.300215E-01	1.884056E-04	1.120098E-01	-1.553577E-07
2	G	1.410935E-02	2.948383E-02	5.049792E-01	-2.410519E-01	-2.841743E-02	1.946298E-02
3	G	1.822086E-02	3.542040E-02	5.015367E-01	-1.817114E-01	3.773203E-02	2.804921E-03
4	G	2.110805E-02	3.290584E-02	4.404820E-01	-1.387622E-01	1.487237E-01	-1.132734E-02
5	G	1.895213E-02	2.480485E-02	3.321836E-01	-8.146521E-02	1.351571E-01	-9.225911E-03
6	G	1.202660E-02	1.360259E-02	1.863017E-01	-1.263258E-01	3.336228E-01	-2.693102E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.232612E-02	2.609704E-02	4.792256E-01	-1.785010E-01	-5.506353E-02	2.474004E-02
9	G	1.585156E-02	3.161426E-02	4.623283E-01	-1.363721E-01	5.292611E-02	1.461242E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 450 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.873153E-03	1.464421E-06	4.471644E-01	2.268256E-04	1.256217E-01	1.313434E-06
2	G	1.522312E-02	3.189040E-02	5.248728E-01	-2.512740E-01	-2.937567E-02	2.101550E-02
3	G	1.967659E-02	3.832032E-02	5.213016E-01	-1.893146E-01	3.899975E-02	3.077804E-03
4	G	2.280509E-02	3.560804E-02	4.578555E-01	-1.445345E-01	1.547885E-01	-1.228956E-02
5	G	2.047917E-02	2.684911E-02	3.452868E-01	-8.423185E-02	1.402746E-01	-9.971236E-03
6	G	1.301681E-02	1.474083E-02	1.937594E-01	-1.323068E-01	3.464457E-01	-2.924314E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.330090E-02	2.821689E-02	4.980745E-01	-1.856306E-01	-5.710305E-02	2.675042E-02
9	G	1.711227E-02	3.419258E-02	4.804986E-01	-1.417155E-01	5.493414E-02	1.601880E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 450 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.055713E-02	1.691123E-06	4.630978E-01	2.674374E-04	1.386564E-01	3.200387E-06
2	G	1.629258E-02	3.420595E-02	5.433258E-01	-2.606972E-01	-3.023108E-02	2.250651E-02
3	G	2.107613E-02	4.111245E-02	5.396332E-01	-1.963353E-01	4.016599E-02	3.344935E-03
4	G	2.443829E-02	3.821145E-02	4.739718E-01	-1.498655E-01	1.604020E-01	-1.321548E-02
5	G	2.194998E-02	2.881965E-02	3.574454E-01	-8.680738E-02	1.450311E-01	-1.069020E-02
6	G	1.397171E-02	1.583891E-02	2.006803E-01	-1.378848E-01	3.582984E-01	-3.147974E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.423641E-02	3.025729E-02	5.155671E-01	-1.922190E-01	-5.894239E-02	2.867907E-02
9	G	1.832437E-02	3.667597E-02	4.973609E-01	-1.466434E-01	5.677561E-02	1.742403E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 500 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.384068E-03	7.291216E-08	2.185965E-01	4.563408E-06	-3.603701E-03	-5.854652E-07
2	G	3.700022E-03	7.246244E-03	2.564931E-01	-1.087304E-01	-1.598692E-02	5.159469E-03
3	G	4.726688E-03	8.707223E-03	2.544610E-01	-8.444023E-02	2.233709E-02	4.453065E-04
4	G	5.457414E-03	8.073675E-03	2.234183E-01	-6.454662E-02	7.136847E-02	-2.508022E-03
5	G	4.911560E-03	6.047737E-03	1.685756E-01	-4.668676E-02	7.302584E-02	-2.456606E-03
6	G	2.997373E-03	3.208845E-03	9.313981E-02	-5.217080E-02	1.692224E-01	-6.130717E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.210887E-03	6.506738E-03	2.444452E-01	-8.676784E-02	-2.627027E-02	6.025924E-03
9	G	4.157424E-03	7.874170E-03	2.359560E-01	-6.694612E-02	2.609726E-02	3.943676E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 500 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.742372E-03	1.838797E-07	2.730900E-01	1.768127E-05	1.468790E-02	-1.282659E-06
2	G	5.771032E-03	1.160762E-02	3.210146E-01	-1.434421E-01	-1.900681E-02	7.961990E-03
3	G	7.391562E-03	1.393682E-02	3.186373E-01	-1.097774E-01	2.617310E-02	8.806915E-04
4	G	8.537259E-03	1.293012E-02	2.797957E-01	-8.400089E-02	9.167722E-02	-4.201985E-03
5	G	7.672146E-03	9.713178E-03	2.110816E-01	-5.599146E-02	8.884928E-02	-3.775878E-03
6	G	4.755110E-03	5.226652E-03	1.173425E-01	-7.136246E-02	2.126325E-01	-1.011580E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.021287E-03	1.035978E-02	3.053391E-01	-1.110195E-01	-3.410549E-02	9.695663E-03
9	G	6.471656E-03	1.253170E-02	2.946809E-01	-8.536322E-02	3.332527E-02	5.786013E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 500 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.870356E-03	3.094987E-07	3.116078E-01	3.588219E-05	3.296534E-02	-1.873760E-06
2	G	7.495740E-03	1.526705E-02	3.664253E-01	-1.678081E-01	-2.130093E-02	1.030973E-02
3	G	9.621022E-03	1.832704E-02	3.637935E-01	-1.276123E-01	2.898657E-02	1.257069E-03
4	G	1.111803E-02	1.700704E-02	3.194594E-01	-9.765361E-02	1.058692E-01	-5.647257E-03
5	G	9.984640E-03	1.278928E-02	2.409637E-01	-6.232030E-02	1.001616E-01	-4.885959E-03
6	G	6.236496E-03	6.926060E-03	1.343523E-01	-8.479369E-02	2.428477E-01	-1.349712E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.532104E-03	1.358457E-02	3.482174E-01	-1.278649E-01	-3.950857E-02	1.277970E-02
9	G	8.404856E-03	1.643408E-02	3.360254E-01	-9.815235E-02	3.830853E-02	7.396855E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 500 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.867814E-03	4.842311E-07	3.423668E-01	6.079773E-05	5.044195E-02	-2.180414E-06
2	G	9.025394E-03	1.853010E-02	4.025754E-01	-1.871589E-01	-2.320392E-02	1.240853E-02
3	G	1.160488E-02	2.224433E-02	3.997368E-01	-1.418603E-01	3.129270E-02	1.595970E-03
4	G	1.341758E-02	2.064528E-02	3.510262E-01	-1.084684E-01	1.171022E-01	-6.944564E-03
5	G	1.204582E-02	1.553487E-02	2.647425E-01	-6.731090E-02	1.092532E-01	-5.879495E-03
6	G	7.561414E-03	8.446063E-03	1.478853E-01	-9.547844E-02	2.667128E-01	-1.653509E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.873347E-03	1.645643E-02	3.823631E-01	-1.412032E-01	-4.370191E-02	1.552797E-02
9	G	1.012355E-02	1.991245E-02	3.689426E-01	-1.082423E-01	4.219606E-02	8.918732E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 500 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.777220E-03	6.564130E-07	3.684214E-01	8.817429E-05	6.702453E-02	-2.211964E-06
2	G	1.042508E-02	2.152477E-02	4.331018E-01	-2.033206E-01	-2.481162E-02	1.434056E-02
3	G	1.342339E-02	2.584235E-02	4.300824E-01	-1.537782E-01	3.325116E-02	1.913114E-03
4	G	1.552811E-02	2.398939E-02	3.776829E-01	-1.175294E-01	1.265378E-01	-8.138334E-03
5	G	1.393886E-02	1.805961E-02	2.848266E-01	-7.151553E-02	1.169822E-01	-6.795271E-03
6	G	8.781188E-03	9.845980E-03	1.593149E-01	-1.045180E-01	2.867466E-01	-1.934411E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.100297E-03	1.909211E-02	4.112203E-01	-1.523654E-01	-4.717573E-02	1.805067E-02
9	G	1.169878E-02	2.310801E-02	3.967631E-01	-1.166792E-01	4.543886E-02	1.038353E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 500 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.621024E-03	8.416990E-07	3.912428E-01	1.187711E-04	8.275703E-02	-1.905620E-06
2	G	1.172813E-02	2.432060E-02	4.597690E-01	-2.173248E-01	-2.620193E-02	1.614707E-02
3	G	1.511926E-02	2.920405E-02	4.565878E-01	-1.641306E-01	3.496630E-02	2.214141E-03
4	G	1.749864E-02	2.711585E-02	4.009701E-01	-1.253948E-01	1.347464E-01	-9.254420E-03
5	G	1.570767E-02	2.042117E-02	3.023763E-01	-7.519259E-02	1.237680E-01	-7.653364E-03
6	G	9.923120E-03	1.115706E-02	1.693021E-01	-1.124411E-01	3.041582E-01	-2.198371E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.024222E-02	2.155294E-02	4.364451E-01	-1.620588E-01	-5.013982E-02	2.040285E-02
9	G	1.316759E-02	2.609419E-02	4.210815E-01	-1.239911E-01	4.823434E-02	1.181902E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 500 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.413209E-03	1.038684E-06	4.116844E-01	1.522265E-04	9.771143E-02	-1.232584E-06
2	G	1.295543E-02	2.696056E-02	4.835976E-01	-2.297454E-01	-2.741941E-02	1.785351E-02
3	G	1.671899E-02	3.238070E-02	4.802687E-01	-1.733332E-01	3.649625E-02	2.503217E-03
4	G	1.935956E-02	3.007211E-02	4.217792E-01	-1.323832E-01	1.420559E-01	-1.030911E-02
5	G	1.737946E-02	2.265533E-02	3.180627E-01	-7.848670E-02	1.298550E-01	-8.466274E-03
6	G	1.100419E-02	1.239874E-02	1.782296E-01	-1.195510E-01	3.196461E-01	-2.449141E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.131735E-02	2.387702E-02	4.589977E-01	-1.706772E-01	-5.272247E-02	2.261956E-02
9	G	1.455304E-02	2.891672E-02	4.428233E-01	-1.304783E-01	5.070049E-02	1.323813E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 500 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.163183E-03	1.246324E-06	4.302878E-01	1.882657E-04	1.119613E-01	-1.712811E-07
2	G	1.412099E-02	2.947355E-02	5.052345E-01	-2.409455E-01	-2.849477E-02	1.947697E-02
3	G	1.824039E-02	3.540674E-02	5.017689E-01	-1.816484E-01	3.787911E-02	2.783149E-03
4	G	2.113130E-02	3.289003E-02	4.406754E-01	-1.386962E-01	1.486738E-01	-1.131351E-02
5	G	1.897243E-02	2.478605E-02	3.323112E-01	-8.148740E-02	1.353994E-01	-9.242395E-03
6	G	1.203578E-02	1.358407E-02	1.863394E-01	-1.260377E-01	3.336518E-01	-2.689236E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.233794E-02	2.608991E-02	4.794872E-01	-1.784683E-01	-5.500634E-02	2.472459E-02
9	G	1.587062E-02	3.160625E-02	4.625756E-01	-1.363304E-01	5.291238E-02	1.464842E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 500 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.877667E-03	1.463802E-06	4.474207E-01	2.266722E-04	1.255741E-01	1.294933E-06
2	G	1.523480E-02	3.188017E-02	5.251188E-01	-2.511711E-01	-2.945046E-02	2.102969E-02
3	G	1.969615E-02	3.830672E-02	5.215254E-01	-1.892541E-01	3.914158E-02	3.055913E-03
4	G	2.282838E-02	3.559228E-02	4.580419E-01	-1.444704E-01	1.547403E-01	-1.227564E-02
5	G	2.049954E-02	2.683038E-02	3.454100E-01	-8.425456E-02	1.405076E-01	-9.987705E-03
6	G	1.302602E-02	1.472232E-02	1.937958E-01	-1.320293E-01	3.464743E-01	-2.920448E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.331274E-02	2.820981E-02	4.983265E-01	-1.855993E-01	-5.704841E-02	2.673504E-02
9	G	1.713137E-02	3.418463E-02	4.807369E-01	-1.416756E-01	5.492110E-02	1.605456E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 500 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.056167E-02	1.690452E-06	4.633456E-01	2.672712E-04	1.386098E-01	3.179228E-06
2	G	1.630429E-02	3.419576E-02	5.435638E-01	-2.605976E-01	-3.030363E-02	2.252086E-02
3	G	2.109572E-02	4.109890E-02	5.398498E-01	-1.962769E-01	4.030324E-02	3.322945E-03
4	G	2.446162E-02	3.819575E-02	4.741523E-01	-1.498032E-01	1.603553E-01	-1.320148E-02
5	G	2.197041E-02	2.880098E-02	3.575647E-01	-8.683044E-02	1.452561E-01	-1.070666E-02
6	G	1.398094E-02	1.582041E-02	2.007157E-01	-1.376165E-01	3.583266E-01	-3.144109E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.424828E-02	3.025026E-02	5.158108E-01	-1.921888E-01	-5.888999E-02	2.866376E-02
9	G	1.834349E-02	3.666808E-02	4.975914E-01	-1.466051E-01	5.676319E-02	1.745951E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 550 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.388267E-03	7.280973E-08	2.191201E-01	4.543870E-06	-3.641889E-03	-5.870224E-07
2	G	3.711288E-03	7.236405E-03	2.569935E-01	-1.085724E-01	-1.611334E-02	5.167950E-03
3	G	4.745899E-03	8.693922E-03	2.549151E-01	-8.432275E-02	2.260252E-02	4.273271E-04
4	G	5.480345E-03	8.058178E-03	2.237973E-01	-6.446496E-02	7.129483E-02	-2.498030E-03
5	G	4.930925E-03	6.028696E-03	1.688163E-01	-4.665829E-02	7.349914E-02	-2.473447E-03
6	G	3.006154E-03	3.190859E-03	9.321354E-02	-5.162504E-02	1.692632E-01	-6.094227E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.222505E-03	6.499638E-03	2.449554E-01	-8.670709E-02	-2.615907E-02	6.011321E-03
9	G	4.176255E-03	7.866195E-03	2.364381E-01	-6.687260E-02	2.607632E-02	3.972538E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 550 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.746633E-03	1.836360E-07	2.735078E-01	1.763768E-05	1.464136E-02	-1.285664E-06
2	G	5.782385E-03	1.159740E-02	3.214133E-01	-1.432966E-01	-1.911722E-02	7.972746E-03
3	G	7.410825E-03	1.392315E-02	3.189994E-01	-1.096807E-01	2.639398E-02	8.611031E-04
4	G	8.560224E-03	1.291427E-02	2.800975E-01	-8.391875E-02	9.160904E-02	-4.190340E-03
5	G	7.691786E-03	9.694032E-03	2.112758E-01	-5.599122E-02	8.922979E-02	-3.792678E-03
6	G	4.763988E-03	5.208339E-03	1.174005E-01	-7.091705E-02	2.126676E-01	-1.007800E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.032929E-03	1.035249E-02	3.057469E-01	-1.109683E-01	-3.401383E-02	9.680378E-03
9	G	6.490520E-03	1.252352E-02	2.950664E-01	-8.530007E-02	3.330480E-02	5.819614E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 550 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.874426E-03	3.275399E-07	3.119546E-01	3.713303E-05	3.291753E-02	-1.855806E-06
2	G	7.506062E-03	1.525750E-02	3.667648E-01	-1.677881E-01	-2.142275E-02	1.032064E-02
3	G	9.640172E-03	1.831387E-02	3.641045E-01	-1.276549E-01	2.920357E-02	1.234053E-03
4	G	1.114087E-02	1.699055E-02	3.197110E-01	-9.759658E-02	1.058083E-01	-5.635855E-03
5	G	1.000419E-02	1.276958E-02	2.411235E-01	-6.233303E-02	1.004918E-01	-4.902317E-03
6	G	6.245314E-03	6.907277E-03	1.343965E-01	-8.439973E-02	2.428685E-01	-1.345797E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.543506E-03	1.357652E-02	3.485531E-01	-1.278752E-01	-3.940127E-02	1.276121E-02
9	G	8.423051E-03	1.642442E-02	3.363362E-01	-9.811316E-02	3.827032E-02	7.442383E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 550 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.872163E-03	4.838752E-07	3.427002E-01	6.071966E-05	5.039133E-02	-2.187198E-06
2	G	9.036882E-03	1.851971E-02	4.028937E-01	-1.870299E-01	-2.329717E-02	1.242118E-02
3	G	1.162423E-02	2.223050E-02	4.000260E-01	-1.417798E-01	3.147392E-02	1.575133E-03
4	G	1.344063E-02	2.062933E-02	3.512670E-01	-1.083917E-01	1.170423E-01	-6.931568E-03
5	G	1.206575E-02	1.551581E-02	2.648995E-01	-6.732607E-02	1.095575E-01	-5.896146E-03
6	G	7.570401E-03	8.427578E-03	1.479316E-01	-9.511843E-02	2.667442E-01	-1.649659E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.885045E-03	1.644914E-02	3.826893E-01	-1.411608E-01	-4.362869E-02	1.551246E-02
9	G	1.014249E-02	1.990429E-02	3.692511E-01	-1.081897E-01	4.217865E-02	8.954583E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 550 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.781608E-03	6.560183E-07	3.687315E-01	8.807931E-05	6.697395E-02	-2.220764E-06
2	G	1.043661E-02	2.151440E-02	4.333981E-01	-2.031991E-01	-2.489968E-02	1.435370E-02
3	G	1.344279E-02	2.582856E-02	4.303518E-01	-1.537039E-01	3.342085E-02	1.891930E-03
4	G	1.555122E-02	2.397347E-02	3.779072E-01	-1.174560E-01	1.264810E-01	-8.125029E-03
5	G	1.395890E-02	1.804062E-02	2.849734E-01	-7.153383E-02	1.172651E-01	-6.811866E-03
6	G	8.790229E-03	9.827474E-03	1.593581E-01	-1.041827E-01	2.867770E-01	-1.930553E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.112027E-03	1.908486E-02	4.115240E-01	-1.523264E-01	-4.710782E-02	1.803513E-02
9	G	1.171776E-02	2.309988E-02	3.970504E-01	-1.166302E-01	4.542249E-02	1.041974E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 550 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.625446E-03	8.412459E-07	3.915350E-01	1.186605E-04	8.270695E-02	-1.916667E-06
2	G	1.173971E-02	2.431026E-02	4.600486E-01	-2.172091E-01	-2.628579E-02	1.616058E-02
3	G	1.513871E-02	2.919030E-02	4.568420E-01	-1.640609E-01	3.512696E-02	2.192709E-03
4	G	1.752179E-02	2.709996E-02	4.011818E-01	-1.253241E-01	1.346922E-01	-9.240888E-03
5	G	1.572781E-02	2.040226E-02	3.025152E-01	-7.521278E-02	1.240344E-01	-7.669917E-03
6	G	9.932203E-03	1.113855E-02	1.693430E-01	-1.121248E-01	3.041880E-01	-2.194508E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.025398E-02	2.154573E-02	4.367316E-01	-1.620223E-01	-5.007617E-02	2.038733E-02
9	G	1.318660E-02	2.608611E-02	4.213524E-01	-1.239450E-01	4.821894E-02	1.185531E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 550 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.417662E-03	1.038174E-06	4.119624E-01	1.521011E-04	9.766211E-02	-1.246004E-06
2	G	1.296705E-02	2.695026E-02	4.838638E-01	-2.296345E-01	-2.749979E-02	1.786730E-02
3	G	1.673847E-02	3.236700E-02	4.805109E-01	-1.732671E-01	3.664955E-02	2.481595E-03
4	G	1.938277E-02	3.005627E-02	4.219809E-01	-1.323149E-01	1.420040E-01	-1.029541E-02
5	G	1.739968E-02	2.263649E-02	3.181954E-01	-7.850809E-02	1.301083E-01	-8.482797E-03
6	G	1.101330E-02	1.238023E-02	1.782687E-01	-1.192498E-01	3.196753E-01	-2.445276E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.132914E-02	2.386986E-02	4.592706E-01	-1.706427E-01	-5.266232E-02	2.260408E-02
9	G	1.457208E-02	2.890869E-02	4.430813E-01	-1.304346E-01	5.068596E-02	1.327433E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 550 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.167667E-03	1.245760E-06	4.305540E-01	1.881262E-04	1.119129E-01	-1.871817E-07
2	G	1.413264E-02	2.946329E-02	5.054896E-01	-2.408388E-01	-2.857219E-02	1.949099E-02
3	G	1.825991E-02	3.539310E-02	5.020012E-01	-1.815853E-01	3.802626E-02	2.761379E-03
4	G	2.115454E-02	3.287424E-02	4.408687E-01	-1.386301E-01	1.486237E-01	-1.129969E-02
5	G	1.899272E-02	2.476727E-02	3.324386E-01	-8.150960E-02	1.356417E-01	-9.258896E-03
6	G	1.204493E-02	1.356556E-02	1.863770E-01	-1.257491E-01	3.336806E-01	-2.685370E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.234975E-02	2.608280E-02	4.797486E-01	-1.784354E-01	-5.494915E-02	2.470917E-02
9	G	1.588969E-02	3.159827E-02	4.628229E-01	-1.362888E-01	5.289862E-02	1.468445E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 550 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.882179E-03	1.463183E-06	4.476770E-01	2.265193E-04	1.255266E-01	1.276459E-06
2	G	1.524648E-02	3.186995E-02	5.253647E-01	-2.510681E-01	-2.952533E-02	2.104390E-02
3	G	1.971570E-02	3.829313E-02	5.217493E-01	-1.891935E-01	3.928346E-02	3.034023E-03
4	G	2.285166E-02	3.557655E-02	4.582283E-01	-1.444063E-01	1.546919E-01	-1.226171E-02
5	G	2.051990E-02	2.681166E-02	3.455330E-01	-8.427729E-02	1.407407E-01	-1.000419E-02
6	G	1.303520E-02	1.470383E-02	1.938321E-01	-1.317515E-01	3.465028E-01	-2.916583E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.332458E-02	2.820274E-02	4.985785E-01	-1.855678E-01	-5.699378E-02	2.671967E-02
9	G	1.715046E-02	3.417670E-02	4.809751E-01	-1.416357E-01	5.490802E-02	1.609035E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 550 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.056621E-02	1.689781E-06	4.635933E-01	2.671055E-04	1.385634E-01	3.158102E-06
2	G	1.631601E-02	3.418560E-02	5.438017E-01	-2.604979E-01	-3.037626E-02	2.253524E-02
3	G	2.111532E-02	4.108538E-02	5.400664E-01	-1.962185E-01	4.044054E-02	3.300956E-03
4	G	2.448494E-02	3.818007E-02	4.743326E-01	-1.497408E-01	1.603085E-01	-1.318749E-02
5	G	2.199082E-02	2.878233E-02	3.576840E-01	-8.685353E-02	1.454813E-01	-1.072313E-02
6	G	1.399016E-02	1.580193E-02	2.007510E-01	-1.373480E-01	3.583548E-01	-3.140245E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.426015E-02	3.024324E-02	5.160545E-01	-1.921587E-01	-5.883757E-02	2.864846E-02
9	G	1.836261E-02	3.666021E-02	4.978218E-01	-1.465668E-01	5.675072E-02	1.749502E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 600 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.392462E-03	7.270886E-08	2.196432E-01	4.524498E-06	-3.679619E-03	-5.885798E-07
2	G	3.722555E-03	7.226671E-03	2.574936E-01	-1.084163E-01	-1.624089E-02	5.176541E-03
3	G	4.765115E-03	8.680749E-03	2.553691E-01	-8.420790E-02	2.286878E-02	4.092935E-04
4	G	5.503282E-03	8.042788E-03	2.241762E-01	-6.438421E-02	7.122042E-02	-2.488084E-03
5	G	4.950272E-03	6.009742E-03	1.690569E-01	-4.663039E-02	7.397334E-02	-2.490305E-03
6	G	3.014871E-03	3.172926E-03	9.328699E-02	-5.107787E-02	1.693034E-01	-6.057856E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.234125E-03	6.492615E-03	2.454651E-01	-8.664764E-02	-2.604723E-02	5.996721E-03
9	G	4.195088E-03	7.858305E-03	2.369195E-01	-6.679972E-02	2.605457E-02	4.001726E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 600 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.750894E-03	1.834546E-07	2.739254E-01	1.759831E-05	1.459519E-02	-1.288709E-06
2	G	5.793739E-03	1.158726E-02	3.218120E-01	-1.431524E-01	-1.922833E-02	7.983570E-03
3	G	7.430095E-03	1.390956E-02	3.193615E-01	-1.095857E-01	2.661547E-02	8.414756E-04
4	G	8.583194E-03	1.289849E-02	2.803992E-01	-8.383708E-02	9.154045E-02	-4.178716E-03
5	G	7.711416E-03	9.674943E-03	2.114699E-01	-5.599129E-02	8.961087E-02	-3.809504E-03
6	G	4.772824E-03	5.190060E-03	1.174583E-01	-7.047077E-02	2.127024E-01	-1.004026E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.044574E-03	1.034526E-02	3.061544E-01	-1.109180E-01	-3.392176E-02	9.665103E-03
9	G	6.509386E-03	1.251540E-02	2.954515E-01	-8.523735E-02	3.328384E-02	5.853473E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 600 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.878764E-03	3.256768E-07	3.123232E-01	3.691364E-05	3.286748E-02	-1.861148E-06
2	G	7.517801E-03	1.524669E-02	3.671125E-01	-1.676054E-01	-2.151464E-02	1.033274E-02
3	G	9.659419E-03	1.829967E-02	3.644191E-01	-1.275174E-01	2.939189E-02	1.214781E-03
4	G	1.116383E-02	1.697468E-02	3.199762E-01	-9.750944E-02	1.057416E-01	-5.622885E-03
5	G	1.002403E-02	1.275060E-02	2.412966E-01	-6.234387E-02	1.008259E-01	-4.919051E-03
6	G	6.254257E-03	6.888930E-03	1.344482E-01	-8.400685E-02	2.429032E-01	-1.342003E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.555189E-03	1.356934E-02	3.489141E-01	-1.278066E-01	-3.933070E-02	1.274671E-02
9	G	8.442115E-03	1.641659E-02	3.366800E-01	-9.804896E-02	3.825825E-02	7.473653E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 600 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.876515E-03	4.835413E-07	3.430334E-01	6.064158E-05	5.034099E-02	-2.193907E-06
2	G	9.048359E-03	1.850940E-02	4.032121E-01	-1.869034E-01	-2.339103E-02	1.243385E-02
3	G	1.164360E-02	2.221677E-02	4.003155E-01	-1.417021E-01	3.165558E-02	1.554242E-03
4	G	1.346370E-02	2.061343E-02	3.515081E-01	-1.083160E-01	1.169823E-01	-6.918628E-03
5	G	1.208569E-02	1.549680E-02	2.650566E-01	-6.734176E-02	1.098621E-01	-5.912810E-03
6	G	7.579378E-03	8.409121E-03	1.479779E-01	-9.475838E-02	2.667755E-01	-1.645817E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.896750E-03	1.644189E-02	3.830154E-01	-1.411198E-01	-4.355496E-02	1.549690E-02
9	G	1.016143E-02	1.989615E-02	3.695593E-01	-1.081376E-01	4.216071E-02	8.990810E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 600 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.785997E-03	6.556292E-07	3.690414E-01	8.798464E-05	6.692357E-02	-2.229545E-06
2	G	1.044814E-02	2.150409E-02	4.336945E-01	-2.030790E-01	-2.498815E-02	1.436687E-02
3	G	1.346220E-02	2.581484E-02	4.306213E-01	-1.536314E-01	3.359086E-02	1.870709E-03
4	G	1.557434E-02	2.395759E-02	3.781316E-01	-1.173831E-01	1.264242E-01	-8.111755E-03
5	G	1.397896E-02	1.802168E-02	2.851202E-01	-7.155243E-02	1.175483E-01	-6.828476E-03
6	G	8.799255E-03	9.808990E-03	1.594013E-01	-1.038471E-01	2.868074E-01	-1.926699E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.123760E-03	1.907763E-02	4.118276E-01	-1.522883E-01	-4.703957E-02	1.801957E-02
9	G	1.173673E-02	2.309178E-02	3.973374E-01	-1.165816E-01	4.540577E-02	1.045624E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 600 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.629870E-03	8.407970E-07	3.918271E-01	1.185501E-04	8.265704E-02	-1.927697E-06
2	G	1.175128E-02	2.429996E-02	4.603282E-01	-2.170943E-01	-2.636996E-02	1.617411E-02
3	G	1.515816E-02	2.917661E-02	4.570964E-01	-1.639923E-01	3.528786E-02	2.171247E-03
4	G	1.754496E-02	2.708412E-02	4.013935E-01	-1.252538E-01	1.346379E-01	-9.227378E-03
5	G	1.574795E-02	2.038338E-02	3.026541E-01	-7.523316E-02	1.243012E-01	-7.686487E-03
6	G	9.941270E-03	1.112005E-02	1.693839E-01	-1.118081E-01	3.042177E-01	-2.190648E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.026575E-02	2.153855E-02	4.370181E-01	-1.619864E-01	-5.001226E-02	2.037179E-02
9	G	1.320561E-02	2.607806E-02	4.216233E-01	-1.238992E-01	4.820328E-02	1.189183E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 600 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.422118E-03	1.037668E-06	4.122403E-01	1.519759E-04	9.761293E-02	-1.259408E-06
2	G	1.297866E-02	2.693999E-02	4.841300E-01	-2.295242E-01	-2.758041E-02	1.788112E-02
3	G	1.675797E-02	3.235335E-02	4.807531E-01	-1.732017E-01	3.680306E-02	2.459951E-03
4	G	1.940597E-02	3.004047E-02	4.221825E-01	-1.322469E-01	1.419519E-01	-1.028173E-02
5	G	1.741990E-02	2.261767E-02	3.183280E-01	-7.852962E-02	1.303618E-01	-8.499337E-03
6	G	1.102241E-02	1.236173E-02	1.783077E-01	-1.189483E-01	3.197044E-01	-2.441412E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.134093E-02	2.386272E-02	4.595433E-01	-1.706086E-01	-5.260197E-02	2.258859E-02
9	G	1.459112E-02	2.890068E-02	4.433392E-01	-1.303911E-01	5.067121E-02	1.331074E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 600 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.172152E-03	1.245198E-06	4.308202E-01	1.879870E-04	1.118645E-01	-2.030653E-07
2	G	1.414429E-02	2.945306E-02	5.057449E-01	-2.407325E-01	-2.864981E-02	1.950504E-02
3	G	1.827944E-02	3.537950E-02	5.022334E-01	-1.815227E-01	3.817359E-02	2.739589E-03
4	G	2.117779E-02	3.285848E-02	4.410621E-01	-1.385642E-01	1.485736E-01	-1.128587E-02
5	G	1.901301E-02	2.474851E-02	3.325661E-01	-8.153189E-02	1.358843E-01	-9.275415E-03
6	G	1.205407E-02	1.354707E-02	1.864146E-01	-1.254603E-01	3.337093E-01	-2.681505E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.236157E-02	2.607570E-02	4.800101E-01	-1.784029E-01	-5.489179E-02	2.469373E-02
9	G	1.590876E-02	3.159032E-02	4.630701E-01	-1.362472E-01	5.288468E-02	1.472065E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 600 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.886692E-03	1.462568E-06	4.479332E-01	2.263666E-04	1.254793E-01	1.258004E-06
2	G	1.525817E-02	3.185976E-02	5.256106E-01	-2.509654E-01	-2.960037E-02	2.105814E-02
3	G	1.973527E-02	3.827958E-02	5.219731E-01	-1.891333E-01	3.942550E-02	3.012115E-03
4	G	2.287495E-02	3.556084E-02	4.584146E-01	-1.443423E-01	1.546435E-01	-1.224780E-02
5	G	2.054025E-02	2.679296E-02	3.456561E-01	-8.430009E-02	1.409740E-01	-1.002069E-02
6	G	1.304437E-02	1.468534E-02	1.938684E-01	-1.314733E-01	3.465311E-01	-2.912717E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.333643E-02	2.819569E-02	4.988303E-01	-1.855366E-01	-5.693899E-02	2.670430E-02
9	G	1.716956E-02	3.416880E-02	4.812133E-01	-1.415959E-01	5.489479E-02	1.612629E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 600 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.057075E-02	1.689114E-06	4.638410E-01	2.669399E-04	1.385170E-01	3.136995E-06
2	G	1.632773E-02	3.417546E-02	5.440395E-01	-2.603984E-01	-3.044904E-02	2.254963E-02
3	G	2.113491E-02	4.107188E-02	5.402830E-01	-1.961604E-01	4.057798E-02	3.278951E-03
4	G	2.450827E-02	3.816441E-02	4.745129E-01	-1.496785E-01	1.602615E-01	-1.317350E-02
5	G	2.201124E-02	2.876369E-02	3.578033E-01	-8.687668E-02	1.457065E-01	-1.073962E-02
6	G	1.399935E-02	1.578345E-02	2.007862E-01	-1.370792E-01	3.583828E-01	-3.136380E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.427202E-02	3.023623E-02	5.162981E-01	-1.921286E-01	-5.878504E-02	2.863316E-02
9	G	1.838174E-02	3.665235E-02	4.980522E-01	-1.465286E-01	5.673813E-02	1.753068E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 650 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.396631E-03	7.263070E-08	2.201649E-01	4.494810E-06	-3.724009E-03	-5.894872E-07
2	G	3.733338E-03	7.218203E-03	2.580023E-01	-1.083646E-01	-1.638951E-02	5.185166E-03
3	G	4.784567E-03	8.669081E-03	2.558362E-01	-8.422542E-02	2.315117E-02	3.893589E-04
4	G	5.526516E-03	8.027871E-03	2.245599E-01	-6.433925E-02	7.115740E-02	-2.479697E-03
5	G	4.969585E-03	5.990875E-03	1.692969E-01	-4.660303E-02	7.445305E-02	-2.507282E-03
6	G	3.023440E-03	3.155019E-03	9.335927E-02	-5.052365E-02	1.693404E-01	-6.021464E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.245792E-03	6.485679E-03	2.459721E-01	-8.664273E-02	-2.591172E-02	5.979973E-03
9	G	4.213694E-03	7.850059E-03	2.373919E-01	-6.675060E-02	2.601795E-02	4.038124E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 650 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.755158E-03	1.827819E-07	2.743428E-01	1.752449E-05	1.454940E-02	-1.291294E-06
2	G	5.805083E-03	1.157723E-02	3.222111E-01	-1.430128E-01	-1.934065E-02	7.994456E-03
3	G	7.449385E-03	1.389610E-02	3.197241E-01	-1.094957E-01	2.683798E-02	8.217559E-04
4	G	8.606188E-03	1.288280E-02	2.807012E-01	-8.375679E-02	9.147172E-02	-4.167160E-03
5	G	7.731054E-03	9.655923E-03	2.116642E-01	-5.599204E-02	8.999249E-02	-3.826357E-03
6	G	4.781630E-03	5.171821E-03	1.175161E-01	-7.002407E-02	2.127371E-01	-1.000262E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.056229E-03	1.033808E-02	3.065618E-01	-1.108703E-01	-3.382880E-02	9.649805E-03
9	G	6.528255E-03	1.250733E-02	2.958363E-01	-8.517576E-02	3.326204E-02	5.887747E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 650 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.883074E-03	3.267453E-07	3.126891E-01	3.700026E-05	3.281844E-02	-1.865612E-06
2	G	7.529245E-03	1.523643E-02	3.674615E-01	-1.674676E-01	-2.161526E-02	1.034477E-02
3	G	9.678734E-03	1.828597E-02	3.647362E-01	-1.274290E-01	2.958900E-02	1.194421E-03
4	G	1.118685E-02	1.695884E-02	3.202405E-01	-9.742996E-02	1.056772E-01	-5.610404E-03
5	G	1.004384E-02	1.273155E-02	2.414681E-01	-6.235462E-02	1.011606E-01	-4.935806E-03
6	G	6.263141E-03	6.870555E-03	1.344988E-01	-8.361237E-02	2.429356E-01	-1.338188E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.566865E-03	1.356211E-02	3.492717E-01	-1.277603E-01	-3.925017E-02	1.273128E-02
9	G	8.461031E-03	1.640850E-02	3.370182E-01	-9.799194E-02	3.823913E-02	7.509108E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 650 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.880866E-03	4.832229E-07	3.433665E-01	6.056406E-05	5.029088E-02	-2.200558E-06
2	G	9.059840E-03	1.849913E-02	4.035305E-01	-1.867773E-01	-2.348521E-02	1.244656E-02
3	G	1.166297E-02	2.220309E-02	4.006049E-01	-1.416249E-01	3.183750E-02	1.533332E-03
4	G	1.348678E-02	2.059755E-02	3.517490E-01	-1.082404E-01	1.169221E-01	-6.905696E-03
5	G	1.210563E-02	1.547782E-02	2.652135E-01	-6.735756E-02	1.101670E-01	-5.929497E-03
6	G	7.588326E-03	8.390685E-03	1.480241E-01	-9.439775E-02	2.668065E-01	-1.641976E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.908457E-03	1.643467E-02	3.833414E-01	-1.410791E-01	-4.348105E-02	1.548135E-02
9	G	1.018037E-02	1.988805E-02	3.698675E-01	-1.080857E-01	4.214255E-02	9.027202E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 650 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.790385E-03	6.552416E-07	3.693512E-01	8.789029E-05	6.687338E-02	-2.238316E-06
2	G	1.045967E-02	2.149381E-02	4.339908E-01	-2.029590E-01	-2.507686E-02	1.438007E-02
3	G	1.348162E-02	2.580116E-02	4.308907E-01	-1.535591E-01	3.376107E-02	1.849474E-03
4	G	1.559746E-02	2.394175E-02	3.783560E-01	-1.173103E-01	1.263671E-01	-8.098488E-03
5	G	1.399900E-02	1.800276E-02	2.852669E-01	-7.157112E-02	1.178317E-01	-6.845107E-03
6	G	8.808253E-03	9.790523E-03	1.594444E-01	-1.035110E-01	2.868376E-01	-1.922846E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.135497E-03	1.907044E-02	4.121312E-01	-1.522503E-01	-4.697121E-02	1.800401E-02
9	G	1.175571E-02	2.308371E-02	3.976243E-01	-1.165331E-01	4.538889E-02	1.049287E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 650 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.634292E-03	8.403499E-07	3.921192E-01	1.184401E-04	8.260728E-02	-1.938713E-06
2	G	1.176285E-02	2.428970E-02	4.606077E-01	-2.169795E-01	-2.645431E-02	1.618767E-02
3	G	1.517761E-02	2.916295E-02	4.573506E-01	-1.639239E-01	3.544893E-02	2.149775E-03
4	G	1.756812E-02	2.706830E-02	4.016052E-01	-1.251836E-01	1.345835E-01	-9.213874E-03
5	G	1.576809E-02	2.036452E-02	3.027930E-01	-7.525361E-02	1.245681E-01	-7.703077E-03
6	G	9.950313E-03	1.110157E-02	1.694247E-01	-1.114910E-01	3.042472E-01	-2.186788E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.027751E-02	2.153139E-02	4.373045E-01	-1.619506E-01	-4.994826E-02	2.035625E-02
9	G	1.322462E-02	2.607003E-02	4.218940E-01	-1.238534E-01	4.818748E-02	1.192846E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 650 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.426571E-03	1.037163E-06	4.125181E-01	1.518511E-04	9.756389E-02	-1.272794E-06
2	G	1.299027E-02	2.692975E-02	4.843962E-01	-2.294141E-01	-2.766119E-02	1.789497E-02
3	G	1.677746E-02	3.233973E-02	4.809952E-01	-1.731366E-01	3.695671E-02	2.438296E-03
4	G	1.942918E-02	3.002469E-02	4.223841E-01	-1.321790E-01	1.418997E-01	-1.026805E-02
5	G	1.744011E-02	2.259867E-02	3.184606E-01	-7.855121E-02	1.306155E-01	-8.515896E-03
6	G	1.103149E-02	1.234325E-02	1.783467E-01	-1.186465E-01	3.197334E-01	-2.437549E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.135272E-02	2.385560E-02	4.598160E-01	-1.705746E-01	-5.254154E-02	2.257310E-02
9	G	1.461016E-02	2.889270E-02	4.435970E-01	-1.303476E-01	5.065635E-02	1.334724E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 650 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.176636E-03	1.244638E-06	4.310863E-01	1.878480E-04	1.118164E-01	-2.189290E-07
2	G	1.415594E-02	2.944286E-02	5.060000E-01	-2.406263E-01	-2.872758E-02	1.951911E-02
3	G	1.829896E-02	3.536592E-02	5.024656E-01	-1.814603E-01	3.832103E-02	2.717790E-03
4	G	2.120104E-02	3.284275E-02	4.412554E-01	-1.384984E-01	1.485233E-01	-1.127207E-02
5	G	1.903330E-02	2.472978E-02	3.326935E-01	-8.155423E-02	1.361270E-01	-9.291951E-03
6	G	1.206319E-02	1.352859E-02	1.864521E-01	-1.251711E-01	3.337378E-01	-2.677640E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.237339E-02	2.606863E-02	4.802715E-01	-1.783704E-01	-5.483436E-02	2.467830E-02
9	G	1.592783E-02	3.158239E-02	4.633172E-01	-1.362057E-01	5.287063E-02	1.475695E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 650 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.891205E-03	1.461955E-06	4.481894E-01	2.262143E-04	1.254320E-01	1.239571E-06
2	G	1.526986E-02	3.184960E-02	5.258564E-01	-2.508627E-01	-2.967553E-02	2.107240E-02
3	G	1.975483E-02	3.826606E-02	5.221969E-01	-1.890732E-01	3.956765E-02	2.990199E-03
4	G	2.289824E-02	3.554516E-02	4.586009E-01	-1.442783E-01	1.545949E-01	-1.223389E-02
5	G	2.056060E-02	2.677428E-02	3.457791E-01	-8.432294E-02	1.412075E-01	-1.003721E-02
6	G	1.305352E-02	1.466686E-02	1.939047E-01	-1.311949E-01	3.465592E-01	-2.908852E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.334827E-02	2.818866E-02	4.990821E-01	-1.855055E-01	-5.688414E-02	2.668894E-02
9	G	1.718866E-02	3.416091E-02	4.814514E-01	-1.415562E-01	5.488146E-02	1.616233E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 650 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.057529E-02	1.688448E-06	4.640886E-01	2.667747E-04	1.384707E-01	3.115913E-06
2	G	1.633945E-02	3.416533E-02	5.442774E-01	-2.602990E-01	-3.052193E-02	2.256406E-02
3	G	2.115451E-02	4.105841E-02	5.404996E-01	-1.961025E-01	4.071552E-02	3.256938E-03
4	G	2.453160E-02	3.814878E-02	4.746933E-01	-1.496163E-01	1.602145E-01	-1.315951E-02
5	G	2.203165E-02	2.874507E-02	3.579225E-01	-8.689986E-02	1.459319E-01	-1.075613E-02
6	G	1.400853E-02	1.576498E-02	2.008214E-01	-1.368101E-01	3.584107E-01	-3.132516E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.428389E-02	3.022925E-02	5.165417E-01	-1.920987E-01	-5.873244E-02	2.861787E-02
9	G	1.840086E-02	3.664452E-02	4.982825E-01	-1.464904E-01	5.672544E-02	1.756643E-03

LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 700 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.400796E-03	7.251109E-08	2.206867E-01	4.494347E-06	-3.746119E-03	-5.919482E-07
2	G	3.744928E-03	7.207649E-03	2.584939E-01	-1.081356E-01	-1.650461E-02	5.193141E-03
3	G	4.803563E-03	8.654914E-03	2.562785E-01	-8.401910E-02	2.340826E-02	3.729377E-04
4	G	5.549120E-03	8.012180E-03	2.249325E-01	-6.422967E-02	7.107346E-02	-2.469299E-03
5	G	4.988766E-03	5.971931E-03	1.695355E-01	-4.656918E-02	7.492381E-02	-2.523085E-03
6	G	3.032032E-03	3.137155E-03	9.343208E-02	-4.997508E-02	1.693791E-01	-5.978626E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.257347E-03	6.478677E-03	2.464812E-01	-8.654481E-02	-2.581581E-02	5.967109E-03
9	G	4.232634E-03	7.842526E-03	2.378772E-01	-6.665990E-02	2.600576E-02	4.060643E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 700 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.759353E-03	2.111261E-07	2.747613E-01	1.944848E-05	1.450293E-02	-1.318511E-06
2	G	5.816979E-03	1.156576E-02	3.225980E-01	-1.427488E-01	-1.943334E-02	8.005741E-03
3	G	7.468268E-03	1.388118E-02	3.200709E-01	-1.092736E-01	2.704347E-02	8.041790E-04
4	G	8.628608E-03	1.286661E-02	2.809948E-01	-8.364225E-02	9.139358E-02	-4.153945E-03
5	G	7.750126E-03	9.636614E-03	2.118528E-01	-5.597922E-02	9.037520E-02	-3.843276E-03
6	G	4.789955E-03	5.153475E-03	1.175702E-01	-6.956083E-02	2.127638E-01	-9.963267E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.067773E-03	1.033084E-02	3.069702E-01	-1.107574E-01	-3.375575E-02	9.636107E-03
9	G	6.547260E-03	1.249966E-02	2.962277E-01	-8.508676E-02	3.325507E-02	5.915537E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 700 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.887389E-03	3.354119E-07	3.130583E-01	3.760235E-05	3.276815E-02	-1.859002E-06
2	G	7.541316E-03	1.522489E-02	3.678037E-01	-1.672227E-01	-2.169714E-02	1.035714E-02
3	G	9.697783E-03	1.827105E-02	3.650435E-01	-1.272249E-01	2.976806E-02	1.176383E-03
4	G	1.120956E-02	1.694284E-02	3.205025E-01	-9.732803E-02	1.056052E-01	-5.596571E-03
5	G	1.006348E-02	1.271258E-02	2.416396E-01	-6.236218E-02	1.014952E-01	-4.952566E-03
6	G	6.271870E-03	6.852221E-03	1.345493E-01	-8.321395E-02	2.429681E-01	-1.334345E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.578496E-03	1.355499E-02	3.496337E-01	-1.276608E-01	-3.919065E-02	1.271779E-02
9	G	8.480207E-03	1.640101E-02	3.373659E-01	-9.791594E-02	3.823468E-02	7.536215E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 700 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.885221E-03	4.828740E-07	3.436994E-01	6.048769E-05	5.024106E-02	-2.207328E-06
2	G	9.071305E-03	1.848895E-02	4.038491E-01	-1.866545E-01	-2.358011E-02	1.245930E-02
3	G	1.168236E-02	2.218951E-02	4.008946E-01	-1.415514E-01	3.202000E-02	1.512347E-03
4	G	1.350987E-02	2.058179E-02	3.519902E-01	-1.081658E-01	1.168618E-01	-6.892829E-03
5	G	1.212559E-02	1.545890E-02	2.653707E-01	-6.737387E-02	1.104721E-01	-5.946197E-03
6	G	7.597264E-03	8.372276E-03	1.480703E-01	-9.403708E-02	2.668376E-01	-1.638143E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.920173E-03	1.642749E-02	3.836672E-01	-1.410402E-01	-4.340646E-02	1.546573E-02
9	G	1.019932E-02	1.987998E-02	3.701754E-01	-1.080345E-01	4.212375E-02	9.064068E-04

FIVE TENTHS, 700 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.794775E-03	6.548590E-07	3.696609E-01	8.779628E-05	6.682339E-02	-2.247071E-06
2	G	1.047119E-02	2.148359E-02	4.342872E-01	-2.028406E-01	-2.516597E-02	1.439329E-02
3	G	1.350104E-02	2.578754E-02	4.311603E-01	-1.534885E-01	3.393159E-02	1.828201E-03
4	G	1.562059E-02	2.392595E-02	3.785804E-01	-1.172380E-01	1.263099E-01	-8.085255E-03
5	G	1.401906E-02	1.798388E-02	2.854137E-01	-7.159010E-02	1.181153E-01	-6.861753E-03
6	G	8.817239E-03	9.772078E-03	1.594875E-01	-1.031748E-01	2.868677E-01	-1.918997E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.147238E-03	1.906328E-02	4.124345E-01	-1.522132E-01	-4.690250E-02	1.798842E-02
9	G	1.177469E-02	2.307567E-02	3.979111E-01	-1.164849E-01	4.537165E-02	1.052979E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 700 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.638715E-03	8.399069E-07	3.924111E-01	1.183303E-04	8.255768E-02	-1.949713E-06
2	G	1.177442E-02	2.427948E-02	4.608873E-01	-2.168658E-01	-2.653898E-02	1.620126E-02
3	G	1.519707E-02	2.914934E-02	4.576049E-01	-1.638566E-01	3.561024E-02	2.128274E-03
4	G	1.759129E-02	2.705253E-02	4.018169E-01	-1.251136E-01	1.345289E-01	-9.200392E-03
5	G	1.578823E-02	2.034569E-02	3.029319E-01	-7.527426E-02	1.248352E-01	-7.719683E-03
6	G	9.959340E-03	1.108311E-02	1.694655E-01	-1.111736E-01	3.042766E-01	-2.182931E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.028928E-02	2.152426E-02	4.375907E-01	-1.619153E-01	-4.988401E-02	2.034070E-02
9	G	1.324363E-02	2.606203E-02	4.221647E-01	-1.238078E-01	4.817142E-02	1.196533E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 700 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.431026E-03	1.036662E-06	4.127959E-01	1.517265E-04	9.751497E-02	-1.286165E-06
2	G	1.300189E-02	2.691955E-02	4.846623E-01	-2.293046E-01	-2.774222E-02	1.790884E-02
3	G	1.679695E-02	3.232615E-02	4.812374E-01	-1.730722E-01	3.711055E-02	2.416618E-03
4	G	1.945239E-02	3.000895E-02	4.225858E-01	-1.321113E-01	1.418473E-01	-1.025439E-02
5	G	1.746033E-02	2.258009E-02	3.185932E-01	-7.857293E-02	1.308694E-01	-8.532472E-03
6	G	1.104056E-02	1.232478E-02	1.783857E-01	-1.183443E-01	3.197623E-01	-2.433687E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.136452E-02	2.384851E-02	4.600886E-01	-1.705410E-01	-5.248091E-02	2.255760E-02
9	G	1.462920E-02	2.888474E-02	4.438547E-01	-1.303043E-01	5.064128E-02	1.338395E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 700 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.181120E-03	1.244082E-06	4.313523E-01	1.877094E-04	1.117683E-01	-2.347758E-07
2	G	1.416760E-02	2.943268E-02	5.062551E-01	-2.405206E-01	-2.880555E-02	1.953322E-02
3	G	1.831850E-02	3.535238E-02	5.026978E-01	-1.813984E-01	3.846865E-02	2.695971E-03
4	G	2.122429E-02	3.282705E-02	4.414487E-01	-1.384327E-01	1.484729E-01	-1.125827E-02
5	G	1.905358E-02	2.471106E-02	3.328209E-01	-8.157667E-02	1.363699E-01	-9.308504E-03
6	G	1.207229E-02	1.351012E-02	1.864895E-01	-1.248816E-01	3.337662E-01	-2.673776E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.238521E-02	2.606158E-02	4.805328E-01	-1.783383E-01	-5.477677E-02	2.466286E-02
9	G	1.594690E-02	3.157447E-02	4.635643E-01	-1.361644E-01	5.285641E-02	1.479342E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 700 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.895717E-03	1.461344E-06	4.484455E-01	2.260622E-04	1.253849E-01	1.221156E-06
2	G	1.528154E-02	3.183946E-02	5.261022E-01	-2.507605E-01	-2.975088E-02	2.108669E-02
3	G	1.977440E-02	3.825257E-02	5.224206E-01	-1.890136E-01	3.970994E-02	2.968265E-03
4	G	2.292153E-02	3.552950E-02	4.587873E-01	-1.442145E-01	1.545462E-01	-1.221999E-02
5	G	2.058095E-02	2.675563E-02	3.459021E-01	-8.434586E-02	1.414411E-01	-1.005375E-02
6	G	1.306265E-02	1.464840E-02	1.939409E-01	-1.309162E-01	3.465873E-01	-2.904987E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.336012E-02	2.818165E-02	4.993339E-01	-1.854746E-01	-5.682915E-02	2.667357E-02
9	G	1.720776E-02	3.415305E-02	4.816894E-01	-1.415165E-01	5.486799E-02	1.619853E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 700 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.057990E-02	1.687764E-06	4.643387E-01	2.666049E-04	1.384259E-01	3.095127E-06
2	G	1.635127E-02	3.415544E-02	5.445182E-01	-2.602017E-01	-3.059519E-02	2.257865E-02
3	G	2.117423E-02	4.104521E-02	5.407192E-01	-1.960463E-01	4.085343E-02	3.234898E-03
4	G	2.455507E-02	3.813339E-02	4.748762E-01	-1.495552E-01	1.601683E-01	-1.314569E-02
5	G	2.205218E-02	2.872662E-02	3.580437E-01	-8.692354E-02	1.461583E-01	-1.077274E-02
6	G	1.401778E-02	1.574662E-02	2.008577E-01	-1.365416E-01	3.584404E-01	-3.128687E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.429585E-02	3.022246E-02	5.167881E-01	-1.920702E-01	-5.868009E-02	2.860277E-02
9	G	1.842009E-02	3.663691E-02	4.985155E-01	-1.464532E-01	5.671296E-02	1.760213E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 750 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.405020E-03	7.243550E-08	2.212085E-01	4.454281E-06	-3.798146E-03	-5.925373E-07
2	G	3.755897E-03	7.199269E-03	2.590016E-01	-1.080606E-01	-1.665000E-02	5.202679E-03
3	G	4.823062E-03	8.643380E-03	2.567441E-01	-8.400698E-02	2.368721E-02	3.532889E-04
4	G	5.572481E-03	7.997682E-03	2.253179E-01	-6.418441E-02	7.100501E-02	-2.459743E-03
5	G	5.008277E-03	5.953457E-03	1.697781E-01	-4.655251E-02	7.540581E-02	-2.541144E-03
6	G	3.040609E-03	3.119446E-03	9.350540E-02	-4.942478E-02	1.694186E-01	-5.949086E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.269059E-03	6.472060E-03	2.469896E-01	-8.653062E-02	-2.568689E-02	5.951175E-03
9	G	4.251397E-03	7.834758E-03	2.383526E-01	-6.660961E-02	2.597188E-02	4.097794E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 750 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.763608E-03	2.090071E-07	2.751781E-01	1.927368E-05	1.445781E-02	-1.320034E-06
2	G	5.828347E-03	1.155579E-02	3.229961E-01	-1.426058E-01	-1.954606E-02	8.016753E-03
3	G	7.487546E-03	1.386781E-02	3.204326E-01	-1.091806E-01	2.726624E-02	7.845075E-04
4	G	8.651583E-03	1.285102E-02	2.812962E-01	-8.356129E-02	9.132352E-02	-4.142356E-03
5	G	7.769720E-03	9.617686E-03	2.120466E-01	-5.598005E-02	9.075785E-02	-3.860175E-03
6	G	4.798657E-03	5.135298E-03	1.176275E-01	-6.911182E-02	2.127973E-01	-9.925666E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.079425E-03	1.032375E-02	3.073770E-01	-1.107083E-01	-3.366301E-02	9.620905E-03
9	G	6.566137E-03	1.249172E-02	2.966121E-01	-8.502465E-02	3.323302E-02	5.949977E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 750 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.891691E-03	3.133195E-07	3.134237E-01	3.590163E-05	3.271918E-02	-1.889497E-06
2	G	7.552533E-03	1.521530E-02	3.681568E-01	-1.671305E-01	-2.180711E-02	1.036926E-02
3	G	9.717239E-03	1.825805E-02	3.653658E-01	-1.271872E-01	2.997446E-02	1.154967E-03
4	G	1.123270E-02	1.692721E-02	3.207683E-01	-9.725703E-02	1.055439E-01	-5.584661E-03
5	G	1.008327E-02	1.269364E-02	2.418109E-01	-6.237239E-02	1.018319E-01	-4.969445E-03
6	G	6.280672E-03	6.833890E-03	1.345996E-01	-8.281651E-02	2.429993E-01	-1.330514E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.590212E-03	1.354785E-02	3.499905E-01	-1.276373E-01	-3.910023E-02	1.270160E-02
9	G	8.499039E-03	1.639283E-02	3.377010E-01	-9.786676E-02	3.820858E-02	7.575958E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 750 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.889570E-03	4.826184E-07	3.440323E-01	6.040931E-05	5.019139E-02	-2.213748E-06
2	G	9.082793E-03	1.847876E-02	4.041672E-01	-1.865286E-01	-2.367481E-02	1.247210E-02
3	G	1.170173E-02	2.217591E-02	4.011839E-01	-1.414748E-01	3.220236E-02	1.491414E-03
4	G	1.353295E-02	2.056602E-02	3.522310E-01	-1.080904E-01	1.168011E-01	-6.879908E-03
5	G	1.214551E-02	1.543999E-02	2.655276E-01	-6.738991E-02	1.107776E-01	-5.962927E-03
6	G	7.606151E-03	8.353881E-03	1.481163E-01	-9.367534E-02	2.668682E-01	-1.634306E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.931883E-03	1.642033E-02	3.839930E-01	-1.409999E-01	-4.333232E-02	1.545021E-02
9	G	1.021827E-02	1.987195E-02	3.704833E-01	-1.079828E-01	4.210523E-02	9.100715E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 750 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.799162E-03	6.544758E-07	3.699705E-01	8.770252E-05	6.677356E-02	-2.255820E-06
2	G	1.048272E-02	2.147338E-02	4.345834E-01	-2.027209E-01	-2.525512E-02	1.440657E-02
3	G	1.352046E-02	2.577394E-02	4.314297E-01	-1.534168E-01	3.410217E-02	1.806941E-03
4	G	1.564371E-02	2.391018E-02	3.788046E-01	-1.171654E-01	1.262524E-01	-8.072000E-03
5	G	1.403909E-02	1.796501E-02	2.855604E-01	-7.160895E-02	1.183992E-01	-6.878426E-03
6	G	8.826184E-03	9.753646E-03	1.595305E-01	-1.028378E-01	2.868975E-01	-1.915147E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.158978E-03	1.905614E-02	4.127379E-01	-1.521756E-01	-4.683390E-02	1.797288E-02
9	G	1.179367E-02	2.306767E-02	3.981979E-01	-1.164365E-01	4.535444E-02	1.056667E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 750 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.643136E-03	8.394632E-07	3.927030E-01	1.182209E-04	8.250824E-02	-1.960703E-06
2	G	1.178600E-02	2.426927E-02	4.611667E-01	-2.167513E-01	-2.662371E-02	1.621490E-02
3	G	1.521653E-02	2.913576E-02	4.578591E-01	-1.637887E-01	3.577162E-02	2.106780E-03
4	G	1.761446E-02	2.703677E-02	4.020285E-01	-1.250436E-01	1.344741E-01	-9.186900E-03
5	G	1.580835E-02	2.032688E-02	3.030707E-01	-7.529485E-02	1.251025E-01	-7.736312E-03
6	G	9.968336E-03	1.106466E-02	1.695062E-01	-1.108557E-01	3.043057E-01	-2.179073E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.030105E-02	2.151715E-02	4.378770E-01	-1.618798E-01	-4.981981E-02	2.032519E-02
9	G	1.326264E-02	2.605406E-02	4.224353E-01	-1.237621E-01	4.815535E-02	1.200220E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 750 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.435479E-03	1.036161E-06	4.130735E-01	1.516023E-04	9.746622E-02	-1.299518E-06
2	G	1.301351E-02	2.690937E-02	4.849284E-01	-2.291946E-01	-2.782332E-02	1.792275E-02
3	G	1.681645E-02	3.231259E-02	4.814795E-01	-1.730074E-01	3.726447E-02	2.394944E-03
4	G	1.947560E-02	2.999322E-02	4.227873E-01	-1.320435E-01	1.417948E-01	-1.024072E-02
5	G	1.748053E-02	2.256134E-02	3.187257E-01	-7.859464E-02	1.311234E-01	-8.549068E-03
6	G	1.104959E-02	1.230632E-02	1.784245E-01	-1.180418E-01	3.197910E-01	-2.429825E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.137631E-02	2.364144E-02	4.603611E-01	-1.705072E-01	-5.242030E-02	2.254213E-02
9	G	1.464825E-02	2.887681E-02	4.441124E-01	-1.302609E-01	5.062617E-02	1.342067E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 750 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.185603E-03	1.243526E-06	4.316183E-01	1.875711E-04	1.117204E-01	-2.506002E-07
2	G	1.417925E-02	2.942253E-02	5.065101E-01	-2.404146E-01	-2.888359E-02	1.954734E-02
3	G	1.833803E-02	3.533886E-02	5.029299E-01	-1.813364E-01	3.861633E-02	2.674154E-03
4	G	2.124754E-02	3.281137E-02	4.416420E-01	-1.383669E-01	1.484223E-01	-1.124447E-02
5	G	1.907386E-02	2.469236E-02	3.329482E-01	-8.159911E-02	1.366130E-01	-9.325075E-03
6	G	1.208137E-02	1.349166E-02	1.865269E-01	-1.245918E-01	3.337945E-01	-2.669912E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.239704E-02	2.605454E-02	4.807940E-01	-1.783060E-01	-5.471918E-02	2.464744E-02
9	G	1.596597E-02	3.156659E-02	4.638112E-01	-1.361230E-01	5.284215E-02	1.482992E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 750 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.900228E-03	1.469734E-06	4.487016E-01	2.259106E-04	1.253379E-01	1.202769E-06
2	G	1.529323E-02	3.182934E-02	5.263479E-01	-2.506580E-01	-2.982629E-02	2.110100E-02
3	G	1.979396E-02	3.823910E-02	5.226444E-01	-1.889539E-01	3.985230E-02	2.946332E-03
4	G	2.294482E-02	3.551386E-02	4.589735E-01	-1.441506E-01	1.544974E-01	-1.220609E-02
5	G	2.060129E-02	2.673698E-02	3.460251E-01	-8.436879E-02	1.416748E-01	-1.007030E-02
6	G	1.307177E-02	1.462995E-02	1.939771E-01	-1.306372E-01	3.466152E-01	-2.901123E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.337197E-02	2.817466E-02	4.995856E-01	-1.854437E-01	-5.677415E-02	2.665821E-02
9	G	1.722686E-02	3.414521E-02	4.819274E-01	-1.414769E-01	5.485447E-02	1.623476E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 750 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.058443E-02	1.687102E-06	4.645862E-01	2.664404E-04	1.383798E-01	3.074097E-06
2	G	1.636299E-02	3.414536E-02	5.447560E-01	-2.601024E-01	-3.066830E-02	2.259312E-02
3	G	2.119383E-02	4.103179E-02	5.409357E-01	-1.959887E-01	4.099115E-02	3.212870E-03
4	G	2.457840E-02	3.811780E-02	4.750564E-01	-1.494931E-01	1.601210E-01	-1.313171E-02
5	G	2.207258E-02	2.873804E-02	3.581629E-01	-8.694680E-02	1.463839E-01	-1.078928E-02
6	G	1.402692E-02	1.572817E-02	2.008928E-01	-1.362720E-01	3.584681E-01	-3.124823E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.430772E-02	3.021551E-02	5.170316E-01	-1.920404E-01	-5.862736E-02	2.858748E-02
9	G	1.843922E-02	3.662911E-02	4.987457E-01	-1.464151E-01	5.670011E-02	1.763805E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 800 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.409217E-03	7.233949E-08	2.217295E-01	4.434285E-06	-3.834364E-03	-5.940812E-07
2	G	3.767214E-03	7.189996E-03	2.595004E-01	-1.079043E-01	-1.678030E-02	5.211547E-03
3	G	4.842312E-03	8.636650E-03	2.571973E-01	-8.389262E-02	2.395480E-02	3.353807E-04
4	G	5.595482E-03	7.982764E-03	2.256968E-01	-6.410769E-02	7.092697E-02	-2.449727E-03
5	G	5.027640E-03	5.934914E-03	1.700190E-01	-4.652965E-02	7.588313E-02	-2.558075E-03
6	G	3.049131E-03	3.101758E-03	9.357842E-02	-4.887508E-02	1.694576E-01	-5.913106E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.280696E-03	6.465385E-03	2.474979E-01	-8.647330E-02	-2.557588E-02	5.937027E-03
9	G	4.270277E-03	7.827287E-03	2.388329E-01	-6.653942E-02	2.594907E-02	4.127356E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 800 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.767862E-03	2.069973E-07	2.755946E-01	1.910698E-05	1.441305E-02	-1.321631E-06
2	G	5.839716E-03	1.154590E-02	3.233941E-01	-1.424637E-01	-1.965939E-02	8.027831E-03
3	G	7.506829E-03	1.385451E-02	3.207943E-01	-1.090887E-01	2.748950E-02	7.648080E-04
4	G	8.674560E-03	1.283551E-02	2.815975E-01	-8.348065E-02	9.125303E-02	-4.130782E-03
5	G	7.789301E-03	9.598813E-03	2.122403E-01	-5.598110E-02	9.114101E-02	-3.877098E-03
6	G	4.807315E-03	5.117154E-03	1.176847E-01	-6.866191E-02	2.128305E-01	-9.888115E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.091081E-03	1.031672E-02	3.077836E-01	-1.106599E-01	-3.356996E-02	9.605721E-03
9	G	6.585016E-03	1.248383E-02	2.969963E-01	-8.496284E-02	3.321057E-02	5.984635E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 800 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.895988E-03	3.025601E-07	3.137889E-01	3.504160E-05	3.267023E-02	-1.906364E-06
2	G	7.563999E-03	1.520512E-02	3.685051E-01	-1.669908E-01	-2.190826E-02	1.038142E-02
3	G	9.736546E-03	1.824448E-02	3.656821E-01	-1.270972E-01	3.017187E-02	1.134657E-03
4	G	1.125570E-02	1.691151E-02	3.210321E-01	-9.717766E-02	1.054782E-01	-5.572170E-03
5	G	1.010305E-02	1.267473E-02	2.419820E-01	-6.238367E-02	1.021677E-01	-4.986264E-03
6	G	6.289448E-03	6.815590E-03	1.346498E-01	-8.241998E-02	2.430308E-01	-1.326708E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.601885E-03	1.354073E-02	3.503475E-01	-1.275905E-01	-3.901977E-02	1.268629E-02
9	G	8.517966E-03	1.638487E-02	3.380387E-01	-9.780969E-02	3.818903E-02	7.611650E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 800 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.893919E-03	4.822714E-07	3.443650E-01	6.033322E-05	5.014195E-02	-2.220505E-06
2	G	9.094284E-03	1.846860E-02	4.044853E-01	-1.864029E-01	-2.376981E-02	1.248495E-02
3	G	1.172111E-02	2.216236E-02	4.014731E-01	-1.413986E-01	3.238497E-02	1.470464E-03
4	G	1.355602E-02	2.055029E-02	3.524718E-01	-1.080152E-01	1.167401E-01	-6.866996E-03
5	G	1.216542E-02	1.542111E-02	2.656844E-01	-6.740604E-02	1.110834E-01	-5.979680E-03
6	G	7.615007E-03	8.335505E-03	1.481622E-01	-9.331303E-02	2.668985E-01	-1.630472E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.943596E-03	1.641321E-02	3.843186E-01	-1.409598E-01	-4.325803E-02	1.543470E-02
9	G	1.023722E-02	1.986396E-02	3.707911E-01	-1.079311E-01	4.208649E-02	9.137515E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 259

FIVE TENTHS, 800 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.803548E-03	6.540931E-07	3.702801E-01	8.760913E-05	6.672394E-02	-2.264563E-06
2	G	1.049426E-02	2.146320E-02	4.348795E-01	-2.026014E-01	-2.534450E-02	1.441989E-02
3	G	1.353988E-02	2.576037E-02	4.316990E-01	-1.533454E-01	3.427294E-02	1.785669E-03
4	G	1.566683E-02	2.389444E-02	3.790288E-01	-1.170929E-01	1.261947E-01	-8.058753E-03
5	G	1.405911E-02	1.794618E-02	2.857069E-01	-7.162790E-02	1.186834E-01	-6.895120E-03
6	G	8.835103E-03	9.735231E-03	1.595734E-01	-1.025003E-01	2.869271E-01	-1.911298E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.170719E-03	1.904903E-02	4.130411E-01	-1.521381E-01	-4.676519E-02	1.795735E-02
9	G	1.181266E-02	2.305970E-02	3.984845E-01	-1.163882E-01	4.533708E-02	1.060367E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 800 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.647557E-03	8.390211E-07	3.929948E-01	1.181119E-04	8.245897E-02	-1.971680E-06
2	G	1.179758E-02	2.425909E-02	4.614461E-01	-2.166370E-01	-2.670863E-02	1.622856E-02
3	G	1.523599E-02	2.912220E-02	4.581133E-01	-1.637211E-01	3.593316E-02	2.085275E-03
4	G	1.763763E-02	2.702105E-02	4.022401E-01	-1.249736E-01	1.344191E-01	-9.173414E-03
5	G	1.582847E-02	2.030809E-02	3.032095E-01	-7.531551E-02	1.253701E-01	-7.752960E-03
6	G	9.977307E-03	1.104623E-02	1.695468E-01	-1.105374E-01	3.043347E-01	-2.175217E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.031282E-02	2.151007E-02	4.381631E-01	-1.618444E-01	-4.975551E-02	2.030968E-02
9	G	1.328166E-02	2.604611E-02	4.227058E-01	-1.237165E-01	4.813914E-02	1.203917E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 800 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.439931E-03	1.035662E-06	4.133511E-01	1.514784E-04	9.741759E-02	-1.312855E-06
2	G	1.302513E-02	2.689921E-02	4.851944E-01	-2.290847E-01	-2.790459E-02	1.793668E-02
3	G	1.683594E-02	3.229906E-02	4.817216E-01	-1.729429E-01	3.741853E-02	2.373259E-03
4	G	1.949881E-02	2.997753E-02	4.229888E-01	-1.319758E-01	1.417421E-01	-1.022706E-02
5	G	1.750073E-02	2.254261E-02	3.188582E-01	-7.861640E-02	1.313777E-01	-8.565682E-03
6	G	1.105861E-02	1.228788E-02	1.784633E-01	-1.177388E-01	3.198195E-01	-2.425964E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.138811E-02	2.383438E-02	4.606336E-01	-1.704736E-01	-5.235960E-02	2.252666E-02
9	G	1.466729E-02	2.886891E-02	4.443699E-01	-1.302176E-01	5.061096E-02	1.345749E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 800 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.190085E-03	1.242971E-06	4.318842E-01	1.874332E-04	1.116726E-01	-2.664049E-07
2	G	1.419091E-02	2.941239E-02	5.067651E-01	-2.403087E-01	-2.896178E-02	1.956150E-02
3	G	1.835756E-02	3.532537E-02	5.031620E-01	-1.812745E-01	3.876413E-02	2.652328E-03
4	G	2.127079E-02	3.279571E-02	4.418352E-01	-1.383013E-01	1.483717E-01	-1.123068E-02
5	G	1.909413E-02	2.467368E-02	3.330756E-01	-8.162159E-02	1.368562E-01	-9.341664E-03
6	G	1.209042E-02	1.347322E-02	1.865643E-01	-1.243016E-01	3.338226E-01	-2.666049E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.240886E-02	2.604753E-02	4.810552E-01	-1.782739E-01	-5.466152E-02	2.463203E-02
9	G	1.598505E-02	3.155873E-02	4.640582E-01	-1.360816E-01	5.282779E-02	1.486651E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 800 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.904739E-03	1.460126E-06	4.489576E-01	2.257592E-04	1.252910E-01	1.184404E-06
2	G	1.530493E-02	3.181924E-02	5.265937E-01	-2.505556E-01	-2.990182E-02	2.111534E-02
3	G	1.981353E-02	3.822565E-02	5.228681E-01	-1.888944E-01	3.999476E-02	2.924391E-03
4	G	2.296811E-02	3.549825E-02	4.591597E-01	-1.440868E-01	1.544485E-01	-1.219219E-02
5	G	2.062162E-02	2.671836E-02	3.461480E-01	-8.439176E-02	1.419087E-01	-1.008687E-02
6	G	1.308086E-02	1.461151E-02	1.940132E-01	-1.303578E-01	3.466430E-01	-2.897259E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.338382E-02	2.816769E-02	4.998373E-01	-1.854129E-01	-5.671909E-02	2.664286E-02
9	G	1.724596E-02	3.413739E-02	4.821653E-01	-1.414373E-01	5.484086E-02	1.627107E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 800 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.058897E-02	1.686442E-06	4.648337E-01	2.662762E-04	1.383338E-01	3.053091E-06
2	G	1.637471E-02	3.413530E-02	5.449938E-01	-2.600031E-01	-3.074152E-02	2.260761E-02
3	G	2.121343E-02	4.101840E-02	5.411522E-01	-1.959312E-01	4.112897E-02	3.190834E-03
4	G	2.460172E-02	3.810223E-02	4.752367E-01	-1.494310E-01	1.600737E-01	-1.311774E-02
5	G	2.209298E-02	2.868947E-02	3.582820E-01	-8.697009E-02	1.466097E-01	-1.080584E-02
6	G	1.403605E-02	1.570974E-02	2.009279E-01	-1.360021E-01	3.584956E-01	-3.120959E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.431960E-02	3.020857E-02	5.172750E-01	-1.920108E-01	-5.857456E-02	2.857220E-02
9	G	1.845835E-02	3.662134E-02	4.989759E-01	-1.463770E-01	5.668717E-02	1.767406E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 255

ONE TENTH, 850 DEG
LOAD STEP = 2.00000E+00 SUBCASE 10

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	2.413418E-03	7.224163E-08	2.222500E-01	4.413967E-06	-3.870352E-03	-5.956138E-07
2	G	3.778560E-03	7.180582E-03	2.599986E-01	-1.077444E-01	-1.691037E-02	5.220483E-03
3	G	4.861564E-03	8.617995E-03	2.576499E-01	-8.377372E-02	2.422177E-02	3.175886E-04
4	G	5.618501E-03	7.967975E-03	2.260758E-01	-6.403174E-02	7.084761E-02	-2.439675E-03
5	G	5.047027E-03	5.916492E-03	1.702601E-01	-4.650891E-02	7.636105E-02	-2.575012E-03
6	G	3.057620E-03	3.084141E-03	9.365150E-02	-4.832567E-02	1.694968E-01	-5.877363E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	3.292335E-03	6.458806E-03	2.480060E-01	-8.641482E-02	-2.546616E-02	5.923080E-03
9	G	4.289178E-03	7.819947E-03	2.393133E-01	-6.646952E-02	2.592663E-02	4.156616E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 256

TWO TENTHS, 850 DEG
LOAD STEP = 3.00000E+00 SUBCASE 20

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	3.772129E-03	1.882832E-07	2.760105E-01	1.780172E-05	1.436925E-02	-1.309143E-06
2	G	5.850880E-03	1.153663E-02	3.237965E-01	-1.423677E-01	-1.978103E-02	8.038891E-03
3	G	7.526264E-03	1.384186E-02	3.211616E-01	-1.090465E-01	2.772048E-02	7.441988E-04
4	G	8.697723E-03	1.282023E-02	2.819012E-01	-8.341078E-02	9.118555E-02	-4.119762E-03
5	G	7.809015E-03	9.580082E-03	2.124352E-01	-5.598504E-02	9.152503E-02	-3.894025E-03
6	G	4.816039E-03	5.099081E-03	1.177426E-01	-6.821406E-02	2.128647E-01	-9.850820E-03
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	5.102781E-03	1.030977E-02	3.081896E-01	-1.106357E-01	-3.346835E-02	9.589828E-03
9	G	6.603840E-03	1.247585E-02	2.973777E-01	-8.491036E-02	3.318162E-02	6.022662E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 257

THREE TENTHS, 850 DEG
LOAD STEP = 4.00000E+00 SUBCASE 30

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	4.900307E-03	3.242815E-07	3.141540E-01	3.665649E-05	3.262341E-02	-1.885886E-06
2	G	7.575484E-03	1.519500E-02	3.688534E-01	-1.668504E-01	-2.200970E-02	1.039363E-02
3	G	9.755863E-03	1.823097E-02	3.659984E-01	-1.270069E-01	3.036955E-02	1.114339E-03
4	G	1.127871E-02	1.689588E-02	3.212960E-01	-9.709845E-02	1.054122E-01	-5.559691E-03
5	G	1.012281E-02	1.265587E-02	2.421531E-01	-6.239516E-02	1.025038E-01	-5.003108E-03
6	G	6.298190E-03	6.797316E-03	1.346999E-01	-8.202291E-02	2.430620E-01	-1.322906E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	6.613571E-03	1.353366E-02	3.507046E-01	-1.275435E-01	-3.893945E-02	1.267102E-02
9	G	8.536905E-03	1.637698E-02	3.383765E-01	-9.775277E-02	3.816962E-02	7.647147E-04

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 258

FOUR TENTHS, 850 DEG
LOAD STEP = 5.00000E+00 SUBCASE 40

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	5.898267E-03	4.819513E-07	3.446976E-01	6.025681E-05	5.009273E-02	-2.227163E-06
2	G	9.105776E-03	1.845849E-02	4.048034E-01	-1.862778E-01	-2.386514E-02	1.249783E-02
3	G	1.174049E-02	2.214886E-02	4.017623E-01	-1.413231E-01	3.256787E-02	1.449489E-03
4	G	1.357910E-02	2.053461E-02	3.527125E-01	-1.079401E-01	1.166789E-01	-6.854097E-03
5	G	1.218533E-02	1.540226E-02	2.658411E-01	-6.742228E-02	1.113895E-01	-5.996456E-03
6	G	7.623834E-03	8.317149E-03	1.482080E-01	-9.295017E-02	2.669286E-01	-1.626639E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	7.955311E-03	1.640611E-02	3.846441E-01	-1.409201E-01	-4.318351E-02	1.541919E-02
9	G	1.025617E-02	1.985601E-02	3.710987E-01	-1.078797E-01	4.206750E-02	9.174506E-04

FIVE TENTHS, 850 DEG
LOAD STEP = 6.00000E+00 SUBCASE 50

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	6.807934E-03	6.537123E-07	3.705895E-01	8.751604E-05	6.667449E-02	-2.273295E-06
2	G	1.050580E-02	2.145305E-02	4.351756E-01	-2.024821E-01	-2.543410E-02	1.443324E-02
3	G	1.355930E-02	2.574685E-02	4.319682E-01	-1.532743E-01	3.444390E-02	1.764385E-03
4	G	1.568995E-02	2.387874E-02	3.792529E-01	-1.170205E-01	1.261368E-01	-8.045512E-03
5	G	1.407912E-02	1.792737E-02	2.858534E-01	-7.164693E-02	1.189678E-01	-6.911833E-03
6	G	8.843997E-03	9.716834E-03	1.596162E-01	-1.021624E-01	2.869564E-01	-1.907451E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	9.182462E-03	1.904195E-02	4.133443E-01	-1.521008E-01	-4.669637E-02	1.794184E-02
9	G	1.183164E-02	2.305176E-02	3.987711E-01	-1.163399E-01	4.531955E-02	1.064080E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 260

SIX TENTHS, 850 DEG
LOAD STEP = 7.00000E+00 SUBCASE 60

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	7.651977E-03	8.385808E-07	3.932865E-01	1.180031E-04	8.240986E-02	-1.982643E-06
2	G	1.180917E-02	2.424895E-02	4.617254E-01	-2.165228E-01	-2.679374E-02	1.624226E-02
3	G	1.525545E-02	2.910868E-02	4.583673E-01	-1.636536E-01	3.609486E-02	2.063758E-03
4	G	1.766079E-02	2.700536E-02	4.024516E-01	-1.249036E-01	1.343639E-01	-9.159934E-03
5	G	1.584858E-02	2.028933E-02	3.033482E-01	-7.533624E-02	1.256379E-01	-7.769627E-03
6	G	9.986255E-03	1.102781E-02	1.695873E-01	-1.102186E-01	3.043635E-01	-2.171361E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.032459E-02	2.150301E-02	4.384492E-01	-1.618092E-01	-4.969111E-02	2.029418E-02
9	G	1.330068E-02	2.603820E-02	4.229762E-01	-1.236710E-01	4.812279E-02	1.207627E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 261

SEVEN TENTHS, 850 DEG
LOAD STEP = 8.00000E+00 SUBCASE 70

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	8.444383E-03	1.035165E-06	4.136287E-01	1.513549E-04	9.736912E-02	-1.326176E-06
2	G	1.303675E-02	2.688907E-02	4.854603E-01	-2.289750E-01	-2.798601E-02	1.795065E-02
3	G	1.685544E-02	3.228557E-02	4.819636E-01	-1.728785E-01	3.757272E-02	2.351565E-03
4	G	1.952202E-02	2.996187E-02	4.231902E-01	-1.319081E-01	1.416893E-01	-1.021340E-02
5	G	1.752092E-02	2.252390E-02	3.189906E-01	-7.863822E-02	1.316321E-01	-8.582314E-03
6	G	1.106761E-02	1.226945E-02	1.785021E-01	-1.174355E-01	3.198478E-01	-2.422103E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.139991E-02	2.382736E-02	4.609060E-01	-1.704401E-01	-5.229882E-02	2.251120E-02
9	G	1.468634E-02	2.886103E-02	4.446275E-01	-1.301744E-01	5.059562E-02	1.349442E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 262

EIGHT TENTHS, 850 DEG
LOAD STEP = 9.00000E+00 SUBCASE 80

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.194567E-03	1.242418E-06	4.321500E-01	1.872956E-04	1.116249E-01	-2.821901E-07
2	G	1.420257E-02	2.940229E-02	5.070201E-01	-2.402029E-01	-2.904010E-02	1.957568E-02
3	G	1.837709E-02	3.531191E-02	5.033941E-01	-1.812128E-01	3.891205E-02	2.630493E-03
4	G	2.129404E-02	3.278008E-02	4.420284E-01	-1.382357E-01	1.483209E-01	-1.121689E-02
5	G	1.911439E-02	2.465502E-02	3.332028E-01	-8.164413E-02	1.370996E-01	-9.358269E-03
6	G	1.209946E-02	1.345478E-02	1.866016E-01	-1.240111E-01	3.338506E-01	-2.662186E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.242068E-02	2.604054E-02	4.813163E-01	-1.782419E-01	-5.460377E-02	2.461663E-02
9	G	1.600412E-02	3.155088E-02	4.643051E-01	-1.360403E-01	5.281332E-02	1.490320E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 263

NINE TENTHS, 850 DEG
LOAD STEP = 1.00000E+01 SUBCASE 90

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	9.909249E-03	1.459520E-06	4.492135E-01	2.256083E-04	1.252442E-01	1.166062E-06
2	G	1.531662E-02	3.180917E-02	5.268393E-01	-2.504533E-01	-2.997748E-02	2.112970E-02
3	G	1.983310E-02	3.821223E-02	5.230917E-01	-1.888350E-01	4.013733E-02	2.902442E-03
4	G	2.299140E-02	3.548266E-02	4.593459E-01	-1.440231E-01	1.543995E-01	-1.217831E-02
5	G	2.064195E-02	2.669975E-02	3.462709E-01	-8.441477E-02	1.421427E-01	-1.010346E-02
6	G	1.308994E-02	1.459308E-02	1.940493E-01	-1.300782E-01	3.466707E-01	-2.893395E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.339567E-02	2.816073E-02	5.000889E-01	-1.853822E-01	-5.666395E-02	2.662752E-02
9	G	1.726506E-02	3.412959E-02	4.824032E-01	-1.413977E-01	5.482716E-02	1.630748E-03

1 LARGE DISPLACEMENT ANALYSIS OF A CIRCULAR MEMBRANE AUGUST 4, 2000 MSC/NASTRAN 2/ 9/99 PAGE 264

ONE, 850 DEG
LOAD STEP = 1.10000E+01 SUBCASE 101

D I S P L A C E M E N T V E C T O R

POINT ID.	TYPE	T1	T2	T3	R1	R2	R3
1	G	1.059351E-02	1.685783E-06	4.650811E-01	2.661124E-04	1.382880E-01	3.032111E-06
2	G	1.638644E-02	3.412526E-02	5.452314E-01	-2.599040E-01	-3.081485E-02	2.262212E-02
3	G	2.123303E-02	4.100503E-02	5.413686E-01	-1.958738E-01	4.126689E-02	3.168791E-03
4	G	2.462505E-02	3.808668E-02	4.754169E-01	-1.493690E-01	1.600262E-01	-1.310377E-02
5	G	2.211337E-02	2.867091E-02	3.584011E-01	-8.699342E-02	1.468356E-01	-1.082241E-02
6	G	1.404516E-02	1.569131E-02	2.009629E-01	-1.357319E-01	3.585230E-01	-3.117096E-02
7	G	0.0	0.0	0.0	0.0	0.0	0.0
8	G	1.433147E-02	3.020165E-02	5.175185E-01	-1.919812E-01	-5.852170E-02	2.855693E-02
9	G	1.847748E-02	3.661359E-02	4.992060E-01	-1.463390E-01	5.667415E-02	1.771015E-03

THIS PAGE INTENTIONALLY LEFT BLANK

LIST OF REFERENCES

Acree, Robert L. "Large Array Antenna Structure (SBR)." CD-ROM. Air Force Research Laboratory.

Acree, Bob. "Inflatable Spacecraft Technology." CD-ROM. Air Force Research Laboratory.

Agrawal, Brij. AA4816 Class Notes. Naval Postgraduate School. 2000. Monterey, CA.

Baldwin, Craig. "SATCOM 101." Naval Space Command and Naval Postgraduate School. 1999. Monterey, CA.

Bradford, Rodney. "Thin Film Inflatable Structures for Space Applications." Chantilly, VA. 27 Apr 1999.

Cassapakis, Costas. "Status of Space Inflatable Structures Technology Elements at L'Garde, Inc." Chantilly, VA. 27 Apr 1999.

Cassapakis, Constantine G., Allan W. Love, and Arthur L. Palisoc. Inflatable Space Antennas: A Brief Overview. IEEE Aerospace Applications Conference Proceedings of the 1998 IEEE Aerospace Conference. 1998.

Cassapakis, Costa, and Mitch Thomas. "Inflatable Structures Technology Development Overview." Diss. L'Garde, Inc. Newport Beach, CA.

Chmielewski, Artur B. "NASA Space Inflatables Program." Chantilly, VA. 27 Apr 1999.

Chmielewski, Artur B. "ARISE Antenna." Diss. Jet Propulsion Laboratory. Pasadena, CA.

Chmielewski, Art B., and Jim Ulvestad. "ARISE." Online. L'Garde. Internet.8 Dec. 1999. Available : www.lgarde.com/people/papers/arise/arise1/arise1a

Criswell, Marvin E. et al. "Design and Performance Criteria for Inflatable Structures in Space." Diss. Space Engineering/Construction/Operations.

Clayton, Chris. "Large Space Optics." Diss. Air Force Research Laboratory.

Douglas, Robert L. Satellite Communications Technology. New Jersey: Prentice Hall, 1988.

Freeland, R. E. et al. "Large Inflatable Deployable Antenna Flight Experiment Results." Diss. Jet Propulsion Laboratory/California Institute of Technology, L'Garde, Incorporated, and National Aeronautics and Space Administration.

Freeland, R. E., and G. Bilyeu. "In-Step Inflatable Antenna Experiment." Diss. Jet Propulsion Laboratory/California Institute of Technology, L'Garde, Incorporated.

Freeland, R. E., G. D. Bilyeu, and M. M. Mikulas. "Inflatable Deployable Space Structures Technology Summary." Diss. Jet Propulsion Laboratory/California Institute of Technology, L'Garde, Incorporated, and University of Colorado.

Freeland, Robert E., and Richard G. Helms. "History of Inflatable Structures." Chantilly, VA. 27 Apr 1999.

Gipson, Lillian. "Commercial Development of Space." Innovation v4 n2 (May/June 1996).

Grahne, Mark. "STA Workshop on Inflatable Structures." Chantilly, VA., 27 Apr 1999.

Hoferer, Robert A., and Yahya Rahmat-Samii. "RF Characterization of an Inflatable Parabolic Torus Reflector Antenna for Space-Borne Applications." IEEE Transactions on Antennas and Propagation v46 n10 (1998): 1449-1457.

Katuin, Kevan D. "An Analysis of Space Inflatable Applications and Technology." Diss. Naval Postgraduate School, 1999.

Kimura, Shinichi, Toshiyuki Okuyama, Yuji Yamaha, Yasushi Nagai, and Hajime Morikawa. Teleoperation System for Antenna Assembly by Space Robots. Proceedings of SPIE – The International Society for Optical Engineering - Proceedings of the 1998 Conference on Telemanipulator and Telepresence Technologies, v 3524. Boston, MA. 1998.

Kunath R. and R. Sharp. "Design of an Inflatable, Optically Controlled and Fed, Phased Array Antenna." Proceeding of AIAA/NASA/OAI Conference on Advanced SEI Technologies. Cleveland, OH, 1991.

Larson, Wiley J., and James R. Wertz, eds. Space Mission Analysis and Design. Torrance, CA: Microcosm, Inc., 1992, and Boston: Kluwer Academic Publishers, 1992.

L'Garde. "Space Technology Alliance: Metting on Inflatable Space Structures." CD-ROM. Chantilly, VA. 27 Apr. 1999.

Loomis, H. H. Jr. "Communications Link Equations." Diss. Naval Postgraduate School. Monterey, CA.

Miller, Mark P. Getting Started with MSC/NASTRAN. USA: The MacNeal-Schwendler Corporation, 1996.

Measurement Specialties, Inc. "Definition of Piezo Film Polarity." Application Note 65773, 1 Aug. 1998 REV D.

Neurgaonkar, R. R., and J. G. Nelson. "High Performance Piezoelectric Thin Films for Shape Control in Large Inflatable Structures: Summary of Research Final Report." Diss. National Aeronautics and Space Administration. 1999.

Palisoc, A. et al. Geometry Attained by Pressurized Membranes. Proceedings of SPIE – The Internatinal Society for Optical Engineering – Proceeding of the 1998 Conference on Space Telescopes and Instruments V. Kona, HI, 1998. SPIE Bellingham, WA.

Robbins, Gary. "Space Target – Air Force to Bounce Lasers off Tustin-Made Balloon." The Orange County Resister. 29 Oct 1999.

Salama, M., J. Kuo, J. Garba, B. Wada, and M. Thomas. On-Orbit Shape Correction of Inflatable Structures. Diss. Jet Propulsion Laboratory, California Institute of Technology. Pasadena, CA, and L'Garde Inc. Tustin, CA.

Satter, Celeste M., and Robert L. Freeland. "Inflatable Structures Technology Applications and Requirements." Diss. Jet Propulsion Laboratory, California Institute of Technology. Pasadena, CA.

Shields, John Potter. Basic Piezoelectricity. New York: Howard W. Sams & Co., Inc. and the Bobbs-Merrill Company, Inc.

ILC Dover. "STA Workshop on Inflatable Structures." 1999.

Thomas, Mitchell, and Gilbert J. Friese. "Pressurized Antennas for Space Radars." Diss. L'Garde, Inc. Newport Beach, CA.

Tomasi, Wayne. Electronic Communications Systems. New Jersey: Prentice Hall, 1998.

Ulvestad, James S., Roger P. Linfield, and Joel G. Smith. "ARISE: A Space VLBI Mission Using an Inflatable Antenna Structure." Diss. Jet Propulsion Laboratory, California Institute of Technology. Pasadena, CA.

United States. National Aeronautics and Space Administration. "Space Technology Development." Online. Internet. 13 Jul. 2000. Available: www.sti.nasa.gov/tto/spinoff1996/13

THIS PAGE INTENTIONALLY LEFT BLANK

INITIAL DISTRIBUTION LIST

Defense Technical Information Center 2
8725 John J. Kingman Road, Suite 0944
Ft. Belvoir, VA 22060-6218

Dudley Knox Library 2
Naval Postgraduate School
411 Dyer Road
Monterey, CA 93943-5101

Craig Whittinghill 1
P.O. Box 472
Athens, WV 24712

Brij Agrawal 1
Department of Aeronautics and Astronautics
Code AA/Ag
Naval Postgraduate School
699 Dyer Road, Bldg 234, Room 137
Monterey, CA 93943-5107

Donald Wadsworth 1
Department of Electrical and Computer Engineering
Code EC/Wd
833 Dyer Room 437
Naval Postgraduate School
Monterey, CA 93943

Ramesh Kolar 1
Department of Aeronautics and Astronautics
Code AA/Kj
Naval Postgraduate School
699 Dyer Road, Bldg 234, Room 137
Monterey, CA 93943-5107

Department of Aeronautics and Astronautics 1
Code AA
Naval Postgraduate School
699 Dyer Road, Bldg 234, Room 137
Monterey, CA 93943-5107